

Radio Test Report

Equipment : Rugged Tablet Computer
Brand Name : AAEON
Model No. : xRTC-700Bx (x - Where x may be any combination of alphanumeric characters or "-" or blank.)
FCC ID : OHBRTC700BWBGH
Standard : 47 CFR FCC Part 22(H), 24(E)
WCDMA Band : II, V
FCC Classification : PCB
Applicant / Manufacturer : AAEON Technology Inc.
5F, No. 135, Lane 235, Pao Chiao Rd., Taipei, Taiwan

The product sample received on Jul. 29, 2016 and completely tested on Aug. 30, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI/TIA-603-D-2010, ANSI C63.4 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.2	Accessories and Support Equipment	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT.....	9
2.1	The Worst Case Measurement Configuration.....	9
2.2	Test Setup Diagram	10
3	TRANSMITTER TEST RESULT	11
3.1	Emission Bandwidth	11
3.2	Transmitter Conducted Output Power.....	13
3.3	Effective Radiated Power	15
3.4	Effective Isotropic Radiated Power	17
3.5	Transmitter Conducted Unwanted Emissions.....	19
3.6	Transmitter Conducted Bandedge Emissions.....	21
3.7	Transmitter Radiated Unwanted Emissions	23
3.8	Frequency Stability.....	30
4	TEST EQUIPMENT AND CALIBRATION DATA.....	32
APPENDIX A. TEST PHOTOS		
APPENDIX B. PHOTOGRAPHS OF EUT		

Summary of Test Result

Test Specifications					
Report Clause	FCC Std. Clause	Description	Measured	Limit	Result
3.1	2.1049 22.917(a) 24.238(a) 27.53(h)	Emission Bandwidth	Bandwidth F9W=4.2065MHz	Information for Emission Designator	Complied
3.1.6	2.1047	Emission Designator	F9W	Information only	Complied
3.2	2.1046	Transmitter Conducted Output Power	Conducted Power [dBm] Cellular: 22.84 PCS: 23.44	Information for RF exposure	Complied
3.2.7	24.232(d) 27.50(d)	Peak to Average Ratio	3.48dB	≤13dB	Complied
3.3	22.913(a)	Effective Radiated Power (ERP)	ERP [dBm] Cellular:14.48	≤7W[38.45dBm]	Complied
3.4	24.232(c) 27.50(d)	Effective Isotropic Radiated Power (EIRP)	EIRP [dBm] PCS: 23.63	PCS: ≤2W[33.01dBm] AWS: ≤1W[30.00dBm]	Complied
3.5	2.1051 22.917(a) 24.238(a) 27.53(h)	Transmitter Conducted Unwanted Emissions	refer to test data	≤43+10log(P) [-13dBm] P=TX Power in Watts	Complied
3.6	2.1051 22.917(a) 24.238(a) 27.53(h)	Transmitter Conducted Bandedge Emissions	refer to test data	≤43+10log(P) [-13dBm] P=TX Power in Watts	Complied
3.7	2.1053 22.917(a) 24.238(a) 27.53(h)	Transmitter Radiated Unwanted Emissions	[dBm]: 800.180MHz 42.72 (Margin 3.28dB)	≤43+10log(P) [-13dBm] P=TX Power in Watts	Complied
3.8	2.1055 22.355 24.353 27.54	Frequency Stability	Cellular: 0.0209ppm PCS: 0.0172ppm	≤ ± 2.5ppm within band	Complied

Revision History

[illegible]

1 General Description

1.1.1 RF General Information

Function	Class/Category	
☒ HSDPA	Category	10
☒ HSUPA	Category	6

RF General Information							
Freq. Band	Mode	TX Ch. Freq. (MHz)	Channel Number	BW (MHz)	Emission Designator	Max. ERP/EIRP	
						(dBm)	(W)
Cellular	WCDMA850	826.4-846.6	4132-4233	5	4M17F9W	14.48	0.0281
PCS	WCDMA1900	1852.4-1907.6	9262-9538	5	4M21F9W	23.63	0.2307
Note 1: WCDMA Rel.99 mode consists of QPSK modulation and HSDPA Rel. 5 mode consists of QPSK and 16QAM modulation.							
Note 2: WCDMA850 (WCDMA Band V), WCDMA1900 (WCDMA Band II)							

1.1.2 Antenna Information

Antenna Category	
☒	Integral antenna (antenna permanently attached)
☒	Temporary RF connector provided
☐	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.

Antenna General Information				
Operating Band	Ant. Cat.	Ant. Type	Connector	Gain (dBi)
Band V	Integral	PIFA	I-pex	-6.21
Band II	Integral	PIFA	I-pex	0.19

1.1.3 Type of EUT

Identify EUT	
Presentation of Equipment	☒ Production ; ☐ Pre-Production ; ☐ Prototype
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
☐	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
☐	Other:

1.1.4 EUT Operational Condition

Supply Voltage	☒ AC mains	☒ DC	
Type of DC Source	☐ Internal DC supply	☒ External AC adapter	☒ Li-ion Battery
Test Voltage	☒ Vnom (7.4 V)	☒ Vmax (8.4 V)	☒ Vmin (6.0 V)
Test Climatic	☒ Tnom (20°C)	☒ Tmax (50°C)	☒ Tmin (-20°C)

1.2 Accessories and Support Equipment

Accessories				
AC Adapter 1	Brand Name	FSP	Model Name	FSP036-RBBN2
	Power Rating	I/P:100-240Vac, 1.2A, O/P: 12Vdc, 3A		
	Power Cord	1.2 meter, non-shielded cable, with one ferrite core		
Battery 1	Brand Name	Getac	Model Name	RTC600S
	Vendor	7.4 Vdc, 1530 mAh	Power Rating	Li-ion, 2S1P
Battery 2	Brand Name	Getac	Model Name	RTC600H
	Vendor	7.4 Vdc, 1530 mAh	Power Rating	Li-ion, 2S1P
LCD Panel	Brand Name	INNOLUX	Model Name	N070ICG-LD1

Reminder: Regarding to more detail and other information, please refer to user manual.

Support Equipment			
No.	Equipment	Brand Name	Model Name
1	SIM Card	Anritsu	-

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Part 22(H), 24(E)
- ♦ ANSI/TIA-603-D-2010
- ♦ KDB 971168 D01 v02r02
- ♦ KDB 412172 D01 v01r01

1.4 Testing Location Information

Testing Location									
☒	HWA YA	ADD	:	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.					
		TEL	:	886-3-327-3456	FAX	:	886-3-327-0973		
Test Site Registration Number: FCC 553509									
Test Condition		Test Site No.		Test Engineer		Test Environment		Test Date	
RF Conducted		TH01-HY		Howard		25°C / 65%		30/08/2016	
Radiated Emission		03CH03-HY		Jeff		21.5°C / 58%		18/08/2016	

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty		
Test Item		Uncertainty
Emission bandwidth		±1.4 %
RF output power, conducted		±0.6 dB
Unwanted emissions, conducted	30 – 1000 MHz	±0.5 dB
	1 – 18 GHz	±0.6 dB
	18 – 40 GHz	±0.8 dB
	40 – 200 GHz	N/A
All emissions, radiated	30 – 1000 MHz	±2.5 dB
	1 – 18 GHz	±3.5 dB
	18 – 40 GHz	±3.8 dB
	40 – 200 GHz	N/A
Temperature		±0.8 °C
Humidity		±3 %
DC and low frequency voltages		±3 %
Time		±1.4 %
Duty Cycle		±1.4 %


2 Test Configuration of EUT

2.1 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emission Bandwidth, Transmitter Conducted Output Power, Peak-Average Ratio, Transmitter Conducted Bandedge Emissions Transmitter Conducted Unwanted Emissions, Frequency Stability
Test Condition	Conducted measurement at transmit chains
Modulation Mode	WCDMA

The Worst Case Mode for Following Conformance Tests			
Tests Item	Effective Radiated Power (ERP) Effective Isotropic Radiated Power (EIRP) Transmitter Radiated Unwanted Emissions		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Modulation Mode	WCDMA		
User Position	☐ EUT will be placed in fixed position.		
	☐ EUT will be placed in mobile position and operating multiple positions.		
	☒ EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions.		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT	V		

2.2 Test Setup Diagram



3 Transmitter Test Result

3.1 Emission Bandwidth

3.1.1 Emission Bandwidth Limit

Emission Bandwidth Limit	
Information for Emission Designator.	
Note 1: The 99% occupied bandwidth is the frequency bandwidth of the signal power at the 99% channel power of occupied bandwidth when resolution bandwidth should be approximately 1 % to 5 % of the span. These measurements shall also be performed at normal test conditions.	


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method	
☒ For the emission bandwidth shall be measured using one of the options below:	
☒	☒ Refer as ANSI/TIA-603-D, clause 1.3.4.4 for test bandwidth.
	☒ Refer as KDB 971168, clause 4 for signal bandwidth.
	☐ Refer as IC RSS-Gen, clause 6.6 for emission bandwidth.
☒ For conducted measurement.	
☒	☒ If EUT supports single transmit chain and measurements performed on this transmit chain.
	☐ If EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
	☐ If EUT supports multiple transmit chains using options given below:
	☐ Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1. ☐ Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.
☐ For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.	

3.1.4 Test Setup




3.1.5 Test Result of Emission Bandwidth

Emission Bandwidth Result				
Mode	Ch.	Freq. (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
WCDMA850	4132	826.4	4.676	4.1687
	4182	836.4	4.689	4.1475
	4233	846.6	4.682	4.1653
WCDMA1900	9262	1852.4	4.727	4.1834
	9400	1880.0	4.808	4.2065
	9538	1907.6	4.740	4.1894
Limit			N/A	
Result			Complied	

3.1.6 Emission Designator

Emission Designator	
Mode	Emission Designator
WCDMA850	4M17F9W
WCDMA1900	4M21F9W

Note 1: WCDMA 99% BW, F = Frequency Modulation, 9 = Composite Digital Info, W = Combination (Audio/Data)



3.2 Transmitter Conducted Output Power

3.2.1 Transmitter Conducted Output Power Limit

Transmitter Conducted Output Power Limit
Information for RF exposure

3.2.2 Transmitter Peak to Average Ratio Limit

Transmitter Peak to Average Ratio Limit
PAR ≤ 13dB


3.2.3 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.4 Test Procedures

Test Method	
☒	Transmitter Conducted Output Power
☐	Refer as KDB 941225 D01 clause 5 for GSM GPRS EDGE modes.
☐	Refer as KDB 941225 D01 clause 5 for GSM/(E)GPRS Dual Transfer Mode.
☒	Refer as KDB 941225 D01 clause 4 for 3G device modes.
☒	Refer as KDB 941225 D01 clause 4 for 3GPP R6, R7 and R8 additional information.
☐	Refer as KDB 941225 D05 for LTE modes.
☐	Refer as RSS-Gen, clause 6.12 for power measurement.
☒	Transmitter Peak-Average Ratio
☒	For WCDMA signals refer as KDB 971168, clause 5.7 for CCDF function.
☐	For GSM signals refer average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power.
☒	For conducted measurement.
☒	If EUT supports single transmit chain and measurements performed on this transmit chain.
☐	If EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
☐	If EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.

3.2.5 Test Setup



3.2.6 Test Result of Transmitter Conducted Output Power

WCDMA Worst Modulation for Output Power		
3GPP Release Ver.	Mode	Configuration
99	WCDMA	12.2kbps RMC
5	HSDPA	Subtest 1 ~ Subtest 4
6	HSUPA	Subtest 1 ~ Subtest 5

Mode	Subtest	RF Output Power [dBm]						
		Band V (Cellular)			Band II (PCS)			MPR [dB]
		4132	4182	4233	9262	9400	9538	
WCDMA	12.2 kbps RMC	22.77	22.76	22.84	23.44	22.22	22.39	-
HSDPA	Subtest 1	21.65	22.81	22.80	22.06	21.14	21.00	0
	Subtest 2	21.72	22.84	22.83	22.15	21.13	21.03	0
	Subtest 3	21.20	22.36	22.41	21.58	20.45	20.62	0.5
	Subtest 4	21.25	22.38	22.35	21.58	20.55	20.55	0.5
HSUPA	Subtest 1	22.08	21.89	21.82	20.54	20.30	20.56	0
	Subtest 2	21.29	21.02	21.21	20.89	19.81	19.84	2
	Subtest 3	21.33	21.27	21.09	20.65	19.33	19.58	1
	Subtest 4	21.81	21.56	21.65	21.38	20.53	20.30	2
	Subtest 5	21.11	20.97	20.90	20.54	20.24	20.24	0

3.2.7 Test Result of Transmitter Peak to Average Ratio

Transmitter Peak to Average Ratio Result			
Mode	Ch.	Freq. (MHz)	Peak to Average Ratio (dB)
WCDMA850	4132	826.4	3.39
	4182	836.4	2.84
	4233	846.6	3.48
WCDMA1900	9262	1852.4	2.5
	9400	1880	2.14
	9538	1907.6	2.27
Limit			13
Result			Complied

3.3 Effective Radiated Power

3.3.1 Effective Radiated Power Limit

Cellular Band Effective Radiated Power (ERP) Limit
ERP $\leq$ 7W [38.45dBm] (EIRP 40.6dBm [135.8 dBuV/m at 3m]).


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
☒	For wideband (> 1 MHz) digital transmission systems power measure following as KDB 971168.
☒	Effective Radiated Power (ERP)
☒	Refer as KDB 412172, clause 1.2 following as power approach. e.i.r.p.= $P_T + G_T + L_C$.
☐	Refer as KDB 412172, clause 1.1 following as field strength approach. e.i.r.p.= $(E \times d)^2 / 30$.
☒	Refer as KDB 412172, clause 1.3 ERP = EIRP - 2.15 dB.
☒	For radiated measurement.
☐	Refer as KDB 412172, clause 2.2 following eirp can be used radiated test configuration.
☒	Refer as KDB 412172, clause 2.3 following eirp can be used signal/antenna substitution techniques.
☐	Refer as ANSI/TIA-603-D-2010, clause 2.2.17 for radiated measurement.
☐	Refer as RSS-Gen, clause 6.12 for power measurement.

3.3.4 Test Setup



3.3.5 Test Result of Effective Radiated Power

Mode	Channel	Frequency (MHz)	ERP(dBm)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
WCDMA850	4132	826.4	14.44	-22.80	8.94	0.25	7.9	H
	4182	836.4	14.48	-23.12	8.79	0.25	8.09	H
	4233	846.6	13.43	-24.26	7.54	0.25	8.29	H
Note 1: EUT was tested in all WCDMA/HSDPA configurations and the highest power is reported in 12.2 kbps RMC and TPC bits all set "1". Note 2: EUT was tested with its standard battery. Note 3: Measurement worst emissions of receive antenna polarization.								

3.4 Effective Isotropic Radiated Power

3.4.1 Effective Isotropic Radiated Power Limit

PCS Band and AWS Band Effective Isotropic Radiated Power (EIRP) Limit
PCS Band: EIRP $\leq$ 2W [33.01dBm] (128.2 dBuV/m at 3m) AWS Band: EIRP $\leq$ 1W [30.00dBm] (125.2 dBuV/m at 3m)


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
☒	For wideband (> 1 MHz) digital transmission systems power measure following as KDB 971168.
☒	Effective Isotropic Radiated Power (EIRP)
☒	Refer as KDB 412172, clause 1.2 following as power approach. $e.i.r.p. = P_T + G_T + L_C$.
☐	Refer as KDB 412172, clause 1.1 following as field strength approach. $e.i.r.p. = (E \times d)^2 / 30$.
☒	For radiated measurement.
☐	Refer as KDB 412172, clause 2.2 following eirp can be used radiated test configuration.
☒	Refer as KDB 412172, clause 2.3 following eirp can be used signal/antenna substitution techniques.
☐	Refer as ANSI/TIA-603-D-2010, clause 2.2.17 for radiated measurement.
☐	Refer as RSS-Gen, clause 6.12 for power measurement.

3.4.4 Test Setup



3.4.5 Test Result of Effective Isotropic Radiated Power

Mode	Channel	Frequency (MHz)	ERP(dBm)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
WCDMA1900	9262	1852.4	21.95	-18.39	20.02	2.57	4.50	V
	9400	1880.0	19.62	-19.11	17.81	2.60	4.41	V
	9538	1907.6	23.63	-16.39	21.92	2.60	4.31	V
Note 1: EUT was tested in all WCDMA/HSDPA configurations and the highest power is reported in 12.2 kbps RMC and TPC bits all set "1". Note 2: EUT was tested with its standard battery. Note 3: Measurement worst emissions of receive antenna polarization.								

3.5 Transmitter Conducted Unwanted Emissions

3.5.1 Transmitter Conducted Unwanted Emissions Limit

Transmitter Conducted Unwanted Emissions Limit
The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $[43 + 10 \log (P)]$ (-13dBm).


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.



3.5.3 Test Procedures

Test Method
☒ Refer as ANSI/TIA-603-D-2010, clause 3.2.13 for conducted measurement.
☐ Refer as RSS-Gen, clause 6.13 for transmitter unwanted emissions measurement.
☐ In case a narrower measurement bandwidth was used, the following conversion formula has to be applied: (e.g. if reference bandwidth 1 MHz and measurement bandwidth 100 kHz, then measurement bandwidth conversion factor is 10 dB); $B = A + 10 \log (BW_{ref} / BW_{measured})$ • A is the value at the narrower measurement bandwidth; • B is the value referred to the reference bandwidth; • Correction Factor(dB)= $10 \log (1\% \text{ Emission BW/RBW})$;
☒ For conducted measurement.
☒ For conducted measurements on devices with single transmit chain. ☐ For conducted measurements on devices with multiple transmit chains using options given below: ☐ Option 1: measure and sum the spectra across the transmitter outputs. ☐ Option 2: N transmitter outputs, then spurious emissions limits on each individual output. Measure and add 10 log (N) dB.

3.5.4 Test Setup



3.5.5 Test Result of Transmitter Conducted Unwanted Emissions

Transmitter Conducted Unwanted Emissions		Mode	WCDMA850
Channel	4182	Test Range	30 MHz - 10 harmonic
			
Transmitter Conducted Unwanted Emissions		Mode	WCDMA1900
Channel	9400	Test Range	30 MHz - 10 harmonic
			

Note: "ALIGN OFF" means that we turn off the auto align. We align the spectrum at each time before test.

3.6 Transmitter Conducted Bandedge Emissions

3.6.1 Transmitter Conducted Bandedge Emissions Limit

Transmitter Conducted Bandedge Emissions Limit	
Cellular Band:	
(i)	In the first 1.0 MHz band immediately outside frequency block, the power of emissions per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log(P)$ (watts) (-13dBm).
(ii)	After the first 1.0 MHz immediately outside frequency block, the power of emissions in any 100 kHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log(P)$ (watts) (-13dBm). If the measurement is performed using 1% of the emission bandwidth, power integration over 100 kHz is required.
PCS/AWS Band:	
(i)	In the 1.0 MHz bands immediately outside frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log(P)$ (watts) (-13dBm).
(ii)	After the first 1.0 MHz immediately outside frequency block, the power of emissions in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log(P)$ (watts) (-13dBm). If the measurement is performed using 1% of the occupied bandwidth, power integration over 1 MHz is required.


3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.6.3 Test Procedures

Test Method	
☒	Refer as ANSI/TIA-603-D-2010, clause 3.2.13 for conducted measurement.
☐	Refer as RSS-Gen, clause 6.13 for transmitter unwanted emissions measurement.
☐	In case a narrower measurement bandwidth was used, the following conversion formula has to be applied: (e.g. if reference bandwidth 1 MHz and measurement bandwidth 100 kHz, then measurement bandwidth conversion factor is 10 dB); $B = A + 10 \log (BW_{ref} / BW_{measured})$ • A is the value at the narrower measurement bandwidth; • B is the value referred to the reference bandwidth; • Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$;
☒	For conducted measurement.
☒	For conducted measurements on devices with single transmit chain.
☐	For conducted measurements on devices with multiple transmit chains using options given below:
☐	Option 1: measure and sum the spectra across the transmitter outputs.
☐	Option 2: N transmitter outputs, then spurious emissions limits on each individual output. Measure and add $10 \log (N)$ dB.

3.6.4 Test Setup



3.6.5 Test Result of Transmitter Conducted Bandedge Emissions



Note: "ALIGN OFF" means that we turn off the auto align. We align the spectrum at each time before test.

3.7 Transmitter Radiated Unwanted Emissions

3.7.1 Transmitter Radiated Unwanted Emissions Limit

Transmitter Radiated Unwanted Emissions Limit
The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $[43 + 10 \log (P)]$ (EIRP -13dBm).

3.7.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method
☒ Refer as ANSI/TIA-603-D-2010, clause 3.2.12 for radiated measurement.
☐ Refer as RSS-Gen, clause 4.9 for transmitter unwanted emissions measurement.
☐ In case a narrower measurement bandwidth was used, the following conversion formula has to be applied: (e.g. if reference bandwidth 1 MHz and measurement bandwidth 100 kHz, then measurement bandwidth conversion factor is 10 dB) $B = A + 10 \log (BW_{ref} / BW_{measured})$ • A is the value at the narrower measurement bandwidth; • B is the value referred to the reference bandwidth; • Correction Factor(dB)= $10 \log(1\% \text{ Emission BW/RBW})$;
☒ Effective Isotropic Radiated Power (EIRP)
☒ Refer as KDB 412172, clause 1.2 following as power approach. $e.i.r.p. = P_T + G_T + L_C$. ☐ Refer as KDB 412172, clause 1.1 following as field strength approach. $e.i.r.p. = (E \times d)^2 / 30$.
☒ For radiated measurement.
☐ Refer as KDB 412172, clause 2.2 following eirp can be used radiated test configuration. ☒ Refer as KDB 412172, clause 2.3 following eirp can be used signal/antenna substitution techniques. ☐ Refer as ANSI/TIA-603-D-2010, clause 2.2.17 for radiated measurement. ☐ Refer as RSS-Gen, clause 6.12 for power measurement.


3.7.4 Test Setup

Transmitter Radiated Unwanted Emissions (below 1GHz)




Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna.

Transmitter Radiated Unwanted Emissions (Above 1GHz)



Electric field tests shall be performed in the frequency range of 1 GHz to 10th harmonic of highest fundamental frequency or 40 GHz using a calibrated horn antenna.

3.7.5 Test Result of Transmitter Radiated Unwanted Emissions(Below 1GHz)




Transmitter Radiated Unwanted Emissions

Operating Band

WCDMA850

Polarization

H



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB
1	30.000	29.31	-10.69	40.00	30.46	25.62	0.78	27.55 Peak
2	136.700	26.67	-16.83	43.50	33.99	18.09	1.81	27.22 Peak
3	299.660	36.48	-9.52	46.00	40.80	19.77	2.61	26.70 Peak
4	482.020	33.13	-12.87	46.00	33.74	23.49	3.50	27.60 Peak
5	800.180	42.72	-3.28	46.00	39.35	26.59	4.56	27.78 QP
6	883.600	42.45	-3.55	46.00	37.74	27.41	4.86	27.56 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).

Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.


Transmitter Radiated Unwanted Emissions

Operating Band

WCDMA1900

Polarization

V



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB
1	41.640	29.94	-10.06	40.00	37.93	18.60	0.93	27.52 Peak
2	249.220	26.99	-19.01	46.00	32.54	18.80	2.46	26.81 Peak
3	299.660	31.09	-14.91	46.00	35.41	19.77	2.61	26.70 Peak
4	532.460	33.22	-12.78	46.00	33.11	24.37	3.61	27.87 Peak
5	666.320	38.26	-7.74	46.00	36.53	25.39	4.30	27.96 Peak
6	800.180	36.36	-9.64	46.00	32.99	26.59	4.56	27.78 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).


Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions
Operating Band

WCDMA1900

Polarization

H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	30.000	25.44	-14.56	40.00	26.59	25.62	0.78	27.55	Peak
2	136.700	23.29	-20.21	43.50	30.61	18.09	1.81	27.22	Peak
3	299.660	36.52	-9.48	46.00	40.84	19.77	2.61	26.70	Peak
4	666.320	34.89	-11.11	46.00	33.16	25.39	4.30	27.96	Peak
5	786.600	39.92	-6.08	46.00	36.66	26.51	4.55	27.80	Peak
6	800.180	42.43	-3.57	46.00	39.06	26.59	4.56	27.78	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).

Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.

3.7.6 Test Result of Transmitter Radiated Unwanted Emissions(Above 1GHz)

Mode	WCDMA850(BAND5)								
Frequency (MHz)	ERP(dBm)	Limit(dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672.80	-64.58	-13	-51.58	-46.21	-65.12	2.42	5.11	V	PASS
2509.20	-61.00	-13	-48.00	-59.10	-61.3	3.07	5.52	V	PASS
3345.60	-65.43	-13	-52.43	-64.88	-67.5	3.48	7.70	H	PASS

Mode	WCDMA1900(BAND2)								
Frequency (MHz)	EIRP(dBm)	Limit(dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-43.77	-13	-30.77	-56.14	-48.41	3.77	8.41	H	PASS
5640	-54.14	-13	-41.14	-56.65	-59.39	5.01	10.26	H	PASS
7520	-49.64	-13	-36.64	-60.33	-55.76	5.7	11.82	H	PASS

3.8 Frequency Stability

3.8.1 Frequency Stability Limit

Frequency Stability Limit	
☒	The transmitter center frequency stability shall be ± 2.5 ppm maximum. The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.
☒	Temperature:
☒	-30°C to +50°C in 10°C step.
☒	If the EUT cannot be turned on at -30°C, the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.
☒	Voltage:
☒	For non hand-carried battery and AC powered equipment: 85% to 115% of the nominal value
☒	For hand-carried, battery-powered equipment: Voltage is reduced to the battery operating end point which shall be specified by the manufacturer.
Note 1: These measurements shall also be performed at normal and extreme test conditions.	


3.8.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.8.3 Test Procedures

Test Method	
☒	Refer as ANSI/TIA-603-D-2010, clause 3.2.2 for frequency stability tests
☐	Refer as RSS-Gen, clause 6.11 for transmitter frequency stability measurement.
☒	Frequency stability with respect to ambient temperature
☒	Frequency stability when varying supply voltage
☒	For conducted measurement.
☒	For conducted measurements on devices with multiple transmit chains: Measurements need only to be performed on one of the active transmit chains (antenna outputs)
☐	For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

3.8.4 Test Setup



3.8.5 Test Result of Frequency Stability

Mode		WCDMA850		WCDMA1900	
Channel		4182		9400	
Frequency (MHz)		836.4		1880.0	
Temp. (°C)	Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)	Frequency Error (Hz)	Frequency Error (ppm)
50	7.4	17.45	0.0209	32.33	0.0172
40	7.4	15.86	0.0190	30.12	0.0160
30	7.4	15.23	0.0182	30.39	0.0162
20	7.4	13.67	0.0163	30.12	0.0160
10	7.4	17	0.0203	31.24	0.0166
0	7.4	9.72	0.0116	15.14	0.0081
-10	7.4	8.67	0.0104	16.07	0.0085
-20	7.4	9.05	0.0108	17.35	0.0092
-30	7.4	-	-	-	-
20	8.4	14.32	0.0171	30.48	0.0162
20	7.4	13.67	0.0163	30.12	0.0160
20	6	10.94	0.0131	30.08	0.0160
Limit [ppm]		± 2.5			

4 Test Equipment and Calibration Data

RF Conducted

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date
Wireless communication test Set	Agilent	8960	108087	Wireless communication test	03/05/2016	02/05/2017
Spectrum	KEYSIGHT	N9010A	MY54200885	10Hz ~ 44GHz	04/07/2016	03/07/2017

Radiated Emissions

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	28/11/2015	27/11/2016
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	1GHz ~ 18GHz 3m	16/12/2015	15/12/ 2016
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	10/05//2016	09/05/2017
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	02/09/2015	01/09/ 2016
Spectrum	R&S	FSV40	101513	9kHz ~ 40GHz	16/02/ 2016	15/02/ 2017
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30MHz ~ 1GHz	18/09/ 2015	17/09/2016
Horn Antenna	SCHWARZBECK	BBHA9120D	1531	1GHz ~ 18GHz	22/04/ 2016	21/04/ 2017
Wireless communication test Set	Agilent	8960	MY53202219	2G/3G Base Station	03/05/2016	02/05/2017