

7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 9.1).


7.5.2. Test Procedure Used

KDB 558074 D01v03r01 – Section 11.3

7.5.3. Test Settling


1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Number of sweep points $\geq 2 \times \text{Span/RBW}$
6. Trace mode = max hold
7. Sweep time = auto couple
8. The trace was allowed to stabilize

7.5.4. Test Setup




7.5.5. Test Result

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Limit	Result
802.11b	1Mbps	01	2412	20dBc	Pass
802.11b	1Mbps	06	2437	20dBc	Pass
802.11b	1Mbps	11	2462	20dBc	Pass
802.11g	6Mbps	01	2412	20dBc	Pass
802.11g	6Mbps	06	2437	20dBc	Pass
802.11g	6Mbps	11	2462	20dBc	Pass
802.11n-HT20	6.5/7.2Mbps	01	2412	20dBc	Pass
802.11n-HT20	6.5/7.2Mbps	06	2437	20dBc	Pass
802.11n-HT20	6.5/7.2Mbps	11	2462	20dBc	Pass
802.11n-HT40	13.5/15Mbps	03	2422	20dBc	Pass
802.11n-HT40	13.5/15Mbps	06	2437	20dBc	Pass
802.11n-HT40	13.5/15Mbps	09	2452	20dBc	Pass



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 06 (2437MHz)


100kHz PSD reference Level



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 11 (2462MHz)


100kHz PSD reference Level




High Band Edge



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




802.11g Out-of-Band Emissions

Channel 01 (2412MHz)


100kHz PSD reference Level




Low Band Edge



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 06 (2437MHz)


100kHz PSD reference Level



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 11 (2462MHz)


100kHz PSD reference Level




High Band Edge



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




802.11n-HT20 Out-of-Band Emissions

Channel 01 (2412MHz)


100kHz PSD reference Level




Low Band Edge



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 06 (2437MHz)

100kHz PSD reference Level



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 11 (2462MHz)


100kHz PSD reference Level




High Band Edge



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




802.11n-HT40 Out-of-Band Emissions

Channel 03 (2422MHz)


100kHz PSD reference Level



Low Band Edge



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 06 (2437MHz)


100kHz PSD reference Level



Spurious Emission 30MHz ~ 3GHz




Spurious Emission 2GHz ~ 25GHz




Channel 09 (2452MHz)


100kHz PSD reference Level




High Band Edge



Spurious Emission 30MHz ~ 3GHz



Spurious Emission 2GHz ~ 25GHz



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 – 0.490	2400/F (kHz)	300
0.490 – 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.6.2. Test Procedure Used

KDB 558074 D01v03r01 – Section 12.2.3 (quasi-peak measurements)

KDB 558074 D01v03r01 – Section 12.2.4 (peak power measurements)

KDB 558074 D01v03r01 – Section 12.2.5 (average power measurements)

7.6.3. Test Setting

Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 D01v03r01


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements per Section 12.2.5.1 of KDB 558074 D01v03r01


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $> 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

7.6.4. Test Setup


9kHz ~ 30MHz Test Setup:



30MHz ~ 1GHz Test Setup:



1GHz ~ 25GHz Test Setup:



7.6.5. Test Result

Test Mode:	802.11b	Test Site:	AC1
Test Channel:	01	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. The worst case of Radiated Spurious Emission. 3. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3618.0	44.19	3.95	48.14	74.0	-25.86	Peak	Horizontal
	4825.0	40.10	6.41	46.51	74.0	-27.49	Peak	Horizontal
*	7236.0	36.46	13.79	50.25	73.8	-23.55	Peak	Horizontal
*	7757.5	36.29	14.79	51.08	73.8	-22.72	Peak	Horizontal
	3618.0	42.41	3.95	46.36	74.0	-27.64	Peak	Vertical
	4824.0	36.66	6.41	43.07	74.0	-30.93	Peak	Vertical
*	7236.0	36.54	13.79	50.33	73.8	-23.47	Peak	Vertical
*	7910.5	36.50	15.04	51.54	73.8	-22.26	Peak	Vertical


Note: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (93.8dBμV/m)

Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

The worst case of Radiated Emission below 1GHz:

Engineer: Line Chen	
Site: AC1	Time: 2014/06/04 - 16:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: Transmit at 802.11n-HT40 Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			96.687	18.942	6.634	-24.558	43.500	12.308	PK
2		*	729.491	25.121	3.844	-20.879	46.000	21.277	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/04 - 16:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: VULB9162_0.03-8GHz	Polarity: Vertical
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: Transmit at 802.11n-HT40 Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			669.472	23.822	3.457	-22.178	46.000	20.365	PK
2		*	750.468	25.861	4.324	-20.139	46.000	21.537	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

Engineer: Roy Cheng	
Site: AC1	Time: 2014/06/04 - 16:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: FMZB1519_0.009-30MHz	Polarity: Face On
EUT: MID	Power: AC 120V/60Hz
Note: There is the ambient noise within frequency range 9kHz~30MHz.	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			0.049	50.367	29.861	-63.422	113.789	20.505	PK
2		*	0.105	44.143	23.996	-63.029	107.173	20.147	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

Engineer: Roy Cheng	
Site: AC1	Time: 2014/06/04 - 16:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: FMZB1519_0.009-30MHz	Polarity: Face On
EUT: MID	Power: AC 120V/60Hz
Note: There is the ambient noise within frequency range 9kHz~30MHz.	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2.513	30.495	10.336	-39.005	69.500	20.159	PK
2		*	7.041	30.974	10.579	-38.526	69.500	20.395	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

Engineer: Roy Cheng	
Site: AC1	Time: 2014/06/04 - 17:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9170_18-40GHz	Polarity: Horizontal
EUT: MID	Power: AC 120V/60Hz
Note: There is the ambient noise within frequency range 18 ~ 25GHz.	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			21517.500	55.869	17.883	-18.131	74.000	37.986	PK
2			21517.650	43.351	5.365	-10.649	54.000	37.986	AV
3			22630.500	56.509	18.223	-17.491	74.000	38.286	PK
4		*	22630.540	44.310	6.024	-9.690	54.000	38.286	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

Engineer: Roy Cheng	
Site: AC1	Time: 2014/06/04 - 17:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9170_18-40GHz	Polarity: Vertical
EUT: MID	Power: AC 120V/60Hz
Note: There is the ambient noise within frequency range 18 ~ 25GHz.	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			22686.500	55.811	17.457	-18.189	74.000	38.354	PK
2		*	22686.540	43.598	5.244	-10.402	54.000	38.354	AV
3			24205.500	56.430	17.607	-17.570	74.000	38.823	PK
4			24205.658	42.518	3.695	-11.482	54.000	38.823	AV


Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) + Amp Factor(dB).

7.7. Radiated Restricted Band Edge Measurement

7.7.1. Test Result

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:13
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	57.470	26.786	-16.530	74.000	30.684	PK
2		*	2415.000	92.218	61.578	N/A	N/A	30.640	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	44.258	13.574	-9.742	54.000	30.684	AV
2		*	2414.440	82.197	51.556	N/A	N/A	30.641	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:17
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	58.076	27.392	-15.924	74.000	30.684	PK
2		*	2408.784	92.867	62.217	N/A	N/A	30.650	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: Test Mode: 802.11n-HT20 Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	44.408	13.724	-9.592	54.000	30.684	AV
2		*	2417.408	82.960	52.324	N/A	N/A	30.636	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2459.656	90.976	60.368	N/A	N/A	30.608	PK
2			2483.500	56.222	25.549	-17.778	74.000	30.673	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2459.584	80.225	49.617	N/A	N/A	30.608	AV
2			2483.500	43.513	12.840	-10.487	54.000	30.673	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2468.608	92.223	61.594	N/A	N/A	30.629	PK
2			2483.500	56.027	25.354	-17.973	74.000	30.673	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

Engineer: Line Chen	
Site: AC1	Time: 2014/06/16 - 17:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: MID	Power: AC 120V/60Hz
Worst Case Mode: 802.11n-HT20 Channel 2462MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2467.648	81.749	51.123	N/A	N/A	30.626	AV
2			2483.500	43.604	12.931	-10.396	54.000	30.673	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

7.8. AC Conducted Emissions Measurement


7.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 – 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2. Test Setup



7.8.3. Test Result

Engineer: Line Chen	
Site: SR2	Time: 2014/06/03 - 13:07
Limit: FCC_Part15.207_CE_AC Power	Margin: 0
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: MID	Power: AC 120V/60Hz
Note: Mode: Normal Operation	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		*	0.158	55.646	45.335	-9.923	65.568	10.311	QP
2			0.158	39.557	29.246	-16.011	55.568	10.311	AV
3			0.234	47.558	37.608	-14.748	62.307	9.951	QP
4			0.234	32.784	22.833	-19.523	52.307	9.951	AV
5			0.326	39.901	29.876	-19.652	59.552	10.025	QP
6			0.326	25.330	15.305	-24.223	49.552	10.025	AV
7			0.390	39.967	29.890	-18.096	58.064	10.077	QP
8			0.390	27.353	17.276	-20.711	48.064	10.077	AV
9			0.742	38.267	28.225	-17.733	56.000	10.041	QP
10			0.742	21.940	11.898	-24.060	46.000	10.041	AV
11			20.394	50.046	39.898	-9.954	60.000	10.148	QP
12			20.394	28.312	18.163	-21.688	50.000	10.148	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

Engineer: Line Chen	
Site: SR2	Time: 2014/06/03 - 13:15
Limit: FCC_Part15.207_CE_AC Power	Margin: 0
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: MID	Power: AC 120V/60Hz
Note: Mode: Normal Operation	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.162	49.726	39.647	-15.635	65.361	10.078	QP
2			0.162	35.286	25.207	-20.075	55.361	10.078	AV
3			0.234	44.818	34.829	-17.489	62.307	9.989	QP
4			0.234	32.307	22.318	-19.999	52.307	9.989	AV
5			0.494	46.087	35.908	-10.014	56.100	10.178	QP
6			0.494	25.572	15.393	-20.529	46.100	10.178	AV
7			0.570	50.027	39.879	-5.973	56.000	10.148	QP
8			0.570	34.828	24.680	-11.172	46.000	10.148	AV
9		*	20.442	56.618	46.436	-3.382	60.000	10.182	QP
10			20.442	45.267	35.084	-4.733	50.000	10.182	AV
11			23.370	54.299	44.047	-5.701	60.000	10.252	QP
12			23.370	37.697	27.445	-12.303	50.000	10.252	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **MID FCC ID: OI2M723C** is in compliance with Part 15C of the FCC Rules.