

Class B Certification Application

Under part 15, subpart B

EUT : WIRELESS MICROPHONES

MODEL : VHF-36

FCC ID : OI5-TR242A

SRT REPORT # T8G06-1

PREPARED FOR :

CALON ELECTRONIC CO., LTD.

36, LANE 105, PEIKANG RD., SEC. 2,
TAIPAO CITY, CHIA-YI COUNTY,
TAIWAN, R.O.C.

COMPANY: CALON ELECTRONIC CO., LTD

ADDRESS: 36, LANE 105, PEIKANG RD., SEC., 2, TAIPAO CITY CHIA - YI COUNTY
TAIWAIN, R.O.C.

TEL: 886-5-2378756 FAX: 886-5-2380237

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046

To whom it may concern :

This is to serve as proper written authorization that Spectrum Research and Testing Laboratory, Inc., 15200, Shady Grove Rd., Rockville, MD. 20850, will act as our representative in all matters relating to FCC applications for equipment approval. This includes the signing of all related documents, the transmitting of required fees, and receiving correspondence and notifications from the FCC. All acts performed by Spectrum Research and Testing Laboratory, Inc., especially modifications to our equipment under testing will be carried out on our behalf.

Meantime, the applicant certifies that in the case of an individual applicant (e.g., corporation), no party to the applicant is subject to a denial of federal benefits, that includes FCC denial of federal benefits, that includes FCC benefits, pursuant to Section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 862. For a definition of a " party " for these purposes see 47 C.F.R. 1.2002 (b).

If you have any questions regarding our applications for equipment approval, please contact Spectrum Research and Testing Laboratory, Inc. by calling (301) 670-2818.

Respectfully,

you Kuen chia
(Name, Surname)

PRESIDENT
(Position/Title)

Effective Dates :

From 1999-3-30 to 2000-3-30

DATE : 1999-3-30

EMI TESTING REPORT

EUT : WIRELESS MICROPHONES

MODEL : VHF-36

FCC ID : OI5-TR242A

PREPARED FOR :

CALON ELECTRONIC CO., LTD.

36, LANE 105, PEIKANG RD., SEC. 2,

TAIPAO CITY, CHIA-YI COUNTY

TAIWAN, R.O.C.

PREPARED BY :

SPECTRUM RESEARCH & TESTING LABORATORY INC.
NO. 101-10, LING 8, SHAN-TONG LI CHUNG-LI CITY,
TAOYUAN, TAIWAN, R. O. C.

TEL : (03) 4987684

FAX : (03) 4986528

TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION.....	4
2. TEST STATEMENT	
2.1 TEST STATEMENT.....	5
2.2 DEPARTURE FROM DOCUMENT POLICIES, PROCEDURE OR SPECIFICATIONS, TEST STATEMENT.....	5
3. EUT MODIFICATIONS.....	6
4. MODIFICATION LETTER.....	7
5. CONDUCTED POWER LINE TEST	
5.1 TEST EQUIPMENT.....	8
5.2 TEST PROCEDURE.....	8
5.3 TEST SETUP.....	9
5.4 CONFIGURATION OF THE EUT.....	10-11
5.5 EUT OPERATING CONDITION.....	12
5.6 EMISSION LIMIT.....	12
5.7 EMISSION TEST RESULT.....	13-14
6. RADIATED EMISSION TEST	
6.1 TEST EQUIPMENT.....	15
6.2 TEST PROCEDURE.....	16
6.3 TEST SETUP.....	16-17
6.4 CONFIGURATION OF THE EUT.....	18
6.5 EUT OPERATING CONDITION.....	18
6.6 EMISSION LIMIT.....	18
6.7 RADIATION EMISSION TEST RESULT.....	19-20
7. BANDWIDTH	
7.1 LIMIT.....	21
7.2 RESULT.....	21
8. PHOTOS OF TESTING.....	22-36

1. TEST REPORT CERTIFICATION**APPLICANT** : CALON ELECTRONIC CO., LTD.**ADDRESS** : 36, LANE 105, PEIKANG RD., SEC. 2,
TAIPAO CITY, CHIA-YI COUNTY,
TAIWAN, R. O. C.**EUT DESCRIPTION** : WIRELESS MICROPHONE(A) POWER SUPPLY : FROM ADAPTOR(B) MODEL : VHF-36(C) FCC ID : OI5-TR242A**FINAL TEST DATE** : 10/04/1999**MEASUREMENT PROCEDURE USED :**

* PART 15 SUB PART B OF FCC RULES AND REGULATIONS (47 CFR PART 15)

* ANSI C63.4 - 1992

* TEST PROCEDURE AND DATA ARE TRACEABLE TO NATIONAL OR INTERNATIONAL STANDARDS.

We hereby show that :

The measurement shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable.

TESTING ENGINEER : Raven Hu DATE 10/04/1999

Raven Hu

SUPERVISOR : Jesse Ho DATE 10/4/99

Jesse Ho

APPROVED BY : Johnson Ho DATE 10/4/99

Johnson Ho

2. TEST STATEMENT

2.1 TEST STATEMENT

1. This letter is to explain the test condition of this project.
The EUT be tested as the following status.
2. The data was shown in this report reflects the worst-case data for the condition as listed above.
Please disregard any other oricessir(s) speed shown in this user manual.
3. EUT Conditions:

Operating frequency: VHF frequency 180 to 240MHz
Depend on OSC or crystal set up frequency.
4. NVLAP logo is to be approved by management (it is according to NVLAP requirement if it need) before use.

2.2 DEPARTURE FROM DOCUMENT POLICIES, PROCEDURE OR SPECIFICATIONS, THE STATEMENT

- A. Did have
Any departure from document policies & procedures or from specifications.
Yes _____, No ✓
If yes, the description as below.
- B. The certificate and report shall not be reproduced except in full, without the written approval of SRT laboratory.
- C. The report must not be used by the client to claim product endorsement by NVLAP or any agency the government.
- D. This product is a prototype product.
- E. The effect that the results relate only to the items tested.

3. EUT MODIFICATIONS

The following accessories were added to the EUT during testing :

- 1). Operating frequency : 183MHz
Parallel a 15pf of cap. with two pins of oscillator.
- 2). Operating frequency : 220MHz
Parallel a 10pf of cap. with two pins of oscillator.

4. MODIFICATION LETTER

This section contains the following documents :

- A. Letter of modifications

COMPANY: CALON ELECTRONIC CO., LTD

ADDRESS: 36, LANE 105, PEIKANG RD., SEC., 2, TAIPAO CITY CHIA - YI COUNTY
TAIWAIN, R.O.C.

TEL: 886-5-2378756 FAX: 886-5-2380237

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046

To whom it may concern :

This is to serve as proper notice that our company agrees to make
all modifications to FCC ID : OI5-TR242A as listed in section
3.0 of modification to submitted by Spectrum Research and Testing
Laboratory, Inc.

Respectfully,

you Kuen chia .
(Name, Surname)

PRESIDENT
(Position/Title)

Effective Dates :

From 1999.3.30 to 2000.3.30

DATE : 1999.3.30

5. CONDUCTED POWER LINE TEST



5.1 TEST EQUIPMENT

The following test equipment were used during the conducted power line test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DATE OF CAL. & CAL. CENTER	DUE DATE	FINAL TEST
SPECTRUM ANALYZER	9 KHz TO 1 GHz	HP	8590L/ 3624A01317	AUGUST 1999 ETC	1Y	
EMI TEST RECEIVER	9 KHz TO 30 MHz	ROHDE & SCHWARZ	ESHS30/ 826003/008	AUGUST 1999 ETC	1Y	√
LISN	50 uH, 50 ohm	SOLAR ELECTRONICS	9252-50- R24-BNC/ 951315	AUGUST 1999 ETC	1Y	√
LISN	50uH, 50 ohm	SOLAR ELECTRONICS	9252-50- R24-BNC/ 951318	AUGUST 1999 ETC	1Y	√
SIGNAL GENERATOR	9 KHz TO 1080 MHz	ROHDE & SCHWARZ	SMY01/ 841104/019	APRIL 1999 ETC	1Y	√
POWER CONVERTER	0 TO 300 VAC VAC 47-500 Hz	AFC	AFC-1KW/ 850510	MARCH 1999 ETC	1Y	√

5.2 TEST PROCEDURE

The EUT was tested according to ANSI C63.4 - 1992. The frequency spectrum from 0.45 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 uHenry as specified by SECTION 5.1 of ANSI C63.4 - 1992. Cables and peripherals were moved to find the maximum emission levels for each frequency.

5.3 TEST SETUP

5.4 CONFIGURATION OF THE EUT

The EUT was configured according to ANSI C63.4 - 1992. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

DEVICE	MANUFACTURER	MODEL #	FCCID
WIRELESS MICROPHONES	CALON ELECTRONIC CO., LTD.	VHF-36	O15-TR242

B. INTERNAL DEVICES

DEVICE	MANUFACTURER	MODEL #	FCCID / Doc
N/A			

C. PERIPHERALS

DEVICE	MANUFAC- TURER	MODEL # SERIAL #	FCCID / DoC	CABLE
SPEAKER	LS	LS-28	N/A	1.5m unshielded data cable
ADAPTOR	MOREX	DV-1250	N/A	1.8m unshielded power cord

REMARK :

- (1). Cable - S1 : Single point shielding
S2 : 360° shielding
S3 : Double shielding
- (2). Cables - all 1m or greater in length – bundled according to ANSI C63.4 – 1992.

5.5 EUT OPERATING CONDITION

Operating condition is according to ANSI C63.4 - 1992.

1. EUT power on.
2. Operating frequency : VHF frequency 180 to 240MHz
3. Depend on OSC or crystal set up frequency.

5.6 CONDUCTED POWER LINE EMISSION LIMIT

FREQUENCY RANGE (MHz)	CLASS A	CLASS B
0.45 - 1.705	1000 uV	250 uV
1.705 - 30	3000 uV	250 uV

NOTE : In the above table, the tougher limit applies at the band edges.

5.7 CONDUCTED POWER LINE TEST RESULT

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All readings are quasi-peak values with a resolution bandwidth of 9 KHz.

Temperature : 25 °CHumidity : 44 %RH

FREQUENCY (MHz)	LINE1 (uV)	LINE2 (uV)	LIMIT (uV)
0.45	*	62.37	250
0.49	3.89	*	250
0.76	11.09	27.23	250
1.06	*	7.24	250
1.12	3.43	*	250
15.57	*	2.72	250
28.64	2.88	*	250

REMARKS : (1). * = Measurement does not apply for this frequency
(2). Uncertainty in conducted emission measured is <+/-2dB
(3). Any departure from specification : N/A
(4). Operating frequency : 183MHz

SIGNED BY TESTING ENGINEER : Raven Hu

5.7 CONDUCTED POWER LINE TEST RESULT

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All readings are quasi-peak values with a resolution bandwidth of 9 KHz.

Temperature : 25 °CHumidity : 44 %RH

FREQUENCY (MHz)	LINE1 (uV)	LINE2 (uV)	LIMIT (uV)
0.45	59.57	*	250
0.62	*	23.17	250
0.76	24.83	8.32	250
1.03	7.50	*	250
1.13	*	3.85	250
15.55	1.48	*	250
29.65	*	1.19	250

REMARKS : (1). * = Measurement does not apply for this frequency
(2). Uncertainty in conducted emission measured is <+/-2dB
(3). Any departure from specification : N/A
(4). Operating frequency : 220MHz

SIGNED BY TESTING ENGINEER : Raven Hu

6. RADIATED EMISSION TEST**6.1 TEST EQUIPMENT**


The following test equipment were used during the radiated emission test :

EQUIPMENT / FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL # / SERIAL #	DATE OF CAL. & CAL. CENTER	DUE DATE	FINAL TEST
RECEIVER	20 MHz TO 1000 MHz	R & S	ESVS30/ 841977/003	APRIL 1999 ETC	1Y	√
SPECTRUM ANALYZER	100 Hz TO 1500 MHz	HP	8568B/ 3019A05294	OCT. 1998 ETC	1Y	
SPECTRUM ANALYZER	9 KHz TO 22 GHz	HP	8593E/ 3322A00670	MAY 1999 ETC	1Y	
SPECTRUM ANALYZER	100 Hz TO 1000 MHz	IFR	A-7550/ 2684/1248	JULY 1999 ETC	1Y	
SIGNAL GENERATOR	9 KHz TO 1080 MHz	ROHDE & SCHWARZ	SMY01/ 841104/019	APRIL 1999 ETC	1Y	√
DIPOLE ANTENNA	28 MHz TO 1000 MHz	EMCO	3121C/ 9003-534	MAR. 1999 SRT	1Y	
DIPOLE ANTENNA	28 MHz TO 1000 MHz	EMCO	3121C/ 9611-1239	SEP. 1999 SRT	1Y	
BI-LOG ANTENNA	26 MHz TO 2000 MHz	EMCO	3142/ 9608-1073	SEP. 1999 SRT	1Y	√
BI-LOG ANTENNA	26 MHz TO 1100 MHz	EMCO	3143/ 9509-1152	SEP. 1999 SRT	1Y	
PRE-AMPLIFIER	0.1 MHz TO 1300 MHz	HP	8447D/ 2944A08402	APRIL 1999 ETC	1Y	
PRE-AMPLIFIER	0.1 MHz TO 1300 MHz	HP	8447D/ 2944A06412	AUGUST 1999 ETC	1Y	
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9012-3619	JAN. 1999 EMCO	1Y	

6.2 TEST PROCEDURE

- (1).The EUT was tested according to ANSI C63.4-1992. The radiated test was performed at SRT lab's open site. this site is on file with the FCC laboratory division, reference 31040/SIT.
- (2).The EUT, peripherals, were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-1992.
- (3).The frequency spectrum from 30 MHz to 2.4 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4). The antenna high were varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5). The antenna polarization : Vertical polarization and horizontal polarization.


6.3 RADIATED TEST SET-UP



6.3 RADIATED TEST SET-UP

ANSI C63.4-1992

ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE RANGE IN THE RANGE OF 9 KHz TO 40 GHz



6.4 CONFIGURATION OF THE THE EUT

Same as section 5.4 of this report

6.5 EUT OPERATING CONDITION

Same as section 5.5 of this report.

6.6 RADIATED EMISSION LIMIT

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below :

CLASS B

FREQUENCY (MHz)	DISTANCE (m)	FIELDS STRENGTH (uV/m)
30 - 88	3	100
88 - 216	3	150
216 - 960	3	200
ABOVE 960	3	500

CLASS B (OPEN CASE)

FREQUENCY (MHz)	DISTANCE (m)	FIELDS STRENGTH (uV/m)
30 - 88	3	199.5
88 - 216	3	298.5
216 - 960	3	398.1
ABOVE 960	3	

CLASS A

FREQUENCY (MHz)	DISTANCE (m)	FIELDS STRENGTH (uV/m)
30 - 88	3	316.3
88 - 216	3	473.2
216 - 960	3	613.0
ABOVE 960	3	1000.0

NOTE : 1. In the emission tables above, the tougher limit applies at the band edges.

2. Distance refers to the distance between measuring instrument, antenna, and the closest point of any part of the device or system.

6.7 RADIATED EMISSION TEST RESULT

The frequency spectrum from 30 MHz to 2.4 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. Measurements were made at 3 meters. The measurements above 1 GHz with a resolution bandwidth of 1 MHz are peak reading at a distance of 3 meters.

Temperature : 24 °CHumidity : 56 %RH

FREQ. (MHz)	FACTOR (dB)	ANT. FACTOR (dB/m)	READING (dBuV)		EMISSION (Uv/m)		LMTS (uV/m)
			HORIZ	VERT	HORIZ	VERT	
179.8400	1.1	10.7	*	20.1	*	39.4	150
183.4380	1.2	15.5	23.5	23.7	102.3	104.7	1500
193.5145	1.2	11.7	*	19.6	*	42.2	150
231.6000	1.3	13.7	28.4	*	147.9	*	200
693.2100	2.2	21.9	16.3	*	104.7	*	200
926.0100	3.0	24.3	13.7	*	112.2	*	200
926.8200	3.0	24.3	*	15.5	*	138.0	200

- REMARKS** : (1). *= Measurement does not apply for this frequency.
 (2). Uncertainty in radiated emission measured is ± 4 dB
 (3). Any departure from specification : N/A
 (4). Factor will include cable loss and correction factor.
 (5). Sample calculation

$$20 \log (\text{emission}) \text{ uV/m} = \text{Factor(dB)} + \text{Ant. factor(dB/m)} + \text{reading(dBuV)}$$

 (6). Operating frequency : 183MHz

SIGNED BY TESTING ENGINEER : Raven Hu

6.7 RADIATED EMISSION TEST RESULT

The frequency spectrum from 30 MHz to 2.4 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. Measurements were made at 3 meters. The measurements above 1 GHz with a resolution bandwidth of 1 MHz are peak reading at a distance of 3 meters.

Temperature : 24 °CHumidity : 56 %RH

FREQ. (MHz)	FACTOR (dB)	ANT. FACTOR (dB/m)	READING (dBuV)		EMISSION (uV/m)		LMTS (uV/m)
			HORIZ	VERT	HORIZ	VERT	
85.2350	0.8	8.3	25.8	*	55.6	*	100
193.5145	1.2	11.7	*	18.8	*	38.5	150
220.3660	1.2	15.9	12.6	10.9	30.5	25.1	1500
231.0230	1.3	13.7	25.9	*	110.9	*	200
694.2980	2.2	21.9	13.7	*	77.6	*	200
694.3200	2.2	21.9	*	15.2	*	92.3	200
926.8200	3.0	24.3	*	15.5	*	138.0	200

REMARKS : (1). *= Measurement does not apply for this frequency.

(2). Uncertainty in radiated emission measured is <+/-4dB

(3). Any departure from specification : N/A

(4). Factor will include cable loss and correction factor.

(5). Sample calculation

$$20 \log (\text{emission}) \text{ uV/m} = \text{Factor(dB)} + \text{Ant. factor(dB/m)} + \text{reading(dBuV)}$$

(6). Operating frequency : 220MHz

SIGNED BY TESTING ENGINEER : Raven Hu

7 BANDWIDTH

7.1 Limit

Minimum 6dB bandwidth = 100MHz

7.2 Test Result

Please see attached plotter.

10/27 '99 12:01 NO.579 01/03

22:31:58 OCT 26, 1999

MARKER Δ 10.88 kHz


REF 90.0 dB μ W

#AT 10 dB

.16 dB

PEAK
LOG
10
dB/

VA SB
SC FC
CORR



CLEAR

WRITE A

MAX

HOLD A

VIEW A

BLANK A

Trace

A B C

More

1 of 3

CENTER 183.43688 MHz

#RES BW 3.0 kHz

VBW 3 kHz

SWP 100 msec

SPAN 50.00 kHz

SWP 100 msec

10/27 '99 12:07 NO.579 03/03

22: 47: 45 OCT 26, 1999

17

MKR Δ 11.38 kHz

REF 90.0 dB μ V

#AT 10 dB

-1.23 dB

PEAK

LOG

10

dB/

MARKER
NORMA...

MARKER

MARKER Δ
11.38 kHz
-1.23 dB

SFO 140

MARKER
AMPTD

SELECT
1 2 3 4

VA SB
SC FC
CORR

MARKER 1
ON OFF

MORE
1 of 2


CENTER 220.35975 MHz

#RES BW 3.0 kHz

VBW 3 kHz

SPAN 50.00 kHz

SWP 100 msec



10/27 '99 12:01 NO.579 02/03

22:37:56 OCT 26, 1999

REF 90.0 dB μ V

#AT 10 dB

MKR Δ 10.25 kHz

-.45 dB

PEAK

LOG

10

dB/

MARKER
NORMAL

MARKER
☐ Δ

MARKER
AMPTD

SELECT
1 2 3 4

MARKER 1
ON OFF

More
1 of 2

VA SB
SC FC
CORR

MARKER Δ
10.25 kHz
-.45 dB

CENTER 233.47163 MHz

#RES BW 3.0 kHz

VBW 3 kHz

SPAN 50.00 kHz

SWP 100 msec