RETLIF TESTING LABORATORIES

TABULAR DATA SHEET

TEST METHOD: **Radiated Emissions 30MHz to 25GHz**

CUSTOMER: Wireless Manufacturing | JOB No.: R-3435N

TEST SAMPLE: Wireless Bridge with 2.4GHZ Spread Spectrum Transmitter Patch Antenna

MODEL No.: BR1200 FCC ID# OIA-BR1200 | SERIAL No.: n/a

TEST SPECIFICATION: FCC Part 15 | PARAGRAPH: 15.205 15.209

OPERATING MODE: Continuously Transmitting

TECHNICIAN: M. Hippert | DATE: 4-23-99

NOTES: Test Distance: 3 Meters

TRANSMIT FREQUENCY	TEST FREQUENCY	ANTENNA POSITION	TURNTABLE POSITION	METER READING	CORRECTION FACTOR	CORRECTED READING	CONVERTED READING	LIMIT @ 3 METERS
MHz	MHz	(H/V)-HEIGHT	DEGREES	dBuV	dB	dBuV/m	uV/m	uV/m
2,460.5	30.0	-	-	-	-	-	-	300.0
	I	-	-	-	-	-	-	I
	125.0	V 1m	315.0	47.3	-11.3	36.0	63.1	500.0
	240.5	V 1m	0.0	43.5	-5.6	37.9	78.5	500.0
	300.0	V 1m	0.0	39.9	-3.6	36.3	65.3	500.0
	I	-	-	-	-	-	-	-
	2,460.5	V 1m	0.0	24.7	39.3	64.0	1584.9	No Limit
	I	-	-	-	-	-	-	-
	25,000.0	-	-	-	-	-	-	158.5

EUT emissions observed throughout the given frequency spectrum were recorded and evaluated. Emission levels closest to the limit are listed on this data sheet.