

TEST REPORT



DANAK

Reg. no. 19

DELTA

DELTA
Electronics Testing


Venlighedsvej 4
DK-2970 Hørsholm
Denmark

Tel. (+45) 45 86 77 22
Fax (+45) 45 86 58 98
www.delta.dk

*This report is issued
under the rules of
DANAK (The Danish
Accreditation Scheme)
– see overleaf.*

*The report must not
be reproduced,
except in full,
without the written
approval of DELTA.*

**Measurements of radio frequency Interference from
EasyCom Xpress 62 411 Including SafeCom X34 150
Manufactured by i-data International A/S
Project no.: K220864-1
Date: 1999-07-05**



Title Measurements of radio frequency interference from
EasyCom Xpress 62 411 including SafeCom X34 150

Test object EasyCom Xpress 62 411 including SafeCom X34 150

Report no. DANAK-194612

Project no. K220864-1

Date of test 1999-06-17

Client i-data International A/S
Vadstrupvej 27
DK-2880 Bagsværd
Denmark

Telephone: +45 44 36 60 00
Fax: +45 44 36 61 11

Contact person Mr. Jens Henneke


Manufacturer i-data International A/S

Specification EN 55022:1994 (CISPR 22:1985 + A1 + A2) class B
+ A1 + A2
FCC part 15 Subpart B class B demonstrated by
compliance with EN 55022:1994, class B.

Test personnel Henrik Egeberg Nielsen

Results The emission from the EasyCom Xpress 62 411 including
SafeCom X34 150 was below the limit of the above
specifications.

Date 1999-07-05

Project manager 
Per Hansen, Facility Manager, EMC
DELTA Electronics Testing


Responsible 
Jørgen Duvald Christensen
Department Manager, EMC
DELTA Electronics Testing

	TABLE OF CONTENTS	PAGE
1.	SUMMARY OF TEST RESULTS	4
2.	TEST SPECIMEN	5
3.	GENERAL TEST CONDITIONS	6
3.1	Test set-up	6
4.	TESTS AND RESULTS	8
4.1	Conducted emission, AC mains (EN 55022, class B)	8
4.2	Radiated electromagnetic field (EN 55022, class B)	9
4.3	Conducted emission, AC mains (FCC class B / EN55022, class B)	10
4.4	Radiated electromagnetic field (FCC class B / EN55022, class B)	11
ANNEX 1	List of instruments	
ANNEX 2	Test record sheets and photos regarding conducted emission, AC mains (EN 55022, class B)	
ANNEX 3	Test record sheets and photos regarding radiated electromagnetic field (EN 55022, class B)	
ANNEX 4	Test record sheets and photos regarding conducted emission, AC mains (FCC class B / EN55022, class B)	
ANNEX 5	Test record sheets and photos regarding radiated electromagnetic field (FCC class B / EN55022, class B)	

1. SUMMARY OF TEST RESULTS

The results of the emission tests can be summarised as follows:

Emission tests	EN 55022:1994 (CISPR 22: 1985 + A1 + A2) class B + A1 + A2	FCC part 15 Subpart B class B *
Conducted emission, AC mains	Passed	Passed
Radiated electromagnetic field	Passed	Passed

Abbreviations : Passed : The emission was below the limit.
Not done : No test was performed.
N/A : Not applicable.
Not relevant : The test was not relevant for the test object.

* The FCC class B was demonstrated by compliance with EN 55022:1994, class B.

The test results relate only to the specimen tested.

2. TEST SPECIMEN 1

Category : Card Reader
Manufacturer : i-data International A/S
Model/Type : SafeCom X34 150
Part no. : -
Serial no. : -
Supply voltage : 12 VDC from 115 VAC
Operational mode : Normal operation

TEST SPECIMEN 2

Category : Printer server
Manufacturer : i-data International A/S
Model/Type : EasyCom Xpress X62 411
Part no. : -
Serial no. : -
Supply voltage : 5 VDC from SafeCom X34 150 via communication cable
Operational mode : Normal operation

3. GENERAL TEST CONDITIONS

3.1 Test set-up




FIG. 1 Test set-up including test object and peripheral equipment.

The complete system used during the tests consisted of the following units:

3.1.1	Card Reader	EUT 1
	Manufacturer	: i-data International A/S
	Model/type	: SafeCom X34 150
	Part no.	: -
	Serial no.	: -
	FCC ID.	: -
3.1.2	Printer Server	EUT 2
	Manufacturer	: i-data International A/S
	Model/type	: EasyCom Xpress X62 411
	Part no.	: -
	Serial no.	: -
	FCC ID.	: -
3.1.3	AC / DC Adapter	
	Manufacturer	: FRIWO
	Model/type	: FW 3288
	Part no.	: -
	Serial no.	: -
	FCC ID	: -
3.1.4	Printer	
	Manufacturer	: Hewlett Packard
	Model/type	: C1676A
	Part no.	: -
	Serial no.	: SGC5302456
	FCC ID	: B94C1676
3.1.5	AC / DC Adapter	
	Manufacturer	: EIA
	Model/type	: T48-6-1000D
	Part no.	: 363 9836 E
	Serial no.	: -
	FCC ID	: -
3.1.6	HUB (100 Mbit)	
	Manufacturer	: EDIMAX Palmtop Dual speed Hub
	Model/type	: ED 15048
	Part no.	: CE2400049
	Serial no.	: -
	FCC ID	: (DoC)

4. TESTS AND RESULTS

4.1 Conducted emission, AC mains (EN 55022, class B)

	Requirements	
Specification	EN 50081-1:1992	
Test method	EN 55022:1994 (CISPR 22:1985 + A1 + A2) class B + A1 + A2	
Frequency range	0.15 - 30 MHz	
Limit: (quasi-peak)	0.15-0.50 MHz: (decreasing lin. with the logarithm of freq.)	66-56 dB μ V
	0.50-5 MHz:	56 dB μ V
	5-30 MHz:	60 dB μ V
Limit: (average)	0.15-0.50 MHz: (decreasing lin. with the logarithm of freq.)	56-46 dB μ V
	0.50-5 MHz:	46 dB μ V
	5-30 MHz:	50 dB μ V
Test record sheets and photos		<i>Annex 2</i>

Results:

The emission was within the specified limits.

Comments:

The supply voltage to EUT 1 was 12 VDC from the 115 VAC adapter. EUT 2 was powered with 5 VDC from EUT 1.

4.2 Radiated electromagnetic field (EN 55022, class B)

	Requirements	
Specification	EN 50081-1:1992	
Test method	EN 55022:1994 (CISPR 22:1985 + A1 + A2) class B + A1 + A2	
Measuring distance	10 m	
Frequency range	30 - 1000 MHz	
Limit: (quasi-peak)	30-230 MHz:	30 dB μ V/m
	230-1000 MHz:	37 dB μ V/m
Test record sheets and photos		<i>Annex 3</i>

Results:

The emission was within the specified limits.

Comments:

The supply voltage to EUT 1 was 12 VDC from the 115 VAC adapter. EUT 2 was powered with 5 VDC from EUT 1.

4.3 Conducted emission, AC mains (FCC, class B / EN 55022, class B)

	Requirements	
Specification	FCC Rules and Regulations:1997, part 15, subpart B class B, demonstrated by compliance with EN 55022:1994, class B	
Test method	CISPR 22:1985 + A1 + A2	
Frequency range	0.15 - 30 MHz	
Test set-up	ANSI C63.4:1992	
Limit: (quasi-peak)	0.15-0.50 MHz: (decreasing lin. with the logarithm of freq.)	66-56 dB μ V
	0.50-5 MHz:	56 dB μ V
	5-30 MHz:	60 dB μ V
Limit: (average)	0.15-0.50 MHz: (decreasing lin. with the logarithm of freq.)	56-46 dB μ V
	0.50-5 MHz:	46 dB μ V
	5-30 MHz:	50 dB μ V
Test record sheets and photos		
Annex 4		

Results:

The emission was within the specified limits.

Comments:

The supply voltage to EUT 1 was 12 VDC from the 115 VAC adapter. EUT 2 was powered with 5 VDC from EUT 1.

4.4 Radiated electromagnetic field (FCC, class B / EN 55022, class B)

	Requirements	
Specification	FCC Rules and Regulations:1997, part 15, subpart B, class B, demonstrated by compliance with EN 55022:1994, class B	
Test method	CISPR 22:1985 + A1 + A2	
Test set-up	ANSI C63.4:1992	
Measuring distance	10 m	
Frequency range	30 - 1000 MHz	
Limit: (quasi-peak)	30-230 MHz:	30 dB μ V/m
	230-1000 MHz:	37 dB μ V/m
Test record sheets and photos		
Annex 5		

Results:

The emission was within the specified limits.

Comments:

The supply voltage to EUT 1 was 12 VDC from the 115 VAC adapter. EUT 2 was powered with 5 VDC from EUT 1.

DANAK-194612
DELTA-K220864-1

ANNEX 1

List of instruments

(1 page)

DANAK-194612
DELTA-K220864-1

LIST OF INSTRUMENTS

EC NO.	INSTRUMENT	MANUFACTURER	TYPE
29985	BILOG ANTENNA, 26-2000 MHz	CHAFFNER / CHASE	6140A
29461	ARTIFICIAL MAINS NETWORK	ROHDE & SCHWARZ	ESH2-Z5
29916	AUTOMATIC EMI RECEIVER	ROHDE & SCHWARZ	ESCS-30
29861	EMI-SOFTWARE Ver. 1.50c	ROHDE & SCHWARZ	ES-K1, PART: 1026.6790.02

DANAK-194612
DELTA-K220864-1


ANNEX 2

Test record sheets and photos regarding
conducted emission, AC mains (EN 55022, class B)

(3 pages)


DELTA Electronics Testing

EUT: EasyCom Xpress and SafeCom
 Manufacturer: I-DATA
 Operating Condition: Line no.: Neutral. 115V
 Test Site: EMC-5
 Operator: HEN-K220864
 Test Specification: EN 55022 class B, **FA 3 (limited by compliance)**
 Comment: Sheet 3
 Start of Test: 1999-06-17



DELTA Electronics Testing

EUT: EasyCom Xpress and SafeCom 100 unit
 Manufacturer: I-DATA
 Operating Condition: Line no.: Line 1. 115 Vac
 Test Site: EMC-5
 Operator: HEN-K220864
 Test Specification: EN 55022 class B
 Comment: Sheet 4
 Start of Test: 1999-06-17



DANAK-194612
DELTA-K220864-1





PHOTO A2.1

ANNEX 3

Test record sheets and photos regarding
radiated electromagnetic field (EN 55022, class B)

(3 pages)

EUT: EasyCom Xpress and SafeCom. 100 Mbit
 Manufacturer: I-DATA
 Operating Condition: Ant. 1 m vertical. 115 Vac
 Test Site: EMC-5
 Operator: HEN-K220864
 Test Specification: EN 55022 class B, FCC B (demonstrated by compliance)
 Comment: Sheet 1
 Start of Test: 1999-06-17



17-06-99 15:19

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
30.600000	28.20	5.1	30.0	1.7	161.0	293.00	VERTICAL
64.800000	29.90	10.7	30.0	0.0	331.0	61.00	VERTICAL
66.300000	24.30	10.6	30.0	5.6	343.0	64.00	VERTICAL
106.700000	24.70	8.2	30.0	5.2	130.0	2.00	VERTICAL
198.720000	19.60	11.9	30.0	10.3	351.0	182.00	HORIZONTAL
250.000000	32.70	15.8	37.0	4.2	102.0	245.00	VERTICAL
700.000000	34.00	25.8	37.0	2.9	114.0	88.00	HORIZONTAL

DANAK-194612
DELTA-K220864-1




PHOTO A3.1




PHOTO A3.2

ANNEX 4

Test record sheets and photos regarding
conducted emission, AC mains (FCC class B, EN 55022 class B)


(3 pages)

EUT: EasyCom Xpress and SafeCom. 100 Mbit
 Manufacturer: I-DATA
 Operating Condition: Line no.: Neutral. 115 Vac
 Test Site: EMC-5
 Operator: HEN-K220864
 Test Specification: EN 55022 class B, **FCC B (demonstrated by compliance)**
 Comment: Sheet 3
 Start of Test: 1999-06-17



— MES CE 0.15-30 PK-AV Avg
 — MES CE 0.15-30 PK- MaxPk
 — LIM EN 55011 V AV
 — LIM EN 55011 V QP

EUT: EasyCom Xpress and SafeCom. 100 Mbit
 Manufacturer: I-DATA
 Operating Condition: Line no.: Line 1. 115 Vac
 Test Site: EMC-5
 Operator: HEN-K220864
 Test Specification: EN 55022 class B
 Comment: Sheet 4
 Start of Test: 1999-06-17



DANAK-194612
DELTA-K220864-1




PHOTO A4.1


(3 pages)

ANNEX 5

Test record sheets and photos regarding
radiated electromagnetic field (FCC, class B / EN 55022, class B)

(3 pages)

EUT: EasyCom Xpress and SafeCom. 100 Mbit
 Manufacturer: I-DATA
 Operating Condition: Ant. 1 m vertical. 115 Vac
 Test Site: EMC-5
 Operator: HEN-K220864
 Test Specification: EN 55022 class B, FCC B (demonstrated by compliance)
 Comment: Sheet 1
 Start of Test: 1999-06-17



x x : MES field_0001_fin QP
 MES RE 1mv 30-1000 MaxPk
 ---- LIM EN 55022 B F QP

17-06-99 15:19

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Height cm	Azimuth deg	Polarisation
30.600000	28.20	5.1	30.0	1.7	161.0	293.00	VERTICAL
64.800000	29.90	10.7	30.0	0.0	331.0	61.00	VERTICAL
66.300000	24.30	10.6	30.0	5.6	343.0	64.00	VERTICAL
106.700000	24.70	8.2	30.0	5.2	130.0	2.00	VERTICAL
198.720000	19.60	11.9	30.0	10.3	351.0	182.00	HORIZONTAL
250.000000	32.70	15.8	37.0	4.2	102.0	245.00	VERTICAL
700.000000	34.00	25.8	37.0	2.9	114.0	88.00	HORIZONTAL

DANAK-194612
DELTA-K220864-1




PHOTO A5.1




PHOTO A5.2