

FCC PART 15 SUBPART C
EMI MEASUREMENT AND TEST REPORT

For

Shenzhen Baoan Hantong Electronics Factory

Block 11 & 12, Jinbi Industrial Area
Hwangtian, Baoan, Shenzhen, China

FCC ID: OK839285HT02

January 15, 2003

This Report Concerns: ☒ Original Report	Equipment Type: 900MHz Cordless Telephone
Test Engineer: <u>Jeff Lee</u>	
Report No.: <u>R0211135</u>	
Test Date: <u>December 3, 2002</u>	
Reviewed By: <u>Benjamin Jing</u>	
 Prepared By: Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732-9164	

Note: This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 OBJECTIVE	3
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	3
1.4 TEST METHODOLOGY	3
1.5 TEST FACILITY	3
1.6 TEST EQUIPMENT LIST	4
1.7 LOCAL SUPPORT EQUIPMENT LIST AND DETAILS.....	4
1.8 EXTERNAL I/O CABLING LIST AND DETAILS.....	4
2 - SYSTEM TEST CONFIGURATION.....	5
2.1 DESCRIPTION OF TEST CONFIGURATION.....	5
2.2 EQUIPMENT MODIFICATIONS.....	5
2.3 CONFIGURATION OF TEST SYSTEM.....	5
2.4 TEST SETUP BLOCK DIAGRAM	5
3 - CONDUCTED EMISSIONS	6
3.1 MEASUREMENT UNCERTAINTY	6
3.2 EUT SETUP	6
3.3 SPECTRUM ANALYZER SETUP	6
3.4 TEST PROCEDURE	6
3.5 SUMMARY OF TEST RESULTS.....	7
3.6 CONDUCTED EMISSIONS TEST DATA.....	7
3.7 PLOT OF CONDUCTED EMISSIONS TEST DATA.....	7
4 - RADIATED EMISSIONS	8
4.1 MEASUREMENT UNCERTAINTY	8
4.2 EUT SETUP	8
4.3 SPECTRUM ANALYZER SETUP	8
4.4 TEST PROCEDURE	8
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	9
4.6 SUMMARY OF TEST RESULTS.....	9
4.7 RADIATED EMISSIONS TEST RESULT DATA	10
5 - BAND EDGES TESTING.....	14
5.1 TEST PROCEDURE	14
5.2 TEST EQUIPMENT	14
5.3 TEST RESULTS.....	14

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Applicant:	Shenzhen Baoan Hantong Electronics Factory
Product Description:	900MHz Cordless Phone
Model:	39285
FCC ID:	OK839285HT02
Dimension:	Base: 6.5"L x 5.75"W x 2.75"H Handset: 7.0"L x 2.25"W x 1.4"H
Power Supply:	Shenzhen Baoan AC/DC Adapter, U090035D

** The test data was good for test sample only. It may have deviation for other product samples.*

1.2 Objective

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4-1992.

The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the specification limits defined by FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.249.

1.3 Related Submittal(s)/Grant(s)

No related submittal(s)/grant(s).

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, CISPR 22: 1997, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8564E	08303	12/6/2003
HP	Spectrum Analyzer	8593B	2919A00242	12/20/2003
HP	Amplifier	8349B	2644A02662	12/20/2003
HP	Quasi-Peak Adapter	85650A	917059	12/6/2003
HP	Amplifier	8447E	1937A01046	12/6/2003
A.H. System	Horn Antenna	SAS0200/571	261	12/27/2003
Com-Power	Log Periodic Antenna	AL-100	16005	11/2/2003
Com-Power	Biconical Antenna	AB-100	14012	11/2/2003
Solar Electronics	LISN	8012-50-R-24-BNC	968447	12/28/2003
Com-Power	LISN	LI-200	12208	12/20/2003
Com-Power	LISN	LI-200	12005	12/20/2003
BACL	Data Entry Software	DES1	0001	12/20/2003

*Statement of Traceability: Bay Area Compliance Laboratory Corp. Certifies that all calibration has been performed using suitable standards traceable to the NATIONAL INSTITUTE of STANDARDS and TECHNOLOGY.

1.7 Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
Panasonic	Telephone	KX-T3175	80071	DOC
Telton Corp.	Simulator	TLS-3B-01	6IBTB142741	ACJMLA-75986-MT-E

1.8 External I/O Cabling List and Details

Cable Description	Length (M)	Port/From	To
Unshielded Telephone Cable	2.0	RJ11Port / EUT	Simulator
Unshielded Telephone Cable	2.0	RJ11 Port / Telephone	Simulator

2 - SYSTEM TEST CONFIGURATION

2.1 Description of Test Configuration

The EUT was configured for testing in a typical fashion (as normally used by a typical user).


Handset being tested: The Handset was placed on the wooden table and tested in three orthogonal axis. The handset was connected to the headset via its headset port. The Low, middle, and high channels were tested. The handset was transmitting to and receiving from the Base unit. The EUT was investigated for emissions while off hook. The radiated data was taken in this mode of operation. All initial and final investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously. The cables were bundled and routed as necessary.

Base being tested: The Base was placed on the wooden table. The Low, middle, and high channels were tested. The base was connected to the line simulator and an AC adapter via its Tel Line and power ports, respectively. The base was transmitting and receiving from the Handset. The conducted as well as radiated data was taken in this mode of operation. All initial and final investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously. The cables were bundled and routed as necessary.


2.2 Equipment Modifications

No modification(s) to the EUT were made by BACL to comply with the applicable limits.

2.3 Configuration of Test System



2.4 Test Setup Block Diagram



3 - CONDUCTED EMISSIONS

3.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

3.2 EUT Setup

The measurement was performed at the **Open Area Test Site**, using the same setup per ANSI C63.4-1992 measurement procedure. Specification used was with the FCC Class B limits.

The Base of EUT was connected to a 120Vac/60Hz power source and it was placed center and the back edge of the test table. The simulator was placed on one side of the EUT base, and the telephone was placed on the other side the EUT base. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.

The spacing between the peripherals was 10 centimeters.

The External I/O cables were draped over edge of the test table and bundle when necessary.

3.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configurations during the conducted emission test:

Start Frequency	450 kHz
Stop Frequency	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Video Bandwidth	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode.....	Normal

3.4 Test Procedure

During the conducted emission test, the EUT power cord was connected to the auxiliary outlet of the first LISN with all support equipment power cords connected to the second.

The EUT was tested to represent worst-case results for the final qualification test. Therefore, these results were used for final test data recorded in the table listed under section 3.6 of this report.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination. All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB of specification limit). Quasi-peak readings are distinguished with a "Qp".

3.5 Summary of Test Results

According to the data in section 3.6, the EUT complied with the FCC Conducted margin for a Class B device and these test results is deemed satisfactory evidence of compliance with RSS-210 of the Canadian Interference-Causing Equipment Regulations, with the *worst* margin reading of:


-2.2 dB μ V at 0.680 MHz in the Line mode

3.6 Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				FCC CLASS B	
Frequency	Amplitude	Detector	Phase	Limit	Margin
MHz	dB μ V	Qp/Ave/Peak	Line/Neutral	dB μ V	dB
0.680	45.8	QP	Line	48	-2.2
0.750	44.7	QP	Neutral	48	-3.3
1.390	40.2	QP	Line	48	-7.8
1.280	31.8	QP	Neutral	48	-16.2
7.940	22.7	QP	Line	48	-25.3
8.090	19.6	QP	Neutral	48	-28.4

3.7 Plot of Conducted Emissions Test Data

Plot of Conducted Emissions test data was presented hereinafter as reference.



4 - RADIATED EMISSIONS

4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

4.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup in accordance with the ANSI C63.4-1992. The specification used was the FCC 15 Subpart C limits.

The Base of EUT was connected to a 120Vac/60Hz power source and it was placed center and the back edge of the test table. The simulator was placed on one side of the EUT base, and the telephone was placed on the other side the EUT base. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.

The spacing between the peripherals was 10 centimeters.

The External I/O cables were draped over edge of the test table and bundle when necessary.

4.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR 15.33 (a) (1), the system was tested to 25GHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency	30MHz
Stop Frequency	25GHz
Sweep Speed.....	Auto
IF Bandwidth.....	1 MHz
Video Bandwidth	1 MHz
Quasi-Peak Adapter Bandwidth.....	120 kHz
Quasi-Peak Adapter Mode.....	Normal
Resolution Bandwidth.....	1MHz

4.4 Test Procedure

For the radiated emissions test, both the EUT and all support equipment power cords were connected to the AC floor outlet since the power supply used in the EUT did not provide an accessory power outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "Qp" in the data table.

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dBμV means the emission is 7dBμV below the maximum limit for applicable limits. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Applicable Limit}$$

4.6 Summary of Test Results

According to the data in section 4.7, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.249 after tested to 10th harmonics as required by FCC and had the worst margin of:

Base, 1GHz to 25GHz, intentional emission, 3 Meters

-4.9 dB at 902.12 MHz in the Vertical polarization at Low Channel
-5.0 dBμV at 903.29 MHz in the Vertical polarization at High Channel

Base, 30MHz to 1GHz, unintentional emission, 3 Meters

-9.0 dBμV at 302.15 MHz in the Vertical polarization

Handset, 1GHz to 25GHz, intentional emission, 3 Meters

-6.7 dBμV at 926.12 MHz in the Vertical polarization at Low Channel
-5.7 dBμV at 927.29 MHz in the Vertical polarization at High Channel

Handset, 30MHz to 1GHz, unintentional, 3 Meters

-21.9 dBμV at 191.76 MHz in the Horizontal polarization

4.7 Radiated Emissions Test Result Data**Base Unit, 30 MHz to 25GHz, 3 meters**

Indicated			Table	Antenna		Correction Factor			FCC 15 Subpart C		Comments
Frequency	Ampl.	Direction	Height	Polar	Antenna	Cable Loss	Amp.	Corr. Ampl.	Limit	Margin	
MHz	dBμV/m	Degree	Meter	H/V	dBμV/m	dBμV/m	dB	dBμV/m	dBμV/m	dB	
Low Channel											
902.12	86.3	270	1.5	V	24.8	3.0	25.0	89.1	94.0	-4.9	Peak
902.12	84.1	30	1.2	H	24.8	3.0	25.0	86.9	94.0	-7.1	Peak
4510.60	29.2	315	1.3	V	32.5	4.9	30.0	36.6	54.0	-17.4	Ave
1804.24	37.8	315	1.3	V	25.3	2.6	30.0	35.7	54.0	-18.3	Ave
2706.36	32.8	315	1.3	V	29.0	3.7	30.0	35.5	54.0	-18.5	Ave
4510.60	27.9	360	1.2	H	32.5	4.9	30.0	35.3	54.0	-18.7	Ave
2706.36	31.7	360	1.2	H	29.0	3.7	30.0	34.4	54.0	-19.6	Ave
1804.24	36.2	360	1.2	H	25.3	2.6	30.0	34.1	54.0	-19.9	Ave
3608.48	28.5	360	1.2	H	30.3	4.3	30.0	33.1	54.0	-20.9	Ave
3608.48	28.3	315	1.3	V	30.3	4.3	30.0	32.9	54.0	-21.1	Ave
4510.60	39.7	315	1.3	V	32.5	4.9	30.0	47.1	74.0	-26.9	Peak
2706.36	42.7	315	1.3	V	29.0	3.7	30.0	45.4	74.0	-28.6	Peak
4510.60	38.0	360	1.2	H	32.5	4.9	30.0	45.4	74.0	-28.6	Peak
2706.36	41.8	360	1.2	H	29.0	3.7	30.0	44.5	74.0	-29.5	Peak
1804.24	45.3	360	1.2	H	25.3	2.6	30.0	43.2	74.0	-30.8	Peak
3608.48	38.5	360	1.2	H	30.3	4.3	30.0	43.1	74.0	-30.9	Peak
1804.24	44.8	315	1.3	V	25.3	2.6	30.0	42.7	74.0	-31.3	Peak
3608.48	37.2	315	1.3	V	30.3	4.3	30.0	41.8	74.0	-32.2	Peak
High Channel											
903.29	86.2	315	1.3	V	24.8	3.0	25.0	89.0	94.0	-5.0	Peak
903.29	81.3	0	1.2	H	24.8	3.0	25.0	84.1	94.0	-9.9	Peak
4516.45	28.3	315	1.3	V	32.5	4.9	30.0	35.7	54.0	-18.3	Ave
4516.45	28.2	0	315.0	H	32.5	4.9	30.0	35.6	54.0	-18.4	Ave
2709.87	32.2	315	1.3	V	29.0	3.7	30.0	34.8	54.0	-19.2	Ave
2709.87	31.8	0	1.2	H	29.0	3.7	30.0	34.5	54.0	-19.5	Ave
1806.58	35.7	0	1.2	H	25.3	2.6	30.0	33.6	54.0	-20.4	Ave
1806.58	34.5	315	1.3	V	25.3	2.6	30.0	32.4	54.0	-21.6	Ave
3613.16	27.2	315	1.3	V	30.3	4.3	30.0	31.8	54.0	-22.2	Ave
3613.16	26.8	0	1.2	H	30.3	4.3	30.0	31.4	54.0	-22.6	Ave
4516.45	39.2	0	1.2	H	32.5	4.9	30.0	46.6	74.0	-27.4	Peak
2709.87	43.8	315	1.3	V	29.0	3.7	30.0	46.5	74.0	-27.5	Peak
4516.45	38.5	315	1.3	V	32.5	4.9	30.0	45.9	74.0	-28.1	Peak
2709.87	42.7	0	1.2	H	29.0	3.7	30.0	45.4	74.0	-28.6	Peak
3613.16	39.8	315	1.3	V	30.3	4.3	30.0	44.5	74.0	-29.5	Peak
1806.58	46.5	0	1.2	H	25.3	2.6	30.0	44.4	74.0	-29.6	Peak
1806.58	46.2	315	1.3	V	25.3	2.6	30.0	44.1	74.0	-29.9	Peak
3613.16	36.7	0	1.2	H	30.3	4.3	30.0	41.3	74.0	-32.7	Peak

Unwanted										
302.15	42.3	160	1.2	V	15.1	4.6	25.0	37.0	46.0	-9.0
184.26	29.5	90	1.5	V	13.6	4.0	25.0	22.1	43.5	-21.4
159.73	31.4	250	1.2	H	13.0	2.0	25.0	21.4	43.5	-22.1
84.40	30.6	110	1.5	H	9.6	1.4	25.0	16.6	40.0	-23.4
117.53	28.8	0	1.2	H	11.9	1.8	25.0	17.5	43.5	-26.0
230.91	30.7	240	1.2	V	12.0	1.2	25.0	18.9	46.0	-27.1

Handset Unit, 30 MHz to 25GHz, 3 meters

Indicated			Table	Antenna		Correction Factor			FCC 15 Subpart C		Comments
Frequency	Ampl.	Direction	Height	Polar	Antenna	Cable Loss	Amp.	Corr. Ampl.	Limit	Margin	
MHz	dBμV/m	Degree	Meter	H/V	dBμV/m	dBμV/m	dB	dBμV/m	dBμV/m	dB	
Low Channel											
926.12	83.2	360	2.1	V	24.7	4.4	25.0	87.3	94.0	-6.7	Peak
926.12	81.3	315	1.3	H	24.7	4.4	25.0	85.4	94.0	-8.6	Peak
2778.36	39.3	315	1.3	H	29.0	3.7	30.0	42.0	54.0	-12.0	Ave
1852.24	43.0	315	1.3	H	25.3	2.6	30.0	40.9	54.0	-13.1	Ave
2778.36	38.0	360	2.1	V	29.0	3.7	30.0	40.7	54.0	-13.3	Ave
1852.24	39.8	360	2.1	V	25.3	2.6	30.0	37.7	54.0	-16.3	Ave
4630.60	30.0	315	1.3	H	32.5	4.9	30.0	37.4	54.0	-16.6	Ave
4630.60	28.5	360	2.1	V	32.5	4.9	30.0	35.9	54.0	-18.1	Ave
3704.48	31.0	315	1.3	H	30.3	4.3	30.0	35.6	54.0	-18.4	Ave
3704.48	27.3	360	2.1	V	30.3	4.3	30.0	31.9	54.0	-22.1	Ave
4630.60	40.0	360	2.1	V	32.5	4.9	30.0	47.4	74.0	-26.6	Peak
2778.36	43.2	315	1.3	H	29.0	3.7	30.0	45.9	74.0	-28.1	Peak
4630.60	38.3	315	1.3	H	32.5	4.9	30.0	45.7	74.0	-28.3	Peak
2778.36	42.8	360	2.1	V	29.0	3.7	30.0	45.5	74.0	-28.5	Peak
1852.24	46.8	315	1.3	H	25.3	2.6	30.0	44.7	74.0	-29.3	Peak
1852.24	45.7	360	2.1	V	25.3	2.6	30.0	43.6	74.0	-30.4	Peak
3704.48	38.2	315	1.3	H	30.3	4.3	30.0	42.8	74.0	-31.2	Peak
3704.48	37.7	360	2.1	V	30.3	4.3	30.0	42.3	74.0	-31.7	Peak
High Channel											
927.29	84.2	360	2.0	V	24.7	4.4	25.0	88.3	94.0	-5.7	Peak
927.29	80.5	135	1.3	H	24.7	4.4	25.0	84.6	94.0	-9.4	Peak
2781.87	40.0	135	1.3	H	29.0	3.7	30.0	42.7	54.0	-11.3	Ave
4636.45	35.2	135	1.3	H	32.5	4.9	30.0	42.6	54.0	-11.4	Ave
2781.87	38.5	360	2.0	V	29.0	3.7	30.0	41.2	54.0	-12.8	Ave
4636.45	33.7	360	2.0	V	32.5	4.9	30.0	41.1	54.0	-12.9	Ave
1854.58	42.2	135	1.3	H	25.3	2.6	30.0	40.1	54.0	-13.9	Ave
1854.58	40.7	360	2.0	V	25.3	2.6	30.0	38.6	54.0	-15.4	Ave
3709.16	31.8	135	1.3	H	30.3	4.3	30.0	36.4	54.0	-17.6	Ave
3709.16	31.0	360	2.0	V	30.3	4.3	30.0	35.6	54.0	-18.4	Ave
4636.45	41.5	360	2.0	V	32.5	4.9	30.0	48.9	74.0	-25.1	Peak
2781.87	42.33	360	2	V	29.0	3.7	30.0	46.2	74.0	-27.8	Peak
4636.45	38.7	135	1.3	H	32.5	4.9	30.0	46.1	74.0	-27.9	Peak
1854.58	45	360	2	V	25.3	2.6	30.0	45.6	74.0	-28.4	Peak
3709.16	39.3	360	2.0	V	30.3	4.3	30.0	44.0	74.0	-30.0	Peak
3709.16	38.5	135	1.3	H	30.3	4.3	30.0	43.1	74.0	-30.9	Peak
2781.87	43.5	135	1.3	H	29.0	3.7	30.0	42.0	74.0	-32.0	Peak
1854.58	47.7	135	1.3	H	25.3	2.6	30.0	40.2	74.0	-33.8	Peak

Unwanted										
191.76	29.5	310	1.2	H	14.4	2.7	25.0	21.6	43.5	-21.9
147.40	30.1	90	1.2	H	13.4	1.6	25.0	20.1	43.5	-23.4
83.62	30.4	270	1.5	H	9.6	1.4	25.0	16.4	40.0	-23.6
241.75	31.9	120	1.5	V	12.6	2.3	25.0	21.8	46.0	-24.2
152.88	29.7	30	1.5	V	13.0	0.7	25.0	18.4	43.5	-25.1

Note: The handset was positioned and tested in 3 orthogonal axis.

Ave: Average

5 - BAND EDGES TESTING

Requirements: FCC 15.249 (c), the emission power at the START and STOP frequencies shall be at least 50 dB below the level of the fundamental or to the general radiated emission limits in FCC 15.209, whichever is the lesser attenuation.

5.1 Test Procedure

With the EUT's antenna attached, the EUT's radiated emission power was received by the test antenna which was connected to the spectrum analyzer with the START and STOP frequencies set to the EUT's operation band.

5.2 Test Equipment

HP 8566B Spectrum Analyzer
HP 7470A Plotter

5.3 Test Results

Base: Low
Handset: High

