



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR 352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

FCC
UHF BASE STATION PART 90
TEST REPORT

APPLICANT	SPECTRA ENGINEERING PTY LTD
	731 MARSHALL RD MALAGA WESTERN AUSTRALIA 6090 AUSTRALIA
FCC ID	OKRMX800NOPV
MODEL NUMBER	MX800N2N2V, MX800O2O2V, MX800P2P2V
PRODUCT DESCRIPTION	MX800 - BASE STATION
STANDARD APPLIED	CFR 47 Part 90
DATE SAMPLE RECEIVED	9/26/2014
DATE TESTED	10/8/2014
REPORT ISSUE DATE	10/9/2014
TESTED BY	Sid Sanders
APPROVED BY	Cory Leverett
TIMCO REPORT NO.	1747AUT14TestReport.docx
TEST RESULTS	☒ PASS ☐ FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**

TABLE OF CONTENTS

GENERAL REMARKS.....	3
GENERAL INFORMATION.....	4
TEST PROCEDURE.....	5
OCCUPIED BANDWIDTH	6
OCCUPIED BANDWIDTH PLOTS: DIGITAL	8
EQUIPMENT LIST	9

Applicant: SPECTRA ENGINEERING PTY LTD.
FCC ID: OKRMX800N0PV
Report:
V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX



GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

- ☒ fulfill the general approval requirements as identified in this test report
☐ not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:

Engineering Project Manager

Date:

Applicant: SPECTRA ENGINEERING PTY LTD.
FCC ID: OKRMX800N0PV
Report:
V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX





GENERAL INFORMATION

EUT Specification

EUT Description	MX800 - BASE STATION
FCC ID	OKRMX800NOPV
Model Number	MX800N2N2V, MX800O2O2V
Operating Frequency	450-470MHz
Test Frequencies	450, 456, 470MHz
Type of Emission	8K10F1E, 8K10F1D, 8K10F1W
Modulation	FM,
EUT Power Source	☐ 110-120Vac/50- 60Hz
	☒ DC Power 12V
	☐ Battery Operated Exclusively
Test Item	☐ Prototype
	☒ Pre-Production
	☐ Production
Type of Equipment	☒ Fixed
	☐ Mobile
	☐ Portable
Test Conditions	The temperature was 24- 26°C with a relative humidity of 50-65%.
Revision History to the EUT	None
Test Exercise	The EUT was placed in continuous transmit mode.
Applicable Standards	ANSI/TIA 603-C:2004, FCC CFR 47 Part 90
Test Facility	Timco Engineering Inc. 849 NW State Road 45 Newberry, FL 32669 USA.

Applicant: SPECTRA ENGINEERING PTY LTD.

FCC ID: OKRMX800NOPV

Report:

V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX





TEST PROCEDURE

Power Line Conducted Interference: The procedure used was ANSI/TIA 603-D:2010, using a 50uH LISN. Both lines were observed with the EUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was ANSI/TIA 603-D:2010, using an Rohde & Schwarz – EMI test receiver. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

Applicant: SPECTRA ENGINEERING PTY LTD.

FCC ID: OKRMX800N0PV

Report:

V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX



OCCUPIED BANDWIDTH

Comment [SSS1]: This must be done for each channel spacing & only 1 freq.

Part 2.1049(c) EMISSION BANDWIDTH: Part 90.210(b) 25kHz Channel Spacing

Data in the plots show that on any frequency removed from the assigned frequency by more than 50%, but not more than 100%: At least 25dB. On any frequency removed from the assigned frequency by more than 100%, but not more than 250%: At least 35 dB. On any frequency removed from the assigned frequency by more than 250%, of the authorized bandwidth: At least $43 + 10\log(P)$ dB.

Part 90.210(c) 25 kHz Channel Spacing Not Equipped with a Low Pass Filter

For transmitters that are not equipped with an audio low pass filter pursuant to S90.211 (b), the power of any emission must be attenuated below the unmodulated carrier output power as follows; (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5 kHz but not more than 10 kHz: At least $83 \log(f_d/5)$ dB; (2) ON any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 10 kHz, but not more than 250% of the authorized bandwidth: At least $29 \log(f_d/11)$ dB or 50 dB, whichever is the lesser attenuation; (3) On any frequency removed from the center of the authorized bandwidth by more than 250% of the authorized bandwidth: At least $43 + 10 \log(P_o)$ dB.

Part 90.210(d) Emission Mask D - 12.5 kHz channel BW equipment.

For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27 (f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10\log(P)$ dB or 70 dB, whichever is the lesser attenuation.


Part 90.210(e) Emission Mask E – 6.25 kHz channel BW equipment.

For transmitters designed to operate with a 6.25 kHz bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 3.0 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least $30 + 16.67(f_d - 3.0 \text{ kHz})$ or $55 + 10 \log(P)$ or 65, whichever is the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least $55 + 10 \log(P)$ dB or 65 dB, whichever is the lesser attenuation.

Method of Measurement: ANSI/TIA 603-D: 2010

Test Setup Diagram:



Test Data: See the plots below


Applicant: SPECTRA ENGINEERING PTY LTD.

FCC ID: OKRMX800N0PV

Report:

V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX

OCCUPIED BANDWIDTH PLOTS: DIGITAL
Part 90.210(d) Emission Mask D - 12.5 kHz channel bandwidth - DIGITAL



Date: 8.OCT.2014 09:55:18

Applicant: SPECTRA ENGINEERING PTY LTD.
FCC ID: OKRMX800N0PV
Report:
V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX



EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
12 Volt Power Supply	Astron	RS-12A	9312779	12/12/99	12/12/99
Digital Multimeter	Fluke	77	35053830	08/22/13	08/22/15
EMI Test Receiver R & S ESIB 40	Rohde & Schwarz	ESIB 40	100274	08/12/14	08/12/16
30 dB Attenuator	Narda	769-30	10267	03/15/13	03/15/15

Applicant: SPECTRA ENGINEERING PTY LTD.
 FCC ID: OKRMX800N0PV
 Report:
 V:\S\SPECTRA_OKR\1747AUT14\EXTRA1747AUT14\1747AUT14TESTREPORTREV1.DOCX

