Senton GmbH
Aeussere Fruehlingstrasse 45
D-94315 Straubing

Straubing, August 25, 2006

T E S T - R E P O R T

No. 50235-060611-1 (Edition 1)

for

ACCESS45-M1415-5-232-LB-EQUITRAC

Inductive Tag Reader

Applicant:	BALTECH AG
Test Specifications:	FCC Code of Federal Regulations, CFR 47, Part 15, Sections 15.205, 15.207, 15.215 and 15.225 Industry Canada Radio Standards Specifications RSS-Gen Issue 1, Section 7.2.2 and RSS-210 Issue 6, Sections 2.2, 2.6, A2.6 (Category I Equipment)

Note:

The test data of this report is related only to the individual item which has been tested. This report shall not be reproduced except in full extent without the written approval of the testing laboratory.

Table of Contents

1 Description of the Equipment Under Test (EUT) ... 3
2 Administrative Data ... 4
3 Identification of the Test Laboratory ... 5
4 Summary ... 6
5 Operation Mode and Configuration of EUT ... 7
6 Measurement Procedures ... 8
6.1 Bandwidth Measurements ... 8
6.2 Conducted AC Powerline Emission ... 10
6.3 Radiated Emission Measurement 9 kHz to 30 MHz ... 12
6.4 Radiated Emission in Fully or Semi Anechoic Room ... 14
6.5 Radiated Emission at Open Field Test Site ... 16
6.6 Carrier Frequency Stability ... 17
7 Photographs Taken During Testing ... 19
8 Test Results ... 27
8.1 Occupied Bandwidth ... 29
8.2 Bandwidth of the Emission ... 34
8.3 Designation of Emissions ... 36
8.4 Conducted Powerline Emission Measurement 150 kHz to 30 MHz ... 37
8.5 Spectrum Mask ... 38
8.6 Radiated Emission Measurement 9 kHz to 30 MHz ... 40
8.7 Radiated Emission Measurement 30 MHz to 1 GHz ... 41
8.8 Carrier Frequency Stability ... 43
8.9 Exposure of Humans to RF Fields ... 46
9 Referenced Regulations ... 48
10 Charts taken during testing ... 49

1 Description of the Equipment Under Test (EUT)

General data of EUT	
Type designation[1]:	ACCESS45-M1415-5-232-LB-EQUITRAC
Parts[2]:	---
Serial number(s):	Sample no. 1
Manufacturer:	BALTECH AG
Type of equipment:	Inductive Tag Reader
Version:	with ferrite core Würth no. 742 711 12 for power supply (close to dc connector, two turns of dc lines)
FCC ID:	OKY1005200251A02B
Additional parts/accessories:	with tag "Mifare Standard 1kByte"

Technical data of EUT	
Application frequency range:	13.110 – 14.010 MHz
Frequency range:	13.560 MHz
Operating frequency:	13.560 MHz
Type of modulation:	Amplitude Modulation (AM)
Number of RF-channels:	1
Channel spacing:	Not applicable
Designation of emissions[3]:	212KA1D
Type of antenna:	Integrated loop antenna (printed board)
Size/length of antenna:	Rectangle: 72 mm x 37 mm
Connection of antenna:	☐ detachable ☒ not detachable
Type of power supply:	DC supply
Specifications for power supply:	nominal voltage: 5.00 V DC minimum voltage: 4.25 V DC maximum voltage: 5.50 V DC

[1] Type designation of the system if EUT consists of more than one part.
[2] Type designations of the parts of the system, if applicable.
[3] Also known as "Class of Emission".

2 Administrative Data

Application details	
Applicant (full address):	BALTECH AG Lilienthalstrasse 27 D-85399 Hallbergmoos Germany
Contact person:	Mr. Jürgen Rösch
Contract identification:	---
Receipt of EUT:	August 1, 2006
Date(s) of test:	August 8 and August 21 to 24, 2006
Note(s):	---

Report details	
Report number:	50235-060611-1
Edition:	1
Issue date:	August 25, 2006

3 Identification of the Test Laboratory

Details of the Test Laboratory	
Company name:	Senton GmbH EMI/EMC Test Center
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
Laboratory accreditation:	DAR-Registration No. DAT-P-171/94-02
FCC test site registration number	90926
Industry Canada test site registration:	IC 3050
Contact person:	Mr. Johann Roidt Phone: (+49) (0)9421 5522-0 Fax: (+49) (0)9421 5522-99

4 Summary

Summary of test results
The tested sample complies with the requirements set forth in the **Code of Federal Regulations CFR 47, Part 15, Sections 15.205, 15.207, 15.215 and 15.225** of the Federal Communication Commission (FCC) and the **Radio Standards Specifications** **RSS-Gen Issue 1, Section 7.2.2 and** **RSS-210 Issue 6, Sections 2.2, 2.6, A2.6 (Category I Equipment)** of Industry Canada (IC).

Personnel involved in this report	
Laboratory Manager:	Mr. Johann Roidt
Responsible for testing:	Mr. Rainer Heller
Responsible for test report:	Mr. Rainer Heller

5 Operation Mode and Configuration of EUT

Operation Mode(s)
EUT is transmitting continuously with power switched on.

Configuration(s) of EUT
EUT was tested connected to the serial port of a notebook and supplied by an external dc power supply (120 V AC mains input).

List of ports and cables

Port	*Description*	*Classification*[4]	*Cable type*	*Cable length*
1	dc power input cable (fixed to power supply)	dc power	Unshielded	1.8 m
2	serial interface cable	signal/control port	Shielded	1.7 m
3	parallel interface cable (connected to notebook)	signal/control port	Shielded	2 m

List of devices connected to EUT

Item	*Description*	*Type Designation*	*Serial no. or ID*	*Manufacturer*
1	power supply (5 V DC, 1000 mA)	FW7650/05	1406	Friwo
2	notebook	Latitude D600	GZJBW0J	Dell

List of support devices

Item	*Description*	*Type Designation*	*Serial no. or ID*	*Manufacturer*
1	inductive tag	Mifare Standard 1kByte	---	Mifare
2	power supply for notebook	AA22850	CN-05U092-16291-39Q-08MZ	Dell

[4] Ports shall be classified as ac power, dc power or signal/control port

6 Measurement Procedures

6.1 Bandwidth Measurements

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 1, sections 4.4.1 and 4.4.2 IC RSS-210 Issue 6, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 1, sections 4.4.1 and 4.4.2
Measurement setup:	☐ Conducted: See below ☒ Radiated: Radiated Emission Measurement 9 kHz to 30 MHz (6.3)
If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable. If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range. The analyzer settings are specified by the test description of the appropriate test record(s).	



Test instruments used for conducted measurements:

Used	Type	Model	Serial No. or ID	Manufacturer
☐	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
☐	EMI test receiver	ESPI7	836914/0002	Rohde & Schwarz
☐	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
☐	Power meter	NRVS	836856/015	Rohde & Schwarz
☐	Peak power sensor	NRV-Z31	8579604.03	Rohde & Schwarz
☐	Power sensor	NRV-Z52	837901/030	Rohde & Schwarz
☐	Power sensor	NRV-Z4	863828/015	Rohde & Schwarz
☐	DC-block	7006	A2798	Weinschel
☐	Attenuator	4776-10	9412	Narda
☐	Attenuator	4776-20	9503	Narda

6.2 Conducted AC Powerline Emission

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, section 15.207 IC RSS-Gen Issue 1, section 7.2.2
Guide:	ANSI C63.4 / CISPR 22

Conducted emission tests in the frequency range 150 kHz to 30 MHz are performed using Line Impedance Stabilization Networks (LISNs). To simplify testing with quasi-peak and average detector the following procedure is used:

First the whole spectrum of emission caused by the equipment under test (EUT) is recorded with detector set to peak using CISPR bandwidth of 10 kHz. After that all emission levels having less margin than 10 dB to or exceeding the average limit are retested with detector set to quasi-peak.
If average limit is kept with quasi-peak levels no additional scan with average detector is necessary. In cases of emission levels between quasi-peak and average limit an additional scan with detector set to average is performed.

According to ANSI C63.4, section 13.1.3.1, testing of intentional radiators with detachable antenna shall be performed using a suitable dummy load connected to the antenna output terminals. Otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended.
Testing with dummy load may be necessary to distinguish (unintentional) conducted emissions on the supply lines from (intentional) emissions radiated by the antenna and coupling directly to supply lines and/or LISN. Usage of dummy load has to be stated in the appropriate test record(s) and notes should be added to clarify the test setup.



Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
☒	EMI receiver	ESHS 10	860043/016	Rohde & Schwarz
☒	LISN	ESH3-Z5	862770/021	Rohde & Schwarz
☒	LISN	ESH3-Z5	830952/025	Rohde & Schwarz
☐	Artificial mains network	ESH 2-Z5	842966/004	Rohde & Schwarz
☐	Shielded room	No. 1	1451	Albatross Projects
☒	Shielded room	No. 4	3FD-100 544	Euroshield

6.3 Radiated Emission Measurement 9 kHz to 30 MHz

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.205, 15.215(b) and 15.225(a)-(d) IC RSS-210 Issue 6, sections 2.2, 2.6 and A2.6
Guide:	ANSI C63.4

Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.
If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).

Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.



Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
☒	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
☐	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
☒	Test receiver	ESHS 10	860043/016	Rohde & Schwarz
☐	Preamplifier	CPA9231A	3393	Schaffner
☒	Loop antenna	HFH2-Z2	882964/1	Rohde & Schwarz
☒	Fully anechoic room	No. 2	1452	Albatross Projects
☐	Semi-anechoic room	No. 3	1453	Siemens
☒	Open field test site	EG 1	1450	Senton

6.4 Radiated Emission in Fully or Semi Anechoic Room

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.205(b) and 15.225(d) IC RSS-210 Issue 6, sections 2.2(b)(c), 2.6 and A2.6
Guide:	ANSI C63.4

Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.

Measurements are made in both the horizontal and vertical planes of polarization in a fully anechoic room using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).

Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.

All tests below 18 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance is reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For final testing below 1 GHz an open field test-site is used and the plots recorded in the fully or semi anechoic room are indicated as prescans.



Fully or semi anechoic room

Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
☒	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
☐	Spectrum analyzer	R 3271	05050023	Advantest
☐	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
☒	Preamplifier	CPA9231A	3393	Schaffner
☐	Preamplifier	R14601		Advantest
☐	Preamplifier 1-8 GHz	AFS3-00100800-32-LN	847743	Miteq
☐	Preamplifier 0.5-8 GHz	AMF-4D-005080-25-13P	860149	Miteq
☐	Preamplifier 8-18 GHz	ACO/180-3530	32641	CTT
☐	External Mixer	WM782A	845881/005	Tektronix
☐	Harmonic Mixer Accessories	FS-Z30	843389/007	Rohde & Schwarz
☒	Trilog broadband antenna	VULB 9163	9163-188	Schwarzbeck
☐	Horn antenna	3115	9508-4553	EMCO
☐	Horn antenna	3160-03	9112-1003	EMCO
☐	Horn antenna	3160-04	9112-1001	EMCO
☐	Horn antenna	3160-05	9112-1001	EMCO
☐	Horn antenna	3160-06	9112-1001	EMCO
☐	Horn antenna	3160-07	9112-1008	EMCO
☐	Horn antenna	3160-08	9112-1002	EMCO
☐	Horn antenna	3160-09	9403-1025	EMCO
☐	Horn antenna	3160-10	399185	EMCO
☒	Fully anechoic room	No. 2	1452	Albatross Projects
☐	Semi-anechoic room	No. 3	1453	Siemens

6.5 Radiated Emission at Open Field Test Site

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.205(b) and 15.225(d) IC RSS-210 Issue 6, sections 2.2(b)(c), 2.6 and A2.6
Guide:	ANSI C63.4

Radiated emission at open field test site is measured in the frequency range 30 MHz to 1 GHz using a biconical antenna up to 300 MHz and a logarithmic periodic antenna above. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in the fully anechoic room. EUT is rotated all around and receiving antenna is raised and lowered within 1 meter to 4 meters to find the maximum levels of emission. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.



Test instruments used:

Used	Type		Model	Serial No. or ID	Manufacturer
☒	EMI receiver		ESVP	881120/024	Rohde & Schwarz
☒	Biconical antenna	EG 1	HK 116	842204/001	Rohde & Schwarz
☒	Log. per. antenna	EG 1	HL 223	841516/023	Rohde & Schwarz
☒	Open field test site		EG 1	1450	Senton

6.6 Carrier Frequency Stability

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, section 15.225(e) IC RSS-Gen Issue 1, section 4.5 and IC RSS-210 Issue 6, section A2.6
Guide:	ANSI C63.4

The frequency tolerance of the carrier signal is measured over a temperature variation of -20 °C to +50 °C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 °C.

If the EUT provides an antenna connector the spectrum analyzer is connected to this port. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). In cases where the EUT does not provide an antenna connector a test fixture is used.

For battery operated equipment, the test is performed using a new battery. Alternatively, an external supply voltage can be used and is at least set to:

- the maximum battery voltage as delivered by a new battery or 115% of the battery nominal voltage
- the battery nominal voltage
- 85% of the battery nominal voltage
- the battery operating end point voltage which shall be specified by the equipment manufacturer

The EUT is operating providing an unmodulated carrier. The peak detector of the spectrum analyzer is selected and resolution as well as video bandwidth are set to values appropriate to the shape of the spectrum of the EUT. The frequency counter mode of the spectrum analyzer is used to maximize the accuracy of the measured frequency tolerance.
If an unmodulated carrier is not available a significant and stable point on the spectrum is selected and the span is reduced to a value that delivers an accuracy which shall be better than 1% of the maximum frequency tolerance allowed for the carrier signal. This method may be performed as long as the margin to the frequency tolerance allowed is larger than the uncertainty of the measured frequency tolerance.



Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
☐	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
☐	EMI test receiver	ESPI7	836914/0002	Rohde & Schwarz
☒	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
☐	DC-block	7006	A2798	Weinschel
☐	Attenuator	4776-10	9412	Narda
☐	Attenuator	4776-20	9503	Narda
☒	Test probe	TP01	001	Senton
☒	DC power supply	NGSM 32/10	203	Rohde & Schwarz
☐	Isolating transformer	RT 5A	10387	Grundig
☐	Isolating transformer	RT 5A	10416	Grundig
☒	Temperature test chamber	HT4010	07065550	Heraeus

7 Photographs Taken During Testing

Test setup for conducted AC powerline emission measurement

Test setup for conducted AC powerline emission measurement
- continued -

Test setup for radiated emission measurement 9 kHz – 30 MHz (prescan in fully anechoic room)



Test setup for radiated emission measurement 9 kHz – 30 MHz

Test setup for radiated emission measurement (prescan in fully anechoic room)



Test setup for radiated emission measurement (open field test site)





Test setup for radiated emission measurement (open field test site) - continued -





8 Test Results

FCC CFR 47 Parts 2 and 15			
Section(s)	*Test*	*Page*	*Result*
2.1046(a)	Conducted output power	---	Not applicable
2.202(a)	Occupied bandwidth	29	Recorded
15.215(c)	Bandwidth of the emission	34	Test passed
2.201, 2.202	Class of emission	36	Calculated
15.35(c)	Pulse train measurement for pulsed operation	---	Not applicable
15.205(a) 15.205(d)(7)	Restricted bands of operation	---[5]	Test passed
15.207	Conducted AC powerline emission 150 kHz to 30 MHz	37	Test passed
15.225(a)-(d)	Spectrum Mask	38	Test passed
15.205(b) 15.215(b) 15.225(a)(d)	Radiated emission 9 kHz to 30 MHz	40	Test passed
15.205(b) 15.225(d)	Radiated emission 30 MHz to 1 GHz	41	Test passed
15.225(e)	Carrier frequency stability	43	Test passed

[5] See "Spectrum Mask" for the 13.36 to 13.41 MHz band. For all other restricted bands see "Radiated Emission".

IC RSS-Gen Issue 1			
Section(s)	*Test*	*Page*	*Result*
4.6	Transmitter output power (conducted)	---	Not applicable
4.4.1	Occupied Bandwidth	29	Recorded
3.2(h), 8	Designation of emissions	36	Calculated
4.3	Pulsed operation	---	Not applicable
7.2.2	Transmitter AC power lines conducted emissions 150 kHz to 30 MHz	37	Test passed
5.5	Exposure of Humans to RF Fields	46	Exempted from SAR and RF evaluation

IC RSS-210 Issue 6			
Section(s)	*Test*	*Page*	*Result*
2.2(a)	Restricted bands and unwanted emission frequencies	---[6]	Test passed
A2.6	Spectrum Mask	38	Test passed
2.2(b)(c), 2.6 A2.6	Unwanted emissions 9 kHz to 30 MHz	40	Test passed
2.2(b)(c), 2.6 A2.6	Unwanted emissions 30 MHz to 1 GHz	41	Test passed
A2.6	Carrier frequency stability	43	Test passed

[6] See "Spectrum Mask" and "Unwanted emissions".

8.1 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6
Guide:	ANSI C63.4
Description:	The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission. The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier. The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:

Fundamental frequency	Minimum resolution bandwidth
9 kHz to 30 MHz	1 kHz
30 MHz to 1000 MHz	10 kHz
1000 MHz to 40 GHz	100 kHz

The video bandwidth shall be at least three times greater than the resolution bandwidth.

Measurement procedure:	Bandwidth Measurements (6.1)

Comment:	Reading tag
Date of test:	August 24, 2006
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



Occupied Bandwidth (99 %):	**298 kHz**

Occupied Bandwidth (-26 dB):



Occupied Bandwidth (-26 dB):	**110 kHz**

Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 1, section 4.4.1
Guide:	IC RSS-Gen Issue 1, section 4.4.1
Description:	If not specified in the applicable RSS the occupied bandwidth is measuredas the 99% emission bandwidth. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.
Measurement procedure:	Bandwidth Measurements (6.1)

Comment:	Reading tag
Date of test:	August 24, 2006
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



Occupied Bandwidth (99 %):	**367 kHz**

8.2 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.215(c)
Guide:	ANSI C63.4
Description:	The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier. For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation. The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:

Fundamental frequency	Minimum resolution bandwidth
9 kHz to 30 MHz	1 kHz
30 MHz to 1000 MHz	10 kHz
1000 MHz to 40 GHz	100 kHz

The video bandwidth shall be at least three times greater than the resolution bandwidth.

Measurement procedure:	Bandwidth Measurements (6.1)

Comment:	Reading tag
Date of test:	August 24, 2006
Test site:	Fully anechoic room, cabin no. 2



Permitted frequency band:	**13.110 – 14.010 MHz**	
20 dB bandwidth:	**3.4 kHz**	
Carrier frequency stability: Maximum frequency tolerances:	☒ **specified** **+0.2 kHz** **-0.3 kHz**	☐ **not specified**
Bandwidth of the emission:	**3.9 kHz**	**within permitted frequency band[7]:** ☒ **yes** ☐ **no**

Test Result:	Test passed

[7] If a frequency stability is not specified, it is recommended that the fundamental emission is kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.3 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 1, sections 3.2(h) and 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Amplitude Modulation

B_n = Necessary Bandwidth B = Modulation rate K = Overall numerical factor	$B_n = 2BK$ B = 106 kbps K = 1
Calculation:	$B_n = 2 \cdot (106\ \text{kHz}) \cdot 1 = 212\ \text{kHz}$

Designation of Emissions:	**212KA1D**

8.4 Conducted Powerline Emission Measurement 150 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, section 15.207 IC RSS-Gen Issue 1, section 7.2.2		
Guide:	ANSI C63.4 / CISPR 22		
Limit:	Frequency of Emission (MHz)	Conducted Limit (dBµV)	
		Quasi-peak	Average
	0.15 - 0.5 0.5 - 5 5 - 30	66 to 56 56 60	56 to 46 46 50
Measurement procedure:	Conducted AC Powerline Emission (6.2)		

Comment:	---
Date of test:	August 24, 2006
Test site:	Shielded room, cabin no. 4

Test Result:	Test passed

Tested on:	AC mains input port of power supply, phase L1

Frequency (MHz)	Detector	Reading Value (dBµV)	Correction Factor (dB)	Final Value (dBµV)	Limit (dBµV)	Margin (dB)
13.560	Quasi-Peak	39.1	0.0	39.1	60.0	**20.9**

Tested on:	AC mains input port of power supply, phase N

Frequency (MHz)	Detector	Reading Value (dBµV)	Correction Factor (dB)	Final Value (dBµV)	Limit (dBµV)	Margin (dB)
13.560	Quasi-Peak	38.0	0.0	38.0	60.0	**22.0**
27.120	Quasi-Peak	18.6	0.0	18.6	60.0	41.4

Sample calculation of final values:

Final Value (dBµV) = Reading Value (dBµV) + Correction Factor (dB)

8.5 Spectrum Mask

Rules and specifications:	CFR 47 Part 15, section 15.225(a)-(d) IC RSS-210 Issue 6, section A2.6			
Guide:	ANSI C63.4			
Description:	Compliance with the spectrum mask is tested using a spectrum analyzer with resolution bandwidth set to a 1 kHz for the band 13.553 to 13.567 MHz and to 10 kHz outside this band. The video bandwidth shall be at least three times greater than the resolution bandwidth.			
Limit:	Frequency of Emission (MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance d (meters)
	1.705 - 13.110	30	29.5	30
	13.110 - 13.410	106	40.5	30
	13.410 - 13.553	334	50.5	30
	13.553 - 13.567	15848	84.0	30
	13.567 - 13.710	334	50.5	30
	13.710 - 14.010	106	40.5	30
	14.010 - 30.000	30	29.5	30
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.3)			

Comment: Date of test: Test site:	 Fully anechoic room, cabin no. 2
Test distance:	3 meters
Extrapolation Factor:	..... dB/decade

Test Result:	Test passed

RBW = 10 kHz, VBW = 30 kHz:



RBW = 1 kHz, VBW = 3 kHz:



8.6 Radiated Emission Measurement 9 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, sections 15.205 and 15.225(a)-(d) IC RSS-210 Issue 6, sections 2.2(b)(c), 2.6 and A2.6			
Guide:	ANSI C63.4			
Limit:	Frequency of Emission (MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance d (meters)
	0.009 - 0.490	2400/F(kHz)	67.6 - 20 · log(F(kHz))	300
	0.490 - 1.705	24000/F(kHz)	87.6 - 20 · log(F(kHz))	30
	1.705 - 13.110	30	29.5	30
	13.110 - 13.410	106	40.5	30
	13.410 - 13.553	334	50.5	30
	13.553 - 13.567	15848	84.0	30
	13.567 - 13.710	334	50.5	30
	13.710 - 14.010	106	40.5	30
	14.010 - 30.000	30	29.5	30
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.			
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.3)			

Comment:	---
Date of test:	August 23, 2006
Test site:	Open field test site

Test Result:	Test passed

Frequency (MHz)	Detector	Distance d1 (m)	Distance d2 (m)	Distance d (m)	Reading Value d1 (dBµV)	Reading Value d2 (dBµV)	Correction Factor (dB/m)	Extrapolation Factor (dB/dec)	Extrapolation Factor (dB)	Pulse Train Correction (dB)	Final Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
13.56040	QP	10	20	30	35.1	25.8	20.0	-30.9	-5.4		40.4	84.0	43.6

Sample calculation of final values:

$$\text{Extrapolation Factor (dB/decade)} = \begin{cases} -40 \text{ (dB/decade)} & \text{if } d_1 = d_2 \\ \dfrac{\text{Reading Value } d_2 \text{ (dµV)} - \text{Reading Value } d_1 \text{ (dBµV)}}{\text{Log}(d_2) - \text{Log}(d_1)} & \text{if } d_1 \neq d_2 \end{cases}$$

$$\text{Extrapolation Factor (dB)} = (\text{Log}(d) - \text{Log}(d_2)) \cdot \text{Extrapolation Factor (dB/decade)}$$

$$\text{Final Value (dBµV/m)} = \text{Reading Value } d_2 \text{ (dBµV)} + \text{Correction Factor (dB/m)} + \text{Extrapolation Factor (dB)} + \text{Pulse Train Correction (dB)}$$

Note: Extrapolation factor (dB) and final value (dBµV/m) are relating to distance d.

8.7 Radiated Emission Measurement 30 MHz to 1 GHz

Rules and specifications:	CFR 47 Part 15, sections 15.205(b) and 15.225(d) IC RSS-210 Issue 6, sections 2.2(b)(c), 2.6 and A2.6		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	Above 960	500	54.0
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.		
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.4) Radiated Emission at Open Field Test Site (6.5)		

Comment:	---
Date of test:	August 21, 2006
Test site:	Frequencies ≤ 1 GHz: Open field test site Frequencies > 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	3 meters

Test Result:	Test passed

Frequency (MHz)	Antenna Polarization	Detector	Receiver Reading (dBµV)	Correction Factor (dB/m)	Pulse Train Correction (dB)	Final Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
40.684	vertical	Quasi-Peak	27.9	11.8		39.7	40.0	**0.3**
54.244	vertical	Quasi-Peak	17.9	10.0		27.9	40.0	12.1
67.804	vertical	Quasi-Peak	20.6	9.6		30.2	40.0	9.8
94.921	vertical	Quasi-Peak	24.5	10.3		34.8	43.5	8.7
108.490	vertical	Quasi-Peak	18.8	11.3		30.1	43.5	13.4
117.188	horizontal	Quasi-Peak	13.7	12.3		26.0	43.5	17.5
122.050	vertical	Quasi-Peak	25.3	12.8		38.1	43.5	5.4
135.610	vertical	Quasi-Peak	23.2	13.5		36.7	43.5	6.8
162.735	vertical	Quasi-Peak	13.4	14.6		28.0	43.5	15.5
176.294	horizontal	Quasi-Peak	18.3	15.2		33.5	43.5	10.0
203.413	horizontal	Quasi-Peak	20.3	16.7		37.0	43.5	6.5
211.833	vertical	Quasi-Peak	13.6	16.8		30.4	43.5	13.1
216.973	horizontal	Quasi-Peak	17.7	16.9		34.6	46.0	11.4
230.533	horizontal	Quasi-Peak	15.3	17.3		32.6	46.0	13.4
244.095	vertical	Quasi-Peak	12.0	17.5		29.5	46.0	16.5
257.660	horizontal	Quasi-Peak	14.1	18.4		32.5	46.0	13.5
284.780	horizontal	Quasi-Peak	14.8	21.0		35.8	46.0	10.2
298.343	horizontal	Quasi-Peak	17.2	23.0		40.2	46.0	5.8
311.903	horizontal	Quasi-Peak	13.2	16.2		29.4	46.0	16.6
325.463	horizontal	Quasi-Peak	23.3	16.6		39.9	46.0	6.1
379.708	horizontal	Quasi-Peak	12.8	18.2		31.0	46.0	15.0
406.830	vertical	Quasi-Peak	9.0	18.5		27.5	46.0	18.5
515.317	horizontal	Quasi-Peak	12.8	20.8		33.6	46.0	12.4
528.879	horizontal	Quasi-Peak	14.2	21.1		35.3	46.0	10.7
542.439	horizontal	Quasi-Peak	18.3	21.0		39.3	46.0	6.7
555.999	horizontal	Quasi-Peak	11.6	21.1		32.7	46.0	13.3

Sample calculation of final values:

Final Value (dBµV/m) = Reading Value (dBµV) + Correction Factor (dB/m) + Pulse Train Correction (dB)

8.8 Carrier Frequency Stability

Rules and specifications:	CFR 47 Part 15, section 15.225(e) IC RSS-Gen Issue 1, section 4.5 and IC RSS-210 Issue 6, section A2.6
Guide:	ANSI C63.4
Limit:	The frequency tolerance of the carrier signal shall be maintained within ±0.01 % (±100 ppm) of the carrier frequency under nominal conditions.
Temperature range: Voltage range:	-20°C to +50°C (at normal supply voltage) 85% to 115% of the rated supply voltage (at a temperature of +20°C)
Measurement procedure:	Carrier Frequency Stability (6.6)

Comment:	According to applicant maximum dc supply voltage is specified to 5.50 V. Therefore this voltage level was selected as the maximum one for testing.
Date of test:	August 21, 2006

8.8.1 Carrier Frequency Stability vs. Temperature



Supply voltage: 5 V Nominal frequency: 13.561330 MHz

Temperature (°C)	Frequency (MHz)	Frequency Tolerance (Hz)	Frequency Tolerance (ppm)	Upper Limit (ppm)	Lower Limit (ppm)	Margin (ppm)
-20	13.561420	90	6.6	+100.0	-100.0	93.4
-10	13.561510	180	13.3	+100.0	-100.0	86.7
±0	13.561420	90	6.6	+100.0	-100.0	93.4
+10	13.561420	90	6.6	+100.0	-100.0	93.4
+20	13.561330	0	0.0	+100.0	-100.0	100.0
+30	13.561240	-90	-6.6	+100.0	-100.0	93.4
+40	13.561140	-190	-14.0	+100.0	-100.0	86.0
+50	13.561020	-310	-22.9	+100.0	-100.0	**77.1**

Test Result:	Test passed

8.8.2 Carrier Frequency Stability vs. Supply Voltage



Temperature: +20 °C Battery End Point: Not applicable
Nominal frequency: 13.561330 MHz

Supply Voltage (V)	Frequency (MHz)	Frequency Tolerance (Hz)	Frequency Tolerance (ppm)	Upper Limit (ppm)	Lower Limit (ppm)	Margin (ppm)
5.50	13.561348	18	1.3	+100.0	-100.0	98.7
5.25	13.561342	12	0.9	+100.0	-100.0	99.1
5.00	13.561330	0	0.0	+100.0	-100.0	100.0
4.75	13.561323	-7	-0.5	+100.0	-100.0	99.5
4.50	13.561317	-13	-1.0	+100.0	-100.0	99.0
4.25	13.561309	-21	-1.5	+100.0	-100.0	**98.5**

Test Result:	Test passed

8.9 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 1, section 5.5
Guide:	IC RSS-102 Issue 2, section 2.5

Exposure of Humans to RF Fields	Applicable	Declared by applicant	Measured	Exemption
The antenna is				
☐ detachable				
The conducted output power (CP in watts) is measured at the antenna connector: CP = **..... W**			☐	
The effective isotropic radiated power (EIRP in watts) is calculated using				
☐ the numerical antenna gain: G = **.....**		☐		
$EIRP = G \cdot CP \Rightarrow EIRP$ = **..... W**				
☐ the field strength[8] in V/m: FS = **..... V/m**			☐	
$EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP$ = **..... W**				
with:				
Distance between the antennas in m: D = **..... m**			☐	
☒ not detachable				
A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by[8]:				
$EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP$ = **4.14 · 10^{-6} W**				
with:				
Field strength in V/m: FS = **0.0037 V/m**			☒	
Distance between the two antennas in m: D = **3 m**			☒	
Selection of output power				
The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.): TP = **4.14 · 10^{-6} W**				

[8] The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses.
If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.

Exposure of Humans to RF Fields (continued)	Applicable	Declared by applicant	Measured	Exemption
Separation distance between the user and the transmitting device is				
☐ less than or equal to 20 cm ☒ greater than 20 cm		☒		
Transmitting device is				
☐ in the vicinity of the human head ☐ body-worn		☒		
SAR evaluation				
SAR evaluation is required if the separation distance between the user and the device is less than or equal to 20 cm.				
☐ The device operates from 3 kHz up to 1 GHz inclusively and its source-based time-averaged output power is less than, or equal to 200 mW for General Public Use and 1000 mW for Controlled Use.				☐
☐ The device operates above 1 GHz up to 2.2 GHz inclusively and its source-based time-averaged output power is less than, or equal to 100 mW for General Public Use and 500 mW for Controlled Use.				☐
☐ The device operates above 2.2 GHz up to 3 GHz inclusively and its source-based time-averaged output power is less than, or equal to 20 mW for General Public Use and 100 mW for Controlled Use.				☐
☐ The device operates above 3 GHz up to 6 GHz inclusively and its source-based time-averaged output power) is less than, or equal to 10 mW for General Public Use and 50 mW for Controlled Use.				☐
☐ SAR evaluation is documented in test report no.				
RF exposure evaluation				
RF exposure evaluation is required if the separation distance between the user and the device is greater than 20 cm.				
☒ The device operates below 1.5 GHz and its e.i.r.p. is equal to or less than 2.5 W.				☒
☐ The device operates at or above 1.5 GHz and the e.i.r.p. of the device is equal to or less than 5 W.				☐
☐ RF exposure evaluation is documented in test report no.				

9 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

☒	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 10, 2004
☒	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	February 16, 2006
☒	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
☒	RSS-Gen	Radio Standards Specification RSS-Gen Issue 1 containing General Requirements and Information for the Certification of Radiocommunication Equimpment, published by Industry Canada	September 2005
☒	RSS-210	Radio Standards Specification RSS-210 Issue 6 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	September 2005
☐	RSS-310	Radio Standards Specification RSS-310 Issue 1 for Low Power Licence-Ecempt Radiocommunicaton Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	September 2005
☒	RSS-102	Radio Standards Specification RSS-102 Issue 2: Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)	November 2005
☐	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
☒	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, “Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement”	1997
☐	CAN/CSA-CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002
☒	TRC-43	Notes Regarding Designation of Emission (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada	October 9, 1982

10 Charts taken during testing

Conducted Emission Test 150 kHz - 30 MHz
according to FCC Part 15 Subpart C

Model: ACCESS45-M1415-5-232-LB-EQUITRAC	Mode:
Serial no.: Sample no. 1	- EUT connected to notebook Dell Latitude D600 (display switched off)
Applicant: Baltech AG	- DC 5 V power supply FW7650/05 with ferrite core on dc supply connector (Würth no. 742 711 12, two turns)
Test site: Shielded room, cabin no. 4	- transmitting continuously
Tested on: Linecord EUT Phase L1	
Date of test: 08/24/2006 — Operator: R. Heller	
Test performed: semi automatically — File name:	

Detector: Peak / Final Results: QP	Final results: Selected by hand



Result: Limit kept	Project file: 50235-060611-1 Page of Pages

Conducted Emission Test 150 kHz - 30 MHz
according to FCC Part 15 Subpart C

Model: ACCESS45-M1415-5-232-LB-EQUITRAC	Mode:
Serial no.: Sample no. 1	- EUT connected to notebook Dell Latitude D600 (display switched off)
Applicant: Baltech AG	- DC 5 V power supply FW7650/05 with ferrite core on dc supply connector (Würth no. 742 711 12, two turns)
Test site: Shielded room, cabin no. 4	- transmitting continuously
Tested on: Linecord EUT Phase N	
Date of test: 08/24/2006 — Operator: R. Heller	
Test performed: semi automatically — File name:	

Detector: Peak / Final Results: QP	Final results: Selected by hand



Result: Limit kept	Project file: 50235-060611-1 Page of Pages

Radiated Emission Test 9 kHz - 30 MHz
acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: ACCESS45-M1415-5-232-LB-EQUITRAC	Comment: - TX Mode
Serial no.: ---	
Applicant: Baltech AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres	
Date of test: 08/08/2006 — Operator: M. Steindl	
Test performed: by hand — File name: default.emi	
Detector: Peak	List of values: 10 dB Margin — 50 Subranges

dBµV/m — Limit1: FCC Part 15 — Limit2: FCC part 15 class A — Transducer: HFH2-Z2



Result: Prescan	Project file: 50235-60611-1 — Page of Pages

Radiated Emission Test 30 MHz - 1 GHz
acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: ACCESS45-M1415-5-232-LB-EQUITRAC	Comment: - EUT connected to notebook Dell Latitude D600 (display switched off) - DC 5 V power supply FW7650/05 with ferrite core on dc supply connector (Würth no. 742 711 12, two turns) - transmitting continuously
Serial no.: Sample no. 1	
Applicant: Baltech AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 08/18/2006 — Operator: R. Heller	
Test performed: automatically — File name: default.emi	

Detector: Peak	List of values: Selected by hand



Result: Prescan	Project file: 50235-60611-1 Page of Pages

Radiated Emission Test 30 MHz - 1 GHz
acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: ACCESS45-M1415-5-232-LB-EQUITRAC	Comment: - EUT connected to notebook Dell Latitude D600 (display switched off) - DC 5 V power supply FW7650/05 with ferrite core on dc supply connector (Würth no. 742 711 12, two turns) - transmitting continuously
Serial no.: Sample no. 1	
Applicant: Baltech AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 08/18/2006 — Operator: R. Heller	
Test performed: automatically — File name: default.emi	
Detector: Peak	List of values: Selected by hand



Result: Prescan	Project file: 50235-60611-1 Page of Pages