

**M. Flom Associates, Inc. - Global Compliance Center**

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: December 21, 1999

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Galaxy Tracking Systems L.L.C.
Equipment: VTRAKF450
FCC ID: 0M3VTRAKF450
FCC Rules: 90, Confidentiality

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, reading 'Morton Flom, P. Eng.' with a stylized, cursive script.

Morton Flom, P. Eng.

enclosure(s)
cc: Applicant
MF/cvr

LIST OF EXHIBITS
(FCC **CERTIFICATION** (TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Galaxy Tracking Systems L.L.C.

FCC ID: OM3VTRAKF450

BY APPLICANT:

1. LETTER OF AUTHORIZATION
2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)
 - ___ LABEL
 - ___ LOCATION OF LABEL
 - ___ COMPLIANCE STATEMENT
 - ___ LOCATION OF COMPLIANCE STATEMENT
3. PHOTOGRAPHS, 2.1033(c)(12)
4. DOCUMENTATION: 2.1033(c)
 - (3) USER MANUAL
 - (9) TUNE UP INFO
 - (10) SCHEMATIC DIAGRAM
 - (10) CIRCUIT DESCRIPTION
5. PART 90.203(e) & (g) ATTESTATION

BY M.F.A. INC.

- A. TESTIMONIAL & STATEMENT OF CERTIFICATION
- B. STATEMENT OF QUALIFICATIONS



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Sub-part
2.1033(c):

EQUIPMENT IDENTIFICATION

FCC ID: 0M3VTRAKF450

NAMEPLATE DRAWING

ATTACHED, EXHIBIT 1.

LOCATION

AS PER LABEL DRAWING(S)

DATE OF REPORT

December 21, 1999

SUPERVISED BY:

A handwritten signature in black ink, reading 'Morton Flom, P. Eng.' The signature is written in a cursive, flowing style.

Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1051	Unwanted Emissions (Transmitter Conducted)	9
2.1053(a)	Field Strength of Spurious Radiation	12
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	15
90.214	Transient Frequency Behavior	24
2.1055(a)(1)	Frequency Stability (Temperature Variation)	30
2.1055(b)(1)	Frequency Stability (Voltage Variation)	33
2.202(g)	Necessary Bandwidth and Emission Bandwidth	34

PAGE NO.

1 of 34.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

TEST REPORT

- b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85224
- c) Report Number: d99c0054
- d) Client: APPLICANT
- e) Identification: VTRAKF450
FCC ID: 0M3VTRAKF450
Description: UHF FM Mobile Data Tracking Transceiver System
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: December 21, 1999
EUT Received: October 15, 1999
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by:
- 
- Morton Flom, P. Eng.
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 34.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

90, Confidentiality

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:

Galaxy Tracking Systems L.L.C.
2500 English Creek Ave., Building C
Egg Harbor Township, NJ 08234

MANUFACTURER:

Applicant

(c)(2): FCC ID: 0M3VTRAKF450

MODEL NO: VTRAKF450

(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 20K0F1D

(c)(5): FREQUENCY RANGE, MHz: 450 to 470

(c)(6): POWER RATING, Watts: 2
Switchable Variable x N/A

(c)(7): MAXIMUM POWER RATING, Watts: 300

PAGE NO.

3 of 34.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



**THE AMERICAN
ASSOCIATION
FOR LABORATORY
ACCREDITATION**

ACCREDITED LABORATORY

A2LA has accredited

M. FLOM ASSOCIATES, INC.
Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24th day of November, 1998.



Peter M. Meyer
President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85224-1571
Morton Flom Phone: 602 926 3100

ELECTRICAL (EMC)

Valid to: December 31, 2000 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1
RF Immunity	EN 50082-1; EN 50082-2; AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
ESD	EN 61000-4-2; IEC 1000-4-2; IEC 801-2
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97

Peter M. Meyer

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8307 • Phone: 301 644 3200 • Fax: 301 662 2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

PAGE NO. 4 of 34.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 12

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for
determining and stabilizing frequency, for suppression of
spurious radiation, for limiting modulation and limiting
power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 X N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 34.

Sub-part
2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- _____ 21 - Domestic Public Fixed Radio Services
- _____ 22 - Public Mobile Services
- _____ 22 Subpart H - Cellular Radiotelephone Service
- _____ 22.901(d) - Alternative technologies and auxiliary services
- _____ 23 - International Fixed Public Radiocommunication services
- _____ 24 - Personal Communications Services
- _____ 74 Subpart H - Low Power Auxiliary Stations
- _____ 80 - Stations in the Maritime Services
- _____ 80 Subpart E - General Technical Standards
- _____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- _____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- _____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- _____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- _____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- _____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- _____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- _____ 80 Subpart X - Voluntary Radio Installations
- _____ 87 - Aviation Services
- X 90 - Private Land Mobile Radio Services
- _____ 94 - Private Operational-Fixed Microwave Service
- _____ 95 Subpart A - General Mobile Radio Service (GMRS)
- _____ 95 Subpart C - Radio Control (R/C) Radio Service
- _____ 95 Subpart D - Citizens Band (CB) Radio Service
- _____ 95 Subpart E - Family Radio Service
- _____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- _____ 97 - Amateur Radio Service
- _____ 101 - Fixed Microwave Services

PAGE NO.

6 of 34.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 34.
NAME OF TEST: Carrier Output Power (Conducted)
SPECIFICATION: 47 CFR 2.1046(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(Worst case)

FREQUENCY OF CARRIER, MHz = 460.000, 450.100, 469.900


POWER SETTING	R. F. POWER, WATTS
High	2

SUPERVISED BY:


 Morton Flom, P. Eng.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
TEST 2: FREQUENCY STABILITY



Asset	Description (as applicable)	s/n
(1)	COAXIAL ATTENUATOR	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2)	POWER METERS	
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(3)	FREQUENCY COUNTER	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 9 of 34.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 460.000, 450.100, 469.900

SPECTRUM SEARCHED, GHz = 0 to 10 x F_c

ALL OTHER EMISSIONS = 20 dB BELOW LIMIT

LIMIT(S), dBc
 $-(50+10 \times \text{LOG } P) = -53 \text{ (2 Watts)}$


SUPERVISED BY:



Morton Flom, P. Eng.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO.

11 of 34.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g99c0279: 1999-Dec-09 Thu 13:26:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
450.100000	900.203000	-38.3	-71.3	-25.3
460.000000	920.016000	-34.7	-67.7	-21.7
469.900000	939.809000	-34.6	-67.6	-21.6
450.100000	1350.781000	-43.1	-76.1	-30.1
460.000000	1379.612000	-43.2	-76.2	-30.2
469.900000	1410.107000	-43.1	-76.1	-30.1
450.100000	1800.623000	-42.8	-75.8	-29.8
460.000000	1839.575000	-43.5	-76.5	-30.5
469.900000	1879.216000	-43	-76	-30
450.100000	2250.840000	-41.3	-74.3	-28.3
460.000000	2300.295000	-42.5	-75.5	-29.5
469.900000	2349.292000	-40.9	-73.9	-27.9
450.100000	2700.249000	-45.2	-78.2	-32.2
460.000000	2760.215000	-44.9	-77.9	-31.9
469.900000	2819.732000	-45.1	-78.1	-32.1
450.100000	3151.064000	-45.7	-78.7	-32.7
460.000000	3220.233000	-44.8	-77.8	-31.8
469.900000	3289.479000	-44.6	-77.6	-31.6
450.100000	3600.666000	-44.6	-77.6	-31.6
460.000000	3679.529000	-45.1	-78.1	-32.1
469.900000	3758.806000	-45.6	-78.6	-32.6
450.100000	4050.513000	-46	-79	-33
460.000000	4139.608000	-43	-76	-30
469.900000	4229.513000	-44.5	-77.5	-31.5
450.100000	4501.344000	-44.7	-77.7	-31.7
460.000000	4599.860000	-44.9	-77.9	-31.9
469.900000	4699.153000	-44.5	-77.5	-31.5
450.100000	4951.038000	-44.9	-77.9	-31.9
460.000000	5059.720000	-45.5	-78.5	-32.5
469.900000	5168.458000	-43.8	-76.8	-30.8
450.100000	5401.014000	-44.8	-77.8	-31.8
460.000000	5519.502000	-44.1	-77.1	-31.1
469.900000	5638.472000	-44.3	-77.3	-31.3
450.100000	5851.298000	-38.1	-71.1	-25.1
460.000000	5979.833000	-39.2	-72.2	-26.2
469.900000	6108.747000	-39.3	-72.3	-26.3
450.100000	6301.714000	-39.4	-72.4	-26.4
460.000000	6439.942000	-38.7	-71.7	-25.7
469.900000	6578.294000	-37.6	-70.6	-24.6
450.100000	6751.622000	-39.7	-72.7	-26.7
460.000000	6899.582000	-38.8	-71.8	-25.8
469.900000	7048.642000	-39.3	-72.3	-26.3

PAGE NO. 12 of 34.
NAME OF TEST: Field Strength of Spurious Radiation
SPECIFICATION: 47 CFR 2.1053(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.12
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 2.948, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. Excess power leads were coiled near the power supply.

The cables were oriented in order to obtain the maximum response. At each emission frequency, the turntable was rotated and the search antennas were raised and lowered vertically.
4. The emission was observed with both a vertically polarized and a horizontally polarized search antenna and the worst case was used.
6. The field strength of each emission within 20 dB of the limit was recorded and corrected with the appropriate cable and transducer factors.
7. The worst case for all channels is shown.
8. Measurement results: ATTACHED FOR WORST CASE

PAGE NO. 14 of 34.

NAME OF TEST: Field Strength of Spurious Radiation
 g99b0542: 1999-Nov-30 Tue 11:48:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV	CF, dB	ERP, dBm	MARGIN, dB
460.000000	919.990300	10.59	32.12	-54.7	-34.7
460.000000	1380.001300	17.57	29.76	-50	-30.1
460.000000	1839.995300	19.31	31.82	-46.2	-26.3
460.000000	2300.008800	26.07	35.3	-36	-16
460.000000	2760.005800	2.4	37.65	-57.3	-37.4
460.000000	3220.005800	-3.6	38.21	-62.8	-42.8
460.000000	3680.005300	5.27	39.38	-52.7	-32.8
460.000000	4140.012000	7.7	40.53	-49.1	-29.2
460.000000	4600.019000	8.04	41.85	-47.5	-27.5


PAGE NO. 15 of 34.
NAME OF TEST: Emission Masks (Occupied Bandwidth)
SPECIFICATION: 47 CFR 2.1049(c)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ± 2.5 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 16 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99b0299: 1999-Nov-16 Tue 09:35:00
STATE: 2:High Power Without RS 232




POWER: HIGH
MODULATION: NONE

SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 17 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99c0277: 1999-Dec-09 Thu 13:07:00
STATE: 2:High Power Without RS 232




POWER: HIGH
MODULATION: DATA 19200 BITS PER SECOND
CHANNEL 00 W0/RS232
MASK: C, VHF/UHF 25kHz, no LPF

SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 18 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99c0276: 1999-Dec-09 Thu 13:05:00
STATE: 2:High Power Without RS 232




POWER: HIGH
MODULATION: DATA 19200 BITS PER SECOND
CHANNEL 01 W0/RS232
MASK: C, VHF/UHF 25kHz, no LPF

SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 19 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99c0278: 1999-Dec-09 Thu 13:09:00
STATE: 2:High Power Without RS 232




POWER: HIGH
MODULATION: DATA 19200 BITS PER SECOND
CHANNEL 02 W0/RS232
MASK: C, VHF/UHF 25kHz, no LPF

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 20 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99c0269: 1999-Dec-02 Thu 09:31:00
STATE: 2:High Power With RS 232




POWER: HIGH
MODULATION: NONE

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 21 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99c0272: 1999-Dec-02 Thu 09:54:00
STATE: 2:High Power With RS 232



POWER: HIGH
MODULATION: DATA 19200 BIT PER SECOND
CHANNEL 00
MASK: C, VHF/UHF 25KHZ, NO LPF


SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO.

22 of 34.

```
NAME OF TEST:      Emission Masks (Occupied Bandwidth)
g99c0271: 1999-Dec-02 Thu 09:42:00
STATE: 2:High Power With RS 232
```



POWER:
MODULATION:


HIGH
DATA 19200 BIT PER SECOND
CHANNEL 01
MASK: C, VHF/UHF 25kHz, no
LPF

SUPERVISED BY:

M. Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 23 of 34.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g99c0270: 1999-Dec-02 Thu 09:36:00
STATE: 2:High Power With RS 232



POWER: HIGH
MODULATION: DATA 19200 BIT PER SECOND
CHANNEL 02
MASK: C, VHF/UHF 25kHz, no LPF

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 24 of 34.
NAME OF TEST: Transient Frequency Behavior
SPECIFICATION: 47 CFR 90.214
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:


step f, dBm	= -19.8
step h, dBm	= -38.2
step l, dBm	= 12.3



SUPERVISED BY:

Morton Flom, P. Eng.


TRANSIENT FREQUENCY BEHAVIOR



Asset	Description (as applicable)	s/n
(1)	ATTENUATOR (Removed after 1st step)	
i00112	Philco 30 dB	989
(2)	ATTENUATOR	
i00112	Philco 30 dB	989
i00172	Bird 30 dB	989
i00122	Narda 10 dB	7802
i00123	Narda 10 dB	7802A
i00110	Kay Variable	145-387
(3)	COMBINER	
i00154	4 x 25 Ω COMBINER	154
(4)	CRYSTAL DETECTOR	
i00159	HP 8470B	1822A10054
(5)	RF SIGNAL GENERATOR	
i00018	HP 8656A	2228A03472
i00031	HP 8656A	2402A06180
i00067	HP 8920A	3345U01242
(6)	MODULATION ANALYZER	
i00020	HP 8901A	2105A01087
(7)	SCOPE	
i00030	HP 54502A	2927A00209

PAGE NO. 26 of 34.

NAME OF TEST: Transient Frequency Behavior
g99c0280: 1999-Dec-20 Mon 15:00:00
STATE: 2:High Power




POWER: HIGH
MODULATION: Ref Gen=25 kHz Deviation
DESCRIPTION: CARRIER ON TIME

SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 27 of 34.

NAME OF TEST: Transient Frequency Behavior
g99c0281: 1999-Dec-20 Mon 15:01:00
STATE: 2:High Power




POWER: HIGH
MODULATION: Ref Gen=25 kHz Deviation
DESCRIPTION: CARRIER ON TIME

SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 28 of 34.

NAME OF TEST: Transient Frequency Behavior
g99c0282: 1999-Dec-20 Mon 15:04:00
STATE: 2:High Power



POWER: HIGH
MODULATION: Ref Gen=25 kHz Deviation
DESCRIPTION: CARRIER OFF TIME


SUPERVISED BY:

Morton Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO. 29 of 34.

NAME OF TEST: Transient Frequency Behavior
g99c0283: 1999-Dec-20 Mon 15:04:00
STATE: 2:High Power



POWER:	HIGH
MODULATION:	Ref Gen=25 kHz Deviation
DESCRIPTION:	CARRIER OFF TIME

SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 30 of 34.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated


TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. OPERATIONAL STABILITY
- TEST B. CARRIER FREQUENCY STABILITY
- TEST C. OPERATIONAL PERFORMANCE STABILITY
- TEST D. HUMIDITY
- TEST E. VIBRATION
- TEST F. ENVIRONMENTAL TEMPERATURE
- TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
- TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Asset	Description (as applicable)	s/n
(1)	<u>TEMPERATURE, HUMIDITY, VIBRATION</u>	
i00027	Tenny Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2)	<u>COAXIAL ATTENUATOR</u>	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	<u>R.F. POWER</u>	
i00014	HP 435A POWER METER	1733A05839
i00039	HP 436A POWER METER	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(4)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

PAGE NO.

32 of 34.

NAME OF TEST: Frequency Stability (Temperature Variation)
g99b0320: 1999-Nov-16 Tue 11:35:00
STATE: 0:General



SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO. 33 of 34.
NAME OF TEST: Frequency Stability (Voltage Variation)
SPECIFICATION: 47 CFR 2.1055(b)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)
 g99b0308: 1999-Nov-16 Tue 11:08:44
 STATE: 0:General

LIMIT, ppm = 2.5
 LIMIT, Hz = 1150
 BATTERY END POINT (Voltage) = 9.2

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	10.2	460.000040	40	0.09
100	12	460.000000	0	0.00
115	13.8	459.999960	-40	-0.09
77	9.2	459.999950	-50	-0.11

SUPERVISED BY:



Morton Flom, P. Eng.

PAGE NO. 34 of 34.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 20K0F1D

BAND RATE = 19.2K bps

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 6.4
MAXIMUM DEVIATION (D), kHz	= 3.6
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2 x M) + (2 x D x K)
	= 20.0

SUPERVISED BY:



Morton Flom, P. Eng.

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:


Morton Flom, P. Eng.