



Test Report No.: FM2008WDG0310

RF EXPOSURE REPORT

Applicant	Icon Health and Fitness, Inc.
Address	1500 South 1000 West, Logan Utah United States 84321

Manufacturer or Supplier	Icon Health and Fitness, Inc.
Address	1500 South 1000 West, Logan Utah United States 84321
Product	Tablet
Brand Name	N/A
Model	MP32-Argon2
Additional Model & Model Difference	N/A
Date of tests	Sep. 29, 2020 ~ Nov. 09, 2020

- ☒ FCC Part 2 (Section 2.1091)
☒ KDB 447498 D01
☒ IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date Nov. 17, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM2008WDG0310

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2008WDG0310	Original release	Nov. 17, 2020



Test Report No.: FM2008WDG0310

1. CERTIFICATION

PRODUCT: Tablet

BRAND NAME: N/A

MODEL NO.: MP32-Argon2

ADDITIONAL MODEL: N/A

FCC ID: OMC425341

TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: Icon Health and Fitness, Inc.

TESTED DATES: Sep. 29, 2020 ~ Nov. 09, 2020

STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Frequency Band	Antenna Gain (dBi)	Antenna Type
Wi-Fi 2.4GHz	2.82	FPCB Antenna
BT 2.4GHz	2.82	FPCB Antenna
Wi-Fi 5GHz (5150-5250MHz)	4.82	FPCB Antenna
Wi-Fi 5GHz (5250-5350MHz)	5.27	FPCB Antenna
Wi-Fi 5GHz (5500-5725MHz)	4.60	FPCB Antenna
Wi-Fi 5GHz (5725-5850MHz)	6.03	FPCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT (GFSK)	2402-2480MHz	7	+/-1	6	8
BT (8DPSK)	2402-2480MHz	5	+/-1	4	6
BT-LE (GFSK)	2402-2480MHz	6	+/-1	5	7
802.11b	2412-2462MHz	13	+/-1	12	14
802.11g	2412-2462MHz	13	+/-1	12	14
802.11n HT20	2412-2462MHz	12	+/-1	11	13
Wi-Fi 5GHz(Band1)	5150-5250MHz	14	+/-2	12	16
Wi-Fi 5GHz(Band2)	5250-5350MHz	14	+/-2	12	16
Wi-Fi 5GHz(Band3)	5500-5725MHz	14	+/-2	12	16
Wi-Fi 5GHz(Band4)	5725-5850MHz	14	+/-2	12	16



The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
BT (GFSK)	2402	6.69
BT (8DPSK)	2402	4.61
BT-LE (GFSK)	2402	5.98
802.11b	2412	12.26
802.11g	2437	12.58
802.11n HT20	2412	11.65
Wi-Fi 5GHz(Band1)	5240	14.41
Wi-Fi 5GHz(Band2)	5320	14.47
Wi-Fi 5GHz(Band3)	5700	14.45
Wi-Fi 5GHz(Band4)	5785	14.27

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
BT 2.4GHz	8	2.82	20	0.002403	1.0
Wi-Fi 2.4GHz	14	2.82	20	0.009566	1.0
Wi-Fi 5GHz	16	6.03	20	0.031749	1.0

CONCLUSION:

The WLAN 2.4GHz and 5GHz can not transmit simultaneously, the BT and WLAN can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$(0.002403 / 1) + (0.031749 / 1) = 0.034151 < 1, \text{ which is less than the "1" limit.}$$

--- END ---