


FCC RADIO TEST REPORT

Applicant..... : La Crosse Technology Ltd.
Address..... : 2809 Losey Blvd. South, La Crosse Wisconsin 54601 United States
Manufacturer..... : La Crosse Technology Ltd.
Address..... : 2809 Losey Blvd. South, La Crosse Wisconsin 54601 United States
Factory : La Crosse Technology Ltd.
Address : 2809 Losey Blvd. South, La Crosse Wisconsin 54601 United States
Product Name..... : REMOTE SENSOR
Brand Name..... : LA CROSSE TECHNOLOGY
Model No. : TX146 (For additional model and model difference refer to section 2)
FCC ID..... : OMOTX146
Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.231)
Receipt Date of Samples..... : January 19, 2022
Date of Tested..... : January 19, 2022 to March 26, 2022
Date of Report..... : March 26, 2022

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.


Prepared by
Alina Guo / Project Engineer


Approved by
Iori Fan / Authorized Signatory



Table of Contents

1. Summary of Test Result	4
2. General Description of EUT	5
3. Test Channels and Modes Detail	7
4. Configuration of EUT	7
5. Modification of EUT	7
6. Description of Support Device	7
7. Test Facility and Location	8
8. Applicable Standards and References	9
9. Deviations and Abnormalities from Standard Conditions.....	9
10. Test Conditions	9
11. Measurement Uncertainty.....	10
12. Sample Calculations	11
13. Test Items and Results	12
13.1 Conducted Emissions Measurement.....	12
13.2 Radiated Spurious Emissions Measurement	14
13.3 20dB Occupied Bandwidth	27
13.4 Transmission time.....	29
13.5 Antenna Requirement.....	32
14. Test Equipment List	33

Revision History

[illegible]

1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.207 (a)	AC Power Line Conducted Emission	N/A ^{see note 2}	---
§15.231(b) & 15.209 §15.231(e)	Radiated Spurious Emission	PASS	---
§15.231(c)	20 dB Occupied bandwidth	PASS	---
§15.231(a) §15.231(e)	Transmission time	PASS	---
§15.203	Antenna Requirement	PASS	---

Note: 1. The EUT has been tested as an independent unit. And continual transmitting in maximum power (New batteries were used during test)

2. AC Power Conducted Emission is not applicable due to the EUT only can be powered by battery.

2. General Description of EUT

Product Information	
Product Name:	REMOTE SENSOR
Main Model Name:	TX146
Additional Model Name:	TX146xx, TX146xx-xxx, TX146xxx, TX146xxx-xxx, TX146xxxx, TX146xxxx-xxx, TX146-xx, TX146-xxx, TX146-xx-xxx (x can be 0~9 or A~Z or a~z, the difference for different version are the product shell color and packaging upgrade version number, when upgrade a version the number progressed to next number)
Model Difference:	These models have the same circuit schematic, construction, PCB Layout and critical components. These differences are model number, color and packaging upgrade version number only due to trading purpose.
S/N:	TX06700001
Brand Name:	LA CROSSE TECHNOLOGY
Hardware Version:	TX067 REV02
Software Version:	XCT067_2705
Rating:	DC 3V from AA battery*2
Classification:	Class B
Typical arrangement:	Table-top
I/O Port:	N/A
Accessories Information	
Adapter:	N/A
Cable:	N/A
Other:	N/A
Additional Information	
Note:	1. According to these model differences, all tests were carried on model TX146. 2. The EUT has two launch states, automatic launch operating and manual button launch.
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification	
Declaring the Frequency:	433.92MHz $\pm$ 150KHz Tolerance
Modulation Type:	ASK
Antenna Type:	PCB antenna
Antenna Gain:	0 dBi (Declared by manufacturer)
Number of Channels:	1

3. Test Channels and Modes Detail

Mode		Test Frequency (MHz)	Modulation	Data Rate (Mbps)
1	TX	433.88MHz	ASK	----

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

4. Configuration of EUT

TX Mode

EUT

5. Modification of EUT

No modifications are made to the EUT during all test items.

6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
---	---	---	---	---	---	---

7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	The Laboratory has been assessed and proved to be in compliance with CNAS/CL01 Listed by CNAS, August 13, 2018 The Certificate Registration Number is L5795. The Certificate is valid until August 13, 2024 The Laboratory has been assessed and proved to be in compliance with ISO17025 Listed by A2LA, November 01, 2017 The Certificate Registration Number is 4429.01 Listed by FCC, November 06, 2017 Test Firm Registration Number: 907417 Listed by Industry Canada, June 08, 2017 The Certificate Registration Number. Is 46405-9743A
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 15, Subpart C, 15.231

ANSI C63.10-2013

References Test Guidance:

N/A

9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	AC Power Conducted Emission	---	---	---	---
2.	Radiated Emission	1	DC 3V	Sean	See note 1
3.	20 dB Occupied bandwidth	1	DC 3V	Sean	See note 1
4.	Transmission time	1	DC 3V	Sean	See note 1
5.	Antenna Requirement	---	---	---	---

Note:

- The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35℃, 30~70%, 86~106kPa
- As the EUT can be operated multiple positions, all X,Y,Z axis were considered during the test and only the worst case X was recorded.

11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	±2.52 dB	---
2.	Radiated Emission Test	9kHz ~ 30MHz	±2.60 dB	---
		30MHz ~ 1GHz	±4.68 dB	---
		1GHz ~ 18GHz	±5.14 dB	---
		18GHz ~ 40GHz	±5.14 dB	

Note:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBUV)	Correct Factor (dB)	Measurement (dBUV)	Limit (dBUV)	Over (dB)	Detector
0.1900	30.10	10.60	40.70	79.00	-38.30	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver Reading Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation Measurement = Reading + Corrector Factor Limit = Limit stated in standard Margin = Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Radiated Spurious Emissions						
Freq. (MHz)	Reading Level (dBUV)	Correct Factor (dB/m)	Measurement (dBUV/m)	Limit (dBUV/m)	Over (dB)	Detector
60.0700	45.88	-18.38	27.50	49.00	-21.50	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver Reading Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier Measurement = Reading + Corrector Factor Limit = Limit stated in standard Over = Margin, which calculated by Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

13. Test Items and Results

13.1 Conducted Emissions Measurement


LIMIT

According to the requirements of FCC PART 15.207, the limits are as follows:

Frequency (MHz)	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

- Note:
1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
 2. The lower limit shall apply at the transition frequencies.
 3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

TEST RESULTS

Not applicable.

13.2 Radiated Spurious Emissions Measurement

LIMIT

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		$\mu\text{V/m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark: (1) Emission level $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

(4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

(5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.


According to 15.231(b), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/ meter)	spurious emissions (microvolts/meter)
40.66 - 40.70	2250	225
70 - 130	1250	125
130 - 174	1250 to 3750*	125 to 375*
174 - 260	3750	375
260 - 470	3750 to 12500*	375 to 1250*
Above 470	12500	1250


Remark: (1) * Linear interpolations
 (2) Emission level (dB) μ V = 20 log Emission level μ V/m.
 (3) The smaller limit shall apply at the cross point between two frequency bands.

BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:

The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

TEST RESULTS

PASS

Please refer to the following pages.

Automatic launch operating status:


M/N: TX146	Testing Voltage: DC 3V
Polarization: Horizontal	Detector: QP
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/2/23

Time: 13:45:39

82.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		433.8800	24.45	24.22	48.67	72.87	-24.20	QP	
2		606.1800	7.13	27.40	34.53	46.00	-11.47	QP	
3		672.1400	7.25	28.40	35.65	46.00	-10.35	QP	
4		745.8600	6.08	29.58	35.66	46.00	-10.34	QP	
5		811.8200	6.13	30.54	36.67	46.00	-9.33	QP	
6	*	867.7600	19.48	31.50	50.98	52.87	-1.89	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.


M/N: TX146	Testing Voltage: DC 3V
Polarization: Vertical	Detector: QP
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/2/23

Time: 13:41:16

82.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		392.7800	13.61	22.55	36.16	46.00	-9.84	QP	
2		406.3599	15.27	22.82	38.09	46.00	-7.91	QP	
3	*	433.8800	47.57	23.22	70.79	72.87	-2.08	QP	
4		542.1599	11.39	25.15	36.54	46.00	-9.46	QP	
5		716.7600	6.92	29.19	36.11	46.00	-9.89	QP	
6		867.7600	14.80	31.50	46.30	52.87	-6.57	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.


M/N: TX146	Testing Voltage: DC 3V
Polarization: Horizontal	Detector: Peak & AVG
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/2/23

Time: 13:50:08

100.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2603.280	60.81	0.76	61.57	74.00	-12.43	peak	
2	*	2603.280	49.86	0.76	50.62	54.00	-3.38	AVG	
3		3037.160	56.55	1.85	58.40	74.00	-15.60	peak	
4		3037.160	43.26	1.85	45.11	54.00	-8.89	AVG	
5		3471.040	60.35	2.68	63.03	74.00	-10.97	peak	
6		3471.040	46.87	2.68	49.55	54.00	-4.45	AVG	
7		3904.920	55.22	3.75	58.97	74.00	-15.03	peak	
8		3904.920	45.29	3.75	49.04	54.00	-4.96	AVG	
9		4338.800	49.51	4.75	54.26	74.00	-19.74	peak	
10		4338.800	38.21	4.75	42.96	54.00	-11.04	AVG	
11		4772.680	51.16	6.19	57.35	74.00	-16.65	peak	
12		4772.680	40.85	6.19	47.04	54.00	-6.96	AVG	


M/N: TX146	Testing Voltage: DC 3V
Polarization: Vertical	Detector: Peak & AVG
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/2/23

Time: 13:56:26

100.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		1735.520	62.42	-4.33	58.09	74.00	-15.91	peak	
2		1735.520	50.98	-4.33	46.65	54.00	-7.35	AVG	
3		2169.400	60.83	-0.47	60.36	74.00	-13.64	peak	
4		2169.400	47.83	-0.47	47.36	54.00	-6.64	AVG	
5		2603.280	60.37	0.76	61.13	74.00	-12.87	peak	
6	*	2603.280	49.71	0.76	50.47	54.00	-3.53	AVG	
7		3037.160	56.25	1.85	58.10	74.00	-15.90	peak	
8		3037.160	43.40	1.85	45.25	54.00	-8.75	AVG	
9		3471.040	63.39	2.68	66.07	74.00	-7.93	peak	
10		3471.040	42.05	2.68	44.73	54.00	-9.27	AVG	
11		3904.920	60.52	3.75	64.27	74.00	-9.73	peak	
12		3904.920	45.85	3.75	49.60	54.00	-4.40	AVG	

Manual button launch status:


M/N: TX146	Testing Voltage: DC 3V
Polarization: Horizontal	Detector: QP
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/3/26

Time: 9:41:27

82.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		433.8800	25.03	24.22	49.25	80.80	-31.55	QP	
2	*	498.6200	11.08	25.44	36.52	46.00	-9.48	QP	
3		618.5780	7.60	27.56	35.16	46.00	-10.84	QP	
4		736.9500	7.02	29.46	36.48	46.00	-9.52	QP	
5		804.6200	5.70	30.39	36.09	46.00	-9.91	QP	
6		867.7600	19.34	31.50	50.84	60.80	-9.96	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.


M/N: TX146	Testing Voltage: DC 3V
Polarization: Vertical	Detector: QP
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/3/26

Time: 9:35:15

82.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		349.6200	13.41	21.75	35.16	46.00	-10.84	QP	
2	*	407.9200	14.77	22.85	37.62	46.00	-8.38	QP	
3		433.8800	47.84	23.22	71.06	80.80	-9.74	QP	
4		578.1599	10.16	26.03	36.19	46.00	-9.81	QP	
5		729.6200	7.17	29.37	36.54	46.00	-9.46	QP	
6		867.7600	15.49	31.50	46.99	60.80	-13.81	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.


M/N: TX146	Testing Voltage: DC 3V
Polarization: Horizontal	Detector: Peak & AVG
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/3/26

Time: 9:37:24

100.0 dBuV/m



No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	2603.280	60.77	0.76	61.53	80.80	-19.27	peak	
2	2603.280	49.72	0.76	50.48	60.80	-10.32	AVG	
3	3037.160	56.08	1.85	57.93	80.80	-22.87	peak	
4	3037.160	44.45	1.85	46.30	60.80	-14.50	AVG	
5	3471.040	59.60	2.68	62.28	80.80	-18.52	peak	
6	3471.040	46.95	2.68	49.63	60.80	-11.17	AVG	
7	3904.920	54.38	3.75	58.13	74.00	-15.87	peak	
8	3904.920	43.13	3.75	46.88	54.00	-7.12	AVG	
9	4338.800	48.73	4.75	53.48	80.80	-27.32	peak	
10	4338.800	39.16	4.75	43.91	60.80	-16.89	AVG	
11	4772.680	50.82	6.19	57.01	74.00	-16.99	peak	
12 *	4772.680	41.19	6.19	47.38	54.00	-6.62	AVG	


M/N: TX146	Testing Voltage: DC 3V
Polarization: Vertical	Detector: Peak & AVG
Test Mode: TX	Distance: 3m

Radiated Emission Measurement

Date: 2022/3/26

Time: 9:42:59

100.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		1735.520	62.57	-4.33	58.24	80.80	-22.56	peak
2		1735.520	50.68	-4.33	46.35	60.80	-14.45	AVG
3		2169.400	60.75	-0.47	60.28	80.80	-20.52	peak
4		2169.400	47.96	-0.47	47.49	60.80	-13.31	AVG
5		2603.280	60.62	0.76	61.38	80.80	-19.42	peak
6		2603.280	50.24	0.76	51.00	60.80	-9.80	AVG
7		3037.160	56.11	1.85	57.96	80.80	-22.84	peak
8		3037.160	44.66	1.85	46.51	60.80	-14.29	AVG
9		3471.040	63.15	2.68	65.83	80.80	-14.97	peak
10		3471.040	41.94	2.68	44.62	60.80	-16.18	AVG
11		3904.920	60.40	3.75	64.15	74.00	-9.85	peak
12	*	3904.920	45.21	3.75	48.96	54.00	-5.04	AVG


13.3 20dB Occupied Bandwidth

LIMIT

According to 15.231(C), the bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz.

Limit = $433.88\text{MHz} \times 0.25\% = 1084.7 \text{ KHz}$

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

1. The output port (antenna) from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.
2. Spectrum analyzer set the corresponding parameters for measurement and record the tested data


TEST RESULTS

PASS

Please refer to the following table.

Frequency (MHz)	20 dB Bandwidth (KHz)	Limit (KHz)	Result
433.88	215.9	1084.7	PASS

Test Photo



13.4 Transmission time


LIMIT

15.231 (a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

15.231(a) (2) A transmitter activated automatically shall cease transmission within 5seconds after activation.

15.231(e), under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at lest 30 times the duration of transmission but in no case less than 10 seconds.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

1. The output port (antenna) from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.
2. Spectrum analyzer set the corresponding parameters for measurement and record the tested data.

TEST RESULTS





PASS

Please refer to the following table.

Automatic launch operating status:

Frequency (MHz)	Transmission time (sec)	Limit (sec)	The silent period time (sec)	Limit (sec)	Result
433.88	0.38	<1	31	>10	PASS


Test Photo



Manual button launch status:

Frequency (MHz)	Transmission time (sec)	Limit (sec)	Result
433.88	0.39	<5	PASS

Test Photo



13.5 Antenna Requirement

STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

ANTENNA CONNECTED CONSTRUCTION

The antenna is PCB antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 0dBi, Therefore, the antenna is consider meet the requirement.

14. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Mar. 13, 2021	1 Year
2.	Antenna	Schwarzbeck	VULB9162	9162-010	Mar. 23, 2021	1 Year
3.	Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	Mar. 13, 2021	1 Year
4.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Mar. 13, 2021	1 Year
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	101094	Mar. 13, 2021	1 Year
6.	Horn Antenna	Schwarzbeck	BBHA9170	9170-172	Mar. 23, 2021	2 Year
7.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Mar. 13, 2021	1 Year
8.	Horn Antenna	COM-Power	AH-118	071078	Mar. 23, 2021	1 Year
9.	Pre-Amplifier	HP	HP 8449B	3008A00964	Mar. 13, 2021	1 Year
10.	Pre-Amplifier	HP	HP 8447D	1145A00203	Mar. 13, 2021	1 Year
11.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Mar. 23, 2021	1 Year
12.	Test Receiver	Rohde & Schwarz	ESCI	101152	Mar. 13, 2021	1 Year
13.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Mar. 13, 2021	1 Year
14.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Mar.13, 2021	1 Year
15.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
16.	Test Software	EZ	EZ_EMC NTC-3A1.1	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---