

# FCC RF EXPOSURE REPORT

## FCC ID: OMOTX191TH

**Project No.** : 1907C198  
**Equipment** : OUTDOOR SENSOR  
**Brand Name** : LA CROSSE  
**Test Model** : TX191TH  
**Series Model** : TX191TH-INT, TX191THvX, TX191THvX-INT, TX191TH-XX, TX191TH-XX-INT (X can be 0~9, the difference for different version are the product shell color, software, and packaging upgrade version number, when upgrade a version the number progressed to next number.)  
**Applicant** : La Crosse Technology Ltd.  
**Address** : 2809 Losey Blvd. S. La Crosse Wisconsin 54601 United States  
**Manufacturer** : La Crosse Technology Ltd.  
**Address** : 2809 Losey Blvd. S. La Crosse Wisconsin 54601 United States  
**Factory** : La Crosse Technology Ltd.  
**Address** : 2809 Losey Blvd. S. La Crosse Wisconsin 54601 United States  
**Date of Receipt** : Jul. 25, 2019  
**Date of Test** : Jul. 26, 2019 ~ Aug. 06, 2019  
**Issued Date** : Aug. 12, 2019  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: DG1907261  
**Standard(s)** : FCC Part15, Subpart C(15.231)  
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

*Rose. Liu*

Prepared by : Rose Liu

*Ethan Ma*

Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: [www.newbtl.com](http://www.newbtl.com)

**REPORT ISSUED HISTORY**

| Report Version | Description     | Issued Date   |
|----------------|-----------------|---------------|
| R00            | Original Issue. | Aug. 12, 2019 |

**GENERAL CONCLUSION:**

Maximum measured transmitter power:

| Output Power<br>(dBm) | Output Power<br>(mW) | Limit(mW) |
|-----------------------|----------------------|-----------|
| -22.76                | 0.0053               | 10        |

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100MHz-6GHz and  $\leq 50$  mm

The maximum measured output peak power of this EUT is 0.0053mW, less than 10mW at 20cm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

**End of Test Report**