



FCC TEST REPORT

According to

FCC CFR Title 47 Part 15 Subpart C

Applicant	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Manufacturer	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Equipment	: MOBILE PHONE
Model No.	: ASTRO 5.5
Trade Name	: MAXWEST
FCC ID	: ONGASTRO55

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **Cerpass Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.



Table of Contents

1. Report of Measurements and Examinations	6
1.1 List of Measurements and Examinations	6
2. Test Configuration of Equipment under Test	7
2.1 Feature of Equipment under Test	7
2.2 Carrier Frequency of Channels	8
2.3 Test Manner	9
2.4 Description of Test System	10
2.5 General Information of Test	11
2.6 Measurement Uncertainty	11
3. Antenna Requirements	12
3.1 Standard Applicable	12
3.2 Antenna Construction and Directional Gain	12
4. Test of Conducted Emission	13
4.1 Test Limit	13
4.2 Test Procedures	13
4.3 Typical Test Setup	14
4.4 Measurement Equipment	14
4.5 Test Result and Data	15
5. Test of Radiated Emission	17
5.1 Test Limit	17
5.2 Test Procedures	17
5.3 Typical Test Setup	18
5.4 Measurement Equipment	19
5.5 Test Result and Data	20
6. Occupied Bandwidth	33
6.1 Test Limit	33
6.2 Test Procedures	33
6.3 Test Setup Layout	33
6.4 Measurement Equipment	33
6.5 Test Result and Data	34
7. Maximum Peak Output Power	42
7.1 Test Limit	42
7.2 Test Procedure	42
7.3 Test Setup Layout	42
7.4 Measurement Equipment	42
7.5 Test Result and Data	43
8. Band Edges Measurement	46
8.1 Test Limit	46
8.2 Test Procedure	46
8.3 Test Setup Layout	46



8.4	Measurement Equipment	46
8.5	Test Result and Data	47
8.6	Restrict Band Emission Measurement Data.....	56
9.	Power Spectral Density	58
9.1	Test Limit.....	58
9.2	Test Procedure	58
9.3	Test Setup Layout.....	58
9.4	Measurement Equipment	58
9.5	Test Result and Data	59
10.	Restricted Bands of Operation	67
10.1	Labeling Requirement	67



Document history

Attachment No.	Date	Description



FCC TEST REPORT

according to

FCC CFR Title 47 Part 15 Subpart C

Applicant	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Manufacturer	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Equipment	: MOBILE PHONE
Model No.	: ASTRO 5.5
Trade Name	: MAXWEST
FCC ID	: ONGASTRO55

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2009** and the energy emitted by this equipment was **passed** **CISPR PUB. 22 and FCC Part 15** in both radiated and conducted emission class B limits. Testing was carried out on Oct 17, 2014 at **Cerpass Technology Corp.**

Signature

Miro Chueh/ Technical director



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209 15.247(d)	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(d)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(e)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

WLAN	
Spreading	802.11b: CCK, DQPSK, DBPSK 802.11g: 64 QAM, 16 QAM, QPSK, BPSK 802.11n: BPSK, QPSK, 16QAM, 64QAM
Frequency Range	802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz
Number of Channels	802.11b/g/n (20MHz): 11 802.11n (40MHz): 7
Data Rate	802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0~MCS7
Antenna	PIFA Antenna 1.5 dBi



2.2 Carrier Frequency of Channels

For 2.4G 802.11b, 802.11g, 802.11n (20MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	---	---

For 2.4G 802.11n (40MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	---	08	2447
02	---	09	2452
03	2422	---	---
04	2427	---	---
05	2432	---	---
06	2437	---	---
07	2442	---	---



2.3 Test Manner

Test Manner	
a	During testing, the interface cables and equipment positions were varied according to 47 CFR, Part 2, Part 15
b	Adjust the EUT at the test mode and the test channel. Then test.
The test modes:	
The EUT transmitting and receiving with one antenna working at b/g/n mode. The chip set MT6627 supports 802.11 b/g/n configuration was finally used in this report. The worst-case data rates are determined to be as follows for each mode based on investigation by measuring the average power, peak power and PPSP across all data rates, bandwidths, and modulations. The worst-case data rates: IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing. IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing. IEEE 802.11n Standard-20 MHz Channel mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with MCS0 data rate were chosen for full testing. IEEE 802.11n Wide-40 MHz Channel mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with MCS0 data rate were chosen for full testing. Then, the EUT configuration and cable configuration of the above highest emission mode was recorded for all final test items.	



2.4 Description of Test System

No	Device	Manufacturer	Model No.	Description
N/A	N/A	N/A	N/A	N/A

Use Cable:

No.	Cable	Quantity	Description
N/A	N/A	N/A	N/A



2.5 General Information of Test

Test Site:	Cerpass Technology Corp.
Performand Location :	No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China
NVLAP LAB Code :	200814-0
FCC Registration Number :	916572, 331395
IC Registration Number :	7290A-1, 7290A-2
VCCI Registration Number :	T-343 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test below 1GHz G-227 for Radiated emission test above 1GHz

Laboratory accreditation



2.6 Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	±2.71 dB
Radiated Emission	30 MHz ~ 25GHz	Vertical	±4.11 dB
		Horizontal	±4.10 dB
Occupied Bandwidth	---	---	±7500 Hz
Maximum Peak Output Power	---	---	±1.4 dB
Band Edges	---	---	±2.2 dB
Power Spectral Density	---	---	±2.2 dB



3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna Model: Z550A
Antenna type: PIFA Antenna
Antenna Gain: 1.5 dBi



4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

4.2 Test Procedures

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of Oct 2002 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)


Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.



4.3 Typical Test Setup




4.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2014.03.24	2015.03.23
AMN	R&S	ESH2-Z5	100182	2014.09.04	2015.09.03
Two-Line V-Network	R&S	ENV216	100325	2013.12.04	2014.12.03
ISN	FCC	FCC-TLISN-T2-02	20379	2014.03.24	2015.03.23
ISN	FCC	FCC-TLISN-T4-02	20380	2014.03.24	2015.03.23
ISN	FCC	FCC-TLISN-T8-02	20381	2014.03.24	2015.03.23
ISN	TESEQ	ISN ST08	30175	2014.03.24	2015.03.23
Current Probe	R&S	EZ-17	100303	2014.04.04	2015.04.03
Passive Voltage Probe	R&S	ESH2-Z3	100026	2014.03.24	2015.03.23
Pulse Limiter	R&S	ESH3-Z2	100529	2014.03.24	2015.03.23
Temperature/Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2014.03.31	2015.03.30



4.5 Test Result and Data

Test Mode :	Mode 1: USB link Notebook PC		
AC Power :	AC 120V/60Hz	Phase :	LINE
Temperature :	26°C	Humidity :	60%
Pressure(mbar) :	1002	Date:	2014/10/15




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1620	10.13	45.60	55.73	65.36	-9.63	QP
2	0.1620	10.13	29.83	39.96	55.36	-15.40	AVG
3	0.3740	10.15	24.36	34.51	58.41	-23.90	QP
4	0.3740	10.15	6.82	16.97	48.41	-31.44	AVG
5	0.7500	10.14	25.13	35.27	56.00	-20.73	QP
6	0.7500	10.14	7.73	17.87	46.00	-28.13	AVG
7	2.2900	10.17	21.08	31.25	56.00	-24.75	QP
8	2.2900	10.17	10.26	20.43	46.00	-25.57	AVG
9	9.0900	10.26	18.24	28.50	60.00	-31.50	QP
10	9.0900	10.26	8.64	18.90	50.00	-31.10	AVG
11	22.3500	10.38	23.18	33.56	60.00	-26.44	QP
12	22.3500	10.38	15.48	25.86	50.00	-24.14	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: USB link Notebook PC		
AC Power :	AC 120V/60Hz	Phase :	NEUTRAL
Temperature :	26°C	Humidity :	60%
Pressure(mbar) :	1002	Date:	2014/10/15



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1700	10.13	46.42	56.55	64.96	-8.41	QP
2	0.1700	10.13	30.26	40.39	54.96	-14.57	AVG
3	0.2140	10.13	33.69	43.82	63.04	-19.22	QP
4	0.2140	10.13	11.15	21.28	53.04	-31.76	AVG
5	0.7539	10.16	24.09	34.25	56.00	-21.75	QP
6	0.7539	10.16	6.38	16.54	46.00	-29.46	AVG
7	9.3340	10.26	21.17	31.43	60.00	-28.57	QP
8	9.3340	10.26	8.67	18.93	50.00	-31.07	AVG
9	16.7979	10.49	18.27	28.76	60.00	-31.24	QP
10	16.7979	10.49	9.25	19.74	50.00	-30.26	AVG
11	22.0340	10.40	22.87	33.27	60.00	-26.73	QP
12	22.0340	10.40	15.06	25.46	50.00	-24.54	AVG

Note: Measurement Level = Reading Level + Correct Factor



5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 9 KHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions. For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ m)
30-230	10	30
230-1000	10	37

5.2 Test Procedures


- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.




- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

5.3 Typical Test Setup

Below 1GHz Test Setup



Above 1GHz Test Setup





5.4 Measurement Equipment

Instrument	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI	100563	2014.02.10	2015.02.09
H64 Preamplifier	HP	8447F	3113A05582	2014.03.24	2015.03.23
Preamplifier	Agilent	8449B	3008A02342	2014.03.24	2015.03.23
Bilog Antenna	Sunol Science	JB1	A072414-2	2014.08.05	2015.08.04
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2014.05.24	2015.05.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	9170-348	2013.11.04	2014.11.03
Spectrum Analyzer	R&S	FSP40	100324	2014.03.23	2015.03.24
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30



5.5 Test Result and Data

The 9kHz-30MHz spurious emission is under limit 20dB more.

5.5.1 Test Result and Data of Transmitter

Under 1G:

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Normal Link

Frequency (MHz)	AntPol. H/V	Correct Factor (dB)	Reading level (dBuV)	Measure Level (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)	Detector mode (PK/QP)
253.242	H	-8.74	v	40.47	46	-5.53	QP
359.922	H	-4.41	47.18	42.77	46	-3.23	QP
378.251	H	-4.95	46.23	41.28	46	-4.72	QP
481.721	H	-1.1	43.81	42.71	46	-3.29	QP
601.204	H	-1.05	41.98	40.93	46	-5.07	QP
960.209	H	3.17	41.34	44.51	54	-9.49	QP
57.204	V	-16.94	50.95	34.01	40	-5.99	QP
252.536	V	-8.74	49.27	40.53	46	-5.47	QP
359.891	V	-4.41	48.04	43.63	46	-2.37	QP
480.187	V	-1.1	43.33	42.23	46	-3.77	QP
501.295	V	-2.2	41.34	39.14	46	-6.86	QP
600.591	V	-1.05	43.37	42.32	46	-3.68	QP

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Above 1G:

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11b (2412MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11b (2437MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11b (2462MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11g (2412MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11g (2437MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11g (2462MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11n (20MHz) (2412MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11n (20MHz) (2437MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11n (20MHz) (2462MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11n (40MHz) (2422MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11n (40MHz) (2437MHz)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor

Site : EMC Lab AC 102	Time : 2014-10-15
Limit : FCC_15_03M_PK	Margin : 6
EUT : Tablet	Probe : VERTICAL/ HORIZONTAL
Power : AC 120V/60Hz	Note : Transmit by 802.11n (40MHz) (2452MH)

[illegible]

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Measurement Level = Reading Level + Correct Factor



6. Occupied Bandwidth


6.1 Test Limit

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725- 5850 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and $VBW \geq 3 \times RBW$.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

6.3 Test Setup Layout



6.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28




6.5 Test Result and Data

Test Item	Occupied Bandwidth
Test Mode	Transmit by 802.11b
Test Date	2014-10-10


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	10110	500	Pass
06	2437	10120	500	Pass
11	2462	10070	500	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)




Channel11(2462MHz)



Test Item	Occupied Bandwidth
Test Mode	Transmit by 802.11g
Test Date	2014-10-10


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	16390	500	Pass
06	2437	16470	500	Pass
11	2462	16460	500	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)



Channel 11 (2462MHz)






Test Item	Occupied Bandwidth
Test Mode	Transmit by 802.11n (20MHz)
Test Date	2014-10-10


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	17670	500	Pass
06	2437	17660	500	Pass
11	2462	17630	500	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)



Channel 11 (2462MHz)






Test Item	Occupied Bandwidth
Test Mode	Transmit by 802.11n (40MHz)
Test Date	2014-10-10


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
03	2422	35890	500	Pass
06	2437	35330	500	Pass
09	2452	36070	500	Pass

Channel 03 (2422MHz)






Channel 06 (2437MHz)



Channel 9 (2452MHz)





7. Maximum Peak Output Power

7.1 Test Limit

The maximum peak power shall be less 1Watt (30dBm).

The conducted output power limits specified in §15.247(b) are based on the use of transmit antennae with directional gains that do not exceed 6 dBi. If transmit antennae with an effective directional gain greater than 6 dBi are used, then the conducted output power from the EUT shall be reduced as specified in §15.247(b) and (c).

7.2 Test Procedure

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a spectrum analyzer.

“9.1.2 integrated band power method” of KDB558074 was used to test the power.

Select the “channel power” selection in “measurement” on spectrum analyzer,

The test procedure and setup as following:

Set the RBW = 1 MHz.

Set the VBW = 3 MHz.

Set the span 50MHz for 802.11b/g/n(20) and 90MHz for n(40)

Set the integ BW 25MHz for 802.11b/g/n(20) and 45MHz for n(40)

Detector = peak.

Sweep time = auto couple.


Trace mode = max hold.

Allow trace to fully stabilize.

Record the power value in dBm.

The power output at the transmitter antenna port was determined by adding the value of the attenuator to the spectrum analyzer reading.

7.3 Test Setup Layout



7.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.10	2015.03.09



7.5 Test Result and Data

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (blue marker) for final test of each channel.

MCS Index for 802.11n	Spatial Streams	Data Rate (Mbps)					
		802.11b	802.11g	20MHz Bandwidth		40MHz Bandwidth	
				800ns GI	400ns GI	800ns GI	400ns GI
0	1	1	6	6.5	7.2	13.5	15.0
1	1	2	9	13.0	14.4	27.0	30.0
2	1	5.5	12	19.5	21.7	40.5	45.0
3	1	11	18	26.0	28.9	54.0	60.0
4	1	--	24	39.0	43.3	81.0	90.0
5	1	--	36	52.0	57.8	108.0	120.0
6	1	--	48	58.5	65.0	121.5	135.0
7	1	--	54	65.0	72.2	135.0	150.0
8	2	--	--	13.0	14.4	27.0	30.0
9	2	--	--	26.0	28.9	54.0	60.0
10	2	--	--	39.0	43.3	81.0	90.0
11	2	--	--	52.0	57.8	108.0	120.0
12	2	--	--	78.0	86.7	162.0	180.0
13	2	--	--	104.0	115.6	216.0	240.0
14	2	--	--	117.0	130.0	243.0	270.0
15	2	--	--	130.0	144.0	270.0	300.0



Test Item	Maximum Peak Output Power
Test Mode	Transmit by 802.11b
Duty cycle	99%
Test Date	2014-10-10

Channel No.	Frequency (MHz)	Measurement (dBm)		Required Limit (dBm)	Result
		Average	Peak		
01	2412	6.25	7.82	30	Pass
06	2437	6.84	8.35	30	Pass
11	2462	7.15	8.60	30	Pass

Test Item	Maximum Peak Output Power
Test Mode	Transmit by 802.11g
Duty cycle	99%
Test Date	2014-10-10

Channel No.	Frequency (MHz)	Measurement (dBm)		Required Limit (dBm)	Result
		Average	Peak		
01	2412	4.36	5.85	30	Pass
06	2437	5.17	6.54	30	Pass
11	2462	5.81	7.38	30	Pass



Test Item	Maximum Peak Output Power
Test Mode	Transmit by 802.11n (20MHz)
Duty cycle	99%
Test Date	2014-10-10

Channel No.	Frequency (MHz)	Measurement (dBm)		Required Limit (dBm)	Result
		Average	Peak		
01	2412	3.64	5.15	30	Pass
06	2437	4.15	5.63	30	Pass
11	2462	5.09	6.51	30	Pass

Test Item	Maximum Peak Output Power
Test Mode	Transmit by 802.11n (40MHz)
Duty cycle	99%
Test Date	2014-10-10

Channel No.	Frequency (MHz)	Measurement (dBm)		Required Limit (dBm)	Result
		Average	Peak		
03	2422	3.95	5.42	30	Pass
06	2437	3.92	5.41	30	Pass
09	2452	4.17	5.62	30	Pass



8. Band Edges Measurement


8.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

8.2 Test Procedure

- The transmitter output was connected to the spectrum analyzer via a low lose cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- The band edges was measured and recorded.

8.3 Test Setup Layout



8.4 Measurement Equipment



Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28

**8.5 Test Result and Data**

Modulation Standard	Channel	Frequency (MHz)	maximum value in frequency (MHz)	maximum value(dBm)	Limit (dBm)
802.11b	01	2412	2399.2	-66.702	-33.36
	11	2462	2483.5	-72.007	-31.20
802.11g	01	2412	2400.0	-63.406	-34.60
	11	2462	2483.5	-63.862	-32.70
802.11n HT20	01	2412	2400.0	-61.490	-35.60
	11	2462	2483.5	-64.262	-34.20
802.11n HT40	03	2422	2400.0	-65.174	-38.50
	09	2452	2484.5	-61.758	-37.40




Transmit by 802.11b Channel 1







Transmit by 802.11b Channel 11






Transmit by 802.11g Channel 1







Transmit by 802.11g Channel 11






Transmit by 802.11n HT20 Channel 1







Transmit by 802.11n HT20 Channel 11







Transmit by 802.11n HT40 Channel 3





Transmit by 802.11n HT40 Channel 9



**8.6 Restrict Band Emission Measurement Data**

Test Date : 2014-10-10
 Temperature : 24 °C
 Humidity : 52 %
 Atmospheric Pressure : 1023 hPa

Modulation Standard: IEEE 802.11b

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (cm)
						Peak	Ave.			
2390.00	H	41.42	10.6	52.02	Peak	74	54	-21.98	348	200
2390.00	H	36.01	10.6	46.61	Ave	74	54	-7.39	348	200
2390.00	V	48.24	10.98	59.22	Peak	74	54	-14.78	360	100
2390.00	V	41.25	10.98	52.23	Ave	74	54	-1.77	360	100
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (cm)
						Peak	Ave.			
2483.50	H	47.52	10.78	58.3	Peak	74	54	-15.7	0	200
2483.50	H	35.21	10.78	45.99	Ave	74	54	-8.01	249	200
2483.50	V	52.22	11.02	63.24	Peak	74	54	-10.76	251	100
2483.50	V	39.59	11.02	50.61	Ave	74	54	-3.39	251	100

Modulation Standard: IEEE 802.11g

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (Cm)
						Peak	Ave.			
2390.00	H	50.97	10.54	61.51	Peak	74	54	-12.49	147	200
2390.00	H	35.98	10.54	46.52	Ave	74	54	-7.48	147	200
2390.00	V	56.99	10.98	67.97	Peak	74	54	-6.03	126	100
2390.00	V	41.31	10.98	52.29	Ave	74	54	-1.71	126	100
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (Cm)
						Peak	Ave.			
2483.50	H	52.21	10.72	62.93	Peak	74	54	-11.07	360	200
2483.50	H	34.24	10.72	44.96	Ave	74	54	-9.04	263	200
2483.50	V	60.24	11.02	71.26	Peak	74	54	-2.74	100	100
2483.50	V	40.81	11.02	51.83	Ave	74	54	-2.17	100	100



Modulation Standard: IEEE 802.11n HT20

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (cm)
						Peak	Ave.			
2390.00	H	60.98	10.55	71.53	Peak	74	54	-2.47	75	200
2390.00	H	40.54	10.55	51.09	Ave	74	54	-2.91	75	200
2390.00	V	53.35	10.99	64.34	Peak	74	54	-9.66	159	100
2390.00	V	33.54	10.99	44.53	Ave	74	54	-9.47	159	100
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (cm)
						Peak	Ave.			
2483.50	H	47.92	10.71	58.63	Peak	74	54	-15.37	327	200
2483.50	H	32.05	10.71	42.76	Ave	74	54	-11.24	327	200
2483.50	V	59.97	11.01	70.98	Peak	74	54	-3.02	320	100
2483.50	V	39.24	11.01	50.25	Ave	74	54	-3.75	320	100

Modulation Standard: IEEE 802.11n HT40

Channel 3						Fundamental Frequency: 2422 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (cm)
						Peak	Ave.			
2390.00	H	49.87	10.53	60.4	Peak	74	54	-13.6	76	200
2390.00	H	36.21	10.53	46.74	Ave	74	54	-7.26	76	200
2390.00	V	61.02	10.97	71.99	Peak	74	54	-2.01	63	100
2390.00	V	38.03	10.97	49	Ave	74	54	-5.00	63	100
Channel 9						Fundamental Frequency: 2452 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (cm)
						Peak	Ave.			
2483.50	H	48.22	10.7	58.92	Peak	74	54	-15.08	106	200
2483.50	H	34.03	10.7	44.73	Ave	74	54	-9.27	106	200
2483.50	V	55.98	11.01	66.99	Peak	74	54	-7.01	216	100
2483.50	V	38.04	11.01	49.05	Ave	74	54	-4.95	216	100

Notes: 1. Result = Meter Reading + Factor

2. Factor = Antenna Factor + Cable Loss – Amplifier

3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.

4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.



9. Power Spectral Density


9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

9.2 Test Procedure

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 10KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- The power spectral density was measured and recorded.

9.3 Test Setup Layout



9.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	N9010A	Agilent	MY51350515	2014.09.29	2015.09.28




9.5 Test Result and Data

Test Item	Power Spectral Density
Test Mode	Transmit by 802.11b
Test Date	2014-10-10


Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
01	2412	-27.710	8	Pass
06	2437	-27.363	8	Pass
11	2462	-25.256	8	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)




Channel 11 (2462MHz)



Test Item	Power Spectral Density
Test Mode	Transmit by 802.11g
Test Date	2014-10-10


Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
01	2412	-30.233	8	Pass
06	2437	-29.095	8	Pass
11	2462	-28.113	8	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)



Channel 11 (2462MHz)






Test Item	Power Spectral Density
Test Mode	Transmit by 802.11n (20MHz)
Test Date	2014-10-10


Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
01	2412	-30.357	8	Pass
06	2437	-30.042	8	Pass
11	2462	-28.443	8	Pass

Channel 01 (2412MHz)






Channel 06 (2437MHz)



Channel 11 (2462MHz)






Test Item	Power Spectral Density
Test Mode	Transmit by 802.11n (40MHz)
Test Date	2014-10-10


Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
03	2422	-34.036	8	Pass
06	2437	-33.057	8	Pass
09	2452	-31.521	8	Pass

Channel 03 (2422MHz)






Channel 06 (2437MHz)



Channel 09 (2452MHz)





10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.