

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
ENSEMBLE COMMUNICATIONS INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT
THE WRITTEN PERMISSION OF ENSEMBLE COMMUNICATIONS INC. IS PROHIBITED

REVISIONS

REV	DESCRIPTION	PREPARED	DATE	APPROVED
1	INITIAL RELEASE			

NOTES: UNLESS OTHERWISE SPECIFIED

1. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994.
2. MATERIAL: 3M, PN - 7817, 2 MIL, WHITE, POLYESTER.
3. LABEL SHALL HAVE ADHESIVE BACKING.
4. LABEL SHALL BE SUBJECTED TO THE ENVIROMENT.
-5°C TO 50°C, 5% TO 95% RELATIVE HUMIDITY.
5. BACKING AND TEXT SHALL BE CONTRASTING TO EACH OTHER.
6. ALL TEXT SHALL BE SILKSCREEN ONTO LABEL AS SHOWN.
7. BAG AND/OR TAG WITH PART NUMBER AND CURRENT REVISION.

THIS DEVICE COMPLIES WITH THE
FCC RF EXPOSURE REQUIREMENTS,
47 CFR 1.1310, GENERAL
POPULATION.

-2.25

.75

4 X R.100

		-1	ITEM NO.	CAGE CODE	PART OR IDENTIFYING NO.	SPECIFICATION	NOMENCLATURE OR DESCRIPTION		NOTE NO.
		QTY PER ASSY	PARTS LIST						
		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:			PREPARED CHECKED DSGN ENGR PROJ ENGR MFG ENGR QA REL		 8890 Towne Centre Dr. San Diego CA 92121		
		DECIMALS .XX = ±.03 .XXX = ±.010			ANGLES ±1/2 DEGREE		TITLE		
		HOLE DIA		TOLERANCE		LABEL, RF EXPOSURE			
		.0135 THRU .125		+.004 — -.001					
		.125 THRU .250		+.008 — -.001					
		.251 THRU .500		+.008 — -.001					
		.501 THRU .750		+.008 — -.001					
		.751 THRU 1.000		+.010 — -.001					
DASH NO.	NEXT ASSEMBLY	USED ON		APPLICATION		SIZE	CAGE CODE	DWG NO.	REV
						D	XXXXXX	930-0022-001	1
						SCALE	2/1	SHEET	1 OF 1