


Prüfbericht - Nr.: 14044220 001		Seite 1 von 14	
<i>Test Report No.:</i>		<i>Page 1 of 14</i>	
Auftraggeber: <i>Client:</i>		Victorsure Ltd. 15/FI, Cambridge House 26-28, Cameron Rd., TST, Kowloon Hong Kong	
Gegenstand der Prüfung: <i>Test Item:</i>		Bluetooth Thermometer	
Bezeichnung: <i>Identification:</i>	CL1	Serien-Nr.: <i>Serial No.:</i>	Engineering sample
Wareneingangs-Nr.: <i>Receipt No.:</i>	A000363797-001	Eingangsdatum: <i>Date of Receipt:</i>	19.05.2016
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of test item at delivery:</i>		Test sample(s) is/are not damaged and suitable for testing.	
Prüfört: <i>Testing Location:</i>		Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong	
Prüfgrundlage: <i>Test Specification:</i>		FCC Part 15 Subpart C ANSI C63.10-2013	
Prüfergebnis: <i>Test Results:</i>		Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .	
Prüflaboratorium: <i>Testing Laboratory:</i>		TÜV Rheinland Hong Kong Ltd. 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong	
geprüft/ tested by:		kontrolliert/ reviewed by:	
24.06.2016 Hugo Wan Senior Project Manager <i>Datum</i> <i>Date</i>  <i>Unterschrift</i> <i>Signature</i>		24.06.2016 Sharon Li Department Manager <i>Datum</i> <i>Date</i>  <i>Unterschrift</i> <i>Signature</i>	
Sonstiges / Other Aspects: FCCID: OO6-LVTL-CL1-B018			
Abkürzungen: P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet		Abbreviations: P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested	
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>			

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information	3
Manufacturers declarations.....	3
Product function and intended use	3
Submitted documents.....	3
Remark.....	3
Independent Operation Modes.....	4
Related Submittal(s) Grants	4
Test Set-up and Operation Mode.....	5
Principle of Configuration Selection	5
Test Operation and Test Software	5
Special Accessories and Auxiliary Equipment	5
Countermeasures to achieve EMC Compliance	5
Test Setup Diagram	6
List of Test and Measurement Instruments.....	8
Results FCC Part 15 – Subpart C	9
Subclause 15.203 – Antenna Information.....	Pass.....9
Subclause 15.204 – Antenna Information.....	Pass.....9
Subclause 15.207 – Disturbance Voltage on AC Mains	N/A.....9
FCC 15.247 (a)(2) – 6dB Bandwidth Measurement.....	Pass.....10
FCC 15.247 (b) (1), (3) – Maximum Peak Output Power	Pass.....10
FCC 15.247 (d) – Spurious Conducted Emissions	Pass.....11
FCC 15.247 (d) – Radiated Spurious Emissions.....	Pass.....12
FCC 15.247 (d) – Band Edge Emissions (Conducted).....	Pass.....13
FCC 15.247 (e) – Power Spectral Density	Pass.....14
Appendix 1 – Test protocols	14 pages
Appendix 2 – Test setup	2 pages
Appendix 3 – Photo documentation	7 pages
Appendix 4 – Product documentation	13 pages
Appendix 5 – Radio Frequency Exposure.....	2 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK / FHSS
Number of channels	40
Channel separation	2 MHz
Type of antenna	PCB antenna
Antenna gain (dBi)	-1.0
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V _{nor} : 3.0 VDC
Independent Operation Modes	Bluetooth communication

Product function and intended use

The Equipment Under Test (EUT) is a Bluetooth thermometer which is powered by battery. It can be connected to Bluetooth enabled smart phone and transfer information to smart phone for displaying measured temperature by the connected probe on the EUT.

For details, please refer to the user manual.

FCCID: OO6-LVTL-CL1-B018

Model	Product Description
CL1	Carbon Lite Thermometer

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User Manual
Label Artwork

Remark

--

Independent Operation Modes

The basic operation modes are:

- Radio communication link maintained with data transfer.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The EUT was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- 1) The EUT was powered by the battery.
- 2) A control software provided by client was used on laptop computer to control the transmission frequencies 2402, 2440 and 2480MHz. at highest RF output power and longest burst time.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessory:


nil

Countermeasures to achieve EMC Compliance

nil

Test Setup Diagram

Diagram of Measurement Configuration for Radiated Emission Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Configuration for Conducted RF Test





Diagram of Measurement Equipment Configuration for AC Mains Conducted Emission Test (if applicable)



List of Test and Measurement Instruments

Hong Kong Productivity Council (FCC Registration number: 90656)

Radiated Emission

Equipment	Manufacturer	Type	S/N	Cal. Date	Cal. Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25 Apr 2016	25 Apr 2017
Cable	Hubersuhner	SUCOFLEX 104	72799 /6	31 Mar 2016	31 Mar 2018
Test Receiver	R & S	ESU40	100190	07 Dec 2015	07 Dec 2016
Bi-conical Antenna	R & S	HK116	100241	01 Sep 2015	01 Sep 2017
Log Periodic Antenna	R & S	HL223	841516/017	01 Sep 2015	01 Sep 2017
Coaxial cable	Harbour	LL335	N/A	10 Jun 2014	10 Jul 2016
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	17 Jul 2014	17 Jul 2016
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28 Oct 2015	28 Oct 2017
Horn Antenna	EMCO	3115	9002-3347	26 Aug 2015	26 Aug 2017
Active Loop Antenna	EMCO	6502	9107-2651	15 Aug 2015	15 Aug 2016

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
FCC Requirement: No antenna other than that furnished by the responsible party shall be used with the device		
Results:	Permanent attached antenna	
Verdict:	Pass	

Subclause 15.204 – Antenna Information		Pass
FCC Requirement: Provide information for every antenna proposed for the use with the EUT		
Results:		
	a) Antenna type:	PCB Antenna
	b) Manufacturer	N/A
	c) Model no:	N/A
	d) Gain with reference to an isotropic radiator:	-1.0 dBi
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains		N/A
There is no AC mains power port on EUT. Hence this test is not applicable.		

FCC 15.247 (a)(2) – 6dB Bandwidth Measurement				Pass
FCC Requirement: Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.				
Test Specification : KDB 558074 D01 DTS Meas Guidance v03r05 Mode of operation : BLE Tx mode, (2402MHz, 2440MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100KHz/ 300KHz Supply voltage : 3.0 VDC from DC power supply Temperature : 23°C Humidity : 50%				
Results: For test protocols please refer to Appendix 1, page 2-3.				
Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (MHz)	
2402	2401.740	2402.424	0.684	
2440	2439.736	2440.426	0.690	
2480	2479.742	2480.420	0.678	

FCC 15.247 (b) (1), (3) – Maximum Peak Output Power						Pass
FCC Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt (30dBm)						
Test Specification : KDB 558074 D01 DTS Meas Guidance v03r05 Mode of operation : BLE Tx mode, (2402MHz, 2440MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : ≥ DTS BW / ≥ 3xRBW Span : ≥ 3 x RBW Supply voltage : 3.0 VDC from DC power supply Temperature : 23°C Humidity : 50%						
Results: For test protocols please refer to Appendix 1, page 4-5.						
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict	
2402	-4.40	1.00	-3.40	1 / 30.0	Pass	
2440	-2.96	1.00	-1.96	1 / 30.0	Pass	
2480	-2.38	1.00	-1.38	1 / 30.0	Pass	

FCC 15.247 (d) – Spurious Conducted Emissions					Pass
Test Specification : KDB 558074 D01 DTS Meas Guidance v03r05 Mode of operation : Tx mode (2402MHz, 2440MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.0 VDC from DC power supply Temperature : 23 °C Humidity : 50 %					
FCC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Results: All three transmit frequency modes comply with the limit stated in subclause 15.247(d). For test protocols refer to Appendix 1, page 6-11.					
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	4802.960	-39.86	-4.33	-35.53	Pass
2440	4880.780	-42.89	-2.75	-40.14	Pass
2480	4958.600	-42.44	-2.07	-40.37	Pass

FCC 15.247 (d) – Radiated Spurious Emissions		Pass
Test Specification	: ANSI C63.10 – 2013	
Mode of operation	: Tx mode (2402MHz, 2440MHz, 2480MHz), hopping off	
Port of testing	: Enclosure	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz	
Measurement range	: 9kHz to 25GHz	
Supply voltage	: 3.0 VDC from battery	
Temperature	: 23°C	
Humidity	: 50%	
FCC Requirement: In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).		
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations in available packet length. All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.	
Tx frequency 2402MHz Vertical Polarization		
Freq MHz	Level dBµV/m	Limit/ Detector dBµV/m
2387.400	46.47	74.0 / P
4804.813	58.61	74.0 / P
4804.138	52.06	54.0 / A
Tx frequency 2402MHz Horizontal Polarization		
Freq MHz	Level dBµV/m	Limit/ Detector dBµV/m
2371.100	47.13	74.0 / P
4804.675	58.57	74.0 / P
4804.163	51.48	54.0 / A
Tx frequency 2440MHz Vertical Polarization		
Freq MHz	Level dBµV/m	Limit/ Detector dBµV/m
4880.863	59.53	74.0 / P
4880.150	52.54	54.0 / A
Tx frequency 2440MHz Horizontal Polarization		
Freq MHz	Level dBµV/m	Limit/ Detector dBµV/m
4880.413	57.80	74.0 / P
4880.150	48.64	54.0 / A

Tx frequency 2480MHz		Vertical Polarization	
Freq MHz	Level dBμV/m	Limit/ Detector dBμV/m	
2483.500	51.89	74.0 / P	
4959.775	60.13	74.0 / P	
4960.138	53.74	54.0 / A	
Tx frequency 2480MHz		Horizontal Polarization	
Freq MHz	Level dBμV/m	Limit/ Detector dBμV/m	
2483.521	60.66	74.0 / P	
2483.500	51.83	54.0 / A	
4959.738	58.35	74.0 / P	
4960.188	49.73	54.0 / A	

FCC 15.247 (d) – Band Edge Emissions (Conducted)					Pass
Test Specification : KDB 558074 D01 DTS Meas Guidance v03r05 Mode of operation : BLE Tx mode (2402MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.0 VDC from DC power supply Temperature : 23°C Humidity : 50%					
FCC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Results: The peak found outside any 100 kHz bandwidth of the operating frequency band comply with the requirement. For test protocols refer to Appendix 1, page 12.					
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	2399.340	-29.53	-4.33	-25.20	Pass
2480	2485.860	-42.55	-2.07	-40.48	Pass

FCC 15.247 (e) – Power Spectral Density			Pass
FCC Requirement: For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.			
Test Specification : KDB 558074 D01 DTS Meas Guidance v03r05 Mode of operation : BLE Tx mode (2402MHz, 2440MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : ≥ 100 kHz / $\geq 3 \times$ RBW span : $\geq 1.5 \times$ DTS BW Supply voltage : 3.0 VDC from DC power supply Temperature : 23°C Humidity : 50%			
Results: For test protocols please refer to Appendix 1, page 13-14.			
Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict
2402	-4.33	8.0	Pass
2440	-2.75	8.0	Pass
2480	-2.07	8.0	Pass