

K1801U Multimedia keyboard Technical Specification

Keys:

- 104 standard keys
- 10 multimedia keys
- 1 Key Stroke life time: 10,000,000 Cycles
- 2 Contact method: Membrane
- 3 Security Code: 4096 different security code
- 4 RF Transmission mode
 - 1 channel FSK RF Transmission 27.045MHz $\pm$ 2.5KHZ
- 5 Channel Bandwidth 50KHZ
- 6 Modulation Deviation 3.0KHZ $\leq \Delta f \leq$ 6.5KHZ
- 7 Tx Emission Level: 60dBuV/m $\leq E_{3m} \leq$ 80dBuV/m at 3m
- 8 Batteries: 2 x AAA Size
- 9 Power consumption
 - Keyboard $\leq$ 8mA(Active)
 - $\leq$ 50uA(Idle)
- 10 Battery life $\geq$ 160 hours at Active mode with Alkaline Batter
- 11 Low battery indicator: 2.1V
- 12 Operating Distance
 - 2m in normal environment
- 13 System Requirement
 - Windows 95/Windows 98/WinNT /Windows me /WinXP /Windows 2000 Driver required in Win95 /Win98 /WinNT
- 14 Storage temperature: -40 $^{\circ}$ C~55 $^{\circ}$ C
- 15 Working temperature: 0 $^{\circ}$ C~40 $^{\circ}$ C
- 16 Operating humidity: 40%~90%
- 17 Net weight 769g
- 17 Mechanical Dimension
 - 420mmX165mmX24.5mm

制表: _____

审定: _____

批准: _____