



TEST REPORT nr. R13145301
Federal Communication Commission (FCC)

Test item

Description: Transceiver unit
Trademark: AUTEC
Model/Type: Model: AJR
Type: DA0BM
Configuration: AA00A10_

Test Specification

Standard: FCC Rules & Regulations, Title 47:2013
Part 15 paragraph(s): 203, 204, 207, 209 and 249

Client's name: AUTEC S.r.l.
Address: Via Pomaroli, 65 – 36030 Caldogno (VI) – ITALY

Manufacturer's name : Same as client
Address: --

Report

Tested by: G. Gandini – Technician
Approved by: R. Beghetto – Laboratory Manager
Date of issue: 13.03.14
Contents: 49 pages

G. Gandini

R. Beghetto

This test report shall not be reproduced except in full without the written approval of CMC.
The test results presented in this report relate only to the item tested.



Index

1. SUMMARY	3
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2.1 TEST SITE	4
3. TESTING AND SAMPLING	4
4. OPERATIVE CONDITIONS	4
5. PHOTOGRAPH(S) OF EUT	5
5.1 PHOTOGRAPH(S) OF EUT	5
6. EQUIPMENT LIST	6
7. MEASUREMENT UNCERTAINTY	7
8. REFERENCE DOCUMENTS	8
9. DEVIATION FROM TEST SPECIFICATION	9
10. TEST CASE VERDICTS	9
11. RESULTS	10
11.1 ANTENNA REQUIREMENTS	11
11.2 RADIATED EMISSIONS	12
11.3 OCCUPIED BANDWIDTH (99% BW)	28
11.4 PEAK OUTPUT POWER	33
11.5 BAND EDGE	41
11.6 SPURIOUS EMISSION	47



1. Summary

Standard:

FCC Rules & Regulations, Title 47:2013
Part 15 paragraph(s): 203, 204, 207, 209 and 249
RSS-210 (2010) – Annex 2 (A2.9)

Test specifications	Environmental Phenomena	Tests sequence	Result
Part 15.203 IC – RSS-210	Antenna requirements	1	Complies
Part 15.207 IC – RSS-210 – Annex 2 (A2.9)	Conducted emissions	--	N.A. (+)
Part 15.209 IC – RSS-210 – Annex 2 (A2.9)	Radiated emissions	2	Complies
IC – RSS-210 – Annex 2 (A2.9)	Occupied bandwidth (99% BW)	3	Complies
Part 15.209 and 15.249 IC – RSS-210 – Annex 2 (A2.9)	Peak Output Power	4	Complies
Part 15.249 (d) IC – RSS-210 – Annex 2 (A2.9)	Band edge	5	Complies
Part 15.209 IC – RSS-210 – Annex 2 (A2.9)	Spurious emission	6	Complies

(+) Devices which only employ battery power. See FCC Part 15.207 (c)

The Test Report was given to the Client representatives for necessary documentation of ratification of the tested equipment and it is valid for the FCC certification



2. Description of Equipment under test (EUT)

Type of station : ☐ Fixed station
☒ Portable station
☐ Mobile station

Nominal frequency : 902 – 928 MHz

FCC ID : OQA-AJRDA0BM

IC number : 9061A-AJRDA0BM

2.1	Test Site
------------	------------------

Company..... : CMC Centro Misure Compatibilità S.r.l.
Address : Via dell'Elettronica, 12/C
36016 Thiene (VI) – ITALY

3. Testing and sampling

Date of receipt of test item : 24.06.13

Testing start date : 05.08.13

Testing end date : 26.02.14

Samples tested nr..... : 1

Sampling procedure. : Equipment used for testing was picked up by the manufacturer, at the end of the production process with random criterion

Internal identification : adhesive label with the product number P130643

4. Operative conditions

EUT exercising : EUT in continuous transmission at maximum power



CMC
Centro Misure Compatibilità S.r.l.
Via dell'Elettronica, 12/C
36016 Thiene (VI)

5. Photograph(s) of EUT

5.1 Photograph(s) of EUT





6. Equipment list

<i>Id. number</i>	<i>Manufacturer</i>	<i>Model</i>	<i>Description</i>	<i>Serial number</i>	<i>Last calibration</i>	<i>Due date calibration</i>
CMC S010	Rohde & Schwarz	ESH3-Z2	Impulses Limiting Device	- - -	January '14	January '15
CMC S108	EMCO	3115	Horn Antenna	9811-5622	May '13	May '16
CMC S127	Schaffner	HLA6120	Loop Antenna	1191	January '13	January '16
CMC S136	Schwarzbeck	VULB 9163	Broadband Antenna	9136-205	May '13	May '16
CMC S164	Rohde & Schwarz	ESU26	EMC interference receiver	100052	January '14	January '15
CMC S200	Schwarzbeck	NSLK 8128	V-LISN	8128-273	January '14	January '15
CMC S227	Rohde & Schwarz	ESR7	EMI Test Receiver 7GHz	101121	January '14	January '15



7. Measurement uncertainty

Test	Expanded Uncertainty	note
Conducted Emission		
(50Ω/50μH AMN) - (9 kHz – 150 kHz)	±3.8 dB	1
(50Ω/50μH AMN) - (150 kHz – 30 MHz)	±3.3 dB	1
(Voltage probe) - (150 kHz – 30 MHz)	±3.3 dB	1
(50Ω/5μH AMN) - (150 kHz – 108 MHz)	±2.8 dB	1
Discontinuous Conducted Emission		
Conducted Emission (50Ω/50μH AMN) - (150 kHz – 30 MHz)	±3.3 dB	1
Disturbance Power (30 MHz – 300 MHz)		
	±3.9 dB	1
Radiated Emission		
(0,150 MHz – 30 MHz)	±4.3 dB	1
(30 MHz – 1000 MHz)	±4.4 dB	1
(1 GHz – 6 GHz)	±4.6 dB	1
Electromagnetic field EMF		
	±15.0 %	1
Harmonic current emissions test		
	±2.7 %	1
Voltage fluctuation and flicker test		
	±2.9 %	1
Insertion loss test		
	±2.7 dB	1
Radiated electromagnetic disturbance test (loop antenna)		
	±2.7 dB	1
Radiated electromagnetic field immunity test		
	0.77 V/m at 3V/m	1
Pulse modulated radiated electromagnetic field immunity test		
	0.77 V/m at 3V/m	1
Injected currents immunity test		
	0.48 V at 3V	1
Bulk current		
	5.3 mA at 60 mA	1
Power frequency magnetic field immunity test		
	0.1 A/m at 10 A/m	1
Effective radiated power (F < 1GHz)		
	±4.4 dB	1
Effective radiated power (F > 1GHz)		
	±3.9 dB	1
Frequency error		
	< 1x10 ⁻⁷	1
Modulation bandwidth		
	< 1x10 ⁻⁷	1
Adjacent channel power		
	±2.6 dB	1
Blocking		
	±2.6 dB	1
Electrostatic discharge immunity test		
		2
Electrical fast transients / burst immunity test		
		2
Surge immunity test		
		2
Pulse magnetic field immunity test		
		2
Damped oscillatory magnetic field immunity test		
		2
Short interruption immunity test		
		2
Voltage transient emission test		
	±2.2 %	1
Transient immunity test		
		2

Notes

Note 1:

The expanded uncertainty reported according to EN55016-4-2:2011 is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of p = 95%

Note 2:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence, covering factor k = 2.



8. Reference documents

Reference no.	Description
FCC Rules and Regulation Title 47 part 15:2013	--
RSS-210 Issue 8 – December 2010	Low-power licence-exempt radiocommunication devices (all frequency bands): Category I Equipment
ANSI C63.4: 2003	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
Internal Procedure PM001 rev. 2.0 (Quality Manual)	Measure Procedure
Internal procedure INC_M rev. 8.2 (Quality Manual)	Measurement uncertainty calculation



9. Deviation from test specification

In agreement with the client, emission tests were performed with peak detector.

At the frequencies where the measures exceed the limit or within 6 dB from it, the test was repeated with quasi-peak detector and/or average detector.

10. Test case verdicts

Test case does not apply to the test object..... : N.A.

Test item does meet the requirement..... : Complies

Test item does not meet the requirement..... : Does not comply

Test not performed : N.E.







11. Results

In this clause tests results are reported.

Measurement uncertainty is in accordance with document CMC INC_M rev. 8.2.

Judgement of compliance:

Case 1	Case 2	Case 3	Case 4
			
The sample is Complies.	The sample is Complies.	The sample is Not Complies.	The sample is Not Complies.
The measurement results is within the specification limit when the measurement uncertainty is taken into account.	It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is below the limit.	It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty also the measurement result is upper the limit.	The measurement results is outside the specification limit when the measurement uncertainty is taken into account.

In agreement with ILAC-G8: 03/2009 Guidelines on the Reporting of Compliance with Specification.



11.1 Antenna requirements

Test set-up and execution

- FCC Rules and Regulation; Titles 47 Part 15.203 and 15.204
- Internal procedure PM001
- See clause 4 of this test report

Test configuration and test method

Test site:
Laboratory

Auxiliary equipment:
See clause 4 of this test report

EUT exercising

See clause 4 of this test report

Test equipment used

--
Measurement uncertainty: See clause 7 of this test report

Test specification

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded

Environmental conditions

Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
23	99	51

Result

Antenna Type	External R.F. power amplifier	Gain	Remarks	Results
Embedded	Not Present	0 dBi	--	Complies

Result: The requirements are met



11.2 Radiated emissions

Test set-up and execution

- FCC Rules and Regulation; Titles 47 Part. 15.209
- Internal procedure PM001
- See clause 4 of this test report

Test configuration and test method

Test site:
Semi-anechoic chamber

Auxiliary equipment:
See clause 4 of this test report

EUT exercising

See clause 4 of this test report

Test equipment used

CMC S108, CMC S127, CMC S136, CMC S164
Measurement uncertainty: See clause 7 of this test report

Test specification

Port: Enclosure
Frequency range: 0,009 MHz – 1000 MHz
Antenna polarization: Horizontal (H) – Vertical (V)
EUT – Antenna distance: 3 m

Environmental conditions

Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
23	98	51


Acceptance limits

Frequency range (MHz)	Limits [dB(μV/m)]
0,009 to 0,490	128,51 to 93,80
0,490 to 1,705	73,80 to 62,97
1,705 to 30	69,54
30 to 88	40
88 to 216	43,52
216 to 960	46,02
Above 960	53,98

Remarks: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.



Setup





Result

Channel	Polarization	Frequency Range (MHz)	Graphs	Remarks	Result
--	Loop	0,009 – 30	G13145313	--	Complies
915,250	H	30 – 1000	G13145319	--	Complies
915,250	V	30 – 1000	G13145314	--	Complies
921,000	H	30 – 1000	G13145320	--	Complies
921,000	V	30 – 1000	G13145321	--	Complies
927,750	H	30 – 1000	G13145329	--	Complies
927,750	V	30 – 1000	G13145324	--	Complies
915,050	V	1000 – 10000	G13145339	--	Complies
915,050	H	1000 – 10000	G13145340	--	Complies
921,000	H	1000 – 10000	G13145341	--	Complies
921,000	V	1000 – 10000	G13145342	--	Complies
927,750	V	1000 – 10000	G13145343	--	Complies
927,750	H	1000 – 10000	G13145344	--	Complies

Remarks: --

Graphs Legend

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +


AV: Average; AV [1s] (average at 1 second) values are marked with a x



Graphs

G13145313

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx
Operator Gandini 13145313
Test Spec Loop




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145314

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmin
Operator Gandini 13145314
Test Spec
Vert




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145319

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmin
Operator Gandini 13145319
Test Spec
Horiz




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145320

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmed
Operator Gandini 13145320
Test Spec
Horiz




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145321

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmed
Operator Gandini 13145321
Test Spec
Vert




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145324

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmax
Operator Gandini 13145324
Test Spec
Vert




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145329

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmax
Operator Gandini 13145329
Test Spec
Horiz




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145339

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition TX-FMED
Operator Gandini 13145339
Test Spec
Vert




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145340

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition TX-FMED
Operator Gandini 13145340
Test Spec
Horiz




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145341

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition TX-FMIN
Operator Gandini 13145341
Test Spec
Horiz




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145342

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition TX-FMIN
Operator Gandini 13145342
Test Spec
Vert




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145343

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition TX-FMAX
Operator Gandini 13145343
Test Spec
Vert




Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0



G13145344

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition TX-FMAX
Operator Gandini 13145344
Test Spec
Horiz



Final Measurement

Meas Time: 1 s
Margin: 6 dB
Subranges: 0

Result: The requirements are met



11.3 Occupied bandwidth (99% BW)

Test set-up and execution

- RSS 210 Annex 2 (A2.9)
- Internal procedure PM001
- See clause 4 of this test report

Test configuration and test method

Test site:
Laboratory

Auxiliary equipment:
See clause 4 of this test report

EUT exercising

See clause 4 of this test report

Test equipment used

CMC S108, CMC S136, CMC S164
Measurement uncertainty: See clause 7 of this test report

Test specification


RSS 210 Annex 2 (A2.9)

Environmental conditions

Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
22	99	51



Setup



Result


f (MHz)	99% bandwidth (kHz)	Graphs	Results
915,250	19,15	G13145318	Complies
921,000	19,23	G13145322	Complies
927,750	19,15	G13145328	Complies



Graphs

G13145318


Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmin
Operator Gandini 13145318
Test Spec





G13145322


Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmed
Operator Gandini 13145322
Test Spec





G13145328

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition Tx-Fmax
Operator Gandini 13145328
Test Spec



Result: The requirements are met



11.4 Peak Output Power

Test set-up and execution

- FCC Rules and Regulation; Titles 47 Part 15.209 and Part 15.249
- Internal procedure PM001
- See clause 4 of this test report

Test configuration and test method

Test site:
Semi-anechoic chamber

Auxiliary equipment:
See clause 4 of this test report

EUT exercising

See clause 4 of this test report

Test equipment used

CMC S108, CMC S136, CMC S164
Measurement uncertainty: See clause 7 of this test report

Test specification

Port: Enclosure
Antenna polarization: Horizontal (H) – Vertical (V)
EUT – Antenna distance: 3 m

Environmental conditions

Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
24	99	52


Acceptance limits

Frequency range (MHz)	RF Power Output dB(μV/m)
902 – 928	94

Frequency range (MHz)	RF Power Output dB(μV/m)
2400 – 2483,5	94



Setup




Result


Frequency (MHz)	Polarization	Graphs	Measured QP level (dB μ V/m)	Peak Output Power (mW)	Remarks
915,050	Horizontal	G13145337	84,46	0,084	--
915,050	Vertical	G13145334	93,50	0,672	--
921,000	Horizontal	G13145306	84,57	0,086	--
921,000	Vertical	G13145305	93,37	0,652	--
927,750	Horizontal	G13145338	85,25	0,100	--
927,750	Vertical	G13145331	92,15	0,492	--


Remarks

////////



G13145305





RBW 100 kHz
 VBW 300 kHz
 SWT 2.5 dB

Marker 1 [T1]
 84.57 dBμV/m
 920.990397436 MHz

Span 1 MHz

Order: M131452

page 34 of 48

Ref 90 dBuV/m * Att 10 dB * RBW 100 kHz VEM 300 kHz Marker 1 [T1] 84.57 dBuV/m
SWT 2.5 ns 920.999397476 MHz

100 90 80 70 60 50 40 30 20 10


100 kHz/

Center 921 MHz Span 1 MHz



G13145331


Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMAX
Operator Gandini 13145331
Test Spec
Vert





G13145334


Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMIN
Operator Gandini 13145334
Test Spec
Vert





G13145337


Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMIN
Operator Gandini 13145337
Test Spec
Horiz





G13145338

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMAX
Operator Gandini 13145338
Test Spec
Horiz



Result: The requirements are met



11.5 Band edge

Test set-up and execution

- FCC Rules and Regulation; Titles 47 Part 15.249 (d)
- Internal procedure PM001
- See clause 4 of this test report

Test configuration and test method

Test site:
Laboratory

Auxiliary equipment:
See clause 4 of this test report

EUT exercising

See clause 4 of this test report

Test equipment used

CMC S108, CMC S136, CMC S164
Measurement uncertainty: See clause 7 of this test report

Test specification

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation


Environmental conditions

Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
23	99	51

Acceptance limits: operation within the band 902 – 928 MHz MHz



Setup



Result


Frequency (MHz)	Graph(s)	Results	
915,050	G13145335	F _L : 914,808	Complies
	G13145336		
927,750	G13145332	F _H : 927,977	Complies
	G13145333		



Graphs

G13145332


Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMAX
Operator Gandini 13145332
Test Spec
Vert






G13145333

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMAX
Operator Gandini 13145333
Test Spec
Vert





1 PR
100Hz

Ref 80 dBuV/m * Att 0 dB

* RBW 100 kHz VEM 300 kHz SWT 2.5 ns

Marker 2 [T1]
91.49 dBuV/m
914.95000000 MHz

90 dB

80 dB

70 dB

60 dB

50 dB

40 dB

30 dB

20 dB

10 dB

0 dB

Center 915.05 MHz

100 kHz/


Span 1 MHz

FCI15209



G13145336

Meas Type Emission
Equipment under Test
Manufacturer
OP Condition FMIN
Operator Gandini 13145336
Test Spec
Vert



Result: The requirements are met



11.6 Spurious Emission

Test set-up and execution

- FCC Rules and Regulation; Titles 47 Part 15.209
- Internal procedure PM001
- See clause 4 of this test report

Test configuration and test method

Test site:
Semi-anechoic chamber

Auxiliary equipment:
See clause 4 of this test report

EUT exercising

See clause 4 of this test report

Test equipment used

CMC S108, CMC S136, CMC S164
Measurement uncertainty: See clause 7 of this test report

Test specification

Port: Enclosure
Antenna polarization: Horizontal (H) – Vertical (V)
EUT – Antenna distance: 3 m
Detector AV + Peak

Environmental conditions


Temperature (°C)	Atmospheric pressure (kPa)	Relative humidity (%)
23	98	51

Acceptance limits

Frequency (MHz)	AV limits [dB(μV/m)]	Peak limits [dB(μV/m)]
> 1000	54	74



Setup





Graph:

From G13145339 to G13145344

Result – AV detector

Harmonic	Limits (dB μ V/m)	Level (dB μ V/m)			Results
		915,250 MHz	921,000 MHz	927,750 MHz	
II	54	46,17	46,50	44,70	Complies
III	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
IV	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
V	54	45,88	44,39	45,31	Complies
VI	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
VII	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
VIII	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
IX	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
X	54	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies

Remarks: EUT was tested in 3 orthogonal planes. The results in this table show the highest values

Result – Peak detector

Harmonic	Limits (dB μ V/m)	Level (dB μ V/m)			Results
		915,250 MHz	921,000 MHz	927,750 MHz	
II	74	49,80	49,66	48,05	Complies
III	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
IV	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
V	74	51,90	51,00	51,52	Complies
VI	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
VII	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
VIII	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
IX	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies
X	74	More than 15dB below limit	More than 15dB below limit	More than 15dB below limit	Complies

Remarks: EUT was tested in 3 orthogonal planes. The results in this table show the highest values

Result: The requirements are met