


Test report nr. R25223901

Federal Communication Commission (FCC)

Customer	Autec S.r.l. Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy	
(#) FCC ID	OQA-AUBGM240P32	
(#) Description of item tested	Radio module	
(#) Trademark	Autec	
(#) Model and/or type reference	AUBGM240P32	
(#) Manufacturer	Autec S.r.l. Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy	
(#) Rating(s)	7,4 Vdc	
Test method requested, standard(s)	FCC Rules & Regulations, Title 47:2024 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247 Tests details at page 12	
Tested by (name / position & signature)	S. Zanivan <i>Technician</i>	
Approved by (name / position & signature)	F. Marenda <i>Laboratory manager</i>	
Date of issue	22.12.2025	
General disclaimer	The test results presented in this report relate only to the item tested. This report shall not be reproduced, except in full, without the written approval of DEKRA Testing and Certification S.r.l.	
Report template No	15-247_DTS_DEKRA	

(#) information provided by the customer

Summary

SUMMARY	2
COMPETENCES AND GUARANTEES	3
GENERAL CONDITIONS	3
DATA PROVIDED BY THE CUSTOMER	3
REFERENCE STANDARDS	4
USAGE OF SAMPLES	5
TEST SAMPLE DESCRIPTION	6
PHOTOS OF THE TEST ITEM	7
TESTING PERIOD AND PLACE	9
DOCUMENT HISTORY	9
LIST OF ATTACHMENTS	9
ENVIRONMENTAL CONDITIONS	10
REMARKS AND COMMENTS	11
DEVIATIONS FROM TEST SPECIFICATION	11
TESTING VERDICTS	11
VERDICT SUMMARY	12
TEST RESULTS	13
ANTENNA REQUIREMENTS	13
EMISSIONS IN RESTRICTED FREQUENCY BANDS AND IN UNRESTRICTED FREQUENCY BANDS	14
ATTACHMENT 1	43

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.r.l. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.r.l. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.r.l. at the time of performance of the test.

DEKRA Testing and Certification S.r.l. is liable to the customer for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.r.l.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.r.l. and the Accreditation Bodies.

Data provided by the customer

Information relating to the description of the sample, components list, and software/hardware version (if reported) are provided by the customer/manufacture. DEKRA Testing and Certification S.r.l. cannot be considered responsible for this information, for any other document provided by the customer/manufacture and for any difference between the software/hardware release present in the tested sample and that present in the object intended for final sale.

In some cases, the software in the tested sample is in a version dedicated exclusively to the test, and therefore does not represent the software installed in the final version of the product.

Reference standards

Standard(s)	Description
FCC Rules and Regulation Title 47 part 15:2024	--
KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices operating under section 15.247 of the FCC rules
ANSI C63.4:2014	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
ANSI C63.10:2020 + COR1:2023	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Usage of samples



Sample(s) used for testing chosen by the customer; DEKRA Testing and Certification S.r.l. cannot be considered responsible for the selection of the sample(s).




Internal identification	Serial number/Customer Id	Date of reception	Notes
P251213	--	13.11.2025	--

Test sample description

Test power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 7,4 V					
	☐	DC:					
Frequency band(s)	2400 – 2483,5 MHz						
Nominal frequencies	2402 MHz 2440 MHz 2480 MHz						
Type of equipment	☒	Transmitter unit					
	☒	Receiver unit					
Type of station	☒	Portable station					
	☐	Mobile station					
Mounting position	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☒	Other, for example rack mounted, body worn, etc.					
Operating modes	N.	Operating mode of test item					
	1	EUT in continuous transmission at maximum power					

Photos of the test item





Testing period and place

Test Location	DEKRA Testing and Certification S.r.l.
FCC Registration Number	182474
Date (start)	27.11.2025
Date (finish)	28.11.2025

Document history

Report number	Date	Description
R25223901	22.12.2025	First release

List of attachments

Name	Description
Attachment 1	Measurement uncertainty, judgement of compliance and quality manual references

Environmental conditions

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment.

The climatic conditions during the tests were within the following limits:

Temperature	Humidity	Atmospheric pressure
15 °C – 35 °C	30 % - 60 %	800 hPa – 1060 hPa

If explicitly required in the basic standard or applied product standard the climatic values are recorded and documented separately in this test report.

Environmental conditions have been monitored with the following instruments:

Id. number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
CMC S302	Testo	175H1	40370182 610	Data Logger	May 2025	May 2026

Remarks and comments

Throughout this report a comma is used as the decimal separator.

Tests reported in this test report marked by wording: "Test not accredited by ACCREDIA" are not part of the ACCREDIA accreditation of this laboratory.

Deviations from test specification

None.

Testing verdicts

N/A (Not Applicable)	Test case does not apply to the test object
P (Pass)	Test object meets the requirement
F (Fail)	Test object does not meet the requirement
N/E (Not Executed)	Test object was not evaluated for the requirement

Verdict summary

FCC Rules & Regulations, Title 47:2024 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247			
Clause	Requirement – Test case	Basic standard	Verdict
Part 15.203	Antenna requirements	--	P
Part 15.207	Conducted emissions	ANSI C63.10	N/E
Part 15.209	Emissions in restricted frequency bands and in unrestricted frequency bands	ANSI C63.10	P
Part 15.247 (a) (2)	DTS bandwidth	ANSI C63.10	N/E
Part 15.215 (c)	20 dB bandwidth	ANSI C63.10	N/E
Part 15.247 (d)	Band edge	ANSI C63.10	N/E
Part 15.209 and 15.247	Fundamental emission output power	ANSI C63.10	N/E
Part 15.209 and 15.247	Maximum power spectral density level in the fundamental emission	ANSI C63.10	N/E

Test results

Antenna requirements

Tested by	S. Zanivan	
Test date	27.11.2025	
Basic standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.203 and 15.204	
Test specification	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded	
Antenna type	☒	Integral antenna
	☐	External antenna
Antenna gain	2,44 dBi	
External R.F. power amplifier	Not Present	

Emissions in restricted frequency bands and in unrestricted frequency bands

Tested by	S. Zanivan
Test date	28.11.2025
Test location (stand)	Semi-anechoic chamber (CMC A070)
Basic standard(s)	ANSI C63.10 cl. 6.3, 6.4, 6.5 and 6.6
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.209
Test set-up description.....	☒ Table top equipment set-up (80 cm above the reference ground plane) ☐ Floor standing equipment set-up (insulating material up to 12 mm thick) ☐ False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary test set-up description.....	--
Test method applied	OATS or SAC with measurement distance [m]: 10 m for frequencies below 1 GHz 3 m for frequencies above 1 GHz
Supplementary information	--

Acceptance limits

Acceptance limits for emissions in restricted frequency bands ($f < 1000$ MHz)		
Frequency range (MHz)	Test distance (m)	Limits [dB(μ V/m)]
0,009 to 0,490	300	$20\log(2400/F(\text{kHz}))$
0,490 to 1,705	30	$20\log(24000/F(\text{kHz}))$
1,705 to 30	30	$20\log(30)$
30 to 88	3	$20\log(100)^{**}$
88 to 216	3	$20\log(150)^{**}$
216 to 960	3	$20\log(200)^{**}$
Above 960	3	$20\log(500)$

** : except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54 – 72 MHz, 76 – 88 MHz, 174 – 216 MHz or 470 – 806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Perimeter protection systems may operate in the 54 – 72 MHz and 76 – 88 MHz bands under the provisions of this section. The use of such perimeter protection systems is limited to industrial, business and commercial applications.

Remarks: the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9 – 90 kHz and 110 – 490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector. The Verdict have been extrapolated to the specified distance using an extrapolation factor.

Acceptance limits for emissions in restricted frequency bands ($f \geq 1000$ MHz)			
Frequency (MHz)	Test distance (m)	AV limits [dB(μ V/m)]	Peak limits [dB(μ V/m)]
> 1000	3	54	74

The restricted frequency bands are listed in the following table:


MHz	MHz	MHz	GHz
0,090 – 0,110	16,42 – 16,423	399,9 – 410	4,5 – 5,15
0,495 – 0,505	16,69475 – 16,69525	608 – 614	5,35 – 5,46
2,1735 – 2,1905	16,80425 – 16,80475	960 – 1240	7,25 – 7,75
4,125 – 4,128	25,5 – 25,67	1300 – 1427	8,025 – 8,5
4,17725 – 4,17775	37,5 – 38,25	1435 – 1626,5	9,0 – 9,2
4,20725 – 4,20775	73 – 74,6	1645,5 – 1646,5	9,3 – 9,5
6,215 – 6,218	74,8 – 75,2	1660 – 1710	10,6 – 12,7
6,26775 – 6,26825	108 – 121,94	1718,8 – 1722,2	13,25 – 13,4
6,31175 – 6,31225	123 – 138	2200 – 2300	14,47 – 14,5
8,291 – 8,294	149,9 – 150,05	2310 – 2390	15,35 – 16,2
8,362 – 8,366	156,52475 – 156,52525	2483,5 – 2500	17,7 – 21,4
8,37625 – 8,38675	156,7 – 156,9	2690 – 2900	22,01 – 23,12
8,41425 – 8,41475	162,0125 – 167,17	3260 – 3267	23,6 – 24,0
12,29 – 12,293	167,72 – 173,2	3332 – 3339	31,2 – 31,8
12,51975 – 12,52025	240 – 285	3345,8 – 3358	36,43 – 36,5
12,57675 – 12,57725	322 – 335,4	3600 – 4400	Above 38,6
13,36 – 13,41			

Acceptance limits for emissions in non-restricted frequency bands (according to ANSI C63.10 cl. 11.11.1)


The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.
- If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.
- In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required

Test setup



Test setup PE004_21							
Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S127	Schaffner	HLA6120	1191	Loop Antenna 9kHz - 30MHz	July 2024	July 2027
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required




Test setup PE004_22

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S271	Schwarzbeck	BBA 9106 + VHBB 9124	831	Broadband Antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Test setup PE004_23

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S287	Schwarzbeck	VUSLP 9111B	9111B-203	Broadband Antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required



Test setup PE004_24

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
4	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
3	CMC S108	Emco	3115	9811-5622	Waveguide antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Test setup PE004_25

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
4	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
3	CMC S290	Schwarzbeck	BBHA 9170	733	Horn Antenna	October 2021	October 2026
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Result

Transmission frequency (MHz)	Polarization	Frequency Range (MHz)	Graphs	Verdict
Worst case	Loop	0,009 – 30	25223901	P
Worst case	H	30 – 300	25223902	P
Worst case	V	30 – 300	25223903	P
Worst case	V	300 – 1000	25223904	P
Worst case	H	300 – 1000	25223905	P
2402	H	1000 – 3000	25223906	P
2402	V	1000 – 3000	25223907	P
2440	V	1000 – 3000	25223908	P
2440	H	1000 – 3000	25223909	P
2480	H	1000 – 3000	25223910	P
2480	V	1000 – 3000	25223911	P
2480	V	3000 – 18000	25223912	P
2480	H	3000 – 18000	25223913	P
2440	H	3000 – 18000	25223914	P
2440	V	3000 – 18000	25223915	P
2402	V	3000 – 18000	25223916	P
2402	H	3000 – 18000	25223917	P
2402	H	18000 – 26000	25223918	P
2402	V	18000 – 26000	25223919	P
2440	V	18000 – 26000	25223920	P
2440	H	18000 – 26000	25223921	P
2480	H	18000 – 26000	25223922	P
2480	V	18000 – 26000	25223923	P

Remarks: EUT was tested in 3 orthogonal planes, graphs are related to the highest detected levels.

Measurements at frequencies lower than 30 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor $40\log(\text{test distance}/10)$ based on the measuring distance provided by the standard.

Measurements at frequencies higher than 30 MHz and lower than 1000 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor $20\log(\text{test distance}/10)$ based on the measuring distance provided by the standard.

Peaks above the limits are caused by the nominal transmitting frequencies.


Graphs Legend

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +

AV: Average; AV [1s] (average at 1 second) values are marked with a X

Graphs

zanivan 25223901




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
9320	+0.94	-47.28
306000	-17.55	-35.44
510000	+7.98	-25.47
1610000	+5.98	-17.49
4298000	+6.25	-23.29
17986000	+8.30	-21.24

25223901_2

zanivan 25223902




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
30520000	+20.54	-19.46
47280000	+16.71	-23.29
93760000	+15.69	-27.83
138520000	+17.06	-26.46
203360000	+20.86	-22.66
274720000	+24.42	-21.60

25223902_2

zanivan 25223903




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
31160000	+20.93	-19.07
63880000	+14.71	-25.29
87600000	+16.12	-23.88
127120000	+16.75	-26.77
203800000	+21.11	-22.41
293920000	+25.91	-20.11

25223903_2

zanivan 25223904




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
365680000	+23.18	-22.84
406160000	+23.85	-22.17
511040000	+25.89	-20.13
625880000	+27.82	-18.20
790760000	+30.08	-15.94
893880000	+31.12	-14.90

25223904_2

Zanivan 25223905




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
362320000	+22.51	-23.51
426920000	+24.21	-21.81
533160000	+25.92	-20.10
621640000	+27.74	-18.28
795320000	+29.79	-16.23
901000000	+31.34	-14.68

25223905_2

Zanivan 25223906




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1196000000	+51.08	-22.90	1199750000	+36.70	-17.28
1245250000	+51.38	-22.60	1440250000	+37.41	-16.57
1732000000	+52.82	-21.16	1732000000	+39.27	-14.71
2057500000	+55.16	-18.82	2080000000	+41.44	-12.54
2599750000	+58.69	-15.29	2599000000	+44.49	-9.49
2991000000	+61.69	-12.29	2998750000	+46.96	-7.02

25223906_2

zanivan 25223907




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1184500000	+51.01	-22.97	1196750000	+36.71	-17.27
1385500000	+51.72	-22.26	1437750000	+37.40	-16.58
1701750000	+53.63	-20.35	1732000000	+39.29	-14.69
2052750000	+55.72	-18.26	2080000000	+41.43	-12.55
2565750000	+58.49	-15.49	2566750000	+44.66	-9.32
2983250000	+61.43	-12.55	2999750000	+46.98	-7.00

25223907_2

zanivan 25223908




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1198000000	+51.09	-22.89	1199750000	+36.71	-17.27
1385750000	+51.75	-22.23	1438250000	+37.41	-16.57
1710500000	+53.59	-20.39	1732000000	+39.29	-14.69
1991750000	+55.32	-18.66	2080000000	+41.42	-12.56
2561250000	+58.77	-15.21	2559750000	+44.70	-9.28
2985000000	+61.13	-12.85	2999500000	+46.97	-7.01

25223908_2

Zanivan 25223909




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1157000000	+50.52	-23.46	1196750000	+36.69	-17.29
1441750000	+51.28	-22.70	1438000000	+37.40	-16.58
1726750000	+53.23	-20.75	1732000000	+39.28	-14.70
2074250000	+55.81	-18.17	2080000000	+41.41	-12.57
2614500000	+57.58	-16.40	2615750000	+44.32	-9.66
2990250000	+60.98	-13.00	2999750000	+46.96	-7.02

25223909_2

zanivan 25223910




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1155750000	+50.88	-23.10	1197750000	+36.70	-17.28
1442000000	+51.90	-22.08	1439750000	+37.39	-16.59
1667750000	+53.15	-20.83	1732000000	+39.28	-14.70
1981500000	+55.34	-18.64	2080000000	+41.42	-12.56
2696250000	+59.09	-14.89	2695000000	+44.63	-9.35
2981000000	+60.92	-13.06	2999750000	+46.95	-7.03

25223910_2

Zanivan 25223911




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1170250000	+51.01	-22.97	1199750000	+36.68	-17.30
1390000000	+51.72	-22.26	1440500000	+37.38	-16.60
1723000000	+53.34	-20.64	1732000000	+39.28	-14.70
2057250000	+55.41	-18.57	2080000000	+41.42	-12.56
2621000000	+57.83	-16.15	2621000000	+44.37	-9.61
2955000000	+60.81	-13.17	2999250000	+46.95	-7.03

25223911_2

zanivan 25223912




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3825000000	+47.49	-26.49	3849750000	+33.73	-20.25
4960500000	+48.65	-25.33	4959750000	+37.28	-16.70
7334500000	+51.82	-22.16	7439250000	+39.43	-14.55
9374000000	+55.40	-18.58	9135500000	+41.62	-12.36
13257000000	+60.67	-13.31	13239000000	+47.03	-6.95
17697250000	+64.38	-9.60	17959500000	+50.64	-3.34

25223912_2

zanivan 25223913




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3869250000	+47.07	-26.91	3849750000	+33.71	-20.27
5412750000	+49.03	-24.95	5413500000	+35.39	-18.59
7275750000	+51.75	-22.23	7336000000	+37.63	-16.35
9339500000	+55.47	-18.51	9139250000	+41.63	-12.35
13236000000	+60.63	-13.35	13239750000	+46.93	-7.05
17892500000	+65.13	-8.85	17958500000	+50.63	-3.35

25223913_2

Zanivan 25223914




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3868750000	+47.13	-26.85	3849750000	+33.67	-20.31
5427750000	+48.79	-25.19	4879750000	+34.91	-19.07
7292250000	+52.02	-21.96	7320500000	+38.12	-15.86
9347500000	+55.23	-18.75	9139250000	+41.61	-12.37
13218750000	+60.75	-13.23	13239250000	+46.93	-7.05
17894500000	+64.47	-9.51	17959000000	+50.62	-3.36

25223914_2

zanivan 25223915




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3911250000	+47.43	-26.55	3849750000	+33.73	-20.25
5414250000	+49.35	-24.63	4879750000	+38.08	-15.90
7333750000	+52.07	-21.91	7320500000	+38.25	-15.73
9388750000	+55.60	-18.38	9138250000	+41.59	-12.39
13235500000	+60.57	-13.41	13238000000	+46.96	-7.02
17847750000	+64.50	-9.48	17958000000	+50.58	-3.40

25223915_2

Zanivan 25223916




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3900250000	+47.30	-26.68	3849750000	+33.68	-20.30
5374250000	+48.90	-25.08	4803750000	+36.80	-17.18
7206500000	+52.36	-21.62	7205250000	+39.16	-14.82
9263000000	+55.69	-18.29	9137750000	+41.56	-12.42
13217250000	+60.64	-13.34	13238000000	+46.96	-7.02
17738000000	+64.54	-9.44	17957750000	+50.54	-3.44

25223916_2

zanivan 25223917




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3836000000	+47.04	-26.94	3849750000	+33.61	-20.37
4804500000	+48.79	-25.19	4804250000	+36.50	-17.48
7260000000	+50.95	-23.03	7205250000	+37.78	-16.20
9365250000	+55.08	-18.90	9138500000	+41.54	-12.44
13237750000	+60.58	-13.40	13237250000	+46.95	-7.03
17833250000	+64.43	-9.55	17957500000	+50.55	-3.43

25223917_2

zanivan 25223918




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
19319250000	+46.73	-27.25	18520750000	+31.74	-22.24
19477750000	+45.88	-28.10	19359250000	+31.58	-22.40
21644750000	+45.53	-28.45	21642750000	+31.72	-22.26
23263250000	+46.59	-27.39	23232000000	+32.46	-21.52
23676500000	+46.35	-27.63	24132750000	+32.79	-21.19
24978750000	+46.71	-27.27	25002250000	+33.20	-20.78

25223918_2

zanivan 25223919




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
18132750000	+45.46	-28.52	19332750000	+31.84	-22.14
20199250000	+45.30	-28.68	19333500000	+31.81	-22.17
21791000000	+45.07	-28.91	21789750000	+31.25	-22.73
23233750000	+46.88	-27.10	23232750000	+32.34	-21.64
24194000000	+46.06	-27.92	24134250000	+32.66	-21.32
24913750000	+46.86	-27.12	25001750000	+33.09	-20.89

25223919_2

zanivan 25223920




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
18035500000	+46.11	-27.87	19304250000	+31.69	-22.29
19662000000	+45.24	-28.74	19333500000	+31.67	-22.31
21846250000	+45.38	-28.60	21751500000	+30.60	-23.38
23268750000	+45.71	-28.27	22902500000	+32.17	-21.81
24198000000	+46.56	-27.42	24134000000	+32.52	-21.46
24975750000	+46.32	-27.66	25003500000	+32.99	-20.99

25223920_2

zanivan 25223921




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
18402750000	+45.40	-28.58	19332250000	+31.56	-22.42
20352000000	+45.01	-28.97	19333500000	+31.52	-22.46
21757250000	+44.12	-29.86	21758250000	+30.93	-23.05
22456250000	+45.98	-28.00	22903250000	+32.06	-21.92
24137750000	+46.82	-27.16	24133750000	+32.41	-21.57
25801000000	+46.60	-27.38	25002750000	+32.87	-21.11

25223921_2

zanivan 25223922




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
19297500000	+45.47	-28.51	18203250000	+31.51	-22.47
19501000000	+45.11	-28.87	19363250000	+31.46	-22.52
21677500000	+45.56	-28.42	21675750000	+31.42	-22.56
23280250000	+45.79	-28.19	22902250000	+32.05	-21.93
24045250000	+46.52	-27.46	24162500000	+32.43	-21.55
25031750000	+47.69	-26.29	25002750000	+32.87	-21.11

25223922_2

zanivan 25223923



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
18099500000	+45.29	-28.69	19333000000	+31.60	-22.38
19338250000	+44.70	-29.28	19333500000	+31.57	-22.41
21781750000	+43.83	-30.15	21786000000	+30.95	-23.03
22933750000	+45.88	-28.10	22873750000	+32.02	-21.96
24074000000	+46.00	-27.98	24133250000	+32.40	-21.58
25154250000	+46.39	-27.59	25002500000	+32.86	-21.12

25223923_2

Attachment 1

Measurement uncertainty

Test	Test Setup	Expanded uncertainty	Note
Conducted emission CISPR 16 LISN 50uH 0,009-0,0150 MHz	PE001_01	3,9 dB	1
Conducted emission CISPR 16 LISN 50uH 0,150-30,0 MHz	PE001_01	3,4 dB	1
Conducted emission CISPR 16 Voltage Probe 0,15-30 MHz	PE001_02	2,2 dB	1
Conducted emission CISPR 16 Current Probe 0,15-30 MHz	PE001_03	2,5 dB	1
Conducted emission CISPR 16 ISN 0,15-30 MHz	PE001_04	4,7 dB	1
Conducted emission CISPR 16 Clic CISPR 16	PE001_05	3,0 dB	1
Radiated Emission CDNE 30-300 MHz	PE001_06	3,3 dB	1
Disturbance Power 30-300 MHz	PE002_X1	3,8 dB	1
Radiated Emission LAS 0,15-30 MHz	PE003_01	2,0 dB	1
Radiated Emission CISPR 16 Loop Ant. 0,15-30 MHz	PE004_X1	4,1 dB	1
Radiated Emission CISPR 16 Bicon. Ant. 30-300 MHz	PE004_X2	4,7 dB	1
Radiated Emission CISPR 16 LogP. Ant. 300-1000 MHz	PE004_X3	4,6 dB	1
Radiated Emission CISPR 16 Horn Ant. 1-18 GHz	PE004_X4	4,7 dB	1
Human Exposure to electromagnetic fields	PE005_01	16,2 %	1
Harmonics	PE006_01	10 mA + 2,9 %	1
Flicker	PE007_01	3,40 %	1
Radiated Immunity 80 MHz - 6 GHz	PE102_XX	2,43 dB 0,97 V/m a 3V/m	1
Conducted Immunity 0,15 - 230 MHz	PE105_XX	1,26 dB 0,47 V a 3V	1
AC Magnetic field	PE106_01	1,55 % 0,15 A/m a 10A/m	1
Pulse Magnetic field	PE107_01	6,21 % 18,6 A/m a 300A/m	1
Dumped Magnetic field	PE108_01	6,21 % 1,86 A/m a 30A/m	1
Common mode conducted immunity	PE112_01	2,11 % 0,21 V a 10V	1

Test	Test Setup	Expanded uncertainty	Note
Power/Spurious 9kHz-30MHz	PR001_X1	4,1 dB	1
Power/Spurious ERP 30-1000MHz d=10m/3m	PR001_X2+X3	4,8 dB	1
Misura della potenza EIRP 1-18GHz d=3m	PR001_X4+X5	4,7 dB	1
Misura della potenza EIRP 18-40GHz d=3m	PR001_X6	5,1 dB	1
Frequency error	PR002_01+02	< 1x10 ⁻⁷	1
Timing zero span (1001pts.)	PR002_01+02	0,2 % SWT	1
Modulation bandwidth	PR002_01+02	< 1x10 ⁻⁷	1
Conducted RF power and spurious emission	PR002_01+02	1,1 dB	1
Adjacent channel power	PR002_01+02	1,1 dB	1
Blocking	PR002_01+02	1,1 dB	1

Test	Test Setup	Expanded uncertainty	Note
Electrostatic discharge immunity test	PE101_0X		2
Electrical fast transients / burst immunity test	PE103_0X		2
Surge immunity test	PE104_0X		2
Short interruption immunity test	PE109_01		2
Ring Wave immunity test	PE110_01		2
Low frequency immunity test	PE111_01		2
Dumped Oscillatory immunity test	PE113_01		2
Rev_25_02 date 21/10/2025			




Note 1:

The expanded uncertainty reported according to the document EA-4-02 is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of p = 95%

Note 2:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence, covering factor k=2

Judgement of compliance

Case 1	Case 2	Case 3	Case 4
 The sample complies with the requirements. The measurement results is within the specification limit when the measurement uncertainty is taken into account.	 The sample complies with the requirements. It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is below the limit.	 The sample does not comply with the requirements. It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty also the measurement result is upper the limit.	 The sample does not comply with the requirements. The measurement results is outside the specification limit when the measurement uncertainty is taken into account.

In agreement with ILAC-G8:09/2019 cl.4.2.1 Guidelines on Decision Rules and Statements of Conformity

Quality manual references – Internal procedure

Internal Procedure PM001 rev. 4.1 (Quality Manual)	Measure procedure
Internal Procedure INC_M rev. 10.1 (Quality Manual)	Measurement uncertainty calculation