DEKRA Testing and Certification S.r.l.
Via della Fisica 20, 36016 Thiene (VI) - Italy
Tel. +39 0445 367702 - info.thiene@dekra.com

00152

Test report nr. R25240401
Federal Communication Commission (FCC)
Innovation, Science and Economic Development Canada (ISED)

Customer	Autec S.r.l. Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy	
(#) Description of item tested	Base station	
(#) Trademark	Autec	
(#) Model and/or type reference	Model TR0N2 Type BC0Z3	
(#) Manufacturer	Autec S.r.l. Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy	
(#) Rating(s)	12-24 Vdc	
Test method requested, standard(s)	KDB 996369 D04 Module Integration Guide v01 FCC Rules & Regulations, Title 47:2024 Part 15 paragraph(s): 209 and 247 (b) (3) RSS-247 Issue 4 July 2025 RSS-GEN Issue 5:April 2018, Amendment 1 March 2019, Amendment 2 February 2021 Tests details at page 11	
Tested by (name / position & signature)	S. Zanivan *Technician*	
Approved by (name / position & signature)	F. Marenda *Laboratory manager*	
Date of issue	21.01.2026	
General disclaimer	The test results presented in this report relate only to the item tested. This report shall not be reproduced, except in full, without the written approval of DEKRA Testing and Certification S.r.l.	
Report template No	KDB_996369_DEKRA	

(#) information provided by the customer

Summary

SUMMARY 2
COMPETENCES AND GUARANTEES 3
GENERAL CONDITIONS 3
DATA PROVIDED BY THE CUSTOMER 3
REFERENCE STANDARDS 4
USAGE OF SAMPLES 5
TEST SAMPLE DESCRIPTION 6
PHOTOS OF THE TEST ITEM 7
TESTING PERIOD AND PLACE 8
DOCUMENT HISTORY 8
LIST OF ATTACHMENTS 8
ENVIRONMENTAL CONDITIONS 9
REMARKS AND COMMENTS 10
DEVIATIONS FROM TEST SPECIFICATION 10
TESTING VERDICTS 10
VERDICT SUMMARY 11
TEST RESULTS 12
EMISSIONS IN RESTRICTED FREQUENCY BANDS AND IN UNRESTRICTED FREQUENCY BANDS 12
ATTACHMENT 1 31
ATTACHMENT 2 34

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.r.l. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.r.l. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.r.l. at the time of performance of the test.

DEKRA Testing and Certification S.r.l. is liable to the customer for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.r.l.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.r.l. and the Accreditation Bodies.

Data provided by the customer

Information relating to the description of the sample, components list, and software/hardware version (if reported) are provided by the customer/manufacturer. DEKRA Testing and Certification S.r.l. cannot be considered responsible for this information, for any other document provided by the customer/manufacturer and for any difference between the software/hardware release present in the tested sample and that present in the object intended for final sale.

In some cases, the software in the tested sample is in a version dedicated exclusively to the test, and therefore does not represent the software installed in the final version of the product.

Reference standards

Standard(s)	Description
KDB 996369 D04 Module Integration Guide v01	Modular transmitter integration guide – Guidance for host product manufacturers
FCC Rules and Regulation Title 47 part 15:2024	Radio frequency devices
RSS-247 Issue 4 July 2025	RSS-247 – Digital Transmission Systems, Frequency Hopping Systems and Licence-Exempt Local Area Network Devices in 902-928 MHz, 2400-2483.5 MHz, 5150-5350 MHz, and 5470-5895 MHz bands
RSS-Gen Issue 5: April 2018, Amendment 1 March 2019, Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices operating under section 15.247 of the FCC rules
ANSI C63.10:2020 + COR1:2023 + C63.10A:2024 + Errata to C63.10A:2024	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Usage of samples

Sample(s) used for testing chosen by the customer; DEKRA Testing and Certification S.r.l. cannot be considered responsible for the selection of the sample(s).

Internal identification	Serial number/Customer Id	Date of reception	Notes
P251281	--	01.12.2025	--

Test sample description

Test power supply ..... :	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 12 V					
	☐	DC:					
Frequency band(s) ..... :	2400 – 2483,5						
Type of equipment ..... :	☒	Transmitter unit					
	☒	Receiver unit					
Type of station ..... :	☐	Portable station					
	☒	Mobile station					
Mounting position ..... :	☐	Table top equipment					
	☒	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☐	Other, for example rack mounted, body worn, etc.					
Components list ..... :	Attachment 2						
Operating modes ..... :	N.	Operating mode of test item					
	1	EUT in continuous transmission at maximum power					

Photos of the test item



Testing period and place

Test Location	DEKRA Testing and Certification S.r.l.
FCC Registration Number	182474
ISED Registration Number	9055A
Date (start)	15.01.2026
Date (finish)	15.01.2026

Document history

Report number	Date	Description
R25240401	21.01.2026	First release

List of attachments

Name	Description
Attachment 1	Measurement uncertainty, judgement of compliance and quality manual references
Attachment 2	Components list

Environmental conditions

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment.

The climatic conditions during the tests were within the following limits:

Temperature	Humidity	Atmospheric pressure
15 °C – 35 °C	30 % - 60 %	800 hPa – 1060 hPa

If explicitly required in the basic standard or applied product standard the climatic values are recorded and documented separately in this test report.

Environmental conditions have been monitored with the following instruments:

Id. number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
CMC S302	Testo	175H1	40370182 610	Data Logger	May 2025	May 2026

Remarks and comments

Throughout this report a comma is used as the decimal separator.

Tests reported in this test report marked by wording: “Test not accredited by ACCREDIA” are not part of the ACCREDIA accreditation of this laboratory.

Deviations from test specification

None.

Testing verdicts

N/A (Not Applicable)	Test case does not apply to the test object
P (Pass)	Test object meets the requirement
F (Fail)	Test object does not meet the requirement
N/E (Not Executed)	Test object was not evaluated for the requirement

Verdict summary

KDB 996369 D04 Module Integration Guide v01 FCC Rules & Regulations, Title 47:2024 Part 15 paragraph(s): 209 and 247 RSS-247 Issue 4 July 2025 RSS-Gen Issue 5: April 2018, Amendment 1 March 2019, Amendment 2 February 2021			
Clause	**Requirement – Test case**	**Basic standard**	**Verdict**
FCC Part 15.209 RSS-Gen Issue 5 RSS-247 Issue 4 cl. 6.6	Emissions in restricted frequency bands and in unrestricted frequency bands	ANSI C63.10	**P**
FCC Part 15.209 and 15.247 (b) (3) RSS-247 Issue 4 cl. 6.3.2(a)	Fundamental emission output power	ANSI C63.10	**Not required (+)**

(+) It should not be necessary to re-test the transmitter output power of any modular transmitter which has been certified based on conducted power

Test results

Emissions in restricted frequency bands and in unrestricted frequency bands

Tested by .....:	S. Zanivan	
Test date .....:	21.01.2026	
Test location (stand) .....:	Semi-anechoic chamber (CMC A070)	
Basic standard(s) .....:	ANSI C63.10 cl. 6.3, 6.4, 6.5 and 6.6	
Product standard(s) .....:	KDB 996369 D04 Module Integration Guide v01 FCC Rules and Regulation; Titles 47 Part 15.209 RSS-GEN Issue 5 RSS-247 Issue 4 cl. 6.6	
Test set-up description.....:	☒	Table top equipment set-up (80 cm above the reference ground plane)
	☐	Floor standing equipment set-up (insulating material up to 12 mm thick)
	☐	False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary test set-up description.....:	--	
Test method applied .....:	OATS or SAC with measurement distance [m]: 10 m for frequencies below 1 GHz 3 m for frequencies above 1 GHz	
Supplementary information .....:	--	

Acceptance limits

Acceptance limits for emissions in restricted frequency bands (f < 1000 MHz)		
Frequency range (MHz)	*Test distance (m)*	*Limits [dB(µV/m)]*
0,009 to 0,490	300	20log(2400/F(kHz))
0,490 to 1,705	30	20log(24000/F(kHz))
1,705 to 30	30	20log(30)
30 to 88	3	20log(100)**
88 to 216	3	20log(150)**
216 to 960	3	20log(200)**
Above 960	3	20log(500)

**: except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54 – 72 MHz, 76 – 88 MHz, 174 – 216 MHz or 470 – 806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
Perimeter protection systems may operate in the 54 – 72 MHz and 76 – 88 MHz bands under the provisions of this section. The use of such perimeter protection systems is limited to industrial, business and commercial applications.
Remarks: the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9 – 90 kHz and 110 – 490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector. The Verdict have been extrapolated to the specified distance using an extrapolation factor.

Acceptance limits for emissions in restricted frequency bands (f ≥ 1000 MHz)			
Frequency (MHz)	*Test distance (m)*	*AV limits [dB(µV/m)]*	*Peak limits [dB(µV/m)]*
> 1000	3	54	74

The FCC restricted frequency bands are listed in the following table:

MHz	***MHz***	***MHz***	***GHz***
0,090 – 0,110	16,42 – 16,423	399,9 – 410	4,5 – 5,15
0,495 – 0,505	16,69475 – 16,69525	608 – 614	5,35 – 5,46
2,1735 – 2,1905	16,80425 – 16,80475	960 – 1240	7,25 – 7,75
4,125 – 4,128	25,5 – 25,67	1300 – 1427	8,025 – 8,5
4,17725 – 4,17775	37,5 – 38,25	1435 – 1626,5	9,0 – 9,2
4,20725 – 4,20775	73 – 74,6	1645,5 – 1646,5	9,3 – 9,5
6,215 – 6,218	74,8 – 75,2	1660 – 1710	10,6 – 12,7
6,26775 – 6,26825	108 – 121,94	1718,8 – 1722,2	13,25 – 13,4
6,31175 – 6,31225	123 – 138	2200 – 2300	14,47 – 14,5
8,291 – 8,294	149,9 – 150,05	2310 – 2390	15,35 – 16,2
8,362 – 8,366	156,52475 – 156,52525	2483,5 – 2500	17,7 – 21,4
8,37625 – 8,38675	156,7 – 156,9	2690 – 2900	22,01 – 23,12
8,41425 – 8,41475	162,0125 – 167,17	3260 – 3267	23,6 – 24,0
12,29 – 12,293	167,72 – 173,2	3332 – 3339	31,2 – 31,8
12,51975 – 12,52025	240 – 285	3345,8 – 3358	36,43 – 36,5
12,57675 – 12,57725	322 – 335,4	3600 – 4400	Above 38,6
13,36 – 13,41			

Acceptance limits for emissions in non-restricted frequency bands (according to ANSI C63.10 cl. 11.11.1)

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.
b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.
c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required

ISED restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).
b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

MHz	***MHz***	***GHz***
0,090 – 0,110	149,9 – 150,05	9,0 – 9,2
0,495 – 0,505	156,52475 – 156,52525	9,3 – 9,5
2,1735 – 2,1905	156,7 – 156,9	10,6 – 12,7
3,020 – 3,026	162,0125 – 167,17	13,25 – 13,4
4,125 – 4,128	167,72 – 173,2	14,47 – 14,5
4,17725 – 4,17775	240 – 285	15,35 – 16,2
4,20725 – 4,20775	322 – 335,4	17,7 – 21,4
5,677 – 5,683	399,9 – 410	22,01 – 23,12
6,215 – 6,218	608 – 614	23,6 – 24,0
6,26775 – 6,26825	960 – 1427	31,2 – 31,8
6,31175 – 6,31225	1435 – 1626,5	36,43 – 36,5
8,291 – 8,294	1645,5 – 1646,5	Above 38,6
8,362 – 8,366	1660 – 1710	
8,37625 – 8,38675	1718,8 – 1722,2	
8,41425 – 8,41475	2200 – 2300	
12,29 – 12,293	2310 – 2390	
12,51975 – 12,52025	2483,5 – 2500	
12,57675 – 12,57725	2655 – 2900	
13,36 – 13,41	3260 – 3267	
16,42 – 16,423	3332 – 3339	
16,69475 – 16,69525	3345,8 – 3358	
16,80425 – 16,80475	3500 – 4400	
25,5 – 25,67	4500 – 5150	
37,5 – 38,25	5350 – 5460	
73 – 74,6	7250 – 7750	
74,8 – 75,2	8025 – 8500	
108 – 138		

Remarks: certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.
Transmitters whose wanted and unwanted emissions fall within the general field strength limits specified in RSS-Gen may operate licence-exempt in any of the frequency bands, other than the restricted frequency bands listed in RSS-Gen and the TV bands 54 – 72 MHz, 76 – 88 MHz, 174 – 216 MHz and 470 – 602 MHz, and shall be certified under RSS-210. Under no circumstances shall the level of any unwanted emissions exceed the level of the fundamental emissions.
Devices operating below 490 kHz for which all emissions are at least 40 dB below the general field strength limits listed in RSS-Gen are Category II devices and are subject to the requirements specified in RSS-310, Licence-Exempt Radio Apparatus: Category II Equipment.

Acceptance limits for emissions in non-restricted frequency bands
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement –provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test setup

Frequency ≤ 30 MHz



Test setup PE004_21							
Nr.	*Id. Number*	*Manufacturer*	*Model*	*Serial number*	*Description*	*Last calibration date*	*Calibration expiration*
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S127	Schaffner	HLA6120	1191	Loop Antenna 9kHz - 30MHz	July 2024	July 2027
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Frequency ≤ 1 GHz



Test setup PE004_22							
Nr.	*Id. Number*	*Manufacturer*	*Model*	*Serial number*	*Description*	*Last calibration date*	*Calibration expiration*
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S271	Schwarzbeck	BBA 9106 + VHBB 9124	831	Broadband Antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Test setup PE004_23							
Nr.	*Id. Number*	*Manufacturer*	*Model*	*Serial number*	*Description*	*Last calibration date*	*Calibration expiration*
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S287	Schwarzbeck	VUSLP 9111B	9111B-203	Broadband Antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Frequency > 1 GHz



Test setup PE004_24							
Nr.	*Id. Number*	*Manufacturer*	*Model*	*Serial number*	*Description*	*Last calibration date*	*Calibration expiration*
4	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
3	CMC S108	Emco	3115	9811-5622	Waveguide antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Test setup PE004_25							
Nr.	*Id. Number*	*Manufacturer*	*Model*	*Serial number*	*Description*	*Last calibration date*	*Calibration expiration*
4	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
3	CMC S290	Schwarzbeck	BBHA 9170	733	Horn Antenna	October 2021	October 2026
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Result

Polarization	*Frequency Range (MHz)*	*Graphs*	*Remarks*	*Verdict*
Loop	0,009 – 30	25240401	--	P
V	30 – 300	25240402	--	P
H	30 – 300	25240403	--	P
H	300 – 1000	25240404	--	P
V	300 – 1000	25240405	--	P
V	1000 – 3000	25240406	--	P
H	1000 – 3000	25240407	--	P
H	3000 – 18000	25240408	--	P
V	3000 – 18000	25240409	--	P
V	18000 – 26000	25240410	--	P
H	18000 – 26000	25240411	--	P

Remarks: EUT was tested in 3 orthogonal planes, graphs are related to the highest detected levels.
Measurements at frequencies lower than 30 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor 40log(test distance/10) based on the measuring distance provided by the standard.
Measurements at frequencies higher than 30 MHz and lower than 1000 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor 20log(test distance/10) based on the measuring distance provided by the standard.
Peaks above the limits are due to the nominal transmitting frequencies.

Graphs Legend
PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +
AV: Average; AV [1s] (average at 1 second) values are marked with a X

Graphs

Zanivan 25240401-Loop (0.009-30MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
9320	-5.53	-53.75
37320	-24.65	-60.82
310000	-13.98	-31.76
1686000	+6.01	-17.06
6518000	+7.22	-22.32
22098000	+8.20	-21.34

25240401_2

Zanivan 25240402-Vert.(30-300MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
31880000	+19.53	-20.47
56240000	+14.98	-25.02
87080000	+20.25	-19.75
136400000	+16.54	-26.98
201000000	+20.30	-23.22
299240000	+25.39	-20.63

25240402_2

Zanivan 25240403-Horiz.(30-300MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
30480000	+19.87	-20.13
47480000	+15.90	-24.10
83320000	+14.69	-25.31
137000000	+16.39	-27.13
202880000	+20.28	-23.24
297440000	+24.98	-21.04

25240403_2

Zanivan 25240404-Horiz.(300-1000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
353640000	+21.85	-24.17
395600000	+22.62	-23.40
534560000	+25.40	-20.62
626200000	+27.53	-18.49
794480000	+29.24	-16.78
884760000	+30.48	-15.54

25240404_2

Zanivan 25240405-Vert.(300-1000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
366120000	+22.72	-23.30
414760000	+23.63	-22.39
517440000	+25.43	-20.59
649600000	+26.78	-19.24
808680000	+29.64	-16.38
921280000	+31.71	-14.31

25240405_2

Zanivan 25240406-Vert.(1000-3000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1138000000	+40.48	-33.50	1199750000	+26.72	-27.26
1391500000	+41.00	-32.98	1442000000	+27.06	-26.92
1712750000	+43.28	-30.70	1732000000	+29.13	-24.85
2044750000	+45.36	-28.62	2080000000	+31.20	-22.78
2641000000	+47.59	-26.39	2643250000	+34.36	-19.62
2999750000	+50.95	-23.03	2999750000	+36.85	-17.13

25240406_2

Zanivan 25240407-Horiz.(1000-3000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1151500000	+40.29	-33.69	1197000000	+26.66	-27.32
1319500000	+41.44	-32.54	1442000000	+27.16	-26.82
1682250000	+42.85	-31.13	1732000000	+29.14	-24.84
1911500000	+45.11	-28.87	2080000000	+31.22	-22.76
2591750000	+48.93	-25.05	2591750000	+34.53	-19.45
2945500000	+50.67	-23.31	2999750000	+36.87	-17.11

25240407_2

Zanivan 25240408-Horiz.(3000-18000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3848750000	+47.08	-26.90	3848750000	+33.66	-20.32
5414500000	+48.85	-25.13	5412500000	+35.29	-18.69
7327000000	+51.47	-22.51	7335000000	+37.49	-16.49
9865500000	+55.73	-18.25	9137750000	+41.27	-12.71
13235250000	+60.10	-13.88	13239000000	+46.58	-7.40
17834000000	+64.53	-9.45	17979500000	+50.68	-3.30

25240408_2

Zanivan 25240409-Vert.(3000-18000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
3850000000	+46.80	-27.18	3849000000	+33.69	-20.29
5412250000	+49.30	-24.68	5413250000	+35.33	-18.65
7333750000	+51.05	-22.93	7347500000	+37.52	-16.46
9365250000	+55.24	-18.74	9380250000	+41.37	-12.61
13216750000	+60.13	-13.85	13239250000	+46.63	-7.35
17797500000	+65.25	-8.73	17979750000	+50.78	-3.20

25240409_2

Zanivan 25240410-Vert.(18000-26000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
18078750000	+46.42	-27.56	19324750000	+32.40	-21.58
19592000000	+46.16	-27.82	19355750000	+32.27	-21.71
21906750000	+46.05	-27.93	21910000000	+32.19	-21.79
23200500000	+46.30	-27.68	23233250000	+33.07	-20.91
24190000000	+46.71	-27.27	24133750000	+33.33	-20.65
25958750000	+46.94	-27.04	25003750000	+33.42	-20.56

25240410_2

Zanivan 25240411-Horiz.(18000-26000MHz)-In funzione. link BLE con ricevente ausiliaria



FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
18469000000	+46,78	-27,20	19305000000	+32,54	-21,44
20201250000	+46,12	-27,86	19333500000	+32,53	-21,45
22415500000	+45,11	-28,87	22421000000	+32,34	-21,64
23233500000	+46,72	-27,26	23233500000	+32,92	-21,06
24281750000	+46,64	-27,34	24133750000	+33,17	-20,81
25208500000	+46,81	-27,17	25003750000	+33,25	-20,73

25240411_2

Attachment 1

Measurement uncertainty

Test	*Test Setup*	*Expanded uncertainty*	*Note*
Conducted emission CISPR 16 LISN 50uH 0,009-0,0150 MHz	PE001_01	3,9 dB	1
Conducted emission CISPR 16 LISN 50uH 0,150-30,0 MHz	PE001_01	3,4 dB	1
Conducted emission CISPR 16 Voltage Probe 0,15-30 MHz	PE001_02	2,2 dB	1
Conducted emission CISPR 16 Current Probe 0,15-30 MHz	PE001_03	2,5 dB	1
Conducted emission CISPR 16 ISN 0,15-30 MHz	PE001_04	4,7 dB	1
Clic CISPR 16 LISN 50uH 0,150-30,0 MHz	PE001_05	3,0 dB	1
Radiated Emission CDNE 30-300 MHz	PE001_06	3,3 dB	1
Disturbance Power 30-300 MHz	PE002_X1	3,8 dB	1
Radiated Emission LAS 0,15-30 MHz	PE003_01	2,0 dB	1
Radiated Emission CISPR 16 Loop Ant. 0,15-30 MHz	PE004_X1	4,1 dB	1
Radiated Emission CISPR 16 Bicon. Ant. 30-300 MHz	PE004_X2	4,7 dB	1
Radiated Emission CISPR 16 LogP. Ant. 300-1000 MHz	PE004_X3	4,6 dB	1
Radiated Emission CISPR 16 Horn Ant. 1-18 GHz	PE004_X4	4,7 dB	1
Human Exposure to electromagnetic fields	PE005_01	16,2 %	1
Harmonics	PE006_01	10 mA + 2,9 %	1
Flicker	PE007_01	3,40 %	1
Radiated Immunity 80 MHz - 6 GHz	PE102_XX	2,43 dB 0,97 V/m a 3V/m	1
Conducted Immunity 0,15 - 230 MHz	PE105_XX	1,26 dB 0,47 V a 3V	1
AC Magnetic field	PE106_01	1,55 % 0,15 A/m a 10A/m	1
Pulse Magnetic field	PE107_01	6,21 % 18,6 A/m a 300A/m	1
Dumped Magnetic field	PE108_01	6,21 % 1,86 A/m a 30A/m	1
Common mode conducted immunity	PE112_01	2,11 % 0,21 V a 10V	1

Test	Test Setup	Expanded uncertainty	Note
Power/Spurious 9kHz-30MHz	PR001_X1	4,1 dB	1
Power/Spurious ERP 30-1000MHz d=10m/3m	PR001_X2+X3	4,8 dB	1
Misura della potenza EiRP 1-18GHz d=3m	PR001_X4+X5	4,7 dB	1
Misura della potenza EiRP 18-40GHz d=3m	PR001_X6	5,1 dB	1
Frequency error	PR002_01+02	< 1x10-7	1
Timing zero span (1001pts.)	PR002_01+02	0,2 % SWT	1
Modulation bandwidth	PR002_01+02	< 1x10-7	1
Conducted RF power and spurious emission	PR002_01+02	1,1 dB	1
Adjacent channel power	PR002_01+02	1,1 dB	1
Blocking	PR002_01+02	1,1 dB	1

Test	Test Setup	Expanded uncertainty	Note
Electrostatic discharge immunity test	PE101_0X		2
Electrical fast transients / burst immunity test	PE103_0X		2
Surge immunity test	PE104_0X		2
Short interruption immunity test	PE109_01		2
Ring Wave immunity test	PE110_01		2
Low frequency immunity test	PE111_01		2
Dumped Oscillotary immunity test	PE113_01		2
Rev_25_02 date 21/10/2025			

Note 1:

The expanded uncertainty reported according to the document EA-4-02 is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of p = 95%

Note 2:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence, covering factor k=2

Judgement of compliance

Case 1	Case 2	Case 3	Case 4
			
The sample complies with the requirements. The measurement results is within the specification limit when the measurement uncertainty is taken into account.	The sample complies with the requirements. It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is below the limit.	The sample does not comply with the requirements. It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty also the measurement result is upper the limit.	The sample does not comply with the requirements. The measurement results is outside the specification limit when the measurement uncertainty is taken into account.

In agreement with ILAC-G8:09/2019 cl.4.2.1 Guidelines on Decision Rules and Statements of Conformity

Quality manual references – Internal procedure

Internal Procedure PM001 rev. 4.1 (Quality Manual)	Measure procedure
Internal Procedure INC_M rev. 10.1 (Quality Manual)	Measurement uncertainty calculation

Attachment 2

Components list provided by the customer

Model	TR0N2
Type	BC0Z3
Configuration	A001C

List	Qty	Vers. HW	FW1	FW2	FW3	FW4	FW5	FW6	FW7
FSACRT01A - ANL DEC CRT TRIBAND DYN+T	1	1.0.B.A	DYN_PT_DECODER_A_R	DYN_PT_DECODER_B_R	DYN_PT_RADIO_IF_REV-	DYN_PT_RADIO_REV-00	DYN_PT_NCP_Rev-00	DYN_PT_CRT_REV-00	XMC4500_BL_REV-03
ANT045 ANTENNA EXT TRIBAND PER STAFFA	1	-	-	-	-	-	-	-	-