

Test report nr. R25242101

Federal Communication Commission (FCC)

Customer	Autec S.r.l. Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy	
(#) FCC ID	OQA-TX0N2BC0A3	
(#) Description of item tested	Base station	
(#) Trademark	Autec	
(#) Model and/or type reference	Model TX0N2 Type BC0A3	
(#) Manufacturer	Autec S.r.l. Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy	
(#) Rating(s)	12-24 Vdc	
Test method requested, standard(s)	FCC Rules & Regulations, Title 47:2024 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247	
Tested by (name / position & signature)	S. Zanivan <i>Technician</i>	
Approved by (name / position & signature)	F. Marenda <i>Laboratory manager</i>	
Date of issue	06.03.2026	
General disclaimer	The test results presented in this report relate only to the item tested. This report shall not be reproduced, except in full, without the written approval of DEKRA Testing and Certification S.r.l.	
Report template No	15-247_Hopping_DEKRA	

(#) information provided by the customer

Summary

SUMMARY	2
COMPETENCES AND GUARANTEES	3
GENERAL CONDITIONS	3
DATA PROVIDED BY THE CUSTOMER	3
REFERENCE STANDARDS	4
USAGE OF SAMPLES	5
TEST SAMPLE DESCRIPTION	6
PHOTOS OF THE TEST ITEM	7
TESTING PERIOD AND PLACE	8
DOCUMENT HISTORY	8
LIST OF ATTACHMENTS	8
ENVIRONMENTAL CONDITIONS	9
REMARKS AND COMMENTS	10
DEVIATIONS FROM TEST SPECIFICATION	10
TESTING VERDICTS	10
VERDICT SUMMARY	11
TEST RESULTS	12
ANTENNA REQUIREMENTS	12
CONDUCTED EMISSION	13
EMISSIONS IN RESTRICTED FREQUENCY BANDS AND IN UNRESTRICTED FREQUENCY BANDS	19
20 dB BANDWIDTH	40
CHANNEL SEPARATION	43
NUMBER OF HOPPING CHANNELS	46
TIME OF OCCUPANCY	50
BAND EDGE	53
PEAK OUTPUT POWER	57
ATTACHMENT 1	61

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.r.l. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.r.l. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.r.l. at the time of performance of the test.

DEKRA Testing and Certification S.r.l. is liable to the customer for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.r.l.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.r.l. and the Accreditation Bodies.

Data provided by the customer

Information relating to the description of the sample, components list, and software/hardware version (if reported) are provided by the customer/manufacturer. DEKRA Testing and Certification S.r.l. cannot be considered responsible for this information, for any other document provided by the customer/manufacturer and for any difference between the software/hardware release present in the tested sample and that present in the object intended for final sale.

In some cases, the software in the tested sample is in a version dedicated exclusively to the test, and therefore does not represent the software installed in the final version of the product.

Reference standards

Standard(s)	Description
FCC Rules and Regulation Title 47 part 15:2024	--
KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices operating under section 15.247 of the FCC rules
ANSI C63.4:2014	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
ANSI C63.10:2020 + COR1:2023 + C63.10A:2024 + Errata to C63.10A:2024	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Usage of samples

Sample(s) used for testing chosen by the customer; DEKRA Testing and Certification S.r.l. cannot be considered responsible for the selection of the sample(s).

Internal identification	Serial number/Customer Id	Date of reception	Notes
P251285	--	02.12.2025	--

Test sample description

Test power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 12 V					
	☐	DC:					
Frequency band(s)	902 – 928 MHz						
Nominal frequencies	915,075 MHz 921,425 MHz 927,825 MHz						
Pseudo randomly ordered list of hopping frequencies	See document j7p_nja55_operational_description-rev0						
Type of equipment	☒	Transmitter unit					
	☒	Receiver unit					
Type of station	☐	Portable station					
	☒	Mobile station					
Mounting position	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☒	Other, for example rack mounted, body worn, etc.					
Operating modes	N.	Operating mode of test item					
	1	EUT in continuous transmission at maximum power					

Photos of the test item



Testing period and place

Test Location	DEKRA Testing and Certification S.r.l.
FCC Registration Number	182474
Date (start)	30.01.2026
Date (finish)	27.02.2026

Document history

Report number	Date	Description
R25242101	06.03.2026	First release

List of attachments

Name	Description
Attachment 1	Measurement uncertainty, judgement of compliance and quality manual references

Environmental conditions

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment.

The climatic conditions during the tests were within the following limits:

Temperature	Humidity	Atmospheric pressure
15 °C – 35 °C	30 % - 60 %	800 hPa – 1060 hPa

If explicitly required in the basic standard or applied product standard the climatic values are recorded and documented separately in this test report.

Environmental conditions have been monitored with the following instruments:

Id. number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
CMC S302	Testo	175H1	40370182 610	Data Logger	May 2025	May 2026

Remarks and comments

Throughout this report a comma is used as the decimal separator.

Tests reported in this test report marked by wording: "Test not accredited by ACCREDIA" are not part of the ACCREDIA accreditation of this laboratory.

Deviations from test specification

None.

Testing verdicts

N/A (Not Applicable)	Test case does not apply to the test object
P (Pass)	Test object meets the requirement
F (Fail)	Test object does not meet the requirement
N/E (Not Executed)	Test object was not evaluated for the requirement

Verdict summary

FCC Rules & Regulations, Title 47:2024 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247			
Clause	Requirement – Test case	Basic standard	Verdict
Part 15.247 (a) (1)	Pseudo randomly ordered list of hopping frequencies	--	P
Part 15.203	Antenna requirements	ANSI C63.10	P
Part 15.207	Conducted emissions	ANSI C63.10	P
Part 15.209	Radiated emissions and spurious emissions	ANSI C63.10	P
Part 15.247	20 dB Bandwidth	ANSI C63.10	P
Part 15.247	Channel Separation	ANSI C63.10	P
Part 15.247	Number of Hopping Channel	ANSI C63.10	P
Part 15.247	Time of occupancy	ANSI C63.10	P
Part 15.247	Band edge	ANSI C63.10	P
Part 15.209 and 15.247	Peak Output Power	ANSI C63.10	P

Test results

Antenna requirements

Tested by	S. Zanivan	
Test date	30.01.2026	
Basic standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.203 and 15.204	
Test specification	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded	
Antenna type	☐	Integral antenna
	☒	External antenna
Antenna gain	1,56 dBi	
External R.F. power amplifier	Not Present	


Conducted emission

Tested by	S. Zanivan	
Test date	20.02.2026	
Test location (stand).....	Shielded chamber (CMC A001)	
Basic standard(s)	ANSI C63.10 cl. 6.2	
Product standard(s).....	FCC Rules and Regulation; Titles 47 Part. 15.207	
Test set-up description	☒	Table top equipment set-up (80 cm above the reference ground plane)
	☐	Floor standing equipment set-up (insulating material up to 12 mm thick)
	☐	False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary Test set-up description	--	
Test method applied.....	☒	Artificial mains network, 50 μ H/50 Ω LISN
	☐	Other:

Acceptance limits

Frequency range (MHz)	$\text{dB}(\mu\text{V})$ Quasi-peak	$\text{dB}(\mu\text{V})$ Average
0,15 to 0,50	66 to 56	56 to 46
0,5 to 5	56	46
5 to 30	60	50

Test setup



Test setup PE001_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
3	CMC S419	Rohde & Schwarz	ESH3-Z2	--	Pulse limiter	September 2025	September 2026
2	CMC S200	Schwarzbeck	NSLK 8128	8128-273	V-LISN	January 2026	January 2027
1	CMC S206	Rohde & Schwarz	ESCI 7	100781	EMC Receiver 9KHz-7GHz	December 2025	December 2026

Result


Line	Frequency Range (MHz)	Graphs	Remarks	Verdict
-12 Vdc	0,15 – 30	25242116	--	P
+12 Vdc	0,15 – 30	25242117	--	P

Graphs Legend

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +

AV: Average; AV [1s] (average at 1 second) values are marked with a X


Graphs



Zanivan 25242116-Line (-)

EDIT PEAK LIST (Final Measurement Results)			
Trace1:	15_207QP		
Trace2:	15_207AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	302 kHz	17.83	-42.35
2 Average	302 kHz	10.28	-39.90
1 Quasi Peak	742 kHz	20.08	-35.91
2 Average	782 kHz	22.23	-23.76
2 Average	1.918 MHz	21.93	-24.07
1 Quasi Peak	1.922 MHz	25.23	-30.76
2 Average	4.002 MHz	44.27	-1.72
1 Quasi Peak	4.25 MHz	45.15	-10.84
1 Quasi Peak	6.002 MHz	36.83	-23.17
2 Average	6.002 MHz	34.10	-15.89
1 Quasi Peak	17.534 MHz	39.24	-20.75
2 Average	17.538 MHz	35.42	-14.57

Zanivan 25242116-Line (-)



Zanivan 25242117-Line (+)

EDIT PEAK LIST (Final Measurement Results)			
Trace1:	15_207QP		
Trace2:	15_207AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	310 kHz	16.71	-43.25
2 Average	330 kHz	11.50	-37.94
1 Quasi Peak	782 kHz	22.54	-33.45
2 Average	782 kHz	22.19	-23.80
2 Average	1.918 MHz	21.89	-24.10
1 Quasi Peak	1.922 MHz	25.22	-30.77
2 Average	4.002 MHz	44.24	-1.75
1 Quasi Peak	4.25 MHz	45.14	-10.86
1 Quasi Peak	6.002 MHz	36.78	-23.21
2 Average	6.002 MHz	34.06	-15.93
1 Quasi Peak	17.258 MHz	39.33	-20.66
2 Average	17.266 MHz	34.84	-15.15

Zanivan 25242117-Line (+)

Emissions in restricted frequency bands and in unrestricted frequency bands

Tested by	S. Zanivan
Test date	30.01.2026
Test location (stand)	Semi-anechoic chamber (CMC A070)
Basic standard(s)	ANSI C63.10 cl. 6.3, 6.4, 6.5 and 6.6
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.209
Test set-up description.....	☒ Table top equipment set-up 80 cm above the reference ground plane at frequencies ≤ 1 GHz 1,5 m above the reference ground plane at frequencies > 1 GHz ☐ Floor standing equipment set-up (insulating material up to 12 mm thick) ☐ False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary test set-up description	--
Test method applied	OATS or SAC with measurement distance [m]: 10 m for frequencies below 1 GHz 3 m for frequencies above 1 GHz
Supplementary information	--

Acceptance limits

Acceptance limits for emissions in restricted frequency bands ($f < 1000$ MHz)		
Frequency range (MHz)	Test distance (m)	Limits [dB(μ V/m)]
0,009 to 0,490	300	$20\log(2400/F(\text{kHz}))$
0,490 to 1,705	30	$20\log(24000/F(\text{kHz}))$
1,705 to 30	30	$20\log(30)$
30 to 88	3	$20\log(100)^{**}$
88 to 216	3	$20\log(150)^{**}$
216 to 960	3	$20\log(200)^{**}$
Above 960	3	$20\log(500)$

****:** except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54 – 72 MHz, 76 – 88 MHz, 174 – 216 MHz or 470 – 806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Perimeter protection systems may operate in the 54 – 72 MHz and 76 – 88 MHz bands under the provisions of this section. The use of such perimeter protection systems is limited to industrial, business and commercial applications.

Remarks: the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9 – 90 kHz and 110 – 490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector. The Verdict have been extrapolated to the specified distance using an extrapolation factor.

Acceptance limits for emissions in restricted frequency bands ($f \geq 1000$ MHz)			
Frequency (MHz)	Test distance (m)	AV limits [dB(μ V/m)]	Peak limits [dB(μ V/m)]
> 1000	3	54	74


The restricted frequency bands are listed in the following table:

MHz	MHz	MHz	GHz
0,090 – 0,110	16,42 – 16,423	399,9 – 410	4,5 – 5,15
0,495 – 0,505	16,69475 – 16,69525	608 – 614	5,35 – 5,46
2,1735 – 2,1905	16,80425 – 16,80475	960 – 1240	7,25 – 7,75
4,125 – 4,128	25,5 – 25,67	1300 – 1427	8,025 – 8,5
4,17725 – 4,17775	37,5 – 38,25	1435 – 1626,5	9,0 – 9,2
4,20725 – 4,20775	73 – 74,6	1645,5 – 1646,5	9,3 – 9,5
6,215 – 6,218	74,8 – 75,2	1660 – 1710	10,6 – 12,7
6,26775 – 6,26825	108 – 121,94	1718,8 – 1722,2	13,25 – 13,4
6,31175 – 6,31225	123 – 138	2200 – 2300	14,47 – 14,5
8,291 – 8,294	149,9 – 150,05	2310 – 2390	15,35 – 16,2
8,362 – 8,366	156,52475 – 156,52525	2483,5 – 2500	17,7 – 21,4
8,37625 – 8,38675	156,7 – 156,9	2690 – 2900	22,01 – 23,12
8,41425 – 8,41475	162,0125 – 167,17	3260 – 3267	23,6 – 24,0
12,29 – 12,293	167,72 – 173,2	3332 – 3339	31,2 – 31,8
12,51975 – 12,52025	240 – 285	3345,8 – 3358	36,43 – 36,5
12,57675 – 12,57725	322 – 335,4	3600 – 4400	Above 38,6
13,36 – 13,41			


Acceptance limits for emissions in non-restricted frequency bands

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test setup



Test setup PE004_21							
Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S127	Schaffner	HLA6120	1191	Loop Antenna 9kHz - 30MHz	July 2024	July 2027
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required




Test setup PE004_22

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S271	Schwarzbeck	BBA 9106 + VHBB 9124	831	Broadband Antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Test setup PE004_23

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
1	CMC S287	Schwarzbeck	VUSLP 9111B	9111B-203	Broadband Antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required



Test setup PE004_24

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
4	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
3	CMC S108	Emco	3115	9811-5622	Waveguide antenna	August 2025	August 2028
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Test setup PE004_25

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
4	CMC S402	Rohde & Schwarz	ESW44	103433	Emi Test Receiver	August 2025	August 2026
3	CMC S290	Schwarzbeck	BBHA 9170	733	Horn Antenna	October 2021	October 2026
--	CMC A105	Frankonia	FC06	FC06.1-2017-073	Turntable & Antenna mast controller (Software V02.05.013)	No calibration required	No calibration required

Result

Transmission frequency (MHz)	Polarization	Frequency Range (MHz)	Graphs	Verdict
Worst case	Loop	0,009 – 30	25242101	P
Worst case	H	30 – 300	25242102	P
Worst case	V	30 – 300	25242103	P
915,075	V	300 – 1000	25242104	P
915,075	H	300 – 1000	25242105	P
921,425	H	300 – 1000	25242106	P
921,425	V	300 – 1000	25242107	P
927,825	V	300 – 1000	25242108	P
927,825	H	300 – 1000	25242109	P
927,825	H	1000 – 10000	25242110	P
927,825	V	1000 – 10000	25242111	P
921,425	V	1000 – 10000	25242112	P
921,425	H	1000 – 10000	25242113	P
915,075	H	1000 – 10000	25242114	P
915,075	V	1000 – 10000	25242115	P

Remarks: EUT was tested in 3 orthogonal planes, graphs are related to the highest detected levels.

Measurements at frequencies lower than 30 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor $40\log(\text{test distance}/10)$ based on the measuring distance provided by the standard.

Measurements at frequencies higher than 30 MHz and lower than 1000 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor $20\log(\text{test distance}/10)$ based on the measuring distance provided by the standard.

Peaks above the limits are caused by the nominal transmitting frequencies.


Graphs Legend

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +

AV: Average; AV [1s] (average at 1 second) values are marked with a X

Graphs

zanivan 25242101




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
9080	+0,80	-47,64
334000	-16,82	-33,95
502000	+7,96	-25,63
1554000	+5,86	-17,92
7614000	+7,24	-22,30
14058000	+8,23	-21,31

25242101_2

zanivan 25242102




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
30960000	+20,09	-19,91
55680000	+14,82	-25,18
91040000	+14,45	-29,07
131760000	+16,27	-27,25
203640000	+20,17	-23,35
295400000	+25,04	-20,98

25242102_2

zanivan 25242103




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
34480000	+18,79	-21,21
44320000	+15,91	-24,09
87040000	+17,82	-22,18
137320000	+16,50	-27,02
197120000	+20,19	-23,33
292800000	+24,82	-21,20

25242103_2

zanivan 25242104




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
362240000	+22,01	-24,01
445640000	+23,62	-22,40
513440000	+25,40	-20,62
614760000	+26,91	-19,11
808080000	+29,12	-16,90
952960000	+30,23	-15,79

25242104_2

zanivan 25242105




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
356480000	+21,82	-24,20
423320000	+23,50	-22,52
507800000	+25,31	-20,71
617000000	+27,13	-18,89
816240000	+29,39	-16,63
970000000	+30,82	-23,16

25242105_2

zanivan 25242106




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
360080000	+21.75	-24.27
413880000	+23.50	-22.52
526960000	+25.55	-20.47
643120000	+26.88	-19.14
790760000	+29.47	-16.55
971520000	+30.89	-23.09

25242106_2

zanivan 25242107




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
361160000	+22,06	-23,96
446480000	+23,90	-22,12
523800000	+25,56	-20,46
663000000	+26,61	-19,41
757960000	+28,08	-17,94
978000000	+31,14	-22,84

25242107_2

zanivan 25242108




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
351680000	+21.77	-24.25
413680000	+23.60	-22.42
506400000	+25.33	-20.69
616920000	+26.93	-19.09
792520000	+29.29	-16.73
970240000	+30.80	-23.18

25242108_2

Zanivan 25242109




FINAL RESULT TABLE

QUASI PEAK

Freq Hz	Lev dBuV/m	Margin dB
366240000	+22.74	-23.28
436240000	+23.51	-22.51
544240000	+24.95	-21.07
634520000	+27.34	-18.68
789120000	+29.59	-16.43
984640000	+31.38	-22.60

25242109_2

zanivan 25242110




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1235750000	+38.66	-35.32	1200000000	+25.63	-28.35
1855750000	+41.28	-32.70	1855750000	+29.60	-24.38
3120500000	+43.68	-30.30	3093500000	+29.95	-24.03
3910250000	+46.74	-27.24	3912250000	+33.08	-20.90
5567000000	+51.52	-22.46	5567000000	+39.86	-14.12
9940500000	+54.72	-19.26	9320500000	+40.78	-13.20

25242110_2

zanivan 25242111




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1200750000	+38.68	-35.30	1200000000	+25.47	-28.51
1855750000	+46.07	-27.91	1855750000	+34.67	-19.31
3148750000	+43.66	-30.32	3093500000	+29.96	-24.02
3959500000	+47.04	-26.94	3912000000	+33.08	-20.90
6776500000	+50.04	-23.94	5567000000	+37.24	-16.74
9996750000	+54.90	-19.08	9320250000	+40.80	-13.18

25242111_2

zanivan 25242112




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1188750000	+38.62	-35.36	1200000000	+25.07	-28.91
1842750000	+44.54	-29.44	1842750000	+32.75	-21.23
3133750000	+43.71	-30.27	3093250000	+29.93	-24.05
3889750000	+46.66	-27.32	3899750000	+33.04	-20.94
6776000000	+49.80	-24.18	6811250000	+35.79	-18.19
9165000000	+55.08	-18.90	9320250000	+40.77	-13.21

25242112_2

zanivan 25242113




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1209750000	+38.48	-35.50	1200000000	+25.48	-28.50
1842750000	+41.85	-32.13	1842750000	+29.73	-24.25
3077750000	+43.54	-30.44	3093250000	+29.91	-24.07
3840000000	+46.45	-27.53	3899500000	+33.03	-20.95
6652000000	+49.58	-24.40	5528500000	+35.86	-18.12
9223750000	+54.94	-19.04	9320500000	+40.78	-13.20

25242113_2

Zanivan 25242114




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1189250000	+38.69	-35.29	1200000000	+25.07	-28.91
1830250000	+42.02	-31.96	1830250000	+29.92	-24.06
2745000000	+45.02	-28.96	2745250000	+32.77	-21.21
3848500000	+47.03	-26.95	4575250000	+33.13	-20.85
5490500000	+50.45	-23.53	5490500000	+38.08	-15.90
9980500000	+54.99	-18.99	9320250000	+40.80	-13.18

25242114_2

zanivan 25242115



FINAL RESULT TABLE


MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1249750000	+38,25	-35,73	1200000000	+25,48	-28,50
1830250000	+46,55	-27,43	1830250000	+34,99	-18,99
2745250000	+45,37	-28,61	2745250000	+33,02	-20,96
3935500000	+47,21	-26,77	3912500000	+33,07	-20,91
6800000000	+50,89	-23,09	5490500000	+36,72	-17,26
9998000000	+54,70	-19,28	9320250000	+40,83	-13,15

25242115_2

20 dB bandwidth

Tested by	S. Zanivan
Test date	27.02.2026
Test location (stand)	Laboratory
Basic standard(s)	ANSI C63.10 cl. 7.8.7
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.215 (c)
Supplementary test set-up description	--
Supplementary information	--

Test setup




Test setup PR002_01							
Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	January 2026	January 2027
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

Result


Transmission frequency (MHz)	Graphs	20 dB bandwidth (kHz)
915,075	25242119	38,66
921,425	25242123	38,76
927,825	25242126	38,66

Graphs


zanivan 25242119



zanivan 25242123



zanivan 25242126




Channel separation

Tested by	S. Zanivan
Test date	27.02.2026
Test location (stand)	Laboratory
Basic standard(s)	KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 9 b) ANSI C63.10 cl. 7.8.2
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.247
Supplementary test set-up description	--
Supplementary information	--

Acceptance limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test setup



Test setup PR002_01


Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	January 2026	January 2027
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

Result

<i>Frequency band (MHz)</i>	<i>Graphs</i>	<i>Channel separation (kHz)</i>	<i>Minimum channel separation required (kHz)</i>	<i>Verdict</i>
902 – 928	25242130	199,80	38,76	P

Graphs

zanivan 25242130




Number of hopping channels

Tested by	S. Zanivan
Test date	27.02.2026
Test location (stand)	Laboratory
Basic standard(s)	KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 9 b) ANSI C63.10 cl. 7.8.3
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.247
Supplementary test set-up description	--
Supplementary information	--

Acceptance limits

For frequency hopping systems operating in the 902 – 928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test setup




Test setup PR002_01							
Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	January 2026	January 2027
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

Result


<i>Frequency band (MHz)</i>	<i>Graphs</i>	<i>Number of hopping channels</i>	<i>Minimum number of hopping channels required</i>	<i>Verdict</i>
902 – 928	25242131 25242132 25242133	64	50	P

Graphs


zanivan 25242131



zanivan 25242132



zanivan 25242133




Time of occupancy

Tested by	S. Zanivan
Test date	27.02.2026
Test location (stand)	Laboratory
Basic standard(s)	KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 9 b) ANSI C63.10 cl. 7.8.4
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.247
Supplementary test set-up description	--
Supplementary information	--

Acceptance limits

For frequency hopping systems operating in the 902 – 928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test setup



Test setup PR002_01							
Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	January 2026	January 2027
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

Result

<i>Transmission frequency (MHz)</i>	<i>Graphs</i>	<i>Dwell time (ms)</i>
915,075	25242134	14,50


<i>Transmission frequency (MHz)</i>	<i>Graphs</i>	<i>Number of transmissions</i>	<i>Period</i>
915,075	25242135	7	20 s

Remarks: only the highest peaks have been considered. The lowest peaks are due to the auxiliary receiver unit


<i>Time of occupancy (Dwell time x Nr. transmissions)</i>	<i>Maximum allowed time of occupancy</i>	<i>Verdict</i>
101,50 ms	400 ms	P

Graphs

zanivan 25242134



zanivan 25242135



Band edge


Tested by	S. Zanivan
Test date	27.02.2026
Test location (stand)	Laboratory
Basic standard(s)	ANSI C63.10 cl. 7.8.6
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.247
Supplementary test set-up description	--
Supplementary information	--

Acceptance limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter P with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Operation within the band 902 – 928 MHz $\pm$ RBW/2.

Test setup



Test setup PR002_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	January 2026	January 2027
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test


Result

Transmission frequency (MHz)	Bandwidth	Graph(s) – Hopping	Absolute power (dBm)	Power limit (dBm)	Frequency	Verdict
915,075	100 kHz	25242129	-25,40	-23,36	F _L : 914,917 MHz	P
927,825	100 kHz	25242137	-23,94	-23,45	F _H : 927,964 MHz	P


Transmission frequency (MHz)	Bandwidth	Graph(s) – No hopping	Absolute power (dBm)	Power limit (dBm)	Frequency	Verdict
915,075	100 kHz	25242121	-25,57	-23,39	F _L : 914,917 MHz	P
927,825	100 kHz	25242128	-23,81	-23,43	F _H : 927,964 MHz	P

Graphs


zanivan 25242121




zanivan 25242128



zanivan 25242129



zanivan 25242137



Peak Output Power


Tested by	S. Zanivan
Test date	27.02.2026
Test location (stand)	Laboratory
Basic standard(s)	KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 2.2 ANSI C63.10 cl. 7.8.5
Product standard(s)	FCC Rules and Regulation; Titles 47 Part. 15.247
Supplementary test set-up description	--
Supplementary information	--

Acceptance limits

For frequency hopping systems operating in the 2400–2483,5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483,5 MHz band: 0,125 watts.

For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and 0,25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Test setup




Test setup PR002_01							
Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	January 2026	January 2027
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

Result


<i>Transmission frequency (MHz)</i>	<i>Graphs</i>	<i>Peak Output Power (dBm)</i>	<i>Peak Output Power (mW)</i>	<i>Limit (mW)</i>	<i>Verdict</i>
915,075	25242118	16,87	48,64	1000	P
921,425	25242122	16,75	47,32	1000	P
927,825	25242125	16,80	47,86	1000	P

Graphs


zanivan 25242118



zanivan 25242122



zanivan 25242125



Attachment 1

Measurement uncertainty

Test	Test Setup	Expanded uncertainty	Note
Conducted emission CISPR 16 LISN 50uH 0,009-0,0150 MHz	PE001_01	3,9 dB	1
Conducted emission CISPR 16 LISN 50uH 0,150-30,0 MHz	PE001_01	3,4 dB	1
Conducted emission CISPR 16 Voltage Probe 0,15-30 MHz	PE001_02	2,2 dB	1
Conducted emission CISPR 16 Current Probe 0,15-30 MHz	PE001_03	2,5 dB	1
Conducted emission CISPR 16 ISN 0,15-30 MHz	PE001_04	4,7 dB	1
Conducted emission CISPR 16 Clic CISPR 16	PE001_05	3,0 dB	1
Radiated Emission CDNE 30-300 MHz	PE001_06	3,3 dB	1
Disturbance Power 30-300 MHz	PE002_X1	3,8 dB	1
Radiated Emission LAS 0,15-30 MHz	PE003_01	2,0 dB	1
Radiated Emission CISPR 16 Loop Ant. 0,15-30 MHz	PE004_X1	4,1 dB	1
Radiated Emission CISPR 16 Bicon. Ant. 30-300 MHz	PE004_X2	4,7 dB	1
Radiated Emission CISPR 16 LogP. Ant. 300-1000 MHz	PE004_X3	4,6 dB	1
Radiated Emission CISPR 16 Horn Ant. 1-18 GHz	PE004_X4	4,7 dB	1
Human Exposure to electromagnetic fields	PE005_01	16,2 %	1
Harmonics	PE006_01	10 mA + 2,9 %	1
Flicker	PE007_01	3,40 %	1
Radiated Immunity 80 MHz - 6 GHz	PE102_XX	2,43 dB 0,97 V/m a 3V/m	1
Conducted Immunity 0,15 - 230 MHz	PE105_XX	1,26 dB 0,47 V a 3V	1
AC Magnetic field	PE106_01	1,55 % 0,15 A/m a 10A/m	1
Pulse Magnetic field	PE107_01	6,21 % 18,6 A/m a 300A/m	1
Dumped Magnetic field	PE108_01	6,21 % 1,86 A/m a 30A/m	1
Common mode conducted immunity	PE112_01	2,11 % 0,21 V a 10V	1

Test	Test Setup	Expanded uncertainty	Note
Power/Spurious 9kHz-30MHz	PR001_X1	4,1 dB	1
Power/Spurious ERP 30-1000MHz d=10m/3m	PR001_X2+X3	4,8 dB	1
Misura della potenza EIRP 1-18GHz d=3m	PR001_X4+X5	4,7 dB	1
Misura della potenza EIRP 18-40GHz d=3m	PR001_X6	5,1 dB	1
Frequency error	PR002_01+02	$< 1 \times 10^{-7}$	1
Timing zero span (1001pts.)	PR002_01+02	0,2 % SWT	1
Modulation bandwidth	PR002_01+02	$< 1 \times 10^{-7}$	1
Conducted RF power and spurious emission	PR002_01+02	1,1 dB	1
Adjacent channel power	PR002_01+02	1,1 dB	1
Blocking	PR002_01+02	1,1 dB	1

Test	Test Setup	Expanded uncertainty	Note
Electrostatic discharge immunity test	PE101_0X		2
Electrical fast transients / burst immunity test	PE103_0X		2
Surge immunity test	PE104_0X		2
Short interruption immunity test	PE109_01		2
Ring Wave immunity test	PE110_01		2
Low frequency immunity test	PE111_01		2
Dumped Oscillatory immunity test	PE113_01		2
Rev_25_02 date 21/10/2025			




Note 1:

The expanded uncertainty reported according to the document EA-4-02 is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of $p = 95\%$

Note 2:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence, covering factor $k=2$

Judgement of compliance

Case 1	Case 2	Case 3	Case 4
 The sample complies with the requirements. The measurement results is within the specification limit when the measurement uncertainty is taken into account.	 The sample complies with the requirements. It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is below the limit.	 The sample does not comply with the requirements. It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty also the measurement result is upper the limit.	 The sample does not comply with the requirements. The measurement results is outside the specification limit when the measurement uncertainty is taken into account.

In agreement with ILAC-G8:09/2019 cl.4.2.1 Guidelines on Decision Rules and Statements of Conformity

Quality manual references – Internal procedure

Internal Procedure PM001 rev. 4.1 (Quality Manual)	Measure procedure
Internal Procedure INC_M rev. 10.1 (Quality Manual)	Measurement uncertainty calculation