LTA
Laboratory for Test & Approval Co.,Ltd.
243 Jubug-Ri,Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
Tel: +82-31-323-6008 Fax: +82-31-323-6010
http://www.ltalab.com

KMW

Dates of Tests: April 10 ~ April 28, 2017
Test Report S/N: LR500111705L
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID. **ORIINTNODEHPV03**

APPLICANT **KMW Inc**

Equipment Class	:	**Digital Transmission System (DTS)**
Manufacturing Description	:	**Zigbee module**
Manufacturer	:	**KMW Inc**
Model name	:	**INT NODE HP V0.3**
Test Device Serial No.:	:	**Identical prototype**
Rule Part(s)	:	**FCC Part 15.247 Subpart C ; ANSI C-63.4-2014**
Frequency Range	:	**2405 MHz ~ 2480 MHz**
Max. Output Power	:	**Max 21.53 dBm – Conducted**
Data of issue	:	**May 22, 2017**

This test report is issued under the authority of:

Yong-Cheol, Wang / Manager

The test was supervised by:

Jung-won, Seo / Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP

NVLAP LAB Code.: 200723-0

Copyright © 2017, LTA Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION ---------- 3

2. INFORMATION ABOUT TEST ITEM ---------- 4

3. TEST REPORT ---------- 6

3.1 SUMMARY OF TESTS ---------- 6

3.2 TECHNICAL CHARACTERISTICS TEST ---------- 7

3.2.1 6 dB BANDWIDTH ---------- 7

3.2.2 PEAK OUTPUT POWER ---------- 10

3.2.3 POWER SPECTRAL DENSITY ---------- 13

3.2.4 BAND EDGE ---------- 16

3.2.5 CONDUCTED SPURIOUS EMISSIONS ---------- 19

3.2.6 RADIATED SPURIOUS EMISSIONS ---------- 22

3.2.7 AC CONDUCTED EMISSIONS ---------- 37

APPENDIX

APPENDIX TEST EQUIPMENT USED FOR TESTS ---------- 44

Copyright © 2017, LTA Co., Ltd.

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
Address : 243, Jubug-ri,Yangji-Myeon,Youngin-Si, Kyunggi-Do, Korea. 449-822
Web site : http://www.ltalab.com
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2017-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	R2133(10 m), C2307	2017-06-21	VCCI registration
VCCI	JAPAN	T-2009	2017-12-23	VCCI registration
VCCI	JAPAN	G-563	2018-12-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	UPDATING	KOLAS accredited Lab.

Copyright © 2017, LTA Co., Ltd.

2. Information about test item

2-1 Client & Manufacturer

Company name	:	KMW Inc
Address	:	183-6, Yeongcheon-ro, Dongtan-myeon, Hwaseong-si, Gyeonggi-do, Republic of Korea
Tel / Fax	:	TEL No : +82-31-370-8600 / FAX No : +82-31-370-2898

2-2 Manufacturers

Company name	:	KMW Inc
Address 1	:	1942, Wireseong-ro, Ipjang-myeon, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea
Address 2	:	3, Dongtansandan 6-gil Dongtan-myeon, Hwaseong-si, Gyeonggi-do, Korea
Company name	:	KMW VIETNAM CO.,LTD
Address	:	Lot C, Dong Van I Industrial Zone, Yen Bac Commune, Duy Tien District, Ha Nam Province, Viet Nam
Company name	:	SEOJIN SYSTEM VINA
Address	:	Lo23, Duong TS5, KCN Tien Son,P.Dong Nguyen, TX, Tu Son,T. VacNinhm Vietnam

2-3 Equipment Under Test (EUT)

Trade name	:	KMW Inc
Model name	:	INT NODE HP V0.3
Serial number	:	Identical prototype
Date of receipt	:	March 29, 2017
EUT condition	:	Pre-production, not damaged
Antenna type	:	IFA antenna - Max Gain 2.13 dBi
Frequency Range	:	2405 MHz ~ 2480 MHz
RF output power	:	Max 21.53 dBm – Conducted
Number of channels	:	16
Type of Modulation	:	Direct Sequence Spread Spectrum(DSSS)
Power Source	:	15 Vdc
Firmware Version	:	V1.0.0

Copyright © 2017, LTA Co., Ltd.

2-3 Tested frequency

Zigbee	LOW	MID	HIGH
Frequency (MHz)	2405	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	CR720	MS-1736	MSI

Copyright © 2017, LTA Co., Ltd.

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1 Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

→ Antenna Requirement
The KMW Inc FCC ID: ORIINTNODEHPV03 unit complies with the requirement of §15.203.
The antenna type is IFA Antenna

The sample was tested according to the following specification:
*FCC Parts 15.247; ANSI C-63.4-2014
*FCC KDB Publication No. 558074 v03r05
*FCC TCB Workshop 2012, April

Copyright © 2017, LTA Co., Ltd.

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 5 MHz

VBW = 100 kHz (VBW ≥ RBW)

Sweep = auto

Trace = max hold

Detector function = peak

Measurement Data : Complies

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	**1.570**	Complies
2440	**1.563**	Complies
2480	**1.570**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth > 500 kHz

Measurement Setup



Figure 1: Measurement setup for the carrier frequency separation

Low Channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.404754 GHz	16.56 dBm	ndB down	1.5702 MHz
T1		1	2.4042258 GHz	10.80 dBm	ndB	6.00 dB
T2		1	2.4057959 GHz	10.45 dBm	Q factor	1531.5

Middle Channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.439754 GHz	16.20 dBm	ndB down	1.563 MHz
T1		1	2.4392258 GHz	10.35 dBm	ndB	6.00 dB
T2		1	2.4407887 GHz	10.35 dBm	Q factor	1561.0

High Channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4797467 GHz	15.36 dBm	ndB down	1.5702 MHz
T1		1	2.4792185 GHz	9.30 dBm	ndB	6.00 dB
T2		1	2.4807887 GHz	9.47 dBm	Q factor	1579.3

3.2.2 Peak Output Power Measurement

Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1MHz Span = auto

VBW = 1MHz (VBW ≥ RBW) Sweep = auto

Detector function = peak

Measurement Data (Port 1) : Complies

Frequency (MHz)	Test Results		
	dBm	W	Result
2405	**21.53**	**0.142**	Complies
2440	**21.13**	**0.129**	Complies
2480	**20.28**	**0.106**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

Peak output power	< 1 W

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2017, LTA Co., Ltd.

Low Channel



Middle Channel



Copyright © 2017, LTA Co., Ltd.

High Channel



3.2.3 Power Spectral Density

Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz	Span = 300 kHz
VBW = 3 kHz	Sweep = auto
Detector function = peak	Trace = max hold

Measurement Data (Port 1) : Complies

Frequency (MHz)	Test Results	
	dBm @ 3kHz	Result
2405	**4.30**	Complies
2440	**7.51**	Complies
2480	**6.21**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

Power Spectral Density	< 8 dBm @ 3 kHz BW

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2017, LTA Co., Ltd.

Power Density Measurement

Low Channel



Middle Channel



Copyright © 2017, LTA Co., Ltd.

High Channel



3.2.4 Band - edge

Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz	VBW = 100 kHz
Span = 40 MHz	Detector function = peak
Trace = max hold	Sweep = auto

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK:	RBW = VBW = 1 MHz, Sweep=Auto
Average:	RBW = 1 MHz, VBW=10 Hz, Sweep=Auto
Measurement Distance:	3 m
Polarization:	Horizontal / Vertical

Measurement Data: Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the require ment.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc

Copyright © 2017, LTA Co., Ltd.

Band edge

Lower edge



Upper edge



Copyright © 2017, LTA Co., Ltd.

Radiated Band-edges in the restricted band 2310-2390 MHz measurement

Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor		Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
				Antenna	Amp. Gain + Cable Loss						
2389.6	33.4	45.9	V	27.86	22.92	54.0	74.0	38.34	50.84	15.66	23.16

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor		Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
				Antenna	Amp. Gain + Cable Loss						
2483.9	45.9	60.4	V	27.86	22.92	54.0	74.0	50.84	65.38	3.16	8.62

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented

Copyright © 2017, LTA Co., Ltd.

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz Detector function = peak

Trace = max hold

Measurement Data: **Complies**

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the require ment.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Unwanted Emission – Low Channel

Frequency Range = 30 MHz ~ 26.5 GHz



Middle Channel



Copyright © 2017, LTA Co., Ltd.

High Channel



3.2.6 Radiated Spurious Emissions

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 100 kHz (30 MHz ~ 1 GHz) VBW ≥ RBW

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz Detector function = peak

Trace = max hold Sweep = auto

below 30 MHz



below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: **Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) **(@ 300 m)**
0.490 ~ 1.705	24000/F(kHz) **(@ 30 m)**
1.705 ~ 30	30**(@ 30 m)**
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-80 6 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Copyright © 2017, LTA Co., Ltd.

Measurement Data : (Above 1 GHz)

Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor		Limits [dBuV/m] AV/Peak		Result [dBuV/m] AV/Peak		Margin [dB] AV / Peak	
				Antenna	Amp.Gain+Cable						
8486.8	19.6	33.1	V	37.64	15.29	54.0	74.0	42.0	55.5	12.1	18.6
8575.5	16.8	33.0	V	37.64	15.29	54.0	74.0	39.2	55.4	14.9	18.7
8633.7	19.6	35.4	V	37.64	15.29	54.0	74.0	42.0	57.8	12.1	16.3

- No other emissions were detected at a level greater than 20 dB below limit.

Measurement Data: (9 kHz – 30 MHz)

Frequency [MHz]	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna +Cable-Amp.Gain	Limits [dBuV/m] Peak	Result [dBuV/m] Peak	Margin [dB] Peak
41.64	52.36	V	-18.05	40	34.31	5.69
41.64	51.21	V	-18.02	40	33.19	6.81
41.64	50.57	V	-18.02	40	32.55	7.45
71.71	50.05	H	-19.82	40	30.23	9.77
71.71	50.31	H	-19.82	40	30.49	9.51
71.71	48.29	H	-19.82	40	28.47	11.53

*No emissions were detected at a level greater than 20 dB below limit.

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4 GHz Zigbee(Low) mode, Vertical

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: INT NODE HP V0.3 Temp/Humi: 21 / 41

Test Mode : Wireless mode (LOW) Tested by: LEE H W

Data: 1254 File: C:\Program Files (x86)\e3\e3.EM6 (1258)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
41.64	52.36	-18.02	34.34	40.00	5.66	128	293	VERTICAL
71.71	45.04	-19.82	25.22	40.00	14.78	185	332	VERTICAL
117.30	50.76	-19.52	31.24	43.50	12.26	325	161	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(Middle) mode, Vertical

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: INT NODE HP V0.3 Temp/Humi: 21 / 41

Test Mode : Wireless mode (MID) Tested by: LEE H W

Data: 1256 File: C:\Program Files (x86)\e3\e3.EM6 (1258)



Freq	Reading	C.F	Result QP	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
41.64	51.21	-18.02	33.19	40.00	6.81	160	242	VERTICAL
71.71	48.66	-19.82	28.84	40.00	11.16	185	261	VERTICAL
118.27	49.15	-19.43	29.72	43.50	13.78	142	92	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(High) mode, Vertical

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: INT NODE HP V0.3 Temp/Humi: 21 / 41

Test Mode : Wireless mode (HIGH) Tested by: LEE H W

Data: 1258 File: C:\Program Files (x86)\e3\e3.EM6 (1258)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
41.64	50.57	-18.02	32.55	40.00	7.45	195	238	VERTICAL
44.55	49.91	-17.69	32.22	40.00	7.78	168	117	VERTICAL
71.71	48.37	-19.82	28.55	40.00	11.45	320	17	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4 GHz Zigbee(Low) mode, Horizental

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: INT NODE HP V0.3 Temp/Humi: 21 / 41

Test Mode : Wireless mode (LOW) Tested by: LEE H W

Data: 1253 File: C:\Program Files (x86)\e3\e3.EM6 (1258)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
69.77	46.77	-19.43	27.34	40.00	12.66	121	51	HORIZONTAL
71.71	50.05	-19.82	30.23	40.00	9.77	169	301	HORIZONTAL
338.46	45.35	-14.60	30.75	46.00	15.25	225	295	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(Middle) mode, Horizental

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: INT NODE HP V0.3 Temp/Humi: 21 / 41

Test Mode : Wireless mode (MID) Tested by: LEE H W

Data: 1255 File: C:\Program Files (x86)\e3\e3.EM6 (1258)



Freq	Reading	C.F	Result QP	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
71.71	50.31	-19.82	30.49	40.00	9.51	195	231	HORIZONTAL
146.40	47.30	-16.92	30.38	43.50	13.12	210	182	HORIZONTAL
256.01	43.28	-17.21	26.07	46.00	19.93	281	189	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(High) mode, Horizental

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: INT NODE HP V0.3 Temp/Humi: 21 / 41

Test Mode : Wireless mode (HIGH) Tested by: LEE H W

Data: 1257 File: C:\Program Files (x86)\e3\e3.EM6 (1258)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
71.71	48.29	-19.82	28.47	40.00	11.53	305	24	HORIZONTAL
146.40	42.06	-16.92	25.14	43.50	18.36	128	192	HORIZONTAL
256.01	45.10	-17.21	27.89	46.00	18.11	222	328	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Above 1 GHz) – 2.4 GHz Zigbee(Low) mode

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: INT NODE HP V0.3 Test Mode: Wireless mode (LOW)

Tested by : LEE H W Temp/Humi: 20 / 38



	Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
1	8486.80	33.10	22.35	55.45	74.00	18.55	VERTICAL
2	8486.80	19.60	22.35	41.95	54.00	12.05	VERTICAL
3	8908.60	31.80	24.92	56.72	74.00	17.28	VERTICAL
4	8908.60	17.80	24.92	42.72	54.00	11.28	VERTICAL
5	8948.80	30.80	25.18	55.98	74.00	18.02	VERTICAL
6	8948.80	16.40	25.18	41.58	54.00	12.42	VERTICAL
7	9098.80	30.40	25.48	55.88	74.00	18.12	VERTICAL
8	9098.80	15.70	25.48	41.18	54.00	12.82	VERTICAL
9	9167.50	17.20	25.46	42.66	54.00	11.34	HORIZONTAL
10	9167.50	31.10	25.46	56.56	74.00	17.44	HORIZONTAL
11	13855.60	21.50	34.84	56.34	74.00	17.66	HORIZONTAL
12	13855.60	7.30	34.84	42.14	54.00	11.86	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: INT NODE HP V0.3 Test Mode: Wireless mode (LOW)

Tested by : LEE H W Temp/Humi: 20 / 38



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
118089.10	17.80	45.36	63.16	74.00	10.84	HORIZONTAL
218089.10	1.50	45.36	46.86	54.00	7.14	HORIZONTAL
318171.00	2.60	45.23	47.83	54.00	6.17	HORIZONTAL
418171.00	18.00	45.23	63.23	74.00	10.77	HORIZONTAL
518267.20	18.60	45.09	63.69	74.00	10.31	HORIZONTAL
618267.20	2.10	45.09	47.19	54.00	6.81	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Above 1 GHz) – 2.4 GHz Zigbee(Middle) mode

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: INT NODE HP V0.3 Test Mode: Wireless mode (MID)

Tested by : LEE H W Temp/Humi: 20 / 38



	Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
1	8575.50	16.80	22.78	39.58	54.00	14.42	HORIZONTAL
2	8575.50	33.00	22.78	55.78	74.00	18.22	HORIZONTAL
3	8638.80	17.20	23.19	40.39	54.00	13.61	HORIZONTAL
4	8638.80	32.60	23.19	55.79	74.00	18.21	HORIZONTAL
5	9499.80	29.60	25.37	54.97	74.00	19.03	HORIZONTAL
6	9499.80	14.90	25.37	40.27	54.00	13.73	HORIZONTAL
7	9685.70	29.90	25.58	55.48	74.00	18.52	VERTICAL
8	9685.70	14.50	25.58	40.08	54.00	13.92	VERTICAL
	912275.50	26.40	28.87	55.27	74.00	18.73	HORIZONTAL
	1012275.50	11.70	28.87	40.57	54.00	13.43	HORIZONTAL
	1112808.30	24.80	30.78	55.58	74.00	18.42	VERTICAL
	1212808.30	10.20	30.78	40.98	54.00	13.02	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: INT NODE HP V0.3 Test Mode: Wireless mode (MID)

Tested by : LEE H W Temp/Humi: 20 / 38



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
118113.60	2.10	45.32	47.42	54.00	6.58	VERTICAL
218113.60	18.60	45.32	63.92	74.00	10.08	VERTICAL
318135.60	16.80	45.29	62.09	74.00	11.91	HORIZONTAL
418135.60	1.80	45.29	47.09	54.00	6.91	HORIZONTAL
518307.50	16.80	45.03	61.83	74.00	12.17	VERTICAL
618307.50	1.50	45.03	46.53	54.00	7.47	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Above 1 GHz) – 2.4 GHz Zigbee(High) mode

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: INT NODE HP V0.3 Test Mode: Wireless mode (HIGH)

Tested by : LEE H W Temp/Humi: 20 / 38



	Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
1	7867.80	32.80	24.57	57.37	74.00	16.63	HORIZONTAL
2	7867.80	17.20	24.57	41.77	54.00	12.23	HORIZONTAL
3	8088.60	16.80	23.72	40.52	54.00	13.48	HORIZONTAL
4	8088.60	32.90	23.72	56.62	74.00	17.38	HORIZONTAL
5	8633.70	35.40	23.16	58.56	74.00	15.44	VERTICAL
6	8633.70	19.60	23.16	42.76	54.00	11.24	VERTICAL
7	8729.50	16.80	23.77	40.57	54.00	13.43	HORIZONTAL
8	8729.50	34.50	23.77	58.27	74.00	15.73	HORIZONTAL
9	8928.10	31.40	25.05	56.45	74.00	17.55	VERTICAL
10	8928.10	16.70	25.05	41.75	54.00	12.25	VERTICAL
11	9167.50	30.80	25.46	56.26	74.00	17.74	VERTICAL
12	9167.50	15.90	25.46	41.36	54.00	12.64	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

Copyright © 2017, LTA Co., Ltd.

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: INT NODE HP V0.3 Test Mode: Wireless mode (HIGH)

Tested by : LEE H W Temp/Humi: 20 / 38



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
118193.20	15.90	45.20	61.10	74.00	12.90	HORIZONTAL
218193.20	2.80	45.20	48.00	54.00	6.00	HORIZONTAL
318216.60	2.90	45.17	48.07	54.00	5.93	VERTICAL
418216.60	16.80	45.17	61.97	74.00	12.03	VERTICAL
518301.60	2.40	45.04	47.44	54.00	6.56	HORIZONTAL
618301.60	15.70	45.04	60.74	74.00	13.26	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

3.2.6 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 20 dB below limit.

Minimum Standard: FCC Part 15.207(a)

Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Copyright © 2017, LTA Co., Ltd.

Conducted Emissions – 2.4 GHz Zigbee(LOW) mode + LINE

LTA
Laboratory for Test & Approval Co.,Ltd.

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: INT NODE HP V0.3	Phase	: LINE
Test Mode	: Wireless mode (LOW)	Test Power	: 120 / 60
Temp. / Humi.	: 21 / 39	Test Engineer	: LEE H W

Data: 3125 File: D:\Conducted Data\2017\LTA_Conduction_2017_03.EM6 (3234)



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.503	34.31	24.46	10.13	44.44	34.59	56.00	46.00	11.56	11.41
0.519	34.63	26.09	10.13	44.76	36.22	56.00	46.00	11.24	9.78
0.523	34.02	26.34	10.13	44.15	36.47	56.00	46.00	11.85	9.53
0.532	34.68	27.44	10.13	44.81	37.57	56.00	46.00	11.19	8.43
0.535	34.82	27.64	10.13	44.95	37.77	56.00	46.00	11.05	8.23
0.544	34.33	26.26	10.13	44.46	36.39	56.00	46.00	11.54	9.61

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Copyright © 2017, LTA Co., Ltd.

Conducted Emissions – 2.4 GHz Zigbee(LOW) mode + NEUTRAL

LTA
Laboratory for Test & Approval Co.,Ltd.

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: INT NODE HP V0.3	Phase	: NEUTRAL
Test Mode	: Wireless mode (LOW)	Test Power	: 120 / 60
Temp. / Humi.	: 21 / 39	Test Engineer	: LEE H W

Data: 3129 File: D:\Conducted Data\2017\LTA_Conduction_2017_03.EM6 (3234)



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.500	34.07	24.73	10.20	44.27	34.93	56.00	46.00	11.73	11.07
0.502	34.34	25.01	10.20	44.54	35.21	56.00	46.00	11.46	10.79
0.516	34.62	25.86	10.20	44.82	36.06	56.00	46.00	11.18	9.94
0.530	34.69	26.85	10.20	44.89	37.05	56.00	46.00	11.11	8.95
0.537	34.85	27.28	10.20	45.05	37.48	56.00	46.00	10.95	8.52
0.541	34.89	27.34	10.20	45.09	37.54	56.00	46.00	10.91	8.46

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

- 1 -

Copyright © 2017, LTA Co., Ltd.

Conducted Emissions – 2.4 GHz Zigbee(Middle) mode + LINE

LTA
Laboratory for Test & Approval Co.,Ltd.

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: INT NODE HP V0.3	Phase	: LINE
Test Mode	: Wireless mode (MID)	Test Power	: 120 / 60
Temp. / Humi.	: 21 / 39	Test Engineer	: LEE H W

Data: 3133 File: D:\Conducted Data\2017\LTA_Conduction_2017_03.EM6 (3234)



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.500	33.96	24.52	10.13	44.09	34.65	56.00	46.00	11.91	11.35
0.513	33.93	25.89	10.13	44.06	36.02	56.00	46.00	11.94	9.98
0.532	34.46	26.82	10.13	44.59	36.95	56.00	46.00	11.41	9.05
0.535	34.81	27.11	10.13	44.94	37.24	56.00	46.00	11.06	8.76
0.544	34.27	25.88	10.13	44.40	36.01	56.00	46.00	11.60	9.99
0.550	32.61	23.91	10.13	42.74	34.04	56.00	46.00	13.26	11.96

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Copyright © 2017, LTA Co., Ltd.

Conducted Emissions – 2.4 GHz Zigbee(Middle) mode + NEUTRAL

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: INT NODE HP V0.3	Phase	: NEUTRAL
Test Mode	: Wireless mode (MID)	Test Power	: 120 / 60
Temp. / Humi.	: 21 / 39	Test Engineer	: LEE H W

Data: 3137 File: D:\Conducted Data\2017\LTA_Conduction_2017_03.EM6 (3234)



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.504	34.23	25.33	10.20	44.43	35.53	56.00	46.00	11.57	10.47
0.515	34.26	26.15	10.20	44.46	36.35	56.00	46.00	11.54	9.65
0.520	34.68	26.56	10.20	44.88	36.76	56.00	46.00	11.12	9.24
0.521	34.84	26.17	10.20	45.04	36.37	56.00	46.00	10.96	9.63
0.533	34.93	27.08	10.20	45.13	37.28	56.00	46.00	10.87	8.72
0.547	33.47	25.04	10.20	43.67	35.24	56.00	46.00	12.33	10.76

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

- 1 -

Copyright © 2017, LTA Co., Ltd.

Conducted Emissions – 2.4 GHz Zigbee(High) mode + LINE

LTA
Laboratory for Test & Approval Co.,Ltd.

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: INT NODE HP V0.3	Phase	: LINE
Test Mode	: Wireless mode (HIGH)	Test Power	: 120 / 60
Temp. / Humi.	: 21 / 39	Test Engineer	: LEE H W

Data: 3145 File: D:\Conducted Data\2017\LTA_Conduction_2017_03.EM6 (3234)



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.502	34.26	24.45	10.13	44.39	34.58	56.00	46.00	11.61	11.42
0.518	34.34	26.54	10.13	44.47	36.67	56.00	46.00	11.53	9.33
0.521	34.64	26.55	10.13	44.77	36.68	56.00	46.00	11.23	9.32
0.531	34.65	26.89	10.13	44.78	37.02	56.00	46.00	11.22	8.98
0.533	34.88	27.46	10.13	45.01	37.59	56.00	46.00	10.99	8.41
0.541	34.77	26.51	10.13	44.90	36.64	56.00	46.00	11.10	9.36

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

- 1 -

Copyright © 2017, LTA Co., Ltd.

Conducted Emissions – 2.4 GHz Zigbee(High) mode + NEUTRAL

LTA
Laboratory for Test & Approval Co.,Ltd.

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: INT NODE HP V0.3	Phase	: NEUTRAL
Test Mode	: Wireless mode (HIGH)	Test Power	: 120 / 60
Temp. / Humi.	: 21 / 39	Test Engineer	: LEE H W

Data: 3141 File: D:\Conducted Data\2017\LTA_Conduction_2017_03.EM6 (3234)



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.494	31.65	22.81	10.20	41.85	33.01	56.10	46.10	14.25	13.09
0.502	34.28	24.89	10.20	44.48	35.09	56.00	46.00	11.52	10.91
0.510	33.90	25.63	10.20	44.10	35.83	56.00	46.00	11.90	10.17
0.520	35.03	26.15	10.20	45.23	36.35	56.00	46.00	10.77	9.65
0.536	34.86	27.20	10.20	45.06	37.40	56.00	46.00	10.94	8.60
0.541	34.79	27.00	10.20	44.99	37.20	56.00	46.00	11.01	8.80

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Copyright © 2017, LTA Co., Ltd.

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2016-10-11
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2017-03-20
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2017-03-20
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2016-09-12
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2016-09-12
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2016-09-12
7	■	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2016-09-12
8	■	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2017-03-21
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2016-08-04
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2016-05-03
11	■	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2016-05-03
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2015-07-13
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2017-03-21
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15		Power Divider	11636A	06243	HP	1 year	2016-09-12
16	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
17		Frequency Counter	5342A	2826A12411	HP	1 year	2017-03-21
18	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2017-03-20
19	■	Power Sensor	8481A	3318A94972	HP	1 year	2016-12-30
20		Audio Analyzer	8903B	3729A18901	HP	1 year	2016-09-12
21		Modulation Analyzer	8901B	3749A05878	HP	1 year	2016-09-12
22		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2016-09-12
23		Stop Watch	HS-3	812Q08R	CASIO	2 year	2017-03-21
24		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2016-09-12
25		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2017-03-20
26		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2017-03-20
27		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2017-03-20
28		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2017-03-20
29	■	Active Loop Antenna	FMZB1519	1519-031	SCHWARZBECK	2 year	2016-01-12
30		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2017-03-21
31		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2017-03-23
32		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2017-03-21

Copyright © 2017, LTA Co., Ltd.