

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 1 of 8

APPLICANT: (CODE : GRI004)

GREATRICH INDUSTRIAL LTD.
ROOM 278, SINO INDUSTRIAL PLAZA,
9 KAI CHEUNG ROAD,
KOWLOON BAY, KOWLOON, HONG KONG.

DATE OF SAMPLES RECEIVED:

1999-09-20

TEST DURATION

1999-09-21 TO 1999-10-09

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: Receiver Unit for Parking Alert
Manufacturer: GREATRICH INDUSTRIAL LTD.
Model Number: 0589-2
Brand Name: Brookstone
Rating: 3Vd.c. ("AA" size battery × 2)
Origin: China

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B - Unintentional Radiator and Subpart C - Intentional Radiator.

RESULT/ REMARK:

Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the clause 15.231 for the Transmitter Section of Federal Communications Commission Rules. Clause 15.231 (1),(2) & (3) and clause 15.109(9) for the Receiver Section of Part 15 and ANSI C63.4-1992 Section 12.1.1.1-2.

TEST EQUIPMENT AUDIT:

Please see Appendix A

Testing Engineer

Verify by

Patrick Wong
for Managing Director

Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations. 6. Applicants wishing to use the Report in court proceedings or

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 2 of 8

TEST SUMMARY

- (1) Measurement of Emission of RF energy on the carrier frequency.....Satisfactory
Measurement of Field strength of supurious emissions..... Satisfactory
- (2) Measurement of Emission Within Band Edges.....Satisfactory
- (3) Measurement of Radiated Emissions..... Satisfactory
- (4) Measurement of Line-Conducted Voltage onto AC Power Line..... Not applicable
- (5) FCC rule clause 15.231 (1),(2) and (3) subpart C-Intentional-radiator..... Satisfactory

TEST DATA

Please refer to the attached result sheets.

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 3 of 8

*** INTENTIONAL RADIATOR ***

(1) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart Section 15.231(433.6 MHz)

TEST CONDITION : Normal

TEST DATE : 1999.10.09

Emission of RF energy on the carrier frequency -- 433.6 MHz (PEAK VALUE)

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)		FCC Limit
MHz	dB(μV)	H-V	dB	dB(μV/m)	μV/m	μV/m
433.6	59.2	H +	19.5	78.7	8609.9	109647

Emission of RF energy on the carrier frequency -- 433.6 MHz (AVERAGE VALUE)

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)		FCC Limit
MHz	dB(μV)	H-V	dB	dB(μV/m)	μV/m	μV/m
433.6	30.8	H +	19.5	50.3	327.3	10965

... to be continued

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 4 of 8

*** INTENTIONAL RADIATOR ***

(1) Measurement of Radiated Interference ... Continued ..

TEST REFERENCE: FCC Rules Part 15 Section 15.231(433.6 MHz)

TEST CONDITION : Normal

TEST DATE : 1999.10.09

Field strength of spurious emissions (PEAK VALUE)

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)		FCC Limit
MHz	dB(μV)	H-V	dB	dB(μV/m)	μV/m	μV/m
867.2	28.7	V +	27.7	56.4	660.7	10965
*1300.8	26.4	H +	32.1	58.5	841.4	5000
1734.4	< 1.0	+	26.2	<27.2	< 22.9	10965
2168.0	< 1.0	+	28.0	<29.0	< 28.2	10965
2601.6	< 1.0	+	28.5	<29.5	< 29.9	10965
3035.2	< 1.0	+	30.6	<31.6	< 38.0	10965
3468.8	< 1.0	+	32.0	<33.0	< 44.7	10965
*3902.4	< 1.0	+	33.2	<34.2	< 51.2	5000
*4336.0	< 1.0	+	33.3	<34.3	< 51.9	5000

Remark : * - Denotes restricted band of operation.

Measurement were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 were not adjusted for averaging and the limit of FCC Rules Part 15 Section 15.209 were applied

=====SUMMARY=====

data is within limits

=====

Broad-band Antennas were used and both polarizations of emissions were measured.

polarizations at highest reading indicated as:

H -- Horizontal

V -- Vertical

=====

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 5 of 8

*** INTENTIONAL RADIATOR ***

(1) Measurement of Radiated Interference . . Continued ..

TEST REFERENCE: FCC Rules Part 15 Section 15.231(433.6 MHz)

TEST CONDITION : Normal

TEST DATE : 1999.10.09

Field strength of spurious emissions (AVERAGE VALUE)

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)		FCC Limit
MHz	dB(μV)	H-V	dB	dB(μV/m)	μV/m	μV/m
867.2	11.4	V +	27.7	39.1	90.15	1097
*1300.8	8.0	H +	32.1	40.1	101.2	500
1734.4	< 1.0	+ +	26.2	< 27.2	< 22.9	1097
2168.0	< 1.0	+ +	28.0	< 29.0	< 28.2	1097
2601.6	< 1.0	+ +	28.5	< 29.5	< 29.9	1097
3035.2	< 1.0	+ +	30.6	< 31.6	< 38.0	1097
3468.8	< 1.0	+ +	32.0	< 33.0	< 44.7	1097
*3902.4	< 1.0	+ +	33.2	< 34.2	< 51.2	500
*4336.0	< 1.0	+ +	33.3	< 34.3	< 51.9	500

Remark : * - Denotes restricted band of operation.

Measurement were made using a peak detector. Any emission less than 1000 Mhz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 were not adjusted for averaging and the limit of FCC Rules Part 15 Section 15.209 were applied

=====SUMMARY=====

data is within limits

=====

Broad-band Antennas were used and both polarizations of emissions were measured.

polarizations at highest reading indicated as:

H -- Horizontal

V -- Vertical

=====

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 6 of 8

*** INTENTIONAL RADIATOR ***

(2) Measurement of Emissions Within Band Edges.

TEST REFERENCE: FCC Rules Part 15 section 15.231(433.6 MHz)
TEST CONDITION: Normal
TEST DATE : 1999.10.09

Please see exhibit report of bandwidth

RESULTS AND NOTES

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz . The bandwidth is determined at the points 20dB down from the modulated carrier.

@433.6 MHz

$433.6 \text{ MHz} \times 0.0025 = 1.084 \text{ MHz}$

$1.084 \text{ MHz} / 2 = 542.0 \text{ KHz}$

The bandwidth at 20dB down is 7.6 kHz which is within the allowable limit of 542KHz at 433.6MHz.

SPECTRUM ANALYZER SETTINGS

Resolution bandwidth : 1.0KHz

Frequency span : 10.0KHz/div

No. of dB/div : 10.0dB/div

=====SUMMARY=====

All data is within limits

=====

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 7 of 8

*** RECEIVER SECTION ***

(3) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109(a)

TEST CONDITION : Normal

TEST DATE : 1999.10.09.

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)	FCC Limit
MHz	dB(μV)	H-V	dB	dB(μV/m) μV/m	μV/m
433.6	19.9	H	+	19.5	39.4 93.3 200
867.2	< 1.0		+	28.5	<29.5 < 29.9 200
1300.8	< 1.0		+	25.8	<26.8 < 21.8 500
1734.4	< 1.0		+	26.2	<27.2 < 22.9 500
2168.0	< 1.0		+	28.0	<29.0 < 28.2 500
2601.6	< 1.0		+	28.5	<29.5 < 29.9 500
3035.2	< 1.0		+	30.6	<31.6 < 38.0 500
3468.8	< 1.0		+	32.0	<33.0 < 44.7 500
3902.4	< 1.0		+	33.2	<34.2 < 51.2 500
4336.0	< 1.0		+	33.3	<34.3 < 51.9 500

=====SUMMARY=====

data is within limits

=====

Broad-band Antennas were used and both polarizations of emissions were measured.
polarizations at highest reading indicated as:

H -- Horizontal V -- Vertical

=====

Date: 1999-10-13
No.: HM101552

TEST REPORT

Page 8 of 8

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC rules.

(2) Distance between the EUT and measuring antenna:

3 meters.

(3) Measuring instrumentations:

CISPR Quasi-peak type field strength meter (25 MHz - 1000 MHz and 1GHz-18GHz). 6 dB bandwidth set at 120KHz. Also, peak level of the fundamental emissions was measured in order to determine compliance with the 20dB peak to average limit specified in Section 15.231 of the FCC new Rules.

(4) Measuring antenna:

Broad band antenna for the frequency range 25-1000 MHz, connected with 10 meters coaxial cable. Horn antenna for the frequency range 1-18 GHz, connected with high frequency coaxial cable. Cable loss of the coaxial cable. included in the Antenna Factor for measurement data. The antenna are capable of measuring both horizontal and vertical polarizations.

(5) Frequency range scanned:

The frequency range from 25 MHz to 1000 MHz and 1GHz to 18GHz had been searched. Readings of the highest emissions relating to the limit were reported as above.

(6) Arrangement of EUT:

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.

(7) Measuring Procedure:

In accordance with the relevant clauses of the FCC Rules Part 15 section 15.231.

In accordance with the relevant clauses of FCC Rules Part Section 15.109(a) and ANSI C63.4:1992 Section 12.1.1.1.2.

(8) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-

30MHz to 300MHz = $\pm 3.7\text{dB}$, 300MHz to 1000MHz = $\pm 3.0\text{dB}/-2.7\text{dB}$.

1GHz to 18GHz = $\pm 3.3\text{dB}/-3.4\text{dB}$.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

*****End of Document*****