

Issuing Laboratory:

Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



## TEST REPORT

Report No.: 14110667HKG-001

**Kidztech Toys Manufacturing Ltd.**

Application  
For  
Certification  
(Original Grant)  
**(FCC ID: OTM-62780-49MTX)**  
  
Transmitter

Prepared and Checked by:

Approved by:



Tse Ying, Cathy  
Senior Lead Engineer



Ng Mei Nar, Chris  
Lead Engineer  
Date: December 02, 2014

- Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.
- This report shall not be reproduced, except in full.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Valued Quality. Delivered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



## GENERAL INFORMATION

|                           |                                                                                                             |
|---------------------------|-------------------------------------------------------------------------------------------------------------|
| Grantee:                  | Kidztech Toys Manufacturing Ltd.                                                                            |
| Grantee Address:          | Room 1201, 12/F., Inter Continental Plaza,<br>94 Granville Road, Tsim Sha Tsui East,<br>Kowloon, Hong Kong. |
| Contact Person:           | Eric Ho                                                                                                     |
| Tel:                      | (852) 2721 8868                                                                                             |
| Fax:                      | (852) 2721 8838                                                                                             |
| e-mail:                   | N/A                                                                                                         |
| Manufacturer:             | Shantou Chenghai JinJun Toys Co. Ltd.                                                                       |
| Manufacturer Address:     | Yongxin Industry Zone, Lianshang, Chenghai,<br>Shantou, China                                               |
| Buyer:                    | TOYSRUS                                                                                                     |
| Brand Name:               | Fastlane                                                                                                    |
| Model:                    | 5F62780                                                                                                     |
| Additional Model:         | 041519, 208636, 134691, 166618                                                                              |
| Type of EUT:              | Transmitter                                                                                                 |
| Description of EUT:       | RC Turbo Rider (5F62780)<br>FL Turbo Rider (041519, 208636, 134691, 166618)                                 |
| Serial Number:            | N/A                                                                                                         |
| FCC ID:                   | OTM-62780-49MTX                                                                                             |
| Date of Sample Submitted: | November 18, 2014                                                                                           |
| Date of Test:             | November 18, 2014 to November 27, 2014                                                                      |
| Report No.:               | 14110667HKG-001                                                                                             |
| Report Date:              | December 02, 2014                                                                                           |
| Environmental Conditions: | Temperature: +10 to 40°C<br>Humidity: 10 to 90%                                                             |



Valued Quality. Delivered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



## SUMMARY OF TEST RESULT

| TEST SPECIFICATION                                   | REFERENCE | RESULTS |
|------------------------------------------------------|-----------|---------|
| Transmitter Field Strength and Bandwidth Requirement | 15.235    | Pass    |

The equipment under test is found to be complying with the following standards:  
FCC Part 15, October 1, 2012 Edition

- Note: 1. The EUT uses detachable antenna with unique antenna connector which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.

## Table of Contents

|     |                                            |    |
|-----|--------------------------------------------|----|
| 1.0 | <b><u>General Description</u></b>          | 1  |
| 1.1 | Product Description                        | 1  |
| 1.2 | Related Submittal(s) Grants                | 1  |
| 1.3 | Test Methodology                           | 1  |
| 1.4 | Test Facility                              | 1  |
| 2.0 | <b><u>System Test Configuration</u></b>    | 2  |
| 2.1 | Justification                              | 2  |
| 2.2 | EUT Exercising Software                    | 2  |
| 2.3 | Special Accessories                        | 2  |
| 2.4 | Measurement Uncertainty                    | 2  |
| 2.5 | Support Equipment List and Description     | 2  |
| 3.0 | <b><u>Emission Results</u></b>             | 3  |
| 3.1 | Field Strength Calculation                 | 3  |
| 3.2 | Radiated Emission Configuration Photograph | 4  |
| 3.3 | Radiated Emission Data                     | 4  |
| 4.0 | <b><u>Equipment Photographs</u></b>        | 6  |
| 5.0 | <b><u>Product Labelling</u></b>            | 6  |
| 6.0 | <b><u>Technical Specifications</u></b>     | 6  |
| 7.0 | <b><u>Instruction Manual</u></b>           | 6  |
| 8.0 | <b><u>Miscellaneous Information</u></b>    | 7  |
| 8.1 | Measured Bandwidth                         | 7  |
| 8.2 | Discussion of Pulse Desensitization        | 8  |
| 8.3 | Calculation of Average Factor              | 8  |
| 8.4 | Emissions Test Procedures                  | 8  |
| 9.0 | <b><u>Equipment List</u></b>               | 10 |



Valued Quality. Delivered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



## 1.0 **General Description**

### 1.1 Product Description

The Equipment Under Test (EUT) is a transmitter of a RC system, which is operating at 49.860MHz as dictated by a crystal. The EUT is powered by 9V DC source (1 x 9.0V Block size battery). The EUT has a on/off switch, a left / right control lever and a forward / backward control lever.

After switching ON the EUT and the corresponding car (ie. Receiver), activating the control key on the EUT can control the car moving forward, backward, left and right.

The Model: 041519, 208636, 134691 and 166618 are the same as the Model: 5F62780 in hardware aspect. The difference in model number serves as marketing strategy. The models are different in model number only.

Antenna Type: External / Telescope-type antenna (with unique antenna connector)

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 1.2 Related Submittal(s) Grants

The Certification procedure of receiver (with FCC ID: OTM-62780-49MRX) for this transmitter (with FCC ID: OTM-62780-49MTX) is being processed as the same time of this application.

### 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

### 1.4 Test Facility

The open area test site facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



## 2.0 **System Test Configuration**

### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by new 1 x 9V Block size battery.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

### 2.5 Support Equipment List and Description

N/A.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB $\mu$ V/m
- RR = RA - AG - AV in dB $\mu$ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V/m}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V/m}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$LF = 9.0 \text{ dB}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$



Valued Quality. Delivered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 199.445 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 7.9 dB

Issuing Laboratory:

Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



Applicant: Kidztech Toys Manufacturing Ltd.

Date of Test: November 27, 2014

Model: 5F62780

Worst-Case Operating Mode: Transmitting

Table 1

**Radiated Emissions**  
**Pursuant to FCC Part 15 Section 15.235 Requirement**

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp (dB) | Antenna Factor (dB) | Average Factor (dB) | Net at 3m (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|--------------|---------------------|---------------------|--------------------|----------------------|-------------|
| V            | 49.860          | 75.5           | 16           | 11.0                | 0.0                 | 70.5               | 80.0                 | -9.5        |
| V            | 99.270          | 39.5           | 16           | 12.0                | -                   | 35.5               | 43.5                 | -8.0        |
| H            | 149.580         | 36.8           | 16           | 14.0                | -                   | 34.8               | 43.5                 | -8.7        |
| H            | 199.445         | 35.6           | 16           | 16.0                | -                   | 35.6               | 43.5                 | -7.9        |
| H            | 249.300         | 32.3           | 16           | 20.0                | -                   | 36.3               | 46.0                 | -9.7        |
| H            | 299.160         | 30.4           | 16           | 22.0                | -                   | 36.4               | 46.0                 | -9.6        |
| H            | 349.020         | 26.4           | 16           | 24.0                | -                   | 34.4               | 46.0                 | -11.6       |
| H            | 398.880         | 24.9           | 16           | 25.0                | -                   | 33.9               | 46.0                 | -12.1       |
| H            | 448.740         | 23.8           | 16           | 26.0                | -                   | 33.8               | 46.0                 | -12.2       |
| H            | 498.600         | 23.3           | 16           | 26.0                | -                   | 33.3               | 46.0                 | -12.7       |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.



Valued Quality. Delivered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



#### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

#### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

#### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

#### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Issuing Laboratory:

Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.




## 8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor.

## 8.1 Measured Bandwidth

The plot shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26 dB below the carrier level. And at 49.81 & 49.91 MHz, there are at least 43.26 dB below the carrier level. It meets requirement of Section 15.235(b).



Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



## 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 350 $\mu$ s for a digital “1” bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 100kHz, so the pulse desensitivity factor is 0dB.

## 8.3 Calculation of Average Factor

It is not necessary to apply average factor as the measured (peak) data has been complied with average limit of the radiated emission.

## 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



Valued Quality. Delivered.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.



#### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

Issuing Laboratory:  
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.

## 9.0 Equipment List

### 1) Radiated Emissions Test

|                      |                   |                   |
|----------------------|-------------------|-------------------|
| Equipment            | EMI Test Receiver | Spectrum Analyzer |
| Registration No.     | EW-2666           | EW-2188           |
| Manufacturer         | R&S               | AGILENTTECH       |
| Model No.            | ESCI7             | E4407B            |
| Calibration Date     | Jun. 20, 2013     | Apr. 16, 2014     |
| Calibration Due Date | Dec. 20, 2014     | Apr. 16, 2015     |

|                      |                   |                      |
|----------------------|-------------------|----------------------|
| Equipment            | Biconical Antenna | Log Periodic Antenna |
| Registration No.     | EW-2512           | EW-0447              |
| Manufacturer         | EMCO              | EMCO                 |
| Model No.            | 3104C             | 3146                 |
| Calibration Date     | Jun. 25, 2013     | Aug. 19, 2013        |
| Calibration Due Date | Dec. 25, 2014     | Feb. 19, 2015        |

### 2) Bandedge Measurement

|                      |                   |
|----------------------|-------------------|
| Equipment            | Spectrum Analyzer |
| Registration No.     | EW-2329           |
| Manufacturer         | R&S               |
| Model No.            | FSP3              |
| Calibration Date     | Jun. 19, 2014     |
| Calibration Due Date | Jun. 19, 2015     |

END OF TEST REPORT