

Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz pure transmit controller (Controller Unit) for a RC car. The operation frequency range is between 2405MHz and 2475MHz with 76 channels. The channels are separated by 1 MHz channel spacing.

The EUT is powered by 3 x 1.5V AA batteries.

After switch on the EUT, the car will be moved forward or backward, turned left or right based on the switches pressed in the controller.

For FCC, the Models: AD17980, 0006119964, 196045, 904204 and 930773 are the same as the Model: 84490 in hardware aspect. The difference in model number serves as marketing strategy. The models are different in non-conductive outer casing only.

Antenna Type: Internal, Integral

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength is 96.8 dB μ V/m at 3m

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 99.8dB μ V/m at 3m in frequency 0.027145GHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 2.865mW$

Conducted power = Radiated Power (EIRP) – Antenna Gain
So;

Conducted Power = 2.865mW.

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 \cdot 5 / \sqrt{2.475}$ mW

= 9.535 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.