

FCC TEST REPORT

FCC ID : OU4XG1000

Applicant : **Xanboo Inc**
115 West 30th Street, 6th Floor New York , NY10001

Equipment Under Test (EUT) :

Product description : Xanboo Remote Monitoring and access Gateway

Model No. : XG1000S

Standards : FCC 15 Subpart C Paragraph 15.231

Date of Test : July 06, 2006

Test Engineer : **Tiger Su**

Reviewed By : 

PERPARED BY:

Waltek Services (Shenzhen) Co., Ltd.

8C, West Tower, Aidi Building, No.5003 Binhe Rd, Futian District, Shenzhen 518045,
Guangdong, China.

Tel: 86-755-83551033

Fax: 86-755-83552400

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 TEST SUMMARY.....	5
4 GENERAL INFORMATION.....	6
4.1 CLIENT INFORMATION	6
4.2 GENERAL DESCRIPTION OF E.U.T.....	6
4.3 DETAILS OF E.U.T.	6
4.4 DESCRIPTION OF SUPPORT UNITS	6
4.5 STANDARDS APPLICABLE FOR TESTING.....	6
4.6 TEST FACILITY.....	7
4.7 TEST LOCATION.....	7
5 EQUIPMENT USED DURING TEST	8
6 CONDUCTED EMISSION TEST	9
6.1 TEST EQUIPMENT.....	9
6.2 TEST PROCEDURE	9
6.3 CONDUCTED TEST SETUP	10
6.4 EUT OPERATING CONDITION	10
6.5 CONDUCTED EMISSION LIMITS	11
6.6 CONDUCTED EMISSION TEST DATA	12
6.7 CONDUCTED EMISSIONS TEST DATA	14
7 RADIATION EMISSION TEST.....	15
7.1 TEST EQUIPMENT.....	15
7.2 MEASUREMENT UNCERTAINTY.....	15
7.3 TEST PROCEDURE	15
7.4 RADIATED TEST SETUP.....	16
7.5 SPECTRUM ANALYZER SETUP.....	16
7.6 CORRECTED AMPLITUDE & MARGIN CALCULATION	17
7.7 SUMMARY OF TEST RESULTS.....	17
7.8 EUT OPERATING CONDITION	18
7.9 RADIATED EMISSIONS LIMIT.....	18
7.10 RADIATED EMISSIONS TEST RESULT.....	19
7.10.1 Radiated Emission Data.....	19
8 PERIODIC OPERATION.....	21
9 BAND EDGE	22
9.1 TEST PROCEDURE	22
9.2 BAND EDGE	22
9.3 BAND EDGE TEST RESULT	23
10 PHOTOGRAPHS OF TESTING.....	24
10.1 CONDUCTION EMISSION TEST VIEW	24

10.2 RADIATION EMISSION TEST VIEW FOR 30MHZ-1000MHZ.....25

10.3 RADIATION EMISSION TEST VIEW FOR 1GHZ-5GHZ.....25

11 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS26

11.1 EUT - FRONT VIEW26

11.2 EUT - BACK VIEW26

11.3 ADAPTER - FRONT VIEW27

11.4 ADAPTER - BACK VIEW27

11.5 PCB1-FRONT VIEW28

11.6 PCB1-BACK VIEW.....28

11.7 PCB2-FRONT VIEW29

11.8 PCB2-BACK VIEW.....29

11.9 PCB3-FRONT VIEW30

11.10 PCB3-BACK VIEW.....30

12 FCC ID LABEL31

3 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 5GHz)	FCC PART 15: 2003	ANSI C63.4: 2003	Class B	PASS
Conducted Emission (150KHz to 30MHz)	FCC PART 15: 2003	ANSI C63.4: 2003	Class B	PASS

4 General Information

4.1 Client Information

Applicant:	Xanboo Inc
Address:	115 West 30 th Street, 6 th Floor New York , NY10001
Manufacturer:	RDI Technology (Shenzhen) Co., Ltd
Address:	Building C2 Xingtang Industrial Park,East Baishixia, Fuyong,Baoan, Shenzhen,PRC

4.2 General Description of E.U.T.

Product description:	Xanboo Remote Monitoring and access Gateway
Model No.:	XG1000S

4.3 Details of E.U.T.

Power Supply:	Adapter:100-240V AC/60Hz
---------------	--------------------------

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Standards Applicable for Testing

The customer requested FCC tests for a Xanboo Remote Monitoring and access Gateway. The standards used were FCC 15 Paragraph 15.231, Paragraph 15.205, Paragraph 15.31,Paragraph 15.33, Paragraph 15.35.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC – Registration No.: 662850**

SGS-CSTC Standards Technical Services Co., Ltd. ShenZhen Branch EMC Lab, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 662850, November 17, 2003.

4.7 Test Location

All Emissions tests were performed at:-

No.1 Workshop, M-10, Middle Section, Science & Technology Park, ShenZhen, China 518057

5 Equipment Used during Test

Equipment	Brand Name	Model	Cal. Int Months	Last Cal. Date
3m Anechoic chamber				
EMC Analyzer	Agilent	E7402A	12	2005-08
EMI Test Receiver	R&S	ESS	12	2005-08
Pre Amplifier	Anritsu	MH648A	12	2005-08
Bilog Antenna	SCHAFFNER	CBL6111C	12	2005-08
Horn Antenna	R&S	HF906	12	2005-08
AM/FM Stereo Signal Generator	Panasonic	VP-8122A	12	2005-08
Signal Generator	R&S	SMG	12	2005-08
RF Selector	TOYO	NS4901A	-	-
Turn Disc	HD	DS4150S	-	-
Antenna Mast	HD	MA2400	-	-
EMI Shielded Room				
Spectrum analyzer	ADVANTEST	R3261C	12	2005-08
EMI Test Receiver	R&S	ESS	12	2005-08
Pre Amplifier	Anritsu	MH648A	12	2005-08
LISN	R&S	ENV216	12	2005-08
LISN	Kyoritsu	KNW-403D	12	2005-08
Absorbing Clamp	R&S	MDS-21	12	2005-08
Distortion Meter	MEGURO	MAK-6578A	12	2005-08
AM/FM Stereo Signal Generator	Panasonic	VP-8122A	12	2005-08
Oscilloscope	LEADER	LS1020	12	2005-08
Function Generator	National	VP-7422A	12	2005-08
Signal Generator	R&S	SMG	12	2005-08
RF Selector	TOYO	NS4000	-	-
RF Selector	TOYO	NS4900	-	-
Remote Controller	TOYO	MAC	-	-

6 Conducted Emission Test

Product:	Xanboo Remote Monitoring and access Gateway
Test Requirement:	FCC Part15 Paragraph 15.207
Test Method:	Based on FCC Part15 Paragraph 15.207
Test Date:	June 09, 2006
Frequency Range:	150kHz to 30MHz
Class:	Class B
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

6.1 Test Equipment


Please refer to Section 5 this report.

6.2 Test Procedure

1. The EUT was tested according to ANSI C63.4: 2003. The frequency spectrum from 150kHz to 30MHz was investigated.
2. The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.3 Conducted Test Setup


The conducted emission tests were performed using the setup accordance with the ANSI C63.4: 2003, The specification used in this report was the FCC Part15 Paragraph 15.207 limits.



6.4 EUT Operating Condition

Operating condition is according to ANSI C63.4: 2003.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



6.5 Conducted Emission Limits

66-56 dB μ V/m between 0.15MHz & 0.5MHz


56 dB μ V/m between 0.5MHz & 5MHz

60 dB μ V/m between 5MHz & 30MHz

Note: In the above limits, the tighter limit applies at the band edges.

6.6 Conducted Emission Test Data


Live Line:



1

Date: 9.JUN.2006 16:39:00

Neutral Line:



1

Date: 9.JUN.2006 16:41:46

6.7 Conducted Emissions Test Data

Freq. MHz	Line	QP Reading dBuV	Limit dBuV	Margin dB	AV Reading dBuV	Limit dBuV	Margin dB
0.185	Live	47.55	64.27	16.72	44.00	54.27	10.27
0.360	Live	41.05	58.78	17.73	40.05	47.78	7.73
0.186	Neutral	49.93	64.22	14.29	47.72	54.22	6.50
0.370	Neutral	45.08	58.55	13.47	36.31	48.55	12.24

7 Radiation Emission Test

Product:	Xanboo Remote Monitoring and access Gateway
Test Requirement:	FCC Part15 Paragraph 15.231
Test Method:	Based on FCC Part15 Paragraph 15.33
Test Date:	July 06, 2006
Frequency Range:	30MHz to 5GHz
Measurement Distance:	3m
Detector:	Peak for pre-scan (120kHz resolution bandwidth) Quasi-Peak if maximised peak within 6dB of limit

7.1 Test Equipment

Please refer to Section 5 this report.

7.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on ANSI C63.4: 2003, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at SGS EMC Lab is +4.0 dB.

7.3 Test Procedure

1. For the radiated emissions test, since the EUT does not have a power source, there was no connection to AC outlets.
2. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.
3. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB μ V of specification limits), and are distinguished with a "Qp" in the data table.
4. The EUT was under normal mode during the final qualification test and the configuration was used to represent the worst case results.

7.4 Radiated Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003, The specification used in this report was the FCC Part15 Paragraph 15.231, Paragraph 15.209 limits.



7.5 Spectrum Analyzer Setup

According to FCC Part15 Paragraph 15.231 Rules, the system was tested to 5000 MHz.

Start Frequency30 MHz
Stop Frequency5000 MHz
Sweep Speed Auto
IF Bandwidth100 kHz
Video Bandwidth1 MHz
Quasi-Peak Adapter Bandwidth120 kHz
Quasi-Peak Adapter Mode.....Normal
Resolution Bandwidth1MHz

7.6 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

7.7 Summary of Test Results

According to the data in section 7.10, the EUT complied with the FCC Part15 Paragraph 15.231 standards.

7.8 EUT Operating Condition

Same as section 6.4 of this report.

7.9 Radiated Emissions Limit

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70.....	2,250.....	225
70-130.....	1,250.....	125
130-174.....	\1\ 1,250 to 3,750	\1\ 125 to 375
174-260.....	3,750.....	375
260-470.....	\1\ 3,750 to 12,500.	\1\ 375 to 1,250
Above 470.....	12,500.....	1,250

7.10 Radiated Emissions Test Result

Formula of conversion factors:the field strength at 3m was egtablished by adding
The meter reading of the spectrum analyer (which is set to read in units of dBuV)
To the antenna correction factor supplied by the antenna manufacturer. The antenna
Correction factors are stared in terms of dB.The gain of the pressletor was accounted
For in the spectrum analyser meter reading.

Example:

Freq(MHz) Meter Reading +ACF=FS
33 20dBuV+10.36dB=30.36dBuV/m @3m

7.10.1 Radiated Emission Data

Test Item:	Radiated Emission Data
Test Voltage:	120V AC/60Hz
Test Mode:	TX On
Temperature:	24 °C
Humidity:	52%RH
Test Result:	PASS

Frequency (MHz)	Antenna Polarization	Emission Level (dBuV/m)	FCC 15 Subpart C Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Turntable Angle (°)
418.07	Vertical	69.45	80.28	10.83	1.5	90
418.07	Horizontal	67.87	80.28	12.41	1.5	90
836.00	Vertical	23.46	60.28	36.82	1.2	90
1254.00	Vertical	20.75	54.0	33.25	2.0	180
1672.00	Vertical	28.72	54.0	25.28	1.8	60
2090.00	Vertical	18.77	54.0	35.23	2.0	45
836.00	Horizontal	19.69	60.28	40.59	1.5	45
1254.00	Horizontal	21.73	54.0	32.27	1.6	60
1672.00	Horizontal	32.66	54.0	21.34	2.0	180
2090.00	Horizontal	26.13	54.0	28.87	2.0	90

Where F is the frequency in MHz, The formulas for calculating the maximum permitted fundamental field strengths are as follows:

- (1). For the band 130-174MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$;
- (2). For the band 260-470MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$.



Sample calculation of limit @ 418MHz

$$41.6667(418) - 7083.3333 = 10333.3473 \mu\text{V/m}$$

$$20\log(10333.3473) = 80.28 \text{ dBuV/m limit @ 418MHz}$$

8 Periodic Operation

Refer to the duty cycle plot (as below),We find each the duration transmission for the device is about 19ms.and silent period between transmissions is about 8.5 seconds,This device does meet the FCC requirement.



9 Band Edge

Test Requirement:	FCC Part15 C
Test Method:	Based on FCC Part15 Paragraph 15.231
Test Date:	July 06, 2006
Test mode:	TX On
Temperature:	24 °C
Humidity:	52%RH

9.1 Test Procedure

1. The EUT, peripherals were put on the turntable which table size is 1mX1.5m, table high 0.8m. All set up is according to ANSI C63.4: 2003.
2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 100KHz RBW and 100KHz VBW.The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power 20dB.

9.2 Band Edge

Requirements: The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

9.3 Band Edge Test Result

418MHz TX



10 Photographs of Testing


10.1 Conduction Emission Test View



10.2 Radiation Emission Test View For 30MHz-1000MHz



10.3 Radiation Emission Test View For 1GHz-5GHz



11 Photographs - Constructional Details

11.1 EUT - Front View



11.2 EUT - Back View



11.3 Adapter - Front View




11.4 Adapter - Back View




11.5 PCB1-Front View



11.6 PCB1-Back View




11.7 PCB2-Front View




11.8 PCB2-Back View



11.9 PCB3-Front View



11.10 PCB3-Back View



12 FCC ID Label

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:(1)this device may not cause harmful interference,and (2) this device must accept any interference received, including interference that may cause undesired operation

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT
EUT Bottom View/proposed FCC Mark Location

