

TEST REPORT

Application No.: GZCR2601000247AT

Applicant: Guangdong Transtek Medical Electronics Co., Ltd.

Address of Applicant: Zone A, No.105, Dongli Road, Torch Development District, 528437
Zhongshan, Guangdong, China

Manufacturer: Guangdong Transtek Medical Electronics Co., Ltd.

Address of Manufacturer: Zone A, No.105, Dongli Road, Torch Development District, 528437
Zhongshan, Guangdong, China

Factory: Guangdong Transtek Medical Electronics Co., Ltd.

Address of Factory: Zone A, No.105, Dongli Road, Torch Development District, 528437
Zhongshan, Guangdong, China

Product Name: Body Fat Analyzer, Body Scale

Model No.: GBF-2008-B, GBS-2012-B ♣

♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

Trade Mark: Transtek

Standard(s) : 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2026-01-28

Date of Test: 2026-03-07 to 2026-04-30

Date of Issue: 2026-05-13

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Revision Record			
Version	Report No.	Date	Remark
01	GZCR260100024702	2026-05-13	Original

Authorized for issue by			
			
		Allen Zhou/Project Engineer	
Approved By			
		Vico Cui/Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 11.10.3	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

✱ Declaration of EUT Family Grouping:

Product Name	Body Fat Analyzer	Body Scale
Model No.:	GBF-2008-B	GBS-2012-B

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference is that GBS-2012-B was removed the body-fat measurement patch.

Therefore, only one model **GBF-2008-B** was tested with full tests and model GBS-2102-B was tested with Radiated Spurious Emissions Below 1GHz and Radiated Spurious Emissions Above 1GHz items in this report.



3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility.....	7
4.6 Deviation from Standards.....	7
4.7 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results.....	11
7.1 Radiated Emissions which fall in the restricted bands	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data.....	12
7.2 Radiated Spurious Emissions Below 1GHz.....	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data.....	18
7.3 Radiated Spurious Emissions Above 1GHz	23
7.3.1 E.U.T. Operation	23
7.3.2 Test Mode Description	23
7.3.3 Test Setup Diagram	23
7.3.4 Measurement Procedure and Data.....	24
7.4 Maximum Conducted Output Power	37
7.4.1 E.U.T. Operation	37
7.4.2 Test Mode Description	37
7.4.3 Test Setup Diagram	37
7.4.4 Measurement Procedure and Data.....	37
7.5 Minimum 6dB Bandwidth.....	38
7.5.1 E.U.T. Operation	38
7.5.2 Test Mode Description	38
7.5.3 Test Setup Diagram	38



7.5.4	Measurement Procedure and Data.....	38
7.6	Power Spectral Density	39
7.6.1	E.U.T. Operation	39
7.6.2	Test Mode Description	39
7.6.3	Test Setup Diagram	39
7.6.4	Measurement Procedure and Data.....	39
7.7	Conducted Band Edges Measurement	40
7.7.1	E.U.T. Operation	40
7.7.2	Test Mode Description	40
7.7.3	Test Setup Diagram	40
7.7.4	Measurement Procedure and Data.....	40
7.8	Conducted Spurious Emissions	41
7.8.1	E.U.T. Operation	41
7.8.2	Test Mode Description	41
7.8.3	Test Setup Diagram	41
7.8.4	Measurement Procedure and Data.....	41
8	Test Setup Photo	42
9	EUT Constructional Details (EUT Photos).....	42
10	Appendix.....	43



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 6V (1.5V "AAA" battery x 4pc)
Cable(s):	N/A
Test Voltage:	DC 6V
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	2.15 dBi according to antenna specification
Antenna Number:	1

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Note Book Computer	LENOVO	ThinkPad T490	PF1D1MVJ

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 5.14\text{dB}$ (3m); $\pm 4.90\text{dB}$ (10m); $\pm 4.88\text{dB}$ (1GHz-6GHz); $\pm 5.06\text{dB}$ (6GHz-18GHz); $\pm 5.30\text{dB}$ (18GHz-40GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 3.08\text{dB}$ (9kHz to 150kHz); $\pm 3.19\text{dB}$ (150kHz to 30MHz); $\pm 5.14\text{dB}$ (30MHz-1GHz) (3m); $\pm 4.90\text{dB}$ (30MHz-1GHz) (10m)
Radiated Spurious Emissions Above 1GHz	$\pm 4.88\text{dB}$ (1GHz-6GHz); $\pm 5.06\text{dB}$ (6GHz-18GHz); $\pm 5.30\text{dB}$ (18GHz-40GHz)
Maximum Conducted Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.274\%$
Power Spectral Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Remark: The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty) or U_{ETSI} (ETSI Uncertainty). Emission decision rule: – Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit, marked as Pass in the report. – Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit, marked as Fail in the report.	



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,
Guangdong, China 510663
Tel: +86 20 82155555
No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

● ISED (Registration No.: 4620B, CAB identifier: CN0052)

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

● VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2025-08-11	2026-08-10
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2025-08-11	2026-08-10
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2023-06-18	2026-06-17
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2025-08-12	2026-08-11
MXE EMI Receiver (10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2025-08-11	2026-08-10
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2025-08-13	2028-08-12
Coaxial cable	Mirco-COAX UTIFLEX	311A	EMC0540	2024-08-19	2026-08-18
Amplifier (9kHz-1.3GHz)	HP	8447F	EMC2065	2025-11-25	2026-11-24
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2026-03-28	2028-03-27
EMI Test Receiver (9kHz-7GHz)	Rohde & Schwarz	ESR7	EMC2220	2025-11-18	2026-11-17
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Trilog Broadband Antenna (25MHz-2GHz)	Schwarzbeck Mess-Elektronik	VULB 9168	EMC2174	2025-04-21	2027-04-20



Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2025-08-11	2026-08-10
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2025-08-11	2026-08-10
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2023-06-18	2026-06-17
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2025-08-12	2026-08-11
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2025-08-12	2026-08-11
MXE EMI Receiver (10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2025-08-11	2026-08-10
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Preamplifier (1-18GHz)	Shenzhen TST	LNA010180G50	EMC6036	2026-04-14	2027-04-13
Intelligent Coaxial RF Switch (DC-18GHz)	Shenzhen TST	ICS01018	EMC6037	2026-04-14	2027-04-13

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Test Software	TST	V2.0	GZE100-78	N/A	N/A
4X4 Power sensor Unit	TST	TSPS2023R	EMC2226	2025-08-12	2026-08-11
MI CABLE	SGS-EMC	0.8M	EMC2137	2025-11-02	2026-11-01

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2025-06-03	2026-06-02



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.15dBi.

Antenna location:

Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12

Test Engineer: Lily Kuang

Limit:

Test Distance: 3 m

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C

Humidity: 55.1 % RH


Atmospheric Pressure: 1007 mbar

7.1.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: Low



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2345.91	53.14	27.56	3.42	37.77	46.35	74.00	-27.65	VERTICAL	peak
2	2390.00	47.02	27.63	3.44	37.77	40.32	74.00	-33.68	VERTICAL	peak
3	2402.00	79.74	27.65	3.45	37.77	73.07	74.00	-0.93	VERTICAL	peak




Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2344.62	56.68	27.56	3.42	37.77	49.89	74.00	-24.11	HORIZONTAL	peak
2	2390.00	47.16	27.63	3.44	37.77	40.46	74.00	-33.54	HORIZONTAL	peak
3*	2402.00	96.52	27.65	3.45	37.77	89.85	74.00	15.85	HORIZONTAL	peak




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1*	2480.00	100.20	27.75	3.48	37.76	93.67	74.00	19.67	VERTICAL	peak
2	2483.50	57.61	27.76	3.49	37.76	51.10	74.00	-22.90	VERTICAL	peak
3	2483.72	56.07	27.76	3.49	37.76	49.56	74.00	-24.44	VERTICAL	peak



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1*	2480.00	104.36	27.75	3.48	37.76	97.83	74.00	23.83	HORIZONTAL	peak
2	2483.50	60.62	27.76	3.49	37.76	54.11	74.00	-19.89	HORIZONTAL	peak
3	2483.72	58.97	27.76	3.49	37.76	52.46	74.00	-21.54	HORIZONTAL	peak



7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Test Engineer: Bob Qu

Limit:

Test Distance: 3m

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 20.7 °C Humidity: 45.7 % RH Atmospheric Pressure: 1024 mbar

7.2.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)
Final test 02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBS-2012-B)



7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.



Test Mode: 00; Polarity: Horizontal




Site : SGS
Job :
Model :
Power :
Test Mode : TX

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	45.375	25.93	13.93	0.72	27.99	12.59	40.00	-27.41	HORIZONTAL	QP
2	113.316	26.69	10.75	0.88	27.88	10.44	43.52	-33.08	HORIZONTAL	QP
3	162.041	26.73	13.40	1.03	27.78	13.38	43.52	-30.14	HORIZONTAL	QP
4	290.017	26.71	13.44	1.66	27.21	14.60	46.02	-31.42	HORIZONTAL	QP
5	483.910	26.26	17.78	1.88	28.55	17.37	46.02	-28.65	HORIZONTAL	QP
6	729.358	27.78	21.85	2.38	28.42	23.59	46.02	-22.43	HORIZONTAL	QP



Test Mode: 00; Polarity: Vertical




Site : SGS
Job :
Model :
Power :
Test Mode : TX

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	40.135	25.86	13.55	0.69	27.99	12.11	40.00	-27.89	VERTICAL	QP
2	60.492	26.70	13.24	0.78	27.96	12.76	40.00	-27.24	VERTICAL	QP
3	123.266	25.84	11.58	0.91	27.87	10.46	43.52	-33.06	VERTICAL	QP
4	160.346	26.18	13.40	1.02	27.79	12.81	43.52	-30.71	VERTICAL	QP
5	331.355	26.41	14.44	1.74	27.30	15.29	46.02	-30.73	VERTICAL	QP
6	665.804	27.54	20.40	2.18	28.47	21.65	46.02	-24.37	VERTICAL	QP



Test Mode: 02; Polarity: Horizontal




Site : SGS
Job :
Model : M7
Power :
Test Mode : TX

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	38.078	23.41	13.33	0.67	27.99	9.42	40.00	-30.58	HORIZONTAL	QP
2	57.594	23.47	13.48	0.77	27.97	9.75	40.00	-30.25	HORIZONTAL	QP
3	121.976	23.85	11.49	0.90	27.87	8.37	43.50	-35.13	HORIZONTAL	QP
4	160.909	24.72	13.40	1.03	27.78	11.37	43.50	-32.13	HORIZONTAL	QP
5	350.477	23.83	14.51	1.77	27.38	12.73	46.00	-33.27	HORIZONTAL	QP
6	665.804	24.69	20.40	2.18	28.47	18.80	46.00	-27.20	HORIZONTAL	QP



Test Mode: 02; Polarity: Vertical



Site : SGS
Job :
Model : M7
Power :
Test Mode : TX

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	36.509	24.21	13.22	0.65	27.99	10.09	40.00	-29.91	VERTICAL	QP
2	52.208	24.64	13.86	0.75	27.98	11.27	40.00	-28.73	VERTICAL	QP
3	112.920	24.66	10.67	0.87	27.88	8.32	43.50	-35.18	VERTICAL	QP
4	161.474	24.85	13.40	1.03	27.78	11.50	43.50	-32.00	VERTICAL	QP
5	372.005	23.72	15.11	1.79	27.51	13.11	46.00	-32.89	VERTICAL	QP
6	614.214	25.47	20.46	2.07	28.56	19.44	46.00	-26.56	VERTICAL	QP



7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12

Test Engineer: Lily Kuang

Limit:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 21.5 °C Humidity: 55.1 % RH Atmospheric Pressure: 1007 mbar

7.3.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)
Final test 02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBS-2012-B)

7.3.3 Test Setup Diagram



Above 1GHz



7.3.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 1m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: Low



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1625.12	66.72	26.04	2.77	54.72	40.81	74.00	-33.19	VERTICAL	Peak
2	3337.71	62.44	28.91	4.03	54.77	40.61	74.00	-33.39	VERTICAL	Peak
3	4804.00	66.56	31.51	4.81	53.86	49.02	74.00	-24.98	VERTICAL	Peak
4	6488.75	53.73	34.15	5.64	53.20	40.32	74.00	-33.68	VERTICAL	Peak
5	7206.00	62.03	35.80	5.93	53.23	50.53	74.00	-23.47	VERTICAL	Peak
6	9205.54	50.73	37.97	6.73	53.48	41.95	74.00	-32.05	VERTICAL	Peak




Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1578.82	62.69	25.98	2.74	54.70	36.71	74.00	-37.29	HORIZONTAL	Peak
2	4482.15	53.06	30.90	4.62	54.08	34.50	74.00	-39.50	HORIZONTAL	Peak
3	4804.00	62.67	31.51	4.81	53.86	45.13	74.00	-28.87	HORIZONTAL	Peak
4	6602.27	52.78	34.35	5.69	53.20	39.62	74.00	-34.38	HORIZONTAL	Peak
5	7206.00	60.11	35.80	5.93	53.23	48.61	74.00	-25.39	HORIZONTAL	Peak
6	9205.54	51.10	37.97	6.73	53.48	42.32	74.00	-31.68	HORIZONTAL	Peak




Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1578.82	61.91	25.98	2.74	54.70	35.93	74.00	-38.07	VERTICAL	Peak
2	4133.70	54.58	30.19	4.52	54.35	34.94	74.00	-39.06	VERTICAL	Peak
3	4880.00	61.05	31.63	4.85	53.84	43.69	74.00	-30.31	VERTICAL	Peak
4	6874.91	53.11	35.04	5.83	53.20	40.78	74.00	-33.22	VERTICAL	Peak
5	7320.00	55.80	36.29	5.98	53.26	44.81	74.00	-29.19	VERTICAL	Peak
6	9152.48	50.47	37.86	6.68	53.49	41.52	74.00	-32.48	VERTICAL	Peak




Test Mode: 00; Polarity: Horizontal; Modulation: GFSK; Channel: middle



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1578.82	62.34	25.98	2.74	54.70	36.36	74.00	-37.64	HORIZONTAL	Peak
2	3337.71	58.03	28.91	4.03	54.77	36.20	74.00	-37.80	HORIZONTAL	Peak
3	4880.00	61.00	31.63	4.85	53.84	43.64	74.00	-30.36	HORIZONTAL	Peak
4	6914.76	52.35	35.11	5.84	53.20	40.10	74.00	-33.90	HORIZONTAL	Peak
5	7320.00	54.27	36.29	5.98	53.26	43.28	74.00	-30.72	HORIZONTAL	Peak
6	9205.54	50.38	37.97	6.73	53.48	41.60	74.00	-32.40	HORIZONTAL	Peak




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1653.55	66.84	26.08	2.80	54.73	40.99	74.00	-33.01	VERTICAL	Peak
2	3299.34	63.05	28.89	4.01	54.79	41.16	74.00	-32.84	VERTICAL	Peak
3	4960.00	65.57	31.74	4.89	53.81	48.39	74.00	-25.61	VERTICAL	Peak
4	6602.27	53.33	34.35	5.69	53.20	40.17	74.00	-33.83	VERTICAL	Peak
5	7440.00	62.64	36.57	6.02	53.28	51.95	74.00	-22.05	VERTICAL	Peak
6	8995.12	51.43	37.60	6.57	53.50	42.10	74.00	-31.90	VERTICAL	Peak




Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1578.82	63.35	25.98	2.74	54.70	37.37	74.00	-36.63	HORIZONTAL	Peak
2	4379.70	53.87	30.76	4.60	54.20	35.03	74.00	-38.97	HORIZONTAL	Peak
3	4960.00	62.13	31.74	4.89	53.81	44.95	74.00	-29.05	HORIZONTAL	Peak
4	6835.28	53.04	34.96	5.81	53.20	40.61	74.00	-33.39	HORIZONTAL	Peak
5	7440.00	59.79	36.57	6.02	53.28	49.10	74.00	-24.90	HORIZONTAL	Peak
6	9099.72	50.62	37.76	6.64	53.49	41.53	74.00	-32.47	HORIZONTAL	Peak




Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:Low



	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1414.60	64.67	25.82	2.67	54.55	38.61	74.00	-35.39	VERTICAL	peak
2	3186.87	57.32	28.79	3.91	54.79	35.23	74.00	-38.77	VERTICAL	peak
3	4804.00	58.91	31.51	4.81	53.91	41.32	74.00	-32.68	VERTICAL	peak
4	6451.35	52.63	34.08	5.63	53.20	39.14	74.00	-34.86	VERTICAL	peak
5	7206.00	53.05	35.80	5.93	53.24	41.54	74.00	-32.46	VERTICAL	peak
6	9608.00	53.57	38.70	7.04	53.44	45.87	74.00	-28.13	VERTICAL	peak




Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.98	65.63	25.99	2.75	54.63	39.74	74.00	-34.26	HORIZONTAL	peak
2	3168.50	57.77	28.77	3.89	54.81	35.62	74.00	-38.38	HORIZONTAL	peak
3	4804.00	58.26	31.51	4.81	53.91	40.67	74.00	-33.33	HORIZONTAL	peak
4	6756.71	53.13	34.77	5.77	53.20	40.47	74.00	-33.53	HORIZONTAL	peak
5	7206.00	51.65	35.80	5.93	53.24	40.14	74.00	-33.86	HORIZONTAL	peak
6	9608.00	50.57	38.70	7.04	53.44	42.87	74.00	-31.13	HORIZONTAL	peak




Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:middle



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1447.69	65.12	25.86	2.68	54.57	39.09	74.00	-34.91	VERTICAL	peak
2	3186.87	60.04	28.79	3.91	54.79	37.95	74.00	-36.05	VERTICAL	peak
3	4880.00	55.70	31.63	4.85	53.87	38.31	74.00	-35.69	VERTICAL	peak
4	6874.91	52.75	35.04	5.83	53.20	40.42	74.00	-33.58	VERTICAL	peak
5	7320.00	51.15	36.29	5.98	53.27	40.15	74.00	-33.85	VERTICAL	peak
6	9760.00	50.74	38.87	7.11	53.42	43.30	74.00	-30.70	VERTICAL	peak




Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:middle



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1460.30	65.75	25.87	2.69	54.57	39.74	74.00	-34.26	HORIZONTAL	peak
2	3969.77	54.83	29.96	4.48	54.41	34.86	74.00	-39.14	HORIZONTAL	peak
3	4880.00	58.01	31.63	4.85	53.87	40.62	74.00	-33.38	HORIZONTAL	peak
4	6954.85	52.69	35.17	5.86	53.20	40.52	74.00	-33.48	HORIZONTAL	peak
5	7320.00	52.25	36.29	5.98	53.27	41.25	74.00	-32.75	HORIZONTAL	peak
6	9760.00	51.13	38.87	7.11	53.42	43.69	74.00	-30.31	HORIZONTAL	peak




Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1390.28	59.70	25.78	2.65	54.54	33.59	74.00	-40.41	VERTICAL	peak
2	4181.77	53.28	30.29	4.54	54.28	33.83	74.00	-40.17	VERTICAL	peak
3	4960.00	57.04	31.74	4.89	53.82	39.85	74.00	-34.15	VERTICAL	peak
4	6995.17	50.12	35.23	5.87	53.20	38.02	74.00	-35.98	VERTICAL	peak
5	7440.00	49.78	36.57	6.02	53.29	39.08	74.00	-34.92	VERTICAL	peak
6	9920.00	49.10	39.07	7.19	53.41	41.95	74.00	-32.05	VERTICAL	peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1460.30	62.13	25.87	2.69	54.57	36.12	74.00	-37.88	HORIZONTAL	peak
2	4133.70	54.21	30.19	4.52	54.31	34.61	74.00	-39.39	HORIZONTAL	peak
3	4960.00	56.93	31.74	4.89	53.82	39.74	74.00	-34.26	HORIZONTAL	peak
4	6717.76	52.68	34.64	5.75	53.20	39.87	74.00	-34.13	HORIZONTAL	peak
5	7440.00	52.14	36.57	6.02	53.29	41.44	74.00	-32.56	HORIZONTAL	peak
6	9920.00	50.82	39.07	7.19	53.41	43.67	74.00	-30.33	HORIZONTAL	peak



7.4 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.1

Test Engineer: Banna Ban

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C

Humidity: 61.0 % RH


Atmospheric Pressure: 1007 mbar

7.4.2 Test Mode Description

Pre-scan / Mode Description
Final test Code

Final test 00 TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.5 Minimum 6dB Bandwidth

Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2020) Section 11.8.1
Test Engineer:	Banna Ban
Limit:	≥500 kHz

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 21.8 °C Humidity: 61.0 % RH Atmospheric Pressure: 1007 mbar

7.5.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.6 Power Spectral Density

Test Requirement	47 CFR Part 15, Subpart C 15.247(e)
Test Method:	ANSI C63.10 (2020) Section 11.10.3
Test Engineer:	Banna Ban
Limit:	≤8dBm in any 3 kHz band during any time interval of continuous transmission


7.6.1 E.U.T. Operation

Operating Environment:			
Temperature:	21.8 °C	Humidity:	61.0 % RH
		Atmospheric Pressure:	1007 mbar

7.6.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Test Engineer: Banna Ban

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 61.0 % RH

Atmospheric Pressure: 1007 mbar

7.7.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Test Engineer: Banna Ban

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 61.0 % RH

Atmospheric Pressure: 1007 mbar

7.8.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation. (Model GBF-2008-B)

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZCR260100024702

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - External and Internal Photos for GZCR2601000247AT



10 Appendix

1. Duty Cycle


1.1 Test Result


1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	100.000	100.000	100.00	0.00	0.00
		2440	100.000	100.000	100.00	0.00	0.00
		2480	100.000	100.000	100.00	0.00	0.00

1.2 Test Graph

1.2.1 Ant1





2. Bandwidth


2.1 Test Result

2.1.1 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.745	≥ 0.5	Pass
		2440	1	0.748	≥ 0.5	Pass
		2480	1	0.752	≥ 0.5	Pass

2.2 Test Graph


2.2.1 6dB BW



1M_MCH_2440MHz_Ant1_NTNV



1M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-0.49	<=30	Pass
		2440	-0.46	<=30	Pass
		2480	-0.45	<=30	Pass



4. Maximum Power Spectral Density


4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-1.36	<=8	Pass
		2440	-1.33	<=8	Pass
		2480	-1.31	<=8	Pass

4.2 Test Graph


4.2.1 PSD



1M_MCH_2440MHz_Ant1_NTNV



1M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	-1.34
		2440	1	-1.29
		2480	1	-1.30


5.1.2 CSE and Band Edges


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	-1.29	-21.29	Pass
		2440	1	-1.29	-21.29	Pass
		2480	1	-1.29	-21.29	Pass




5.2 Test Graph

5.2.1 Ref







5.2.2 CSE and Band Edges





1M_LCH_2402MHz_Ant1_NTNV



1M_MCH_2440MHz_Ant1_NTNV







- End of the Report -

