



# **RADIO TEST REPORT**


**Test Report No. : 11990777H-A-R2**

**Applicant** : OMRON Automotive Electronics Co. Ltd.  
**Type of Equipment** : Immobilizer and Alarm system  
**Model No.** : K56R0  
**FCC ID** : OUCK56R0  
**Test regulation** : FCC Part 15 Subpart C: 2018  
**Test Result** : Complied


1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. This report is a revised version of 11990777H-A-R1. 11990777H-A-R1 is replaced with this report.

**Date of test:** October 14, 2017 to January 23, 2018

**Representative test engineer:**

  
Koji Yamamoto  
Engineer  
Consumer Technology Division

**Approved by:**

  
Shinichi Miyazono  
Engineer  
Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
[http://japan.ul.com/resources/emc\\_accredited/](http://japan.ul.com/resources/emc_accredited/)

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

Facsimile : +81 596 24 8124

| <b>CONTENTS</b>                                                              | <b>PAGE</b> |
|------------------------------------------------------------------------------|-------------|
| <b>SECTION 1: Customer information .....</b>                                 | <b>4</b>    |
| <b>SECTION 2: Equipment under test (E.U.T.).....</b>                         | <b>4</b>    |
| <b>SECTION 3: Test specification, procedures &amp; results .....</b>         | <b>5</b>    |
| <b>SECTION 4: Operation of E.U.T. during testing.....</b>                    | <b>8</b>    |
| <b>SECTION 5: Radiated emission (Fundamental and Spurious Emission).....</b> | <b>10</b>   |
| <b>SECTION 6: -26dB Bandwidth.....</b>                                       | <b>12</b>   |
| <b>SECTION 7: 99% Occupied Bandwidth.....</b>                                | <b>12</b>   |
| <b>APPENDIX 1: Test data .....</b>                                           | <b>13</b>   |
| Radiated Emission below 30 MHz (Fundamental and Spurious Emission) .....     | 13          |
| Radiated Emission above 30MHz (Spurious Emission).....                       | 15          |
| -26dB Bandwidth and 99% Occupied Bandwidth .....                             | 16          |
| <b>APPENDIX 2: Test instruments .....</b>                                    | <b>17</b>   |
| <b>APPENDIX 3: Photographs of test setup .....</b>                           | <b>18</b>   |
| Radiated Emission.....                                                       | 18          |

## **SECTION 1: Customer information**

Company Name : OMRON Automotive Electronics Co. Ltd.  
Address : 6368 NENJOZAKA OKUSA KOMAKI AICHI, 485-0802 JAPAN  
Telephone Number : +81-568-78-6159  
Facsimile Number : +81-568-78-7659  
Contact Person : Takashi Betsui

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment : Immobilizer and Alarm system  
Model No. : K56R0  
Serial No. : Refer to Section 4, Clause 4.2  
Rating : DC 12.0 V  
Receipt Date of Sample : October 5, 2017  
Country of Mass-production : Japan and India  
Condition of EUT : Production prototype  
(Not for Sale: This sample is equivalent to mass-produced items.)  
Modification of EUT : No Modification by the test lab

### **2.2 Product Description**

Model No: K56R0 (referred to as the EUT in this report) is the Immobilizer and Alarm system.

#### **General Specification**

Clock frequency(ies) in the system : 8 MHz (CPU)

#### **Radio Specification**

##### **[Transmitter part]**

Radio Type : Transceiver  
Frequency of Operation : 125 kHz  
Modulation : ASK  
Power Supply (inner) : DC 12 V (Typ), DC 36 V (Max)  
Antenna type : External Antenna

##### **[Receiver part] \*1)**

Equipment Type : Receiver  
Frequency of Operation : 433.92 MHz  
Local clock frequency : 21.948717 MHz  
Antenna Type : Pattern Antenna  
Type of Modulation : FSK  
Method of Frequency Generation : Crystal resonator

\*1) The test of receiver part was performed separately from this test report, and the conformability is confirmed.

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### **SECTION 3: Test specification, procedures & results**

#### **3.1 Test Specification**

Test Specification : FCC Part 15 Subpart C  
FCC Part 15 final revised on January 2, 2018 and effective February 1, 2018

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
Section 15.207 Conducted limits  
Section 15.209 Radiated emission limits; general requirements.

\* The revision on January 2, 2018, does not affect the test specification applied to the EUT.

\* Also the EUT complies with FCC Part 15 Subpart B.

#### **3.2 Procedures and results**

| No. | Item                                            | Test Procedure                                                                    | Specification                                                 | Remarks  | Deviation | Worst margin                                            | Results  |
|-----|-------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------|----------|-----------|---------------------------------------------------------|----------|
| 1   | Conducted Emission                              | <FCC><br>ANSI C63.10:2013<br>6 Standard test methods<br><IC><br>RSS-Gen 8.8       | <FCC><br>Section 15.207<br><IC><br>RSS-Gen 8.8                | -        | N/A *1)   | N/A                                                     | N/A      |
| 2   | Electric Field Strength of Fundamental Emission | <FCC><br>ANSI C63.10:2013<br>6 Standard test methods<br><IC><br>RSS-Gen 6.4, 6.12 | <FCC><br>Section 15.209<br><IC><br>RSS-210 4.4<br>RSS-Gen 8.9 | Radiated | N/A       | 4.4 dB<br>0.12500 MHz<br>0 deg.,<br>PK with Duty factor | Complied |
| 3   | Electric Field Strength of Spurious Emission    | <FCC><br>ANSI C63.10:2013<br>6 Standard test methods<br><IC><br>RSS-Gen 6.4, 6.13 | <FCC><br>Section 15.209<br><IC><br>RSS-210 4.4<br>RSS-Gen 8.9 | Radiated | N/A       | 8.9 dB<br>32.128 MHz,<br>Vertical, QP                   | Complied |
| 4   | -26dB Bandwidth                                 | <FCC><br>ANSI C63.10:2013<br>6 Standard test methods<br><IC><br>-                 | <FCC><br>Reference data<br><IC><br>-                          | Radiated | N/A       | N/A                                                     | N/A      |

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

\*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

#### **FCC 15.31 (e)**

The EUT provides stable voltage (DC 36 V) constantly to the wireless transmitter regardless of input voltage. Instead of a new battery, DC power supply was used for the test.  
That does not affect the test result, therefore the EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle. Therefore, the equipment complies with the antenna requirement of Section 15.203.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.3 Addition to standard

| No. | Item                     | Test Procedure | Specification | Remarks  | Deviation | Worst margin | Results |
|-----|--------------------------|----------------|---------------|----------|-----------|--------------|---------|
| 1   | 99 % Occupied Band Width | RSS-Gen 6.6    | -             | Radiated | N/A       | N/A          | N/A     |

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

| Test distance | Radiated emission (+/-) |
|---------------|-------------------------|
|               | 9 kHz - 30 MHz          |
| 3 m           | 3.8 dB                  |
| 10 m          | 3.7 dB                  |

\*Measurement distance

| Polarity   | Radiated emission (Below 1 GHz) |                    |                  |                    |
|------------|---------------------------------|--------------------|------------------|--------------------|
|            | (3 m*)(+/-)                     |                    | (10 m*)(+/-)     |                    |
|            | 30 MHz - 200 MHz                | 200 MHz - 1000 MHz | 30 MHz - 200 MHz | 200 MHz - 1000 MHz |
| Horizontal | 5.0 dB                          | 5.3 dB             | 5.0 dB           | 5.0 dB             |
| Vertical   | 4.7 dB                          | 5.9 dB             | 5.0 dB           | 5.1 dB             |

#### Radiated emission test(3 m)

The data listed in this test report has enough margin, more than the site margin.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab.  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone: +81 596 24 8999, Facsimile: +81 596 24 8124  
NVLAP Lab. code: 200572-0 / FCC Test Firm Registration Number: 199967

| Test site                  | IC Registration Number | Width x Depth x Height (m) | Size of reference ground plane (m) / horizontal conducting plane | Other rooms            | Maximum measurement distance |
|----------------------------|------------------------|----------------------------|------------------------------------------------------------------|------------------------|------------------------------|
| No.1 semi-anechoic chamber | 2973C-1                | 19.2 x 11.2 x 7.7          | 7.0 x 6.0                                                        | No.1 Power source room | 10 m                         |
| No.2 semi-anechoic chamber | 2973C-2                | 7.5 x 5.8 x 5.2            | 4.0 x 4.0                                                        | -                      | 3 m                          |
| No.3 semi-anechoic chamber | 2973C-3                | 12.0 x 8.5 x 5.9           | 6.8 x 5.75                                                       | No.3 Preparation room  | 3 m                          |
| No.3 shielded room         | -                      | 4.0 x 6.0 x 2.7            | N/A                                                              | -                      | -                            |
| No.4 semi-anechoic chamber | 2973C-4                | 12.0 x 8.5 x 5.9           | 6.8 x 5.75                                                       | No.4 Preparation room  | 3 m                          |
| No.4 shielded room         | -                      | 4.0 x 6.0 x 2.7            | N/A                                                              | -                      | -                            |
| No.5 semi-anechoic chamber | -                      | 6.0 x 6.0 x 3.9            | 6.0 x 6.0                                                        | -                      | -                            |
| No.6 shielded room         | -                      | 4.0 x 4.5 x 2.7            | 4.0 x 4.5                                                        | -                      | -                            |
| No.6 measurement room      | -                      | 4.75 x 5.4 x 3.0           | 4.75 x 4.15                                                      | -                      | -                            |
| No.7 shielded room         | -                      | 4.7 x 7.5 x 2.7            | 4.7 x 7.5                                                        | -                      | -                            |
| No.8 measurement room      | -                      | 3.1 x 5.0 x 2.7            | N/A                                                              | -                      | -                            |
| No.9 measurement room      | -                      | 8.8 x 4.6 x 2.8            | 2.4 x 2.4                                                        | -                      | -                            |
| No.11 measurement room     | -                      | 6.2 x 4.7 x 3.0            | 4.8 x 4.6                                                        | -                      | -                            |

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 m x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

## SECTION 4: Operation of E.U.T. during testing

### 4.1 Operating Modes

| Test mode                     | Remarks |
|-------------------------------|---------|
| Transmitting mode (Tx) 125kHz | -       |


Justification : The system was configured in typical fashion (as a user would normally use it) for testing.

The EUT has 5 types of LF Antennas and 2 Systems.

| [System 1]           | [System 2]           |
|----------------------|----------------------|
| - LF Antenna-1 (INF) | - LF Antenna-3 (INF) |
| - LF Antenna-1 (INR) | - LF Antenna-3 (INR) |
| - LF Antenna-1 (T/G) | - LF Antenna-3 (T/G) |
| - LF Antenna-2 (Dr)  | - LF Antenna-2 (Dr)  |
| - LF Antenna-2 (As)  | - LF Antenna-2 (As)  |

- \* LF Antenna-1 (INF, INR, T/G) has variation of appearance difference (LF Antenna-3 (INF, INR, T/G)).
- \* It was confirmed that there was no difference in RF characteristics between LF Antenna-1 (INF, INR, T/G) and LF Antenna-3 (INF, INR, T/G).
- \* The test was performed with System 1 as representative.

### 4.2 Configuration and peripherals



\* Cabling and setup were taken into consideration and test data was taken under worse case conditions.

- \* The EUT does not transmit simultaneously from multiple antennas.
- \* Antenna was evaluated with the worst duty respectively.
- \* The EUT was set to transmit the data continuously from one antenna as a worst case, not to transmit it randomly from each antenna.
- \* According to the result of pre-check to five antennas, it was confirmed that there was no difference in RF characteristics among antennas. So the test was performed with one antenna B (LF Antenna-1 (INF)) as a representative.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

#### Description of EUT and Support equipment

| No. | Item                         | Model number | Serial number | Manufacturer                          | Remark |
|-----|------------------------------|--------------|---------------|---------------------------------------|--------|
| A   | Immobilizer and Alarm system | K56R0        | No.008        | OMRON Automotive Electronics Co. Ltd. | EUT    |
| B   | LF Antenna-1 (INF)           | CGF-S002-D01 | 1             | OMRON Automotive Electronics Co. Ltd. | EUT    |
| C   | LF Antenna-1 (INR)           | CGF-S002-D01 | 2             | OMRON Automotive Electronics Co. Ltd. | EUT    |
| D   | LF Antenna-1 (T/G)           | CGF-S002-D01 | 3             | OMRON Automotive Electronics Co. Ltd. | EUT    |
| E   | LF Antenna-2 (Dr)            | CGF-S002-D02 | 261           | OMRON Automotive Electronics Co. Ltd. | EUT    |
| F   | LF Antenna-2 (As)            | CGF-S002-D02 | 267           | OMRON Automotive Electronics Co. Ltd. | EUT    |
| G   | Push Start Switch            | P55R0        | No.013        | OMRON Automotive Electronics Co. Ltd. | -      |
| H   | Switch BOX                   | RV494        | No.002        | OMRON Automotive Electronics Co. Ltd. | -      |

#### List of cables used

| No. | Name              | Length (m) | Shield     |            | Remark |
|-----|-------------------|------------|------------|------------|--------|
|     |                   |            | Cable      | Connector  |        |
| 1   | DC Cable          | 2.0        | Unshielded | Unshielded | -      |
| 2   | Signal & DC Cable | 2.0        | Unshielded | Unshielded | -      |
| 3   | Antenna Cable     | 2.4        | Unshielded | Unshielded | -      |
| 4   | Antenna Cable     | 2.4        | Unshielded | Unshielded | -      |
| 5   | Antenna Cable     | 2.4        | Unshielded | Unshielded | -      |
| 6   | Antenna Cable     | 2.4        | Unshielded | Unshielded | -      |
| 7   | Antenna Cable     | 2.4        | Unshielded | Unshielded | -      |
| 8   | Signal & DC Cable | 2.0        | Unshielded | Unshielded | -      |

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 5: Radiated emission (Fundamental and Spurious Emission)**

### **Test Procedure**

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

Frequency : From 9 kHz to 30 MHz

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0 deg., 45 deg., 90 deg., and 135 deg.) and horizontal polarization.

\*Refer to Figure 1 about Direction of the Loop Antenna.

Frequency: From 30 MHz to 1 GHz

The measuring antenna height varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

The test was made with the detector (RBW / VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

### **Test Antennas are used as below;**

| Frequency    | Below 30 MHz | 30 MHz to 200 MHz | 200 MHz to 1 GHz |
|--------------|--------------|-------------------|------------------|
| Antenna Type | Loop         | Biconical         | Logperiodic      |

| Frequency       | From 9 kHz to 90 kHz and From 110 kHz to 150 kHz | From 90 kHz to 110 kHz | From 150 kHz to 490 kHz | From 490 kHz to 30 MHz | From 30 MHz to 1 GHz |
|-----------------|--------------------------------------------------|------------------------|-------------------------|------------------------|----------------------|
| Instrument used | Test Receiver                                    |                        |                         |                        |                      |
| Detector        | PK / AV                                          | QP                     | PK / AV                 | QP                     | QP                   |
| IF Bandwidth    | 200 Hz                                           | 200 Hz                 | 9 kHz                   | 9 kHz                  | 120 kHz              |
| Test Distance   | 3 m *1)                                          | 3 m *1)                | 3 m *1)                 | 3 m *2)                | 3 m                  |

\*1) Distance Factor:  $40 \times \log(3 \text{ m} / 300 \text{ m}) = -80 \text{ dB}$

\*2) Distance Factor:  $40 \times \log(3 \text{ m} / 30 \text{ m}) = -40 \text{ dB}$

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

These tests were performed in semi anechoic chamber. Therefore the measured level of emissions may be higher than if measurements were made without a ground plane.

However test results were confirmed to pass against standard limit.

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

**Measurement range** : 9 kHz - 1 GHz

**Test data** : APPENDIX 1

**Test result** : Pass

Date: January 22 and 23, 2018

Test engineer:

Koji Yamamoto

**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999


Facsimile : +81 596 24 8124

**Figure 1: Direction of the Loop Antenna**

*Side View (Vertical)*




*Top View (Horizontal)*



Antenna was not rotated.

---

*Top View (Vertical)*



## **SECTION 6: -26dB Bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

| Test             | Span    | RBW   | VBW   | Sweep | Detector | Trace    | Instrument used   |
|------------------|---------|-------|-------|-------|----------|----------|-------------------|
| -26 dB Bandwidth | 100 kHz | 1 kHz | 3 kHz | Auto  | Peak     | Max Hold | Spectrum Analyzer |

Test data : APPENDIX 1

Test result : Pass

## **SECTION 7: 99% Occupied Bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

| Test                    | Span                                    | RBW             | VBW                | Sweep | Detector | Trace    | Instrument used   |
|-------------------------|-----------------------------------------|-----------------|--------------------|-------|----------|----------|-------------------|
| 99 % Occupied Bandwidth | Enough width to display emission skirts | 1 to 5 % of OBW | Three times of RBW | Auto  | Peak     | Max Hold | Spectrum Analyzer |

Peak hold was applied as Worst-case measurement.

Test data : APPENDIX 1

Test result : Pass

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## APPENDIX 1: Test data

### Radiated Emission below 30 MHz (Fundamental and Spurious Emission)

Test place : Ise EMC Lab. No.4 Semi Anechoic Chamber  
Order No. : 11990777H  
Date : 01/22/2018  
Temperature/ Humidity : 23 deg. C / 32 % RH  
Engineer : Koji Yamamoto  
Mode : Tx 125 kHz

#### PK or QP

| Ant Deg [deg] | Frequency [MHz] | Detector | Reading [dBuV] | Ant Factor [dB/m] | Loss [dB] | Gain [dB] | Duty Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark      |
|---------------|-----------------|----------|----------------|-------------------|-----------|-----------|------------------|-----------------|----------------|-------------|-------------|
| 0             | 0.12500         | PK       | 107.5          | 19.8              | -73.9     | 32.2      | -                | 21.2            | 45.6           | 24.4        | Fundamental |
| 0             | 0.25000         | PK       | 77.5           | 19.7              | -73.9     | 32.2      | -                | -8.9            | 39.6           | 48.5        |             |
| 0             | 0.37500         | PK       | 61.7           | 19.7              | -73.9     | 32.2      | -                | -24.7           | 36.1           | 60.8        |             |
| 0             | 0.50000         | QP       | 40.3           | 19.7              | -33.8     | 32.1      | -                | -5.9            | 33.6           | 39.5        |             |
| 0             | 0.62500         | QP       | 34.9           | 19.7              | -33.8     | 32.2      | -                | -11.4           | 31.7           | 43.1        |             |
| 0             | 0.75000         | QP       | 32.5           | 19.7              | -33.8     | 32.2      | -                | -13.8           | 30.1           | 43.9        |             |
| 0             | 0.87500         | QP       | 32.3           | 19.7              | -33.8     | 32.2      | -                | -14.0           | 28.7           | 42.7        |             |
| 0             | 1.00000         | QP       | 32.0           | 19.7              | -33.8     | 32.2      | -                | -14.3           | 27.6           | 41.9        |             |
| 0             | 1.12500         | QP       | 31.6           | 19.7              | -33.8     | 32.2      | -                | -14.7           | 26.5           | 41.2        |             |
| 0             | 1.25000         | QP       | 31.5           | 19.7              | -33.8     | 32.2      | -                | -14.8           | 25.6           | 40.4        |             |

Result = Reading + Ant Factor + Loss (Cable + Attenuator + D.Factor) - Gain(Amplifier)

#### PK with Duty factor

| Ant Deg [deg] | Frequency [MHz] | Detector | Reading [dBuV] | Ant Factor [dB/m] | Loss [dB] | Gain [dB] | Duty Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark |
|---------------|-----------------|----------|----------------|-------------------|-----------|-----------|------------------|-----------------|----------------|-------------|--------|
| 0             | 0.125           | PK       | 107.5          | 19.8              | -73.9     | 32.2      | 0.0              | 21.2            | 25.6           | 4.4         |        |
| 0             | 0.250           | PK       | 77.5           | 19.7              | -73.9     | 32.2      | 0.0              | -8.9            | 19.6           | 28.5        |        |
| 0             | 0.375           | PK       | 61.7           | 19.7              | -73.9     | 32.2      | 0.0              | -24.7           | 16.1           | 40.8        |        |

Result = Reading + Ant Factor + Loss (Cable + Attenuator + D.Factor) - Gain(Amplifier) + Duty factor \*

\* Since the peak emission result satisfied the average limit, duty factor was omitted.

#### Result of the fundamental emission at 3m without Distance factor

##### PK

| Ant Deg [deg] | Frequency [MHz] | Detector | Reading [dBuV] | Ant Factor [dB/m] | Loss [dB] | Gain [dB] | Duty Factor [dB] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Remark      |
|---------------|-----------------|----------|----------------|-------------------|-----------|-----------|------------------|-----------------|----------------|-------------|-------------|
| 0             | 0.12500         | PK       | 107.5          | 19.8              | 6.1       | 32.2      | -                | 101.2           | -              | -           | Fundamental |

Result = Reading + Ant Factor + Loss (Cable + Attenuator) - Gain(Amplifier)

\* All spurious emissions lower than this result.

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

**Radiated Emission below 30 MHz (Fundamental and Spurious Emission)**  
**(Plot data, Worst case)**

Test place : Ise EMC Lab. No.4 Semi Anechoic Chamber  
Order No. : 11990777H  
Date : 01/22/2018  
Temperature/ Humidity : 23 deg. C / 32 % RH  
Engineer : Koji Yamamoto  
Mode : Tx 125 kHz

LIMIT : FCC15.209(a), 9-90kHz:PK, 110-490kHz:PK, other:QP  
FCC15.209(a), 9-90kHz:AV, 110-490kHz:AV, other:QP




\*These plots data contains sufficient number to show the trend of characteristic features for EUT.

## Radiated Emission above 30MHz (Spurious Emission)

Test place : Ise EMC Lab. No.4 Semi Anechoic Chamber  
Order No. : 11990777H  
Date : 01/23/2018  
Temperature/ Humidity : 22 deg. C / 34 % RH  
Engineer : Koji Yamamoto  
Mode : Tx 125kHz

LIMIT : FCC15.209 3m, below 1GHz:QP, above 1GHz:PK  
FCC15.209 3m, below 1GHz:QP, above 1GHz:AV



| Frequency | Reading | DET | Antenna | Loss& | Level    | Angle | Height | Polar. | Limit    | Margin | Comment |
|-----------|---------|-----|---------|-------|----------|-------|--------|--------|----------|--------|---------|
| [MHz]     | [dBuV]  |     | Factor  | Gain  | [dBuV/m] | [Deg] | [cm]   |        | [dBuV/m] | [dB]   |         |
| 32.048    | 28.4    | QP  | 17.0    | -23.8 | 21.6     | 328   | 216    | Hori.  | 40.0     | 18.4   |         |
| 32.128    | 37.9    | QP  | 17.0    | -23.8 | 31.1     | 260   | 100    | Vert.  | 40.0     | 8.9    |         |
| 40.778    | 33.0    | QP  | 14.2    | -23.6 | 23.6     | 177   | 315    | Hori.  | 40.0     | 16.4   |         |
| 40.761    | 37.3    | QP  | 14.2    | -23.6 | 27.9     | 278   | 100    | Vert.  | 40.0     | 12.1   |         |
| 48.493    | 35.9    | QP  | 11.4    | -23.5 | 23.8     | 2     | 344    | Hori.  | 40.0     | 16.2   |         |
| 48.523    | 36.8    | QP  | 11.4    | -23.5 | 24.7     | 128   | 100    | Vert.  | 40.0     | 15.3   |         |
| 84.029    | 41.0    | QP  | 7.0     | -23.0 | 25.0     | 359   | 217    | Hori.  | 40.0     | 15.0   |         |
| 84.029    | 41.5    | QP  | 7.0     | -23.0 | 25.5     | 282   | 100    | Vert.  | 40.0     | 14.5   |         |
| 172.063   | 35.3    | QP  | 15.8    | -21.8 | 29.3     | 359   | 100    | Vert.  | 43.5     | 14.2   |         |
| 188.074   | 29.3    | QP  | 16.3    | -21.6 | 24.0     | 37    | 198    | Hori.  | 43.5     | 19.5   |         |
| 234.078   | 33.6    | QP  | 11.6    | -21.0 | 24.2     | 289   | 117    | Hori.  | 46.0     | 21.8   |         |
| 234.090   | 33.7    | QP  | 11.6    | -21.0 | 24.3     | 346   | 100    | Vert.  | 46.0     | 21.7   |         |

CHART: WITH FACTOR

ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN  
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN (CABLE + ATT - GAIN (AMP))

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### -26dB Bandwidth and 99% Occupied Bandwidth

Test place : Ise EMC Lab. No.4 Semi Anechoic Chamber  
Order No. : 11990777H  
Date : 10/14/2017  
Temperature/ Humidity : 25 deg. C / 56 % RH  
Engineer : Hiroyuki Furutaka  
Mode : Tx 125kHz

| Frequency<br>[kHz] | -26dB<br>Bandwidth<br>[kHz] | 99% Occupied<br>Bandwidth<br>[kHz] |
|--------------------|-----------------------------|------------------------------------|
| 125                | 11.836                      | 9.9278                             |



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## APPENDIX 2: Test instruments

### EMI test equipment

| Control No. | Instrument                       | Manufacturer        | Model No                                                                | Serial No  | Test Item | Calibration Date *<br>Interval(month) |
|-------------|----------------------------------|---------------------|-------------------------------------------------------------------------|------------|-----------|---------------------------------------|
| MAEC-04     | Semi Anechoic Chamber(NSA)       | TDK                 | Semi Anechoic Chamber 3m                                                | DA-10005   | RE        | 2017/10/30 * 12                       |
| MOS-15      | Thermo-Hygrometer                | Custom              | CTH-180                                                                 | 1501       | RE        | 2017/01/20 * 12                       |
| MJM-26      | Measure                          | KOMELON             | KMC-36                                                                  | -          | RE        | -                                     |
| COTS-MEMI   | EMI measurement program          | TSJ                 | TEPTO-DV                                                                | -          | RE        | -                                     |
| MTR-10      | EMI Test Receiver                | Rohde & Schwarz     | ESR26                                                                   | 101408     | RE        | 2017/01/12 * 12                       |
| MLPA-01     | Loop Antenna                     | Rohde & Schwarz     | HFH2-Z2                                                                 | 100017     | RE        | 2017/10/11 * 12                       |
| MCC-113     | Coaxial cable                    | Fujikura/Suhner/TSJ | 5D-2W(10m)/SFM141(5m)/421-010(1m)/sucoform141-PE(1m)/RFM-E121(Switcher) | -/04178    | RE        | 2017/07/26 * 12                       |
| MCC-143     | Coaxial Cable                    | UL Japan            | -                                                                       | -          | RE        | 2017/06/12 * 12                       |
| MPA-14      | Pre Amplifier                    | SONOMA INSTRUMENT   | 310                                                                     | 260833     | RE        | 2017/03/27 * 12                       |
| MMM-10      | DIGITAL HiTESTER                 | Hioki               | 3805                                                                    | 051201148  | RE        | 2018/01/09 * 12                       |
| MAEC-02     | Semi Anechoic Chamber(NSA)       | TDK                 | Semi Anechoic Chamber 3m                                                | DA-06902   | RE        | 2017/08/31 * 12                       |
| MOS-22      | Thermo-Hygrometer                | Custom              | CTH-201                                                                 | 0003       | RE        | 2017/12/21 * 12                       |
| MJM-14      | Measure                          | KOMELON             | KMC-36                                                                  | -          | RE        | -                                     |
| MBA-08      | Biconical Antenna                | Schwarzbeck         | VHA9103B                                                                | 08031      | RE        | 2017/09/13 * 12                       |
| MLA-21      | Logperiodic Antenna(200-1000MHz) | Schwarzbeck         | VUSLP9111B                                                              | 911B-190   | RE        | 2017/12/10 * 12                       |
| MCC-12      | Coaxial Cable                    | Fujikura/Agilent    | -                                                                       | -          | RE        | 2017/02/24 * 12                       |
| MAT-07      | Attenuator(6dB)                  | Weinschel Corp      | 2                                                                       | BK7970     | RE        | 2017/11/14 * 12                       |
| MPA-09      | Pre Amplifier                    | Agilent             | 8447D                                                                   | 2944A10845 | RE        | 2017/09/27 * 12                       |
| MMM-01      | Digital Tester                   | Fluke               | FLUKE 26-3                                                              | 78030611   | RE        | 2017/08/07 * 12                       |

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item:

RE: Spurious emission

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124