

RADIO TEST REPORT

Test Report No. 16200663H-A-R1

Customer	NIDEC MOBILITY CORPORATION
Description of EUT	Body Control Module for Keyless Start System
Model Number of EUT	K59S0
FCC ID	OUCK59S0
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	March 10, 2026
Remarks	-

Representative test engineer

Shousei Hamaguchi
Engineer

Approved by

Akihiko Maeda
Leader



CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 26.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For any test report referred in this report, the latest version (including any revisions) is always referred to.
- If the latest version is a revision, it replaces the previous version. See the table below for revisions and versions.

REVISION HISTORY

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	16200663H-A	March 6, 2026	-
1	16200663H-A-R1	March 10, 2026	Addition of antenna identifiers to the model names in the configuration diagram list (Items B to F in Clause 4.2).

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	IEC	International Electrotechnical Commission
AC	Alternating Current	IEEE	Institute of Electrical and Electronics Engineers
AFH	Adaptive Frequency Hopping	IF	Intermediate Frequency
AM	Amplitude Modulation	ILAC	International Laboratory Accreditation Conference
Amp, AMP	Amplifier	ISED	Innovation, Science and Economic Development Canada
ANSI	American National Standards Institute	ISO	International Organization for Standardization
Ant, ANT	Antenna	JAB	Japan Accreditation Board
AP	Access Point	LAN	Local Area Network
ASK	Amplitude Shift Keying	LIMS	Laboratory Information Management System
Atten., ATT	Attenuator	MCS	Modulation and Coding Scheme
AV	Average	MRA	Mutual Recognition Arrangement
BPSK	Binary Phase-Shift Keying	N/A	Not Applicable
BR	Bluetooth Basic Rate	NIST	National Institute of Standards and Technology
BT	Bluetooth	NS	No signal detect.
BT LE	Bluetooth Low Energy	NSA	Normalized Site Attenuation
BW	BandWidth	NVLAP	National Voluntary Laboratory Accreditation Program
Cal Int	Calibration Interval	OBW	Occupied Band Width
CCK	Complementary Code Keying	OFDM	Orthogonal Frequency Division Multiplexing
Ch., CH	Channel	P/M	Power meter
CISPR	Comite International Special des Perturbations Radioelectriques	PCB	Printed Circuit Board
CW	Continuous Wave	PER	Packet Error Rate
DBPSK	Differential BPSK	PHY	Physical Layer
DC	Direct Current	PK	Peak
D-factor	Distance factor	PN	Pseudo random Noise
DFS	Dynamic Frequency Selection	PRBS	Pseudo-Random Bit Sequence
DQPSK	Differential QPSK	PSD	Power Spectral Density
DSSS	Direct Sequence Spread Spectrum	QAM	Quadrature Amplitude Modulation
EDR	Enhanced Data Rate	QP	Quasi-Peak
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QPSK	Quadri-Phase Shift Keying
EMC	ElectroMagnetic Compatibility	RBW	Resolution Band Width
EMI	ElectroMagnetic Interference	RDS	Radio Data System
EN	European Norm	RE	Radio Equipment
ERP, e.r.p.	Effective Radiated Power	RF	Radio Frequency
EU	European Union	RMS	Root Mean Square
EUT	Equipment Under Test	RSS	Radio Standards Specifications
Fac.	Factor	Rx	Receiving
FCC	Federal Communications Commission	SA, S/A	Spectrum Analyzer
FHSS	Frequency Hopping Spread Spectrum	SG	Signal Generator
FM	Frequency Modulation	SVSWR	Site-Voltage Standing Wave Ratio
Freq.	Frequency	TR	Test Receiver
FSK	Frequency Shift Keying	Tx	Transmitting
GFSK	Gaussian Frequency-Shift Keying	VBW	Video BandWidth
GNSS	Global Navigation Satellite System	Vert.	Vertical
GPS	Global Positioning System	WLAN	Wireless LAN
Hori.	Horizontal	WPT	Wireless Power Transfer
ICES	Interference-Causing Equipment Standard	-	-

CONTENTS	PAGE
SECTION 1: Customer Information.....	5
SECTION 2: Equipment Under Test (EUT)	5
SECTION 3: Test Summary	7
SECTION 4: Operation of EUT during testing.....	10
SECTION 5: Radiated emission (Fundamental and Spurious Emission).....	12
SECTION 6: -20 dB Bandwidth.....	14
SECTION 7: 99 % emission bandwidth	14
APPENDIX 1: Test data	15
Radiated Emission (Fundamental and Spurious Emission)	15
Radiated Spurious Emission	20
-20 dB Bandwidth / 99 % emission bandwidth	21
APPENDIX 2: Test instruments	23
APPENDIX 3: Photographs of test setup.....	24
Radiated Emission	24
Worst Case Position	25

SECTION 1: Customer Information

Company Name	NIDEC MOBILITY CORPORATION
Address	6368, Nenjozaka, Okusa, Komaki, Aichi, 485-0802, Japan
Telephone Number	+81-568-78-6159
Contact Person	Takashi Betsui

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	Body Control Module for Keyless Start System
Model Number	K59S0
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	February 2, 2026
Test Date	February 2 to 22, 2026

2.2 Product Description

General Specification

Rating	DC 12 V Typ. (DC 8 V to 16 V)
Operating temperature	Except Antennas: -40 deg. C to 85 deg. C Antennas: -40 deg. C to 90 deg. C

Radio Specification

[LF part]

Equipment Type	Transmitter
Frequency of Operation	125 kHz
Type of Modulation	ASK

[UHF part] *1)

Equipment Type	Receiver
Frequency of Operation	433.92 MHz
IF frequency	251 kHz (Lower heterodyne)

*1) The test of UHF part was performed separately from this test report, and the conformability is confirmed.

This EUT has 5 antenna ports (ANA, ANB, AND, ANL, ANI).
The antennas attached to these antenna ports are following;

[Antenna Type]

LF Antenna (Type B, YB)
LF antenna (Type 1, Y1, G, G-2, YG, YG-2, E, E-2)
LF antenna (Type 3, Y3)
LF antenna (Type 2-2, Y2-2)
LF antenna (Type H, YH)
LF antenna (Type 2, Y2, 2-3, Y2-3)

Each vehicle can be fitted with five antennas, but they can be installed in any combination.

SECTION 3: Test Summary

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.209 Radiated emission limits; general requirements.

3.2 Reference Standards

ANSI/USEMCSC C63.2-2023
ANSI C63.4-2014+C63.4a-2017
ANSI C63.5-2017
ANSI C63.10-2020
ANSI/USEMCSC C63.10/Cor 1-2023
ANSI/USEMCSC C63.10a-2024 (incl. Errata) for ISED
ANSI C63.25.1-2018

3.3 Summary of Test Results

Item	Specification	Results	Remarks
Conducted Emission	<FCC> Section 15.207 <ISED> RSS-Gen 8.8	N/A	*1)
Electric Field Strength of Fundamental Emission	<FCC> Section 15.209 <ISED> RSS-210 8.2 RSS-Gen 8.9	Complied	Radiated
Electric Field Strength of Spurious Emission	<FCC> Section 15.209 <ISED> RSS-210 8.3 RSS-Gen 8.9	Complied	Radiated
-20 dB Bandwidth	<FCC> Reference data <ISED> -	Complied	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

FCC Part 15.31 (e)

This EUT provides stable voltage constantly to RF Parts regardless of input voltage.
Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle.

Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.4 Addition to standard

Item	Specification	Results	Remarks
99 % emission bandwidth	-	-	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.5 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	4.8
10 m			dB	4.7
3 m	30 MHz to 200 MHz	Horizontal	dB	5.0
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	5.5
		Vertical	dB	5.4
	200 MHz to 1000 MHz	Horizontal	dB	5.5
		Vertical	dB	5.5

-20 dB Bandwidth and 99% Occupied Bandwidth, Frequency Tolerance

Item	Unit	Calculated Uncertainty (+/-)
Bandwidth (OBW)	%	0.96
Frequency Readout (Frequency counter)	ppm	0.67
Frequency Readout (Spectrum analyzer frequency readout function)	ppm	2.13

3.6 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber (SAC1)	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber (SAC2)	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber (SAC3)	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room (PR3)	3 m
No.3 shielded room (SR3)	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber (SAC4)	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room (PR4)	3 m
No.4 shielded room (SR4)	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber (SAC5)	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room (MR5)	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room (SR6)	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room (MR6)	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room (SR7)	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room (MR8)	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room (MR9)	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room (SR10)	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room (MR11)	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room (MR12)	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.7 Test data, Test instruments, and Test set up


Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1. Operating Mode(s)

Test mode	Remarks
1) Continuous Transmitting mode (AND)	-
2) Continuous Transmitting mode (ANA)	-
3) Continuous Transmitting mode (ANI)	-
4) Continuous Transmitting mode (ANL)	-
5) Continuous Transmitting mode (ANB)	-
*Power of the EUT was set by the software as follows; Software: Version: 0x5101002F-02 (Date: 2026.01.07, Storage location: EUT memory) *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product. Justification: The system was configured in typical fashion (as a user would normally use it) for testing.	

4.2 Configuration and Peripherals



- * Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.
- * The input voltage (DC 12 V) passes through Item No. H without affecting it and is supplied to the Body Control Module (Item No. A) without any drop in voltage.
- * The EUT does not transmit simultaneously from multiple antennas.
- * Antenna was evaluated with the worst duty respectively.
- * The EUT was set to transmit the data continuously from one antenna as a worst case, not to transmit it randomly from each antenna.
- * The tests were performed with representative antenna combination requested by manufacture.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remark
A	BCM	K59S0	No.100	NIDEC MOBILITY CORPORATION	EUT
B	LF Antenna (ANA)	CGF-S003-D32 (Type Y2-3)	2023/12 No.4	NIDEC MOBILITY CORPORATION	EUT
C	LF Antenna (ANB)	CGF-S002-J2E (Type E-2)	Type E-2 No.01	NIDEC MOBILITY CORPORATION	EUT
D	LF Antenna (AND)	CGF-S002-J0B (Type B)	Type B No.01	NIDEC MOBILITY CORPORATION	EUT
E	LF Antenna (ANL)	CGF-S003-D03 (Type Y3)	2023/12 No.3	NIDEC MOBILITY CORPORATION	EUT
F	LF Antenna (ANI)	CGF-S002-D03 (Type 3)	Type 3 No.01	NIDEC MOBILITY CORPORATION	EUT
G	PUSH START SWITCH	P55R0	5th PSW No.05	NIDEC MOBILITY CORPORATION	-
H	Jig Borad	-	SIM No.01	NIDEC MOBILITY CORPORATION	-

List of Cables Used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	DC Cable	1.0	Unshielded	Unshielded	-
2	Antenna Cable	2.0	Unshielded	Unshielded	ANA Port
3	Antenna Cable	2.0	Unshielded	Unshielded	ANB Port
4	Antenna Cable	1.9	Unshielded	Unshielded	AND Port
5	Antenna Cable	1.9	Unshielded	Unshielded	ANL Port
6	Antenna Cable	1.9	Unshielded	Unshielded	ANI Port
7	Antenna Cable	2.0	Unshielded	Unshielded	-
8	DC and Signal Cable	1.8	Unshielded	Unshielded	-

SECTION 5: Radiated emission (Fundamental and Spurious Emission)

Test Procedure

EUT was placed on the platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[Limit conversion]

The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

[Frequency: From 9 kHz to 30 MHz]

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0 deg., 45 deg., 90 deg., and 135 deg., 180 deg.) and horizontal polarization.

*Refer to Figure 2 about Direction of the Loop Antenna.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

These tests were performed in semi anechoic chamber. Therefore, the measured level of emissions may be higher than if measurements were made without a ground plane. However, test results were confirmed to pass against standard limit.

[Frequency: From 30 MHz to 1 GHz]

The measuring antenna height varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

[Test instruments and test settings]

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz
Antenna Type	Loop	Biconical	Logperiodic

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz
Instrument used	Test Receiver				
Detector	PK / AV	QP	PK / AV	QP	QP
IF Bandwidth	200 Hz	200 Hz	9 kHz	9 kHz	120 kHz
Test Distance	3 m *1)	3 m *1)	3 m *1)	3 m *2)	3 m

*1) Distance Factor: $40 \times \log (3 \text{ m} / 300 \text{ m}) = -80 \text{ dB}$

*2) Distance Factor: $40 \times \log (3 \text{ m} / 30 \text{ m}) = -40 \text{ dB}$

Figure 1: Test Setup






Figure 2: Direction of the Loop Antenna

Side View (Vertical)




Top View (Horizontal)



Antenna was not rotated.

Top View (Vertical)



- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 9 kHz to 1 GHz
Test data : APPENDIX
Test result : Pass

SECTION 6: -20 dB Bandwidth

Test Procedure

The test was measured with a spectrum analyzer.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-20 dB Bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer

Test data : APPENDIX

Test result : Pass

SECTION 7: 99 % emission bandwidth

Test Procedure

The test was measured with a spectrum analyzer.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
99 % emission bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer

Peak hold was applied as Worst-case measurement.

Test data : APPENDIX

Test result : Pass

APPENDIX 1: Test data

Radiated Emission (Fundamental and Spurious Emission)

Mode	Mode 1				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
February 2, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi	Below 30 MHz
February 3, 2026	SAC2	22 deg. C	46 % RH	Nachi Konegawa	Above 30 MHz

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.5	19.7	-73.9	32.3	-	23.0	45.6	22.6	Fundamental
0deg	0.25000	PK	46.6	19.8	-64.1	32.3	-	-30.0	39.6	69.6	
0deg	0.37500	PK	42.1	19.8	-64.2	32.2	-	-34.5	36.1	70.6	
0deg	0.50000	QP	29.6	19.9	-24.2	32.2	-	-6.9	33.6	40.5	
0deg	0.62500	QP	28.7	19.9	-24.1	32.2	-	-7.7	31.7	39.4	
0deg	0.75000	QP	28.1	19.9	-24.1	32.3	-	-8.4	30.1	38.5	Floor Noise
0deg	0.87500	QP	28.1	19.8	-24.1	32.3	-	-8.5	28.7	37.2	Floor Noise
0deg	1.00000	QP	28.1	19.8	-24.1	32.3	-	-8.5	27.6	36.1	Floor Noise
0deg	1.12500	QP	28.1	19.8	-24.1	32.3	-	-8.5	26.5	35.0	Floor Noise
0deg	1.25000	QP	28.0	19.8	-24.1	32.3	-	-8.6	25.6	34.2	Floor Noise
Hori.	33.850	QP	35.0	17.4	6.8	28.6	-	30.6	40.0	9.4	
Hori.	38.160	QP	25.7	15.7	6.9	28.6	-	19.7	40.0	20.3	
Hori.	41.613	QP	39.6	14.5	6.9	28.6	-	32.4	40.0	7.6	
Hori.	93.277	QP	29.9	9.3	7.4	28.4	-	18.2	43.5	25.3	
Hori.	100.481	QP	26.5	10.5	7.5	28.4	-	16.1	43.5	27.4	
Hori.	395.194	QP	32.2	15.6	9.4	28.5	-	28.7	46.0	17.3	
Vert.	33.850	QP	40.6	17.4	6.8	28.6	-	36.2	40.0	3.8	
Vert.	38.160	QP	33.1	15.7	6.9	28.6	-	27.1	40.0	12.9	
Vert.	42.820	QP	46.1	14.0	6.9	28.6	-	38.4	40.0	1.6	
Vert.	100.903	QP	29.8	10.5	7.5	28.4	-	19.4	43.5	24.1	
Vert.	105.630	QP	31.5	11.2	7.5	28.4	-	21.8	43.5	21.7	
Vert.	363.070	QP	34.9	15.2	9.2	28.2	-	31.1	46.0	14.9	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.5	19.7	-73.9	32.3	0.0	23.0	25.6	2.6	Fundamental
0deg	0.25000	PK	46.6	19.8	-64.1	32.3	0.0	-30.0	19.6	49.6	
0deg	0.37500	PK	42.1	19.8	-64.2	32.2	0.0	-34.5	16.1	50.6	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.5	19.7	6.1	32.3	-	103.0	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Radiated Emission (Fundamental and Spurious Emission)

Mode	Mode 2
------	--------

Date	Test site	Temperature	Humidity	Engineer	Measurement Range
February 2, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi	Below 30 MHz
February 3, 2026	SAC2	22 deg. C	46 % RH	Nachi Konegawa	Above 30 MHz

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.8	19.7	-73.9	32.3	-	23.3	45.6	22.3	Fundamental
0deg	0.25000	PK	46.4	19.8	-64.1	32.3	-	-30.2	39.6	69.8	
0deg	0.37500	PK	44.7	19.8	-64.2	32.2	-	-31.9	36.1	68.0	
0deg	0.50000	QP	29.7	19.9	-24.2	32.2	-	-6.8	33.6	40.4	
0deg	0.62500	QP	29.2	19.9	-24.1	32.2	-	-7.2	31.7	38.9	
0deg	0.75000	QP	28.1	19.9	-24.1	32.3	-	-8.4	30.1	38.5	Floor Noise
0deg	0.87500	QP	28.1	19.8	-24.1	32.3	-	-8.5	28.7	37.2	Floor Noise
0deg	1.00000	QP	28.1	19.8	-24.1	32.3	-	-8.5	27.6	36.1	Floor Noise
0deg	1.12500	QP	28.1	19.8	-24.1	32.3	-	-8.5	26.5	35.0	Floor Noise
0deg	1.25000	QP	28.0	19.8	-24.1	32.3	-	-8.6	25.6	34.2	Floor Noise
Hori.	33.666	QP	31.5	17.4	6.8	28.6	-	27.1	40.0	12.9	
Hori.	41.640	QP	37.8	14.5	6.9	28.6	-	30.6	40.0	9.4	
Hori.	51.353	QP	25.4	10.9	7.0	28.5	-	14.8	40.0	25.2	
Hori.	92.678	QP	28.2	9.2	7.4	28.5	-	16.3	43.5	27.2	
Hori.	106.029	QP	29.8	11.3	7.5	28.4	-	20.2	43.5	23.3	
Hori.	395.961	QP	33.8	15.7	9.4	28.5	-	30.4	46.0	15.6	
Vert.	33.424	QP	36.0	17.5	6.8	28.6	-	31.7	40.0	8.3	
Vert.	41.558	QP	43.0	14.5	6.9	28.6	-	35.8	40.0	4.2	
Vert.	52.152	QP	33.4	10.6	7.0	28.5	-	22.5	40.0	17.5	
Vert.	65.571	QP	30.1	6.8	7.2	28.5	-	15.6	40.0	24.4	
Vert.	105.317	QP	33.2	11.2	7.5	28.4	-	23.5	43.5	20.0	
Vert.	387.965	QP	30.9	15.4	9.3	28.4	-	27.2	46.0	18.8	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.8	19.7	-73.9	32.3	0.0	23.3	25.6	2.3	Fundamental
0deg	0.25000	PK	46.4	19.8	-64.1	32.3	0.0	-30.2	19.6	49.8	
0deg	0.37500	PK	44.7	19.8	-64.2	32.2	0.0	-31.9	16.1	48.0	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.8	19.7	6.1	32.3	-	103.3	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Radiated Emission (Fundamental and Spurious Emission)

Mode	Mode 3
------	--------

Date	Test site	Temperature	Humidity	Engineer	Measurement Range
February 2, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi	Below 30 MHz
February 3, 2026	SAC2	22 deg. C	46 % RH	Nachi Konegawa	Above 30 MHz

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	110.0	19.7	-73.9	32.3	-	23.5	45.6	22.1	Fundamental
0deg	0.25000	PK	46.0	19.8	-64.1	32.3	-	-30.6	39.6	70.2	
0deg	0.37500	PK	44.1	19.8	-64.2	32.2	-	-32.5	36.1	68.6	
0deg	0.50000	QP	29.5	19.9	-24.2	32.2	-	-7.0	33.6	40.6	
0deg	0.62500	QP	28.8	19.9	-24.1	32.2	-	-7.6	31.7	39.3	
0deg	0.75000	QP	28.1	19.9	-24.1	32.3	-	-8.4	30.1	38.5	Floor Noise
0deg	0.87500	QP	28.1	19.8	-24.1	32.3	-	-8.5	28.7	37.2	Floor Noise
0deg	1.00000	QP	28.1	19.8	-24.1	32.3	-	-8.5	27.6	36.1	Floor Noise
0deg	1.12500	QP	28.1	19.8	-24.1	32.3	-	-8.5	26.5	35.0	Floor Noise
0deg	1.25000	QP	28.0	19.8	-24.1	32.3	-	-8.6	25.6	34.2	Floor Noise
Hori.	33.836	QP	39.4	17.4	6.8	28.6	-	35.0	40.0	5.0	
Hori.	43.258	QP	33.5	13.9	6.9	28.6	-	25.7	40.0	14.3	
Hori.	46.119	QP	25.5	12.8	7.0	28.6	-	16.7	40.0	23.3	
Hori.	75.549	QP	27.2	6.5	7.3	28.5	-	12.5	40.0	27.5	
Hori.	103.903	QP	24.7	11.0	7.5	28.4	-	14.8	43.5	28.7	
Hori.	379.978	QP	41.8	15.3	9.3	28.3	-	38.1	46.0	7.9	
Vert.	33.836	QP	43.8	17.4	6.8	28.6	-	39.4	40.0	0.6	
Vert.	43.258	QP	41.3	13.9	6.9	28.6	-	33.5	40.0	6.5	
Vert.	46.119	QP	33.7	12.8	7.0	28.6	-	24.9	40.0	15.1	
Vert.	75.549	QP	22.6	6.5	7.3	28.5	-	7.9	40.0	32.1	
Vert.	103.903	QP	26.3	11.0	7.5	28.4	-	16.4	43.5	27.1	
Vert.	379.978	QP	32.4	15.3	9.3	28.3	-	28.7	46.0	17.3	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	110.0	19.7	-73.9	32.3	0.0	23.5	25.6	2.1	Fundamental
0deg	0.25000	PK	46.0	19.8	-64.1	32.3	0.0	-30.6	19.6	50.2	
0deg	0.37500	PK	44.1	19.8	-64.2	32.2	0.0	-32.5	16.1	48.6	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	110.0	19.7	6.1	32.3	-	103.5	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Radiated Emission (Fundamental and Spurious Emission)

Mode	Mode 4
------	--------

Date	Test site	Temperature	Humidity	Engineer	Measurement Range
February 2, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi	Below 30 MHz
February 3, 2026	SAC2	22 deg. C	46 % RH	Nachi Konegawa	Above 30 MHz

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	110.0	19.7	-73.9	32.3	-	23.5	45.6	22.1	Fundamental
0deg	0.25000	PK	46.9	19.8	-64.1	32.3	-	-29.7	39.6	69.3	
0deg	0.37500	PK	43.2	19.8	-64.2	32.2	-	-33.4	36.1	69.5	
0deg	0.50000	QP	29.0	19.9	-24.2	32.2	-	-7.5	33.6	41.1	
0deg	0.62500	QP	28.4	19.9	-24.1	32.2	-	-8.0	31.7	39.7	
0deg	0.75000	QP	28.1	19.9	-24.1	32.3	-	-8.4	30.1	38.5	Floor Noise
0deg	0.87500	QP	28.1	19.8	-24.1	32.3	-	-8.5	28.7	37.2	Floor Noise
0deg	1.00000	QP	28.1	19.8	-24.1	32.3	-	-8.5	27.6	36.1	Floor Noise
0deg	1.12500	QP	28.1	19.8	-24.1	32.3	-	-8.5	26.5	35.0	Floor Noise
0deg	1.25000	QP	28.0	19.8	-24.1	32.3	-	-8.6	25.6	34.2	Floor Noise
Hori.	35.664	QP	29.7	16.7	6.8	28.6	-	24.6	40.0	15.4	
Hori.	45.178	QP	34.0	13.2	7.0	28.6	-	25.6	40.0	14.4	
Hori.	54.418	QP	29.1	9.8	7.1	28.5	-	17.5	40.0	22.5	
Hori.	79.083	QP	26.2	6.9	7.3	28.5	-	11.9	40.0	28.1	
Hori.	109.084	QP	26.7	11.7	7.6	28.4	-	17.6	43.5	25.9	
Hori.	379.978	QP	41.7	15.3	9.3	28.3	-	38.0	46.0	8.0	
Vert.	37.221	QP	33.3	16.1	6.9	28.6	-	27.7	40.0	12.3	
Vert.	45.737	QP	40.5	13.0	7.0	28.6	-	31.9	40.0	8.1	
Vert.	54.362	QP	36.1	9.8	7.1	28.5	-	24.5	40.0	15.5	
Vert.	79.083	QP	27.3	6.9	7.3	28.5	-	13.0	40.0	27.0	
Vert.	109.084	QP	23.7	11.7	7.6	28.4	-	14.6	43.5	28.9	
Vert.	379.978	QP	32.3	15.3	9.3	28.3	-	28.6	46.0	17.4	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	110.0	19.7	-73.9	32.3	0.0	23.5	25.6	2.1	Fundamental
0deg	0.25000	PK	46.9	19.8	-64.1	32.3	0.0	-29.7	19.6	49.3	
0deg	0.37500	PK	43.2	19.8	-64.2	32.2	0.0	-33.4	16.1	49.5	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	110.0	19.7	6.1	32.3	-	103.5	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Radiated Emission (Fundamental and Spurious Emission)

Mode	Mode 5
------	--------

Date	Test site	Temperature	Humidity	Engineer	Measurement Range
February 2, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi	Below 30 MHz
February 3, 2026	SAC2	22 deg. C	46 % RH	Nachi Konegawa	Above 30 MHz

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.8	19.7	-73.9	32.3	-	23.3	45.6	22.3	Fundamental
0deg	0.25000	PK	46.6	19.8	-64.1	32.3	-	-30.0	39.6	69.6	
0deg	0.37500	PK	44.9	19.8	-64.2	32.2	-	-31.7	36.1	67.8	
0deg	0.50000	QP	29.7	19.9	-24.2	32.2	-	-6.8	33.6	40.4	
0deg	0.62500	QP	29.1	19.9	-24.1	32.2	-	-7.3	31.7	39.0	
0deg	0.75000	QP	28.1	19.9	-24.1	32.3	-	-8.4	30.1	38.5	Floor Noise
0deg	0.87500	QP	28.1	19.8	-24.1	32.3	-	-8.5	28.7	37.2	Floor Noise
0deg	1.00000	QP	28.1	19.8	-24.1	32.3	-	-8.5	27.6	36.1	Floor Noise
0deg	1.12500	QP	28.1	19.8	-24.1	32.3	-	-8.5	26.5	35.0	Floor Noise
0deg	1.25000	QP	28.0	19.8	-24.1	32.3	-	-8.6	25.6	34.2	Floor Noise
Hori.	32.810	QP	31.6	17.8	6.8	28.6	-	27.6	40.0	12.4	
Hori.	36.618	QP	28.7	16.3	6.9	28.6	-	23.3	40.0	16.7	
Hori.	43.045	QP	33.9	13.9	6.9	28.6	-	26.1	40.0	13.9	
Hori.	92.512	QP	29.4	9.1	7.4	28.5	-	17.4	43.5	26.1	
Hori.	105.365	QP	31.1	11.2	7.5	28.4	-	21.4	43.5	22.1	
Hori.	395.952	QP	34.7	15.7	9.4	28.5	-	31.3	46.0	14.7	
Vert.	32.850	QP	37.2	17.8	6.8	28.6	-	33.2	40.0	6.8	
Vert.	36.955	QP	34.0	16.2	6.9	28.6	-	28.5	40.0	11.5	
Vert.	42.781	QP	42.3	14.0	6.9	28.6	-	34.6	40.0	5.4	
Vert.	104.890	QP	32.3	11.1	7.5	28.4	-	22.5	43.5	21.0	
Vert.	158.670	QP	24.8	15.4	7.9	28.2	-	19.9	43.5	23.6	
Vert.	451.973	QP	33.3	16.6	9.7	28.9	-	30.7	46.0	15.3	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.8	19.7	-73.9	32.3	0.0	23.3	25.6	2.3	Fundamental
0deg	0.25000	PK	46.6	19.8	-64.1	32.3	0.0	-30.0	19.6	49.6	
0deg	0.37500	PK	44.9	19.8	-64.2	32.2	0.0	-31.7	16.1	47.8	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor


Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.12500	PK	109.8	19.7	6.1	32.3	-	103.3	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Radiated Spurious Emission
(Plot data, Worst case for Spurious Emission)

Mode	Mode 3			
Date	Test site	Temperature	Humidity	Engineer
February 2, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi
February 3, 2026	SAC2	22 deg. C	46 % RH	Nachi Konegawa




-20 dB Bandwidth / 99 % emission bandwidth

Mode	Mode 1 to 5
------	-------------

Date	Test site	Temperature	Humidity	Engineer
February 22, 2026	SAC2	20 deg. C	54 % RH	Shousei Hamaguchi

Mode	Antenna	-20 dB Bandwidth [kHz]	99 % emission bandwidth [kHz]
1	AND	9.254	10.4456
2	ANA	9.489	10.9346
3	ANI	9.565	11.6089
4	ANL	8.507	9.7660
5	ANB	8.374	9.7813

-20 dB Bandwidth / 99 % emission bandwidth



APPENDIX 2: Test instruments

Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	141222	Coaxial Cable	Fujikura,HP,Mini-Circuits,Fujikura	3D-2W(12m)/ 5D-2W(5m)/ 5D-2W(0.8m)/ 5D-2W(1m)	-	02/14/2025	12
RE	141265	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-190	07/22/2025	12
RE	141317	Coaxial Cable	UL-ISE	-	-	09/29/2025	12
RE	141331	Attenuator(6dB)	TME	UFA-01	-	-	-
RE	141427	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103B+BBA9106	08031	07/22/2025	12
RE	141542	Digital Tester	Fluke Corporation	FLUKE 26-3	78030611	08/01/2025	12
RE	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/14/2025	12
RE	141594	Pre Amplifier	Keysight Technologies Inc	8447D	2944A10150	02/19/2025	12
RE	141951	EMI Test Receiver	Rohde & Schwarz	ESR26	101408	05/07/2025	12
RE	141978	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY46180899	05/14/2025	12
RE	142004	AC2_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	07/08/2025	24
RE	142228	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	207745	Coaxial Cable	UL-ISE	-	-	03/19/2025	12
RE	244707	Thermo-Hygrometer	HIOKI E. E. CORPORATION	LR5001	231202102	01/13/2026	12
RE	252514	Active Loop Antenna	Schwarzbeck Mess-Elektronik OHG	FMZB 1519-60 D	1519-60 D-067	10/14/2025	12
RE	266727	Attenuator	Huber+Suhner	6806_N-50-1	40701613	07/09/2025	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated Emission