



Product Service

**Choose certainty.
Add value.**

Report On

RF Exposure Assessment of the
Microlise Ltd
MTU4 Internal Antenna Vehicle Tracking and Telematics Unit

FCC ID: OUUMTU4



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuvps.co.uk

REPORT ON

RF Exposure Assessment of the
Microlise Ltd
MTU4 Internal Antenna Vehicle Tracking and Telematics Unit

Document 75916503 Report 08 Issue 3

July 2012

PREPARED FOR

Microlise Ltd
Farrington Way
Eastwood
Nottingham
NG16 3AG

PREPARED BY


M Whiting
Project Manager

APPROVED BY


M Jenkins
Authorised Signatory

DATED

23 July 2012

This report has been up issued to Issue 3 to add the Antenna Type and correct FCC ID.



Product Service

CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Product Information 7
1.4	Summary 7
2	TEST DETAILS 8
2.1	Rationale for Assessment of the RF Exposure 9
2.2	Defined Limits 10
2.3	Establishing Wavelength and 1/4 Wavelength 10
2.4	Far Field Calculations 11
3	DISCLAIMERS AND COPYRIGHT 12
3.1	Disclaimers and Copyright 13



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Microlise Ltd
MTU4 Internal Antenna Vehicle Tracking and Telematics Unit



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Microlise Ltd MTU4 Internal Antenna Vehicle Tracking and Telematics Unit to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Microlise Ltd
Manufacturer	Microlise Ltd
Manufacturing Description	Vehicle Tracking and Telematics Unit
Model Number(s)	MTU4-A Internal Antenna
Test Specification/Issue/Date	OET Bulletin 65 Edition 97-01 August 1997 RSS-102 Issue 4 March 2010
Related Document(s)	Council Recommendation 1999/519/EC:1999 FCC CFR 47 Part 1: 2010 FCC CFR 47 Part 2.1091: 2010 Health Canada's Safety Code 6 ICNIRP 1998 National Council on Radiation Protection and Measurements (NRP) - Report No. 86(1986)



Product Service

1.2 BRIEF SUMMARY OF RESULTS

1.2.1 General Public Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 0.2 m (20cm)	General Public Exposure Limit	Application
0.741	2000	S	2.95 W/m ²	4.400 W/m ²	ICNIRP
		S	0.295 mW/cm ²	0.587 mW/cm ²	FCC 47 CFR § 1.1310
		S	2.95 W/m ²	5.867 W/m ²	Canada's RF Safety Code 6
		E	33.35 V/m	40.789 V/m	ICNIRP
		E	33.35 V/m	N/A V/m	FCC 47 CFR § 1.1310
		E	33.35 V/m	47.019 V/m	Canada's RF Safety Code 6
		H	0.09 A/m	0.110 A/m	ICNIRP
		H	0.09 A/m	N/A A/m	FCC 47 CFR § 1.1310
		H	0.09 A/m	0.125 A/m	Canada's RF Safety Code 6

The calculations have shown that they **meet** the General Public Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines and the Health Canada's RF exposure guideline Safety Code 6 limits at **20cm**, the point of investigation.



Product Service

1.2.2 Occupational Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 0.2 m (20cm)	Occupational Exposure Limit	Application
0.741	2000	S	2.95 W/m ²	22.000 W/m ²	ICNIRP
		S	0.295 mW/cm ²	2.933 mW/cm ²	FCC 47 CFR § 1.1310
		S	2.95 W/m ²	29.333 W/m ²	Canada's RF Safety Code 6
		E	33.35 V/m	88.994 V/m	ICNIRP
		E	33.35 V/m	N/A V/m	FCC 47 CFR § 1.1310
		E	33.35 V/m	105.013 V/m	Canada's RF Safety Code 6
		E	33.35 V/m	91.071 V/m	ARPANSA
		H	0.09 A/m	0.237 A/m	ICNIRP
		H	0.09 A/m	N/A A/m	FCC 47 CFR § 1.1310
		H	0.09 A/m	0.279 A/m	Canada's RF Safety Code 6

The calculations have shown that they **meet** the Occupational Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines and the Health Canada's RF exposure guideline Safety Code 6 limits at **20 cm**, the point of investigation.



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Attestation

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields (10 MHz - 300 MHz) - General public. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

1.3.2 Technical Description

The Equipment under test was a Microlise Ltd MTU4 Internal Antenna Vehicle Tracking and Telematics Unit. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the MTU4 Internal Antenna Vehicle Tracking and Telematics Unit to demonstrate compliance with the applied test specification(s) the sample assessed was found to comply with the requirements of the applied rules.

1.4 SUMMARY

The RF exposure assessment is based upon the following criteria:

The MTU4 Internal Antenna Vehicle Tracking and Telematics Unit operates in the frequency range of 880 – 915 MHz.

Gain	-1.3 dBi
Power	2 W
Distance	0.2 m (20 cm)
Duty Cycle	100%

As the Microlise Ltd MTU4 Internal Antenna Vehicle Tracking and Telematics Unit incorporates **five transmitters** the assessment has been carried out based on the worst case parameters. All calculations are therefore based on the **GSM850** frequency band only.

S Values (Power Flux) for each Band were as follows:

GSM 850: 2.95W/m²
GSM 900: 2.95W/m²
GSM1800: 1.41W/m²
GSM1900: 1.41W/m²
Bluetooth: 0.000W/m²

For simultaneous transmit the S Values of each frequency band are divided by the limit and then added together, if the results is less than 1 then they will be compliant.

GSM 850: $2.95/4.121 = 0.716$
GSM1900: $1.41/8.551 = 0.165$
Bluetooth: $0.000/22 = 0$

GSM 850 + Bluetooth

$0.716 + 0 = 0.716$

GSM 1900 + Bluetooth

$0.165 + 0 = 0.165$

0.716 and 0.165 are both less than 1 and therefore compliant.



Product Service

SECTION 2

TEST DETAILS

2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in EN50383:2002 Clause 5.2; E-field or H-field calculation. The method of calculation used is defined in EN50383:2002; Clause 8.2.2, 8.2.3 and 8.2.4.

The calculated values have been compared with limits provided in the ICNIRP guidelines.

Calculations can be made in three separate regions, based on distance from the antenna. These are called:

- far-field region,
- radiating near-field region,
- reactive near-field region.

The theory that defines these regions is given in EN50383:2002 Annex A.

Far-field region

As shown in EN50383 Annex A, the far-field calculations are accurate when the distance, r , from an antenna of length D to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

Where, r is the distance from the antenna to the point of investigation.

Radiating near-field region

The radiating near-field region of an antenna of length D as shown in EN50383 Annex A, this region is defined by

$$\frac{\lambda}{4} < r < \frac{2D^2}{\lambda}$$

Reactive near-field region

The reactive near-field region of an antenna as shown in EN50383 Annex A, this region is defined by

$$r \leq \frac{\lambda}{4}$$

Where, r is the distance from the antenna to the point of investigation.

Recommend $\lambda/4$ as the boundary between the radiated near-field and reactive near-field for RF exposure compliance assessment.



Product Service

2.2 DEFINED LIMITS

Normative Reference: ICNIRP Advice on Limiting Exposure to Electromagnetic Fields (0-300GHz). Table A4, Reference Levels for General Public Exposure to Time Varying Electric & Magnetic Fields. Vol 15 No.2. 2004. The defined limits are in accordance with 47 CFR § 1.1310 Radiofrequency radiation exposure limits.

Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 824.2 MHz		
Power density (W/m ²)	= 4.121	ICNIRP
Power density (mW/cm ²)	= 0.549	FCC 47 CFR § 1.1310
Power density (W/m ²)	= 5.495	Canada's RF Safety Code 6
E-Field (Vm-1)	= 39.475	ICNIRP
E-Field (Vm-1)	= N/A	FCC 47 CFR § 1.1310
E-Field (Vm-1)	= 45.504	Canada's RF Safety Code 6
H-Field (Am-1)	= 0.106	ICNIRP
H-Field (Am-1)	= N/A	FCC 47 CFR § 1.1310
H-Field (Am-1)	= 0.121	Canada's RF Safety Code 6

Reference levels for occupational exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 824.2 MHz		
Power density (W/m ²)	= 20.605	ICNIRP
Power density (mW/cm ²)	= 2.747	FCC 47 CFR § 1.1310
Power density (W/m ²)	= 27.473	Canada's RF Safety Code 6
E-Field (Vm-1)	= 86.127	ICNIRP
E-Field (Vm-1)	= N/A	FCC 47 CFR § 1.1310
E-Field (Vm-1)	= 101.629	Canada's RF Safety Code 6
H-Field (Am-1)	= 0.230	ICNIRP
H-Field (Am-1)	= N/A	FCC 47 CFR § 1.1310
H-Field (Am-1)	= 0.270	Canada's RF Safety Code 6

2.3 ESTABLISHING WAVELENGTH AND 1/4 WAVELENGTH

Frequency (MHz)	$\lambda = \frac{3 \times 10^8}{f}$		$\frac{\lambda}{4}$	
	m	cm	m	cm
824.2	0.363989322979859	36.3989322979859	0.0909973307449648	9.09973307449648
836.7	0.358551452133381	35.8551452133381	0.0896378630333453	8.96378630333453
849.2	0.353273669335845	35.3273669335846	0.0883184173339614	8.83184173339614



Product Service

2.4 FAR FIELD CALCULATIONS

The following calculations are based on: -1.3 dBi gain antenna

P = 2 (Power (Watts)) or 2000 (Power milliwatts)
G = 0.741 (Numeric Gain)
r = 20 (Distance (centimetres)) or 0.2 (Distance (meters))

The power flux:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

S = 2.95 W/m²
S = 0.295 mW/cm²

The electric field strength:

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

E = 33.35 V/m

The magnetic field strength:

$$H = \frac{E}{\eta_0}$$

H = 0.09 A/m

The calculations meet the General Public Exposure Levels described in the ICNIRP Guidelines.
The calculations meet the General Public Exposure Levels described in the FCC 47CFR§1.1310.
The calculations meet the General Public Exposure Levels described in the Canada's RF Safety Code 6.

The calculations meet the Occupational Exposure Levels described in the ICNIRP Guidelines.
The calculations meet the Occupational Exposure Levels described in the FCC 47CFR§1.1310
The calculations meet the Occupational Exposure Levels described in the Canada's RF Safety Code 6



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service Limited

© 2012 TÜV SÜD Product Service Limited