

FCC Part 15C Compliance Test Report

Test Report no.:	Tre_FCC_0630_04.doc	Date of Report:	25.07.2006
Number of pages:	28	Customer's Contact person:	Robert W. Müller
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation Rensingstrasse 15 44807 BOCHUM GERMANY Tel. +49 234 984 0
FCC listing no.:	94436		
IC recognition no.:	3608		
Tested devices/ accessories:	Hands-free Unit HF-20, Microphone MP-2, Loudspeaker SP-3, System cable (pop-port) CA-76, Input device CU-8, Power cable PCU-4		
FCC ID:	OW3HF-20	IC:	661AA-HF20
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), IC standards RSS-GEN and RSS-210. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			
	Juho Tuohino, System Manager		

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	25.07.2006
Testing completed	26.07.2006
The customer's contact person	Robert W. Müller
Test Plan referred to	T:\Projects\accessor\HF-20\TestPlan_RS\RS_test_plan_HF-20.xls
Notes	-
Document name	T:\Projects\accessor\HF-20\EMC\Results\FCC\Tre_FCC_0630_04.doc

1.1. EUT and Accessory Information

The EUT is a Bluetooth device. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Handsfree Unit	HF-20	052682700001208	0902	-	6.290	40776
Handsfree Unit	HF-20	052682700001206	0902	-	6.290	40777
Speaker	SP-3	-	-	-	-	40778
Input device	CU-8	-	-	-	-	40779
Microphone	MP-2	-	-	-	-	40780
System cable	CA-76	-	-	-	-	40781
Power cable	PCU-4	-	-	-	-	40782

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (2)	Peak output power	Passed
15.247(c)	A8.5	Band edge compliance of RF emissions	Passed
15.247(c)	A8.5	Spurious RF conducted emissions	Passed
15.247(c), 15.209	A8.5	Spurious radiated emissions	Passed
15.207	7.2.2	AC powerline conducted emissions	-
15.247(a)(1)	A8.1 (1)	20 dB bandwidth	Passed
15.247(a)(1)	A8.1 (2)	Carrier frequency separation	Passed
15.247(a)(1)(iii)	A8.1 (4)	Number of hopping frequencies	Passed
15.247(a)(1)(iii)	A8.1 (4)	Time of occupancy	Passed

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Tampere Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Test setups.....	5
2.1. Conducted RF test setup	5
2.2. AC powerline conducted emissions test setup.....	5
2.3. Spurious radiated emissions test setup	5
3. Peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2)).....	6
3.1. Test method and limit.....	6
3.2. Bluetooth Test results	7
4. Band edge compliance of RF emissions (FCC §15.247(c), RSS-210 A8.5)	9
4.1. Test method and limit.....	9
4.2. Bluetooth Test results	10
5. Spurious RF conducted emissions (FCC §15.247(c), RSS-A8.5).....	13
5.1. Test method and limit.....	13
5.2. Bluetooth Test results	14
6. Spurious radiated emissions (FCC §15.247(c), §15.209, RSS-210 A8.5).....	16
6.1. Test method and limit.....	16
6.2. Bluetooth Test results	17
7. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (1))	19
7.1. Test method and limit.....	19
7.2. Bluetooth Test results	20
8. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (2))	22
8.1. Test method and limit.....	22
8.2. Bluetooth Test results	23
9. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))	24
9.1. Test method and limit.....	24
9.2. Bluetooth Test results	25
10. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))	26
10.1. Test method and limit.....	26
10.2. Bluetooth test results.....	27
11. Test Equipment	28


11.1.	Conducted measurements	28
11.2.	Radiated measurements	28

2. Test setups


2.1. Conducted RF test setup



2.2. AC powerline conducted emissions test setup



2.3. Spurious radiated emissions test setup



3. Peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

3.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5	≤ 1	≤ 30

3.2. Bluetooth Test results


3.2.1 GSKF modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	1.40	1.380	PASSED
40 / 2442	0.40	1.096	PASSED
78 / 2480	0.50	1.122	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz)



Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz)



4. Band edge compliance of RF emissions (FCC §15.247(c), RSS-210 A8.5)

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

4.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit Average [dBμV/m]	Limit Peak [dBμV/m]
Below 2390 and above 2483.5	≤ 54	≤ 74

4.2. Bluetooth Test results

4.2.1 GFSK modulation, PRBS packet type


Average (RBW: 1 MHz)

Channel / f_c [MHz]	E [dB μ V/m]	Result
0 / 2402	38.80	Passed
78 / 2480	43.05	Passed
Hopping on, low end	29.80	Passed
Hopping on, high end	32.29	Passed


Peak (RBW: 1 MHz)

Channel / f_c [MHz]	E [dB μ V/m]	Result
0 / 2402	51.73	Passed
78 / 2480	59.49	Passed
Hopping on, low end	51.83	Passed
Hopping on, high end	58.19	Passed


Channel 0 / 2402 MHz




Channel 78 / 2480 MHz



Hopping on, low end



Hopping on, high end



5. Spurious RF conducted emissions (FCC §15.247(c), RSS-A8.5)

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

5.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	≤ -20

5.2. Bluetooth Test results


5.2.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Frequency [MHz]	P [dBc]	Result
4803.846154	-43.313792	PASSED
7283.173077	-45.713792	PASSED
7500.000000	-45.513792	PASSED

Channel 40 / 2442 MHz



Frequency [MHz]	P [dBc]	Result
4883.974359	-39.003771	PASSED
7292.788462	-44.803771	PASSED
23894.230769	-32.903771	PASSED

Channel 78 / 2480 MHz



Frequency [MHz]	P [dBc]	Result
4959.935897	-38.113940	PASSED
7275.961538	-43.913940	PASSED
7500.000000	-44.213940	PASSED

6. Spurious radiated emissions (FCC §15.247(c), §15.209, RSS-210 A8.5)

EUT with DUT number	HF-20 #40777
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	26.07.2006
Measured by	Juho Tuohino

6.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 – 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

6.2. Bluetooth Test results

6.2.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	52.50	421.70	53.80	-1.30	HORIZONTAL	Passed
7206.000000	41.90	124.45	39.90	2.00	VERTICAL	Passed

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	43.30	146.22	44.60	-1.30	HORIZONTAL	Passed
7206.000000	29.50	29.85	27.50	2.00	HORIZONTAL	Passed

Channel 40 / 2442 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4883.769539	53.90	495.45	55.50	-1.60	HORIZONTAL	Passed
7325.653307	44.60	169.82	41.90	2.70	HORIZONTAL	Passed
7411.327655	43.70	153.11	40.40	3.30	HORIZONTAL	Passed
7436.367735	43.20	144.54	40.00	3.20	HORIZONTAL	Passed
17998.989980	56.10	638.26	34.60	21.50	HORIZONTAL	Passed

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4883.769539	43.70	153.11	45.30	-1.60	HORIZONTAL	Passed
7323.153307	30.20	32.36	27.50	2.70	HORIZONTAL	Passed
7410.827655	30.70	34.28	27.40	3.30	HORIZONTAL	Passed
7431.867735	30.60	33.88	27.40	3.20	HORIZONTAL	Passed
17991.489980	42.80	138.04	21.30	21.50	HORIZONTAL	Passed

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	53.40	467.74	54.40	-1.00	HORIZONTAL	Passed
7440.000000	44.30	164.06	41.10	3.20	HORIZONTAL	Passed

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	43.60	151.36	44.60	-1.00	HORIZONTAL	Passed
7440.000000	31.10	35.89	27.90	3.20	HORIZONTAL	Passed

7. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (1))

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

7.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements


Limit [MHz]
N/A

7.2. Bluetooth Test results


7.2.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	791.667	PASSED
40 / 2442	794.872	PASSED
78 / 2480	791.667	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz



Channel 78 / 2480 MHz



8. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (2))

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

8.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or 2/3 of the 20 dB bandwidth

8.2. Bluetooth Test results

8.2.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1001.603	PASSED

Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



9. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

9.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

9.2. Bluetooth Test results

9.2.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
79.00	PASSED

Hopping on, number of hopping frequencies



10. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))

EUT with DUT number	HF-20 #40776
Accessories with DUT numbers	SP-3 #40778, CU-8 #40779, MP-2 #40780, CA-76 #40781, PCU-4 #40782
Operation Voltage [V] / [Hz]	13.8 / DC
Result	Passed
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 45 / 1015.5
Date of measurements	25.07.2006
Measured by	Timo Raiskio

10.1. Test method and limit

The measurement is made according to FCC rules part 15.247 and IC standard RSS-210 as follows:

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
≤ 0.4

10.2. Bluetooth test results


10.2.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μ s]	Time of occupancy [s]	Result
172.0	449	0.077179	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz



Hopping on, duration of one transmission, channel 40 / 2442 MHz



11. Test Equipment

11.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM37610	Spectrum analyzer	FSU	R&S	15C,22/24
TM37678	Radio communication tester	CMU-200	R&S	15C,22/24
	Attenuator 10 dB	6251.17.A	Huber+Suhner AG	15C,22/24
TM22901	Step attenuator 110dB	8496A	Agilent	15C,22/24
TM37499	Power splitter	11667A	Agilent	15C,22/24
	Temperature chamber	VT4002	Vötsch	15C,22/24
TM38112	DC power supply	6632A	Agilent	15C,22/24
TM38111	Multimeter	34401A	Agilent	15C,22/24
TM38845	EMI receiver	ESI 40	R&S	15B,15C
TM37773	Radio communication tester	CMU-200	R&S	15B,15C
TM38631	Signal generator	83640L	Agilent	15B,15C
TM38114	DC power supply	6632A	Agilent	15B,15C
TM22835	Multimeter	87	Fluke	15B,15C
TM30600	Pulse Limiter	ESH3-Z2	R&S	15B,15C
TM26490	LISN 50 µH	ESH3-Z5/	R&S	15B,15C
TM30636	LISN 50 µH	L2-16/	PMM	15B,15C

11.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30599	3m semi-anechoic chamber		TDK	15B,15C, 22/24
TM38845	EMI receiver	ESI 40	R&S	15B,15C, 22/24
TM37498	Preamplifier	AMF-5D-020180-26-10P	MITEQ	15B,15C, 22/24
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	MITEQ	15B,15C, 22/24
TM37516	Biconilog antenna	HL562	R&S	15B,15C, 22/24
TM26496	Double ridged waveguide antenna	3115	EMCO	15B,15C, 22/24
TM39158	Horn antenna	3116	EMCO	15B,15C, 22/24
TM26492	Reference dipole set	UHAP/VHAP	Schwarzbeck	15B,15C, 22/24
TM37501	Dipole antenna	3125-870	EMCO	22/24
TM37502	Dipole antenna	3125-1880	EMCO	22/24
TM37773	Radio communication tester	CMU-200	R&S	15B,15C, 22/24
TM38631	Signal generator	83640L	Agilent	15B,15C, 22/24
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	15B,15C, 22/24
	High pass filter	WHK2010-10SS	Trilithic	15B,15C, 22/24
	Low pass filter	WLK1750-10SS	Trilithic	15B,15C, 22/24
TM26511	Tunable notch filter	WRCA870	Wainwright	22/24
TM38215	Tunable notch filter	WRCD1850/1910-0.2/40	Wainwright	22/24
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30	Wainwright	15C
TM30642	Turntable controller	HD-100	Deisel	15B,15C, 22/24
TM26500	Turntable	DS412	Deisel	15B,15C, 22/24
TM38842	Antenna mast controller	2090	EMCO	15B,15C, 22/24
TM38843	Antenna mast	2075	EMCO	15B,15C, 22/24
TM38114	DC power supply	6632A	Agilent	15B,15C, 22/24
TM22835	Multimeter	87	Fluke	15B,15C, 22/24