



Engineering Solutions & Electromagnetic Compatibility Services

**FCC & IC Certification Report for
FCC Part 15.247 & Industry Canada RSS-247**

Test Lab: Rhein Tech Laboratories, Inc. 360 Herndon Parkway Suite 1400 Herndon, VA 20170 E-Mail: atcbinfo@rheintech.com		Applicant: Harris Corporation 221 Jefferson Ridge Parkway Lynchburg, VA 24501 Tel: 434-455-9290	
FCC ID/ IC	OWDTR-0145-E 3636B-0145	Test Report Date:	February 9, 2016
Platform	N/A	RTL Work Order #	2015216
Model	XL-200P (International)	RTL Quote #	QRTL15-216B
American National Standard Institute	ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices		
FCC Classification	DTS – Part 15 Digital Transmission System		
FCC Rule Part(s)/Guidance	FCC Rules Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz Direct Sequence System (10/01/2014)		
Industry Canada	RSS-247 Issue 1 Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSS) and Licence-Exempt Local Area Network (LE-LAN) Devices		
Digital Interface Information	Digital Interface was found to be compliant		
Frequency Range (MHz)	Output Power (W)*	Frequency Tolerance	Emission Designator
2402 - 2480	0.0069	N/A	517KFXD

* power is conducted

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this test report. No modifications were made to the equipment during testing in order to achieve compliance with these standards. Furthermore, there was no deviation from, additions to, or exclusions from, the applicable parts of FCC Part 2, FCC Part 15, Industry Canada RSS-247, RSS-Gen, and ANSI C63.10.

Signature: 

Date: February 9, 2016

Typed/Printed Name: Desmond A. Fraser

Position: President

This report may not be reproduced, except in full, without the full written approval of Rhein Tech Laboratories, Inc. and Harris Corporation. Test results relate only to the item(s) tested.

These test(s) are accredited under Rhein Tech Laboratories, Inc. ISO/IEC 17025 accreditation issued by the ANSI-ASQ National Accreditation Board. Refer to certificate and scope of accreditation AT-1445.

Table of Contents

1	General Information	5
1.1	Scope	5
1.2	Description of EUT	5
1.3	Test Facility(.....	5
1.4	Related Submittal(s)/Grant(s)	5
1.5	Modifications	5
2	Test Information	6
2.1	Description of Test Modes	6
2.2	Exercising the EUT	6
2.3	Test Result Summary	6
2.4	Test System Details	7
2.5	Configuration of Tested System	7
3	Peak Output Power - 15.247(b)(3); IC RSS-247 5.4(4), RSS-Gen 6.12	8
3.1	Power Output Test Procedure	8
3.2	Peak Output Power Test Data	8
4	Peak Power Spectral Density – FCC 15.247(e); IC RSS-247 5.2(2)	12
4.1	Peak Spectral Density Test Procedure	12
4.2	Peak Spectral Density Test Data	12
5	Antenna Conducted Spurious Emissions – FCC 15.247(d), RSS-247 5.5	16
5.1	Antenna Conducted Spurious Emissions Test Procedure	16
5.2	Antenna Conducted Spurious Emissions Test Data	16
6	Compliance with the Band Edge – FCC 15.247(d); RSS-247 5.5	19
6.1	Band Edge Test Procedure	19
6.2	Band Edge Test Results	20
6.2.1	Lower Band Edge – Plots	20
6.2.2	Upper Band Edge Plots	22
7	Bandwidth – FCC 15.247(a)(2); RSS-247 5.2(1)	24
7.1	6 dB Bandwidth Test Procedure	24
7.2	Bandwidth Test Results	24
8	Radiated Emissions - 15.209; RSS-247 2.2; RSS-Gen 6.13/7.1	28
8.1	Limits of Radiated Emissions Measurement	28
8.2	Radiated Emissions Measurement Test Procedure	28
8.3	Radiated Emissions Test Results	30
8.3.1	Unintentional Radiated Emissions Test Data	30
8.3.2	Spurious/Harmonics Radiated Emissions Test Data	31
9	Conclusion	32

Figure Index

Figure 2-1:	Configuration of System Under Test.....	7
-------------	---	---

Table Index

Table 2-1:	Channels Tested	6
Table 2-2:	Test Result Summary – FCC Part 15 Subpart C (Section 15.247) & IC.....	6
Table 2-3:	Equipment Under Test	7
Table 2-4:	Support Equipment.....	7
Table 3-1:	Power Output Test Equipment	8
Table 3-2:	Peak Output Power Test Data	8
Table 4-1:	Power Spectral Density Test Equipment.....	12
Table 4-2:	Peak Spectral Density Test Data	12
Table 5-1:	Antenna Conducted Spurious Emissions Test Equipment	16
Table 6-1:	Band Edge Test Equipment	19
Table 7-1:	6 dB Bandwidth Test Equipment.....	24
Table 7-2:	6 dB Bandwidth Test Data	24
Table 8-1:	Radiated Emissions Test Equipment	29
Table 8-2:	Digital Radiated Emissions Test Data.....	30
Table 8-3:	Peak Radiated Emissions Spurious/Harmonics – 2402 MHz	31
Table 8-4:	Average Radiated Emissions Spurious/Harmonics – 2402 MHz	31
Table 8-5:	Peak Radiated Emissions Spurious/Harmonics - 2440 MHz.....	31
Table 8-6:	Average Radiated Emissions Spurious/Harmonics – 2440 MHz	31
Table 8-7:	Peak Radiated Emissions Spurious/Harmonics - 2480 MHz.....	32
Table 8-8:	Average Radiated Emissions Spurious/Harmonics – 2480 MHz	32

Plot Index

Plot 3-1:	Peak Output Power – 2402 MHz.....	9
Plot 3-2:	Peak Output Power – 2440 MHz.....	10
Plot 3-3:	Peak Output Power – 2480 MHz.....	11
Plot 4-1:	Peak Spectral Density – 2402 MHz	13
Plot 4-2:	Peak Spectral Density – 2440 MHz	14
Plot 4-3:	Peak Spectral Density – 2480 MHz	15
Plot 5-1:	Antenna Conducted Spurious Emissions – 2402 MHz	16
Plot 5-2:	Antenna Conducted Spurious Emissions – 2440 MHz	17
Plot 5-3:	Antenna Conducted Spurious Emissions – 2480 MHz	18
Plot 6-1:	Lower Band Edge - Peak	20
Plot 6-2:	Lower Band Edge – Average	21
Plot 6-3:	Upper Band Edge – Peak	22
Plot 6-4:	Upper Band Edge - Average	23
Plot 7-1:	6 dB Bandwidth – 2402 MHz.....	25
Plot 7-2:	6 dB Bandwidth – 2440 MHz.....	26
Plot 7-3:	6 dB Bandwidth – 2480 MHz.....	27

Appendix Index

Appendix A:	FCC Part 1.1307, 1.1310, 2.1091, 2.1093; IC RSS-Gen: RF Exposure.....	33
Appendix B:	Test Photographs	34

Photograph Index

Photograph 1:	Radiated Emissions Testing – Front View >1 GHz	34
Photograph 2:	Radiated Emissions Testing – Back View >1 GHz	35
Photograph 3:	Radiated Emissions Testing – Front View <1 GHz	36
Photograph 4:	Radiated Emissions Testing – Back View <1 GHz	37

1 General Information

1.1 Scope

This is an original FCC and Industry Canada certification application report.

1.2 Description of EUT

Equipment Under Test	XL-200P (International) Multi-Band Portable Radio
Power Supply	7.5 VDC battery
Modulation Type	FSK
Frequency Range	2402 - 2480 MHz
Antenna Type	Internal Chip

1.3 Test Facility(

The open area test site and conducted measurement facility used to collect the radiated data is located at 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing.

1.4 Related Submittal(s)/Grant(s)

This certification application includes an Industry Canada Family Certification application, which includes 8 model numbers under IC: 3636B-0145:

XL-PFM2M	XL-PFM2Y	XL-PFM2B	XL-PFM2G
XL-PPM2M	XL-PPM2Y	XL-PPM2B	XL-PPM2G

1.5 Modifications

None.

2 Test Information

2.1 Description of Test Modes

In accordance with FCC 15.31(m), and because the EUT utilizes an operating band greater than 10 MHz, the following frequencies were tested:

Table 2-1: Channels Tested

Channel	Frequency
Low	2402
Middle	2440
High	2480

2.2 Exercising the EUT

The EUT was supplied with test software instructions to change channels, with a high, mid, and low channel for testing. The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The EUT was provided with software to continuously transmit during testing. The carrier was also checked to verify that information was being transmitted. There were no deviations from the test standard(s) and/or methods. The test results reported relate only to the item tested.

2.3 Test Result Summary

Table 2-2: Test Result Summary – FCC Part 15 Subpart C (Section 15.247) & IC

Test	FCC Reference	IC Reference	Result
AC Power Conducted Emissions	FCC 15.207	RSS-Gen 8.8	Pass
Radiated Emissions	FCC 15.209	RSS-247 5.5; RSS-Gen 6.13/7.1	Pass
Maximum Peak Power Output	FCC 15.247(b)(3)	RSS-247 5.4(4), RSS-Gen 6.12	Pass
Peak Power Spectral Density	FCC 15.247(e)	RSS-247 5.2(2)	Pass
Antenna Conducted Spurious Emissions	FCC 15.247(d)	RSS-247 5.5, RSS-Gen 6.13	Pass
Band Edge Measurement	FCC 15.247(d)	RSS-247 5.5	Pass
6 dB Bandwidth	FCC 15.247(a)(2)	RSS-247 5.2(1)	Pass

2.4 Test System Details

The test samples were received on December 21, 2015. The FCC identifiers for all applicable equipment, plus descriptions of all cables used in the tested system, are identified in the following table.

Table 2-3: Equipment Under Test

Part	Manufacturer	Model	Serial Number	FCC ID	Cable Description	RTL Bar Code
Transceiver (conducted port)	Harris Corporation	XL-200P (International)	A40300000215	OWDTR-0145-E	N/A	21725
Transceiver	Harris Corporation	XL-200P (International)	A40304000045	OWDTR-0145-E	N/A	21965

Table 2-4: Support Equipment

Part	Manufacturer	Model	Serial Number	FCC ID	Cable Description	RTL Bar Code
Battery Eliminator	Harris Corporation	N/A	N/A	N/A	0.5m unshielded	21553
UHF Antenna	Harris Corporation	N/A	N/A	N/A	N/A	21922
Power Supply	Alinco	DM-33MVT 32A	1638	N/A	N/A	901124
Audio Breakout	Harris Corporation	12082-7980-01	N/A	N/A	.8m unshielded I/O	20599

2.5 Configuration of Tested System




Figure 2-1: Configuration of System Under Test

3 Peak Output Power - 15.247(b)(3); IC RSS-247 5.4(4), RSS-Gen 6.12

3.1 Power Output Test Procedure

A SMA connector provided a port for measurement using the automated channel power measurement on the spectrum analyzer, for the low, mid, and high channels.

Table 3-1: Power Output Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/16

3.2 Peak Output Power Test Data

Table 3-2: Peak Output Power Test Data


Emission Frequency (MHz)	Power Measured (dBm)	Power Measured (W)
2402	8.0	0.0063
2440	8.4	0.0069
2480	8.3	0.0068



Plot 3-2: Peak Output Power – 2440 MHz



Plot 3-3: Peak Output Power – 2480 MHz



Test Personnel:

Dan Baltzell
Test Engineer

Signature

December 22, 2015
Date of Test

4 Peak Power Spectral Density – FCC 15.247(e); IC RSS-247 5.2(2)

4.1 Peak Spectral Density Test Procedure

Digitally modulated systems shall have conducted peak power spectral density of 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Table 4-1: Power Spectral Density Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/16

4.2 Peak Spectral Density Test Data


Table 4-2: Peak Spectral Density Test Data

Channels	Frequency (MHz)	Peak Output Power (dBm)
Low	2402	-5.3
Mid	2440	-9.8
High	2480	-10.9


Plot 4-1: Peak Spectral Density – 2402 MHz



Plot 4-2: Peak Spectral Density – 2440 MHz



Plot 4-3: Peak Spectral Density – 2480 MHz



Test Personnel:

Dan Baltzell
 Test Engineer

Dan W. Baltzell

Signature

December 22, 2015
 Date of Test

5 Antenna Conducted Spurious Emissions – FCC 15.247(d), RSS-247 5.5

5.1 Antenna Conducted Spurious Emissions Test Procedure


A SMA connector provided a port for measurement from 9 kHz to the 10th harmonic with the spectrum analyzer, for the low, mid, and high channels.

Table 5-1: Antenna Conducted Spurious Emissions Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/16

5.2 Antenna Conducted Spurious Emissions Test Data


Plot 5-1: Antenna Conducted Spurious Emissions – 2402 MHz



Plot 5-2: Antenna Conducted Spurious Emissions – 2440 MHz



Plot 5-3: Antenna Conducted Spurious Emissions – 2480 MHz



Test Personnel:

Daniel W. Baltzell
EMC Test Engineer

Signature

December 22, 2015
Date of Test

6 Compliance with the Band Edge – FCC 15.247(d); RSS-247 5.5

6.1 Band Edge Test Procedure

Conducted measurements were taken. The span was set wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation. The spectrum analyzer was set to the following:

RBW > = 1 % of span
VBW > = RBW
Sweep = auto
Detector function = peak
Trace = max hold

The trace was allowed to stabilize. The marker was set on the emission at the band edge. The marker-delta was used to show the delta between the maximum in-band emission and the emission at the band edge, and was compared to the 20 dBc requirement of 15.247(d) (when using peak emissions) or restricted band.


Table 6-1: Band Edge Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/16


6.2 Band Edge Test Results

6.2.1 Lower Band Edge – Plots

Plot 6-1: Lower Band Edge - Peak



Plot 6-2: Lower Band Edge – Average



6.2.2 Upper Band Edge Plots

Plot 6-3: Upper Band Edge – Peak



Plot 6-4: Upper Band Edge - Average



Test Personnel:

Dan Baltzell
 Test Engineer

Dan W. Baltzell

Signature

December 22, 2015
 Date of Test

7 Bandwidth – FCC 15.247(a)(2); RSS-247 5.2(1)

7.1 6 dB Bandwidth Test Procedure

The minimum 6 bandwidth per FCC 15.247 (a)(1) and RSS-247 was measured using a 50-ohm spectrum analyzer. The carrier was adjusted on the analyzer so that it was displayed entirely on the spectrum analyzer. The sweep time was set to auto and allowed through several sweeps with the max hold function used in peak detector mode. The resolution bandwidth was set to 100 kHz, and the video bandwidth set at 300 kHz.

Table 7-1: 6 dB Bandwidth Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/16

7.2 Bandwidth Test Results

Table 7-2: 6 dB Bandwidth Test Data

Frequency (MHz)	6 dB Bandwidth (kHz)	Limit (MHz)	Pass/Fail
2402	516.5	0.5	Pass
2440	514.4	0.5	Pass
2480	513.5	0.5	Pass


Plot 7-1: 6 dB Bandwidth – 2402 MHz



Plot 7-2: 6 dB Bandwidth – 2440 MHz



Plot 7-3: 6 dB Bandwidth – 2480 MHz



Test Personnel:

Dan Baltzell
 Test Engineer

Dan W. Baltzell

Signature

December 22, 2015
 Date of Test

8 Radiated Emissions - 15.209; RSS-247 2.2; RSS-Gen 6.13/7.1

8.1 Limits of Radiated Emissions Measurement

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009-0.490	2400/f (kHz)	300
0.490-1.705	2400/f (kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any circumstances of modulation.

8.2 Radiated Emissions Measurement Test Procedure

Before final measurements of radiated emissions were made on the open-field three/ten meter range, the EUT was scanned indoors at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to ensure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 meters above the ground plane. The spectrum was examined from 9 kHz to the 10th harmonic of the highest fundamental transmitter frequency (10 GHz).

At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations. For frequencies between 30 and 1000 MHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1000 MHz, emissions are measured using a VBW of 10 Hz, with a minimum resolution bandwidth of 1 MHz. No video filter less than 10 times the resolution bandwidth was used. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

Table 8-1: Radiated Emissions Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter antenna mast, polarizing	Outdoor Range 1	Not Required
901592	Insulated Wire Inc.	KPS-1503-3600-KPR	SMK RF Cables 20'	NA	9/3/16
901593	Insulated Wire Inc.	KPS-1503-360-KPR	SMK RF Cables 36"	NA	9/3/16
901242	Rhein Tech Laboratories	WRT-000-0003	Wood rotating table	N/A	Not Required
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/16
900772	EMCO	3161-02	Horn Antenna (2 - 4 GHz)	9804-1044	4/9/18
900321	EMCO	3161-03	Horn Antenna (4.0 - 8.2 GHz)	9508-1020	4/9/18
900323	EMCO	3160-07	Horn Antenna (8.2 - 12.4 GHz)	9605-1054	4/9/18
900791	Chase	CBL6111B	Bilog Antenna (30 MHz – 2000 MHz)	N/A	6/11/17

8.3 Radiated Emissions Test Results

8.3.1 Unintentional Radiated Emissions Test Data

Table 8-2: Digital Radiated Emissions Test Data

Temperature: 60°F Humidity: 97%							
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pass/Fail
87.8	Qp	3.9	0.3	4.2	40.0	-35.8	Pass
125.8	Qp	-6.1	0.5	-5.6	43.5	-49.1	Pass
166.2	Qp	-6.2	0.6	-5.6	43.5	-49.1	Pass
800.6	Qp	-9.8	2.4	-7.4	46.0	-53.4	Pass
813.3	Qp	-9.5	2.4	-7.1	46.0	-53.1	Pass
826.6	Qp	-9.4	2.4	-7.0	46.0	-53.0	Pass
1601.2	Av	-9.0	3.4	-5.6	54.0	-59.6	Pass
1626.6	Av	-9.3	3.4	-5.9	54.0	-59.9	Pass
1653.3	Av	-8.9	3.4	-5.5	54.0	-59.5	Pass
3202.5	Av	3.4	27.1	30.5	54.0	-23.5	Pass
3253.3	Av	-5.3	27.2	21.9	54.0	-32.1	Pass
3306.6	Av	-5.3	27.3	22.0	54.0	-32.0	Pass
4003.1	Av	0.5	33.9	34.4	54.0	-19.6	Pass
4066.6	Av	-10.2	34.0	23.8	54.0	-30.2	Pass
4133.2	Av	-9.4	33.9	24.5	54.0	-29.5	Pass
5604.3	Av	2.2	34.6	36.8	54.0	-17.2	Pass
5693.2	Av	-9.8	34.7	24.9	54.0	-29.1	Pass
5786.5	Av	-9.4	34.9	25.5	54.0	-28.5	Pass
6404.9	Av	1.1	35.1	36.2	54.0	-17.8	Pass
10746.4	Av	-9.4	42.4	33.0	54.0	-21.0	Pass
11573.1	Av	-9.5	42.8	33.3	54.0	-20.7	Pass
12809.8	Av	0.4	46.5	46.9	54.0	-7.1	Pass
13226.4	Av	-7.2	46.9	39.7	54.0	-14.3	Pass

8.3.2 Spurious/Harmonics Radiated Emissions Test Data

Table 8-3: Peak Radiated Emissions Spurious/Harmonics – 2402 MHz

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/ 3 MHz VBW)	Site Correction Factor (dB/m)	Peak Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4804.0	11.9	33.8	45.7	74.0	-28.3
12010.0	12.5	43.4	55.9	74.0	-18.1
19216.0	10.4	51.7	62.1	74.0	-11.9

Table 8-4: Average Radiated Emissions Spurious/Harmonics – 2402 MHz

Emission Frequency (MHz)	Average Analyzer Reading (dBuV) (1 MHz RBW/ 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4804.0	6.5	33.8	40.3	54.0	-13.7
12010.0	0.7	43.4	44.1	54.0	-9.9
19216.0	-9.1	51.7	42.6	54.0	-11.4

Table 8-5: Peak Radiated Emissions Spurious/Harmonics - 2440 MHz

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/ 3 MHz VBW)	Site Correction Factor (dB/m)	Peak Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4880.0	11.1	33.9	45.0	74.0	-29.0
7320.0	12.4	35.6	48.0	74.0	-26.0
12200.0	9.2	43.3	52.5	74.0	-21.5
19520.0	12.0	52.0	64.0	74.0	-10.0

Table 8-6: Average Radiated Emissions Spurious/Harmonics – 2440 MHz

Emission Frequency (MHz)	Average Analyzer Reading (dBuV) (1 MHz RBW/ 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4880.0	5.0	33.9	38.9	54.0	-15.1
7320.0	1.0	35.6	36.6	54.0	-17.4
12200.0	0.1	43.3	43.4	54.0	-10.6
19520.0	-8.5	52.0	43.5	54.0	-10.5

Table 8-7: Peak Radiated Emissions Spurious/Harmonics - 2480 MHz

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/ 3 MHz VBW)	Site Correction Factor (dB/m)	Peak Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4960.0	10.6	34.1	44.7	74.0	-29.3
7440.0	12.7	35.8	48.5	74.0	-25.5
12400.0	9.1	43.3	52.4	74.0	-21.6
19840.0	11.9	52.3	64.2	74.0	-9.8
22320.0	11.6	53.4	65.0	74.0	-9.0

Table 8-8: Average Radiated Emissions Spurious/Harmonics – 2480 MHz

Emission Frequency (MHz)	Average Analyzer Reading (dBuV) (1 MHz RBW/ 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4960.0	8.6	34.1	42.7	54.0	-11.3
7440.0	0.6	35.8	36.4	54.0	-17.6
12400.0	0.6	43.3	43.9	54.0	-10.1
19840.0	-8.2	52.3	44.1	54.0	-9.9
22320.0	-7.9	53.4	45.5	54.0	-8.5

Test Personnel:

Daniel W. Baltzell
Test Engineer



Signature

December 23, 2015
Date of Test

9 Conclusion

The data in this measurement report shows that the EUT as tested, Harris Corporation Model XL-200P (International), FCC ID: OWDTR-0145-E, IC: 3636B-0145, complies with the applicable requirements of Parts 2 and 15 of the FCC Rules and Regulations and Industry Canada RSS-247 and RSS-Gen.