



Engineering Solutions & Electromagnetic Compatibility Services

## FCC Part 15.247 & IC RSS-247 Certification Report

Harris Corporation  
221 Jefferson Ridge Parkway  
Lynchburg, VA 24501  
Contact: Paresh Chauhan  
Phone: (434) 455-9290

Model: XL-200P (International)  
Multi-Band Portable Land Mobile Radio

FCC ID: OWDTR-0145-E  
IC: 3636B-0145

February 9, 2016

| Standards Referenced for this Report |                                                                                                                                               |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| FCC Classification                   | DTS – Part 15 Digital Transmission System                                                                                                     |
| FCC Rule Part(s)                     | FCC Rules Part 15.247: Operation within the bands 920-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz Frequency Hopping System (10-01-14)          |
| IC Standard                          | RSS-247 Issue 1: Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and License Exempt Local Area Network (LE-LAN) Devices |
| FCC Procedure                        | ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices                              |
| Digital Interface Information        | Digital Interface was found to be compliant                                                                                                   |

| Frequency Range (MHz) | Rated Transmit Power (W) (Radiated) | Frequency Tolerance (ppm) | Emission Designator |
|-----------------------|-------------------------------------|---------------------------|---------------------|
| 2412 – 2462           | 0.234                               | N/A                       | 1M46FXD             |

Report Prepared By: Daniel Baltzell

Document Number: 2015216DTS

*This report may not be reproduced, except in full, without the full written approval of Rhein Tech Laboratories, Inc. and Harris Corporation. Test results relate only to the item tested.*

*This/these test(s) is/are accredited under Rhein Tech Laboratories, Inc. ISO/IEC 17025 accreditation issued by the ANSI-ASQ National Accreditation Board. Refer to certificate and scope of accreditation AT-1445.*

## Table of Contents

|       |                                                                                  |    |
|-------|----------------------------------------------------------------------------------|----|
| 1     | General Information .....                                                        | 5  |
| 1.1   | Scope .....                                                                      | 5  |
| 1.2   | Description of EUT .....                                                         | 5  |
| 1.3   | Test Facility .....                                                              | 5  |
| 1.4   | Related Submittal(s)/Grant(s) .....                                              | 5  |
| 1.5   | Modifications .....                                                              | 5  |
| 2     | Test Information .....                                                           | 6  |
| 2.1   | Description of Test Modes .....                                                  | 6  |
| 2.2   | Exercising the EUT .....                                                         | 6  |
| 2.3   | Test Result Summary .....                                                        | 6  |
| 2.4   | Tested System Details .....                                                      | 7  |
| 3     | Peak Output Power – FCC 15.247(b)(1); RSS-247 5.4(4) .....                       | 9  |
| 3.1   | Power Output Test Procedure .....                                                | 9  |
| 3.2   | Power Output Test Data .....                                                     | 9  |
| 4     | Compliance with the Band Edge – FCC 15.247(d); RSS-247 5.5 .....                 | 10 |
| 4.1   | Band Edge Test Procedure .....                                                   | 10 |
| 4.1.1 | Lower Band Edge – 802.11b .....                                                  | 11 |
| 4.1.2 | Upper Band Edge – 802.11b .....                                                  | 12 |
| 4.1.3 | Lower Band Edge – 802.11g .....                                                  | 13 |
| 4.1.4 | Upper Band Edge – 802.11g .....                                                  | 14 |
| 4.1.5 | Lower Band Edge – 802.11n .....                                                  | 15 |
| 4.1.6 | Upper Band Edge – 802.11n .....                                                  | 16 |
| 4.1.7 | Lower Band Edge – 802.11n (40 MHz BW) .....                                      | 17 |
| 4.1.8 | Upper Band Edge – 802.11n (40 MHz BW) .....                                      | 18 |
| 5     | Antenna Conducted Spurious Emissions – FCC 15.247(d); RSS-247 5.5; RSS-Gen ..... | 19 |
| 5.1   | Antenna Conducted Spurious Emissions Test Procedures .....                       | 19 |
| 5.2   | Antenna Conducted Spurious Emissions Test Results .....                          | 19 |
| 5.3   | 6 dB Bandwidth - FCC 15.247(a)(2); RSS-247 5.2(1) .....                          | 20 |
| 5.4   | 6 dB Bandwidth Test Results .....                                                | 20 |
| 6     | Power Spectral Density – FCC 15.247(e); RSS-247 5.2 .....                        | 31 |
| 6.1   | Power Spectral Density Test Procedure .....                                      | 31 |
| 6.2   | Power Spectral Density Test Data – DSSS WLAN .....                               | 31 |
| 7     | Radiated Emissions – FCC 15.209; RSS-247 5.5 and RSS-Gen .....                   | 42 |
| 7.1   | Limits of Radiated Emissions Measurement .....                                   | 42 |
| 7.2   | Radiated Emissions Measurement Test Procedure .....                              | 42 |
| 7.3   | Radiated Emissions Test Results .....                                            | 44 |
| 7.3.1 | Radiated Emissions Harmonics/Spurious .....                                      | 44 |
| 8     | Conclusion .....                                                                 | 50 |

## Table Index

|             |                                                                                     |    |
|-------------|-------------------------------------------------------------------------------------|----|
| Table 2-1:  | Channels Tested for DSSS – 802.11b (2 Mbps); 802.11g (12 Mbps) .....                | 6  |
| Table 2-2:  | Test Result Summary – FCC Part 15, Subpart C (Section 15.247), IC RSS-247/RSS-Gen 6 |    |
| Table 2-3:  | Equipment Under Test (EUT).....                                                     | 7  |
| Table 2-4:  | Accessory Test Equipment .....                                                      | 7  |
| Table 3-1:  | Power Output Test Equipment .....                                                   | 9  |
| Table 3-2:  | Power Output Test Data – 802.11b.....                                               | 9  |
| Table 3-3:  | Power Output Test Data – 802.11g.....                                               | 9  |
| Table 3-4:  | Power Output Test Data – 802.11n.....                                               | 9  |
| Table 4-1:  | Band Edge Test Equipment .....                                                      | 10 |
| Table 5-1:  | Antenna Conducted Spurious Test Equipment.....                                      | 19 |
| Table 5-2:  | 6 dB Bandwidth Test Equipment.....                                                  | 20 |
| Table 5-3:  | 6 dB Bandwidth Test Data – 802.11b (2 Mbps) .....                                   | 20 |
| Table 5-4:  | 6 dB Bandwidth Test Data – 802.11g (18 Mbps) .....                                  | 20 |
| Table 5-5:  | 6 dB Bandwidth Test Data – 802.11n (6.5 Mbps-20 MHz BW) .....                       | 20 |
| Table 5-6:  | 6 dB Bandwidth Test Data – 802.11n (40 MHz BW).....                                 | 20 |
| Table 6-1:  | Power Spectral Density Test Equipment .....                                         | 31 |
| Table 6-2:  | Power Spectral Density Test Data – 802.11b (2 Mbps).....                            | 31 |
| Table 6-3:  | Power Spectral Density Test Data – 802.11g (18 Mbps).....                           | 31 |
| Table 6-4:  | Power Spectral Density Test Data – 802.11n (13 Mbps-20MHz BW) .....                 | 31 |
| Table 6-5:  | Power Spectral Density Test Data – 802.11n (40 MHz BW) .....                        | 31 |
| Table 7-1:  | Radiated Emissions Test Equipment .....                                             | 43 |
| Table 7-2:  | 2412 MHz; 802.11b; 2 Mbps; Channel 1; Average Mode .....                            | 44 |
| Table 7-3:  | 2437 MHz; 802.11b; 2 Mbps; Channel 6; Average Mode .....                            | 44 |
| Table 7-4:  | 2462 MHz; 802.11b; 2 Mbps; Channel 11; Average Mode .....                           | 44 |
| Table 7-5:  | 2412 MHz; 802.11g; 11 Mbps; Channel 1; Average Mode .....                           | 45 |
| Table 7-6:  | 2437 MHz; 802.11g; 11 Mbps; Channel 6; Average Mode .....                           | 45 |
| Table 7-7:  | 2462 MHz; 802.11g; 11 Mbps; Channel 11; Average Mode .....                          | 45 |
| Table 7-8:  | 2412 MHz; 802.11n; 65 Mbps; Channel 1; Average Mode .....                           | 46 |
| Table 7-9:  | 2437 MHz; 802.11n; 65 Mbps; Channel 6; Average Mode .....                           | 46 |
| Table 7-10: | 2462 MHz; 802.11n; 65 Mbps; Channel 11; Average Mode .....                          | 46 |
| Table 7-11: | 2412 MHz; 802.11b; 2 Mbps; Channel 1; Peak Mode .....                               | 47 |
| Table 7-12: | 2437 MHz; 802.11b; 2 Mbps; Channel 6; Peak Mode .....                               | 47 |
| Table 7-13: | 2462 MHz; 802.11b; 2 Mbps; Channel 11; Peak Mode .....                              | 47 |
| Table 7-14: | 2412 MHz; 802.11g; 11 Mbps; Channel 1; Peak Mode .....                              | 48 |
| Table 7-15: | 2437 MHz; 802.11g; 11 Mbps; Channel 6; Peak Mode .....                              | 48 |
| Table 7-16: | 2462 MHz; 802.11g; 11 Mbps; Channel 11; Peak Mode .....                             | 48 |
| Table 7-17: | 2412 MHz; 802.11n; 65 Mbps; Channel 1; Peak Mode .....                              | 49 |
| Table 7-18: | 2437 MHz; 802.11n; 65 Mbps; Channel 6; Peak Mode .....                              | 49 |
| Table 7-19: | 2462 MHz; 802.11n; 65 Mbps; Channel 11; Peak Mode .....                             | 49 |

### Plot Index

|            |                                                                       |    |
|------------|-----------------------------------------------------------------------|----|
| Plot 4-1:  | In Band Emissions - Channel 1 (2412 MHz); 802.11b (2 Mbps)            | 11 |
| Plot 4-2:  | In Band Emissions - Channel 11 (2462 MHz); 802.11b (2 Mbps)           | 12 |
| Plot 4-3:  | In Band Emissions - Channel 1 (2412 MHz); 802.11g (12 Mbps)           | 13 |
| Plot 4-4:  | In Band Emissions - Channel 11 (2462 MHz); 802.11g (12 Mbps)          | 14 |
| Plot 4-5:  | In Band Emissions - Channel 1 (2412 MHz); 802.11n (65 Mbps)           | 15 |
| Plot 4-6:  | In Band Emissions - Channel 11 (2462 MHz); 802.11n (65 Mbps)          | 16 |
| Plot 4-7:  | In Band Emissions - Channel 5 (2422 MHz); 802.11n (65 Mbps)           | 17 |
| Plot 4-8:  | In Band Emissions - Channel 7 (2432 MHz); 802.11n (40 MHz)            | 18 |
| Plot 5-1:  | 6 dB Bandwidth Channel 1 (TX Frequency 2412 MHz) - 802.11b            | 21 |
| Plot 5-2:  | 6 dB Bandwidth Channel 6 (TX Frequency 2437 MHz) - 802.11b            | 22 |
| Plot 5-3:  | 6 dB Bandwidth Channel 11 (TX Frequency 2462 MHz) - 802.11b           | 23 |
| Plot 5-4:  | 6 dB Bandwidth Channel 1 (TX Frequency 2412 MHz) - 802.11g            | 24 |
| Plot 5-5:  | 6 dB Bandwidth Channel 6 (TX Frequency 2437 MHz) - 802.11g            | 25 |
| Plot 5-6:  | 6 dB Bandwidth Channel 11 (TX Frequency 2462 MHz) - 802.11g           | 26 |
| Plot 5-7:  | 6 dB Bandwidth Channel 1 (TX Frequency 2412 MHz-20 MHz BW) - 802.11n  | 27 |
| Plot 5-8:  | 6 dB Bandwidth Channel 6 (TX Frequency 2437 MHz-20 MHz BW) - 802.11n  | 28 |
| Plot 5-9:  | 6 dB Bandwidth Channel 11 (TX Frequency 2462 MHz-20 MHz BW) - 802.11n | 29 |
| Plot 5-10: | 6 dB Bandwidth Channel 8 (TX Frequency 2437 MHz-40 MHz BW) - 802.11n  | 30 |
| Plot 6-1:  | Power Spectral Density: Channel 1 (2412 MHz); 802.11b (2 Mbps)        | 32 |
| Plot 6-2:  | Power Spectral Density: Channel 6 (2437 MHz); 802.11b (2 Mbps)        | 33 |
| Plot 6-3:  | Power Spectral Density: Channel 11 (2462 MHz); 802.11b (2 Mbps)       | 34 |
| Plot 6-4:  | Power Spectral Density: Channel 1 (2412 MHz); 802.11g (18 Mbps)       | 35 |
| Plot 6-5:  | Power Spectral Density: Channel 6 (2437 MHz); 802.11g (18 Mbps)       | 36 |
| Plot 6-6:  | Power Spectral Density: Channel 11 (2462 MHz); 802.11g (18 Mbps)      | 37 |
| Plot 6-7:  | Power Spectral Density: Channel 1 (2412 MHz); 802.11n (13 Mbps)       | 38 |
| Plot 6-8:  | Power Spectral Density: Channel 6 (2437 MHz); 802.11n (13 Mbps)       | 39 |
| Plot 6-9:  | Power Spectral Density: Channel 11 (2462 MHz); 802.11n (13 Mbps)      | 40 |
| Plot 6-10: | Power Spectral Density: Channel 5 (2442 MHz); 802.11n (40MHz BW)      | 41 |

### Appendix Index

|             |                  |    |
|-------------|------------------|----|
| Appendix A: | Test Photographs | 51 |
|-------------|------------------|----|

### Photograph Index

|               |                               |    |
|---------------|-------------------------------|----|
| Photograph 1: | Radiated Testing – Front View | 51 |
| Photograph 2: | Radiated Testing – Back View  | 52 |

## 1 General Information

### 1.1 Scope

Applicable Standards:

- FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.
- RSS-247 Issue 1: Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License Exempt Local Area Network (LE-LAN) Devices

### 1.2 Description of EUT

|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| <b>Equipment Under Test</b>   | XL200P (International) Multi-Band Portable Radio |
| <b>Power Supply</b>           | 7.4 VDC Li-Ion battery                           |
| <b>Modulation Type</b>        | DSSS                                             |
| <b>Frequency Range</b>        | 2412 – 2462 MHz                                  |
| <b>Antenna Connector Type</b> | N/A                                              |
| <b>Antenna Type</b>           | Internal chip                                    |

### 1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing.

### 1.4 Related Submittal(s)/Grant(s)

This is an Industry Canada Family Certification application, which includes 8 model numbers under IC: 3636B-0145:

|          |          |          |          |
|----------|----------|----------|----------|
| XL-PFM2M | XL-PFM2Y | XL-PFM2B | XL-PFM2G |
| XL-PPM2M | XL-PPM2Y | XL-PPM2B | XL-PPM2G |

### 1.5 Modifications

No physical modifications were required for compliance.

## 2 Test Information

### 2.1 Description of Test Modes

In accordance with FCC 15.31(m), and because the EUT utilizes an operating band greater than 10 MHz, the following frequencies were tested.

**Table 2-1: Channels Tested for DSSS – 802.11b (2 Mbps); 802.11g (12 Mbps)**

| Channel | Frequency (MHz) |
|---------|-----------------|
| 1       | 2412            |
| 6       | 2437            |
| 11      | 2462            |

### 2.2 Exercising the EUT

The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The EUT was provided with software to continuously transmit during testing. The carrier was also checked to verify that information was being transmitted. There were no deviations from the test standard(s) and/or methods. The test results reported relate only to the item tested.

### 2.3 Test Result Summary

**Table 2-2: Test Result Summary – FCC Part 15, Subpart C (Section 15.247), IC RSS-247/RSS-Gen**

| FCC Reference    | IC Reference                   | C63.10 Procedure | Test                                 | Pass/Fail or N/A |
|------------------|--------------------------------|------------------|--------------------------------------|------------------|
| FCC 15.209       | RSS-247 5.5, RSS-Gen 6.5, A2.9 | 6.5, 6.6         | Radiated Emissions                   | Pass             |
| FCC 15.207       | RSS-Gen 8.8                    | 6.2              | AC Power Conducted Emissions         | N/A              |
| FCC 15.247(a)(2) | RSS-247 5.2                    | 11.8             | 6 dB Bandwidth                       | Pass             |
| FCC 15.247(b)    | RSS-247 5.4(4), RSS-Gen 6.12   | 11.9             | Maximum Peak Power Output            | Pass             |
| FCC 15.247(d)    | RSS-247 5.5, RSS-Gen 6.13      | 11.12.2          | Antenna Conducted Spurious Emissions | Pass             |
| FCC 15.247(e)    | RSS-247 5.2                    | 11.10            | Power Spectral Density               | Pass             |
| FCC 15.247(d)    | RSS-247 5.5                    | 11.13            | Band Edge Measurement                | Pass             |

## 2.4 Tested System Details

The test samples were received on February 27, 2014. Listed below are the identifiers and descriptions of all equipment, cables, and internal devices used with the EUT for this test, as applicable.

The EUT includes a System model and a Scan model, the difference being that the System model has a DTMF keypad. The System model is considered to be representative of the radio family and to have the worst case emissions, and was therefore used for testing.

The device was programmed for multiple modes of operation and modulation types.

**Table 2-3: Equipment Under Test (EUT)**


| Part  | Manufacturer       | Model #           | PN/SN                      | FCC ID       | RTL Bar Code |
|-------|--------------------|-------------------|----------------------------|--------------|--------------|
| Radio | Harris Corporation | XL-PFM2M (System) | 14035-1000-51/A40304000045 | OWDTR-0145-E | 21965        |

| Part                         | Manufacturer       | Model            | Serial Number             | FCC ID       | RTL Bar Code |
|------------------------------|--------------------|------------------|---------------------------|--------------|--------------|
| Radio                        | Harris Corporation | XL-200P (System) | 14035-1000-01/E00236      | OWDTR-0145-E | 21612        |
| Radio (conducted connection) | Harris Corporation | XL-200P (System) | 14035-1000-01/0WXD-E00239 | OWDTR-0145-E | 21614        |

**Table 2-4: Accessory Test Equipment**

| Part               | Manufacturer       | Model #            | Serial Number          | FCC ID | RTL Bar Code |
|--------------------|--------------------|--------------------|------------------------|--------|--------------|
| Battery Eliminator | Harris Corporation | 14035-4300-01      | N/A                    | N/A    | 21553        |
| Breakout Box       | Harris Corporation | 12082-7980-01      | N/A                    | N/A    | 20599        |
| Battery            | Harris Corporation | BAT-L-CASE-R-HR003 | Engineering Sample #73 | N/A    | 21552        |
| Laptop             | Samsung            | NP300E5A-A01UB     | HJVF93EB903201D        | N/A    | 901550       |

**Figure 2-1: Configuration of Tested System**



### 3 Peak Output Power – FCC 15.247(b)(1); RSS-247 5.4(4)

#### 3.1 Power Output Test Procedure

A conducted power measurement of the EUT was taken using a Rohde & Schwarz Spectrum Analyzer.

**Table 3-1: Power Output Test Equipment**

| RTL Asset # | Manufacturer    | Model | Part Type         | Serial Number | Calibration Due Date |
|-------------|-----------------|-------|-------------------|---------------|----------------------|
| 901581      | Rohde & Schwarz | FSU   | Spectrum Analyzer | 1166.1660.50  | 11/13/15             |

#### 3.2 Power Output Test Data

**Table 3-2: Power Output Test Data – 802.11b**

| Channel | Frequency (MHz) | Peak Power (dBm) |
|---------|-----------------|------------------|
| 1       | 2412            | 20.3             |
| 6       | 2437            | 20.7             |
| 11      | 2462            | 20.0             |

**Table 3-3: Power Output Test Data – 802.11g**

| Channel | Frequency (MHz) | Peak Power (dBm) |
|---------|-----------------|------------------|
| 1       | 2412            | 20.9             |
| 6       | 2437            | 23.7             |
| 11      | 2462            | 20.8             |

**Table 3-4: Power Output Test Data – 802.11n**

| Channel | Frequency (MHz) | Peak Power (dBm) |
|---------|-----------------|------------------|
| 1       | 2412            | 21.6             |
| 6       | 2437            | 23.4             |
| 11      | 2462            | 21.3             |

#### Test Personnel:

Daniel W. Baltzell  
Test Engineer

  
Signature

March 14, 2015  
Date of Test

#### 4 Compliance with the Band Edge – FCC 15.247(d); RSS-247 5.5

##### 4.1 Band Edge Test Procedure

The transmitter output was connected to its appropriate antenna. Peak (1 MHz RBW/3 MHz VBW) and average (1 MHz RBW/10 Hz VBW) corrected radiated measurements were taken within the restricted band to show compliance.

**Table 4-1: Band Edge Test Equipment**

| RTL Asset # | Manufacturer                  | Model             | Part Type                        | Serial Number   | Calibration Due Date |
|-------------|-------------------------------|-------------------|----------------------------------|-----------------|----------------------|
| 900878      | Rhein Tech Laboratories, Inc. | AM3-1197-0005     | 3 meter antenna mast, polarizing | Outdoor Range 1 | Not Required         |
| 901592      | Insulated Wire Inc.           | KPS-1503-3600-KPR | SMK RF Cables 20'                | NA              | 9/3/15               |
| 901242      | Rhein Tech Laboratories, Inc. | WRT-000-0003      | Wood rotating table              | N/A             | Not Required         |
| 900772      | EMCO                          | 3161-02           | Horn Antenna (2 - 4 GHz)         | 9804-1044       | 4/09/18              |
| 901581      | Rohde & Schwarz               | FSU               | Spectrum Analyzer                | 1166.1660.50    | 11/13/15             |

#### 4.1.1 Lower Band Edge – 802.11b

94.6 dBuV/m is the average field strength measurement, from which the delta measurement of 51.7 dB is subtracted (reference plots), resulting in a level 42.9 dB. This level has a margin of 11.1 dB below the limit of 54 dBuV/m.

Calculation:  $94.6 \text{ dBuV/m} - 51.7 \text{ dB} - 54 \text{ dBuV/m} = -11.1 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW) = 99.8 dBuV/m

Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 94.6 dBuV/m

Delta measurement = 51.7 dB

#### Plot 4-1: In Band Emissions - Channel 1 (2412 MHz); 802.11b (2 Mbps)




#### 4.1.2 Upper Band Edge – 802.11b

94.8 dBuV/m is the average field strength measurement, from which the delta measurement of 47.6 dB is subtracted (reference plots), resulting in a level 47.2 dB. This level has a margin of 6.8 dB below the limit of 54 dBuV/m.

Calculation:  $94.8 \text{ dBuV/m} - 47.6 \text{ dB} - 54 \text{ dBuV/m} = -6.8 \text{ dB}$

Peak Field Strength of Upper Band Edge (1 MHz RBW/1 MHz VBW) = 100.0 dBuV/m  
Average Field Strength of Upper Band Edge (1 MHz RBW/10 Hz VBW) = 94.8 dBuV/m  
Delta measurement = 47.6 dB

#### Plot 4-2: In Band Emissions - Channel 11 (2462 MHz); 802.11b (2 Mbps)




#### 4.1.3 Lower Band Edge – 802.11g

89.1 dBuV/m is the average field strength measurement, from which the delta measurement of 35.6 dB is subtracted (reference plots), resulting in a level 53.5 dB. This level has a margin of 0.5 dB below the limit of 54 dBuV/m.

Calculation:  $89.1 \text{ dBuV/m} - 35.6 \text{ dB} - 54 \text{ dBuV/m} = -0.5 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW) = 100.3 dBuV/m  
 Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 89.1 dBuV/m  
 Delta measurement = 35.6 dB

**Plot 4-3: In Band Emissions - Channel 1 (2412 MHz); 802.11g (12 Mbps)**




#### 4.1.4 Upper Band Edge – 802.11g

90.9 dBuV/m is the average field strength measurement, from which the delta measurement of 39 dB is subtracted (reference plots), resulting in a level 51.9 dB. This level has a margin of 2.1 dB below the limit of 54 dBuV/m.

Calculation:  $90.9 \text{ dBuV/m} - 39.0 \text{ dB} - 54 \text{ dBuV/m} = -2.1 \text{ dB}$

Peak Field Strength of Upper Band Edge (1 MHz RBW/1 MHz VBW) = 101.6 dBuV/m  
 Average Field Strength of Upper Band Edge (1 MHz RBW/10 Hz VBW) = 90.9 dBuV/m  
 Delta measurement = 39.0 dB

**Plot 4-4: In Band Emissions - Channel 11 (2462 MHz); 802.11g (12 Mbps)**




#### 4.1.5 Lower Band Edge – 802.11n

75.4 dBuV/m is the average field strength measurement, from which the delta measurement of 40 dB is subtracted (reference plots), resulting in a level 35.4 dB. This level has a margin of 18.6 dB below the limit of 54 dBuV/m.

Calculation:  $75.4 \text{ dBuV/m} - 40 \text{ dB} = 35.4 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW) = 93.9 dBuV/m  
 Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 75.4 dBuV/m  
 Delta measurement = 40 dB

#### Plot 4-5: In Band Emissions - Channel 1 (2412 MHz); 802.11n (65 Mbps)




#### 4.1.6 Upper Band Edge – 802.11n

80.5 dBuV/m is the average field strength measurement, from which the delta measurement of 40.7 dB is subtracted (reference plots), resulting in a level 39.8 dB. This level has a margin of 14.2 dB below the limit of 54 dBuV/m.

Calculation:  $80.5 \text{ dBuV/m} - 40.7 \text{ dB} - 54 \text{ dBuV/m} = -14.2 \text{ dB}$

Peak Field Strength of Upper Band Edge (1 MHz RBW/1 MHz VBW) = 94.7 dBuV/m  
 Average Field Strength of Upper Band Edge (1 MHz RBW/10 Hz VBW) = 80.5 dBuV/m  
 Delta measurement = 40.7 dB

#### Plot 4-6: In Band Emissions - Channel 11 (2462 MHz); 802.11n (65 Mbps)




#### 4.1.7 Lower Band Edge – 802.11n (40 MHz BW)

88.2 dBuV/m is the average field strength measurement, from which the delta measurement of 39.3 dB is subtracted (reference plots), resulting in a level 48.9 dB. This level has a margin of 5.1 dB below the limit of 54 dBuV/m.

Calculation:  $88.2 \text{ dBuV/m} - 39.3 \text{ dB} - 54 \text{ dBuV/m} = -5.1 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW) = 94.7 dBuV/m  
 Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 88.2 dBuV/m  
 Delta measurement = 39.3 dB

#### Plot 4-7: In Band Emissions - Channel 5 (2422 MHz); 802.11n (65 Mbps)



#### 4.1.8 Upper Band Edge – 802.11n (40 MHz BW)

88.2 dBuV/m is the average field strength measurement, from which the delta measurement of 35.8 dB is subtracted (reference plots), resulting in a level 52.4 dB. This level has a margin of 1.6 dB below the limit of 54 dBuV/m.


Calculation:  $88.2 \text{ dBuV/m} - 35.8 \text{ dB} - 54 \text{ dBuV/m} = -1.6 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW) = 94.7 dBuV/m

Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 88.2 dBuV/m

Delta measurement = 35.8 dB 23.1@ch9=

#### Plot 4-8: In Band Emissions - Channel 7 (2432 MHz); 802.11n (40 MHz)



#### Test Personnel:

Daniel W. Baltzell  
Test Engineer

*Daniel W. Baltzell*  
Signature

March 15 & April 5, 2015  
Dates of Test

## 5 Antenna Conducted Spurious Emissions – FCC 15.247(d); RSS-247 5.5; RSS-Gen

### 5.1 Antenna Conducted Spurious Emissions Test Procedures

Antenna spurious emissions per FCC 15.247(d) were measured from the EUT antenna port using a 50-ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 300 kHz. The modulated carrier was identified at the following frequencies: 2412 MHz, 2437 MHz and 2462 MHz.

### 5.2 Antenna Conducted Spurious Emissions Test Results

No harmonics or spurs were found within 20 dB (note that we are reporting power as peak) of the carrier level from the carrier to the 10<sup>th</sup> harmonic of the carrier frequency. Per FCC 15.31(o), no data is being reported.

**Table 5-1: Antenna Conducted Spurious Test Equipment**

| RTL Asset # | Manufacturer    | Model | Part Type         | Serial Number | Calibration Due Date |
|-------------|-----------------|-------|-------------------|---------------|----------------------|
| 901581      | Rohde & Schwarz | FSU   | Spectrum Analyzer | 1166.1660.50  | 11/13/15             |

#### Test Personnel:

|                    |                                                                                    |                |
|--------------------|------------------------------------------------------------------------------------|----------------|
| Daniel W. Baltzell |  | March 15, 2015 |
| Test Engineer      | Signature                                                                          | Date of Test   |

### 5.3 6 dB Bandwidth - FCC 15.247(a)(2); RSS-247 5.2(1)

The minimum 6 dB bandwidths per FCC 15.247(a)(2) were measured using a 50-ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at  $\geq 3 \times \text{RBW}$ . The device was modulated. The minimum 6 dB bandwidths are presented below.

**Table 5-2: 6 dB Bandwidth Test Equipment**

| RTL Asset # | Manufacturer    | Model | Part Type         | Serial Number | Calibration Due Date |
|-------------|-----------------|-------|-------------------|---------------|----------------------|
| 901581      | Rohde & Schwarz | FSU   | Spectrum Analyzer | 1166.1660.50  | 11/13/15             |

### 5.4 6 dB Bandwidth Test Results

**Table 5-3: 6 dB Bandwidth Test Data – 802.11b (2 Mbps)**

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 1       | 2412            | 10.1                 | 0.5                 | Pass      |
| 6       | 2437            | 10.3                 | 0.5                 | Pass      |
| 11      | 2462            | 10.1                 | 0.5                 | Pass      |

**Table 5-4: 6 dB Bandwidth Test Data – 802.11g (18 Mbps)**

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 1       | 2412            | 14.7                 | 0.5                 | Pass      |
| 6       | 2437            | 14.6                 | 0.5                 | Pass      |
| 11      | 2462            | 14.4                 | 0.5                 | Pass      |


**Table 5-5: 6 dB Bandwidth Test Data – 802.11n (6.5 Mbps-20 MHz BW)**

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 1       | 2412            | 14.7                 | 0.5                 | Pass      |
| 6       | 2437            | 14.6                 | 0.5                 | Pass      |
| 11      | 2462            | 14.6                 | 0.5                 | Pass      |


**Table 5-6: 6 dB Bandwidth Test Data – 802.11n (40 MHz BW)**

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 8       | 2437            | 35.9                 | 0.5                 | Pass      |


**Plot 5-1: 6 dB Bandwidth Channel 1 (TX Frequency 2412 MHz) - 802.11b**




**Plot 5-2: 6 dB Bandwidth Channel 6 (TX Frequency 2437 MHz) - 802.11b**




**Plot 5-3: 6 dB Bandwidth Channel 11 (TX Frequency 2462 MHz) - 802.11b**




**Plot 5-4: 6 dB Bandwidth Channel 1 (TX Frequency 2412 MHz) - 802.11g**




**Plot 5-5: 6 dB Bandwidth Channel 6 (TX Frequency 2437 MHz) - 802.11g**




**Plot 5-6: 6 dB Bandwidth Channel 11 (TX Frequency 2462 MHz) - 802.11g**




**Plot 5-7: 6 dB Bandwidth Channel 1 (TX Frequency 2412 MHz-20 MHz BW) - 802.11n**




**Plot 5-8: 6 dB Bandwidth Channel 6 (TX Frequency 2437 MHz-20 MHz BW) - 802.11n**



**Plot 5-9: 6 dB Bandwidth Channel 11 (TX Frequency 2462 MHz-20 MHz BW) - 802.11n**



**Plot 5-10: 6 dB Bandwidth Channel 8 (TX Frequency 2437 MHz-40 MHz BW) - 802.11n**



**Test Personnel:**

Daniel W. Baltzell  
 Test Engineer

*Daniel W. Baltzell*  
 Signature

March 15 - April 1, 2015  
 Dates of Test

## 6 Power Spectral Density – FCC 15.247(e); RSS-247 5.2

### 6.1 Power Spectral Density Test Procedure

The power spectral density per FCC 15.247(e) was measured using a 50-ohm spectrum analyzer with the resolution bandwidth set at 3 kHz, the video bandwidth set at 10 kHz, and the auto sweep time. The spectral lines were resolved for the modulated carriers at 2412 MHz, 2437 MHz, 2462 MHz, 5745 MHz, 5785 MHz, and 5825 MHz respectively. These levels are below the +8 dBm limit. See the power spectral density table and plots.

**Table 6-1: Power Spectral Density Test Equipment**

| RTL Asset # | Manufacturer    | Model | Part Type         | Serial Number | Calibration Due Date |
|-------------|-----------------|-------|-------------------|---------------|----------------------|
| 901581      | Rohde & Schwarz | FSU   | Spectrum Analyzer | 1166.1660.50  | 11/13/15             |

### 6.2 Power Spectral Density Test Data – DSSS WLAN

**Table 6-2: Power Spectral Density Test Data – 802.11b (2 Mbps)**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Maximum Limit +8dBm | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 1       | 2412            | -6.6                 | 8                   | Pass      |
| 6       | 2437            | -8.2                 | 8                   | Pass      |
| 11      | 2462            | -7.7                 | 8                   | Pass      |

**Table 6-3: Power Spectral Density Test Data – 802.11g (18 Mbps)**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Maximum Limit +8dBm | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 1       | 2412            | -14.5                | 8                   | Pass      |
| 6       | 2437            | -18.1                | 8                   | Pass      |
| 11      | 2462            | -17.2                | 8                   | Pass      |


**Table 6-4: Power Spectral Density Test Data – 802.11n (13 Mbps-20MHz BW)**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Maximum Limit +8dBm | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 1       | 2412            | -17.0                | 8                   | Pass      |
| 6       | 2437            | -15.3                | 8                   | Pass      |
| 11      | 2462            | -17.6                | 8                   | Pass      |


**Table 6-5: Power Spectral Density Test Data – 802.11n (40 MHz BW)**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Maximum Limit +8dBm | Pass/Fail |
|---------|-----------------|----------------------|---------------------|-----------|
| 5       | 2442            | -18.2                | 8                   | Pass      |


**Plot 6-1: Power Spectral Density: Channel 1 (2412 MHz); 802.11b (2 Mbps)**




**Plot 6-2: Power Spectral Density: Channel 6 (2437 MHz); 802.11b (2 Mbps)**




**Plot 6-3: Power Spectral Density: Channel 11 (2462 MHz); 802.11b (2 Mbps)**




**Plot 6-4: Power Spectral Density: Channel 1 (2412 MHz); 802.11g (18 Mbps)**







**Plot 6-6: Power Spectral Density: Channel 11 (2462 MHz); 802.11g (18 Mbps)**




**Plot 6-7: Power Spectral Density: Channel 1 (2412 MHz); 802.11n (13 Mbps)**




**Plot 6-8: Power Spectral Density: Channel 6 (2437 MHz); 802.11n (13 Mbps)**



**Plot 6-9: Power Spectral Density: Channel 11 (2462 MHz); 802.11n (13 Mbps)**



**Plot 6-10: Power Spectral Density: Channel 5 (2442 MHz); 802.11n (40 MHz BW)**



**Test Personnel:**

|                    |                           |                          |
|--------------------|---------------------------|--------------------------|
| Daniel W. Baltzell | <i>Daniel W. Baltzell</i> | March 15 - April 5, 2015 |
| Test Engineer      | Signature                 | Dates of Test            |

## 7 Radiated Emissions – FCC 15.209; RSS-247 5.5 and RSS-Gen

### 7.1 Limits of Radiated Emissions Measurement

| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009-0.490     | 2400/f (kHz)          | 300                      |
| 0.490-1.705     | 2400/f (kHz)          | 30                       |
| 1.705-30.0      | 30                    | 30                       |
| 30-88           | 100                   | 3                        |
| 88-216          | 150                   | 3                        |
| 216-960         | 200                   | 3                        |
| Above 960       | 500                   | 3                        |

As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any circumstances of modulation.

### 7.2 Radiated Emissions Measurement Test Procedure

Procedure: C63.10-2013 6.5, 6.6

Before final measurements of radiated emissions were made on the open-field three/ten meter range, the EUT was scanned indoors at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to ensure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 meters above the ground plane. The spectrum was examined from 9 kHz to the 10<sup>th</sup> harmonic of the highest fundamental transmitter frequency (24.8 GHz).

At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations. For frequencies between 30 and 1000 MHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1,000 MHz, emissions are measured using the average detector function with a minimum resolution bandwidth of 1 MHz. No video filter less than 10 times the resolution bandwidth was used. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

**Table 7-1: Radiated Emissions Test Equipment**

| <b>RTL Asset #</b> | <b>Manufacturer</b>           | <b>Model</b>      | <b>Part Type</b>                  | <b>Serial Number</b> | <b>Calibration Due Date</b> |
|--------------------|-------------------------------|-------------------|-----------------------------------|----------------------|-----------------------------|
| 900878             | Rhein Tech Laboratories, Inc. | AM3-1197-0005     | 3 meter antenna mast, polarizing  | OATS1                | N/A                         |
| 901592             | Insulated Wire Inc.           | KPS-1503-3600-KPR | SMK RF Cables 20'                 | NA                   | 9/3/15                      |
| 901593             | Insulated Wire Inc.           | KPS-1503-360-KPR  | SMK RF Cables 36"                 | NA                   | 9/3/15                      |
| 901594             | Insulated Wire Inc.           | KPS-1503-360-KPR  | SMK RF Cables 36"                 | NA                   | 9/3/15                      |
| 901242             | Rhein Tech Laboratories, Inc. | WRT-000-0003      | Wood rotating table               | N/A                  | N/A                         |
| 900791             | Chase                         | CBL6111B          | Bilog Antenna (30 MHz – 2000 MHz) | N/A                  | 6/11/17                     |
| 901218             | EMCO                          | 3160-09           | Horn Antenna (18 - 26.5 GHz)      | 960281-003           | 4/14/18                     |
| 900772             | EMCO                          | 3161-02           | Horn Antenna (2 - 4 GHz)          | 9804-1044            | 4/09/18                     |
| 900321             | EMCO                          | 3161-03           | Horn Antennas (4 – 8.2 GHz)       | 9508-1020            | 4/09/18                     |
| 900323             | EMCO                          | 3160-07           | Horn Antennas (8.2 – 12.4 GHz)    | 9605-1054            | 4/09/18                     |
| 900356             | EMCO                          | 3160-08           | Horn Antennas (12.4 – 18 GHz)     | 9607-1044            | 4/09/18                     |
| 901581             | Rohde & Schwarz               | FSU               | Spectrum Analyzer                 | 1166.1660.50         | 11/13/15                    |

### 7.3 Radiated Emissions Test Results

#### 7.3.1 Radiated Emissions Harmonics/Spurious

**Table 7-2: 2412 MHz; 802.11b; 2 Mbps; Channel 1; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4824            | 17.7                                                          | 33.2                          | 50.9                             | 54.0           | -3.1        |
| 12060           | -7.9                                                          | 44.0                          | 36.1                             | 54.0           | -17.9       |
| 14472           | -14.8                                                         | 47.9                          | 33.1                             | 54.0           | -20.9       |
| 19296           | -9.7                                                          | 52.9                          | 43.2                             | 54.0           | -10.8       |

**Table 7-3: 2437 MHz; 802.11b; 2 Mbps; Channel 6; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4874            | 11.1                                                          | 33.3                          | 44.4                             | 54.0           | -9.6        |
| 7311            | 0.6                                                           | 35.7                          | 36.3                             | 54.0           | -17.7       |
| 12185           | -8.7                                                          | 44.0                          | 35.3                             | 54.0           | -18.7       |
| 19496           | -10.2                                                         | 53.0                          | 42.8                             | 54.0           | -11.2       |

**Table 7-4: 2462 MHz; 802.11b; 2 Mbps; Channel 11; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4924            | 6.9                                                           | 33.4                          | 40.3                             | 54.0           | -13.7       |
| 7386            | 0.2                                                           | 35.7                          | 35.9                             | 54.0           | -18.1       |
| 12310           | -8.6                                                          | 44.0                          | 35.4                             | 54.0           | -18.6       |
| 19696           | -9.9                                                          | 53.1                          | 43.2                             | 54.0           | -10.8       |
| 22158           | -11.7                                                         | 54.2                          | 42.5                             | 54.0           | -11.5       |

**Table 7-5: 2412 MHz; 802.11g; 11 Mbps; Channel 1; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4824            | 5.6                                                           | 33.2                          | 38.8                             | 54.0           | -15.2       |
| 12060           | 0.3                                                           | 44.0                          | 44.3                             | 54.0           | -9.7        |
| 14472           | -4.1                                                          | 47.9                          | 43.8                             | 54.0           | -10.2       |
| 19296           | -6.7                                                          | 52.9                          | 46.2                             | 54.0           | -7.8        |

**Table 7-6: 2437 MHz; 802.11g; 11 Mbps; Channel 6; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4874            | 5.7                                                           | 33.3                          | 39.0                             | 54.0           | -15.0       |
| 7311            | 0.1                                                           | 35.7                          | 35.8                             | 54.0           | -18.2       |
| 12185           | 0.5                                                           | 44.0                          | 44.5                             | 54.0           | -9.5        |
| 19496           | -9.3                                                          | 53.0                          | 43.7                             | 54.0           | -10.3       |

**Table 7-7: 2462 MHz; 802.11g; 11 Mbps; Channel 11; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4924            | 3.0                                                           | 33.4                          | 36.4                             | 54.0           | -17.6       |
| 7386            | 0.1                                                           | 35.7                          | 35.8                             | 54.0           | -18.2       |
| 12310           | 0.1                                                           | 44.0                          | 44.1                             | 54.0           | -9.9        |
| 19696           | -9.3                                                          | 53.1                          | 43.8                             | 54.0           | -10.2       |
| 22158           | -8.2                                                          | 54.2                          | 46.0                             | 54.0           | -8.0        |

**Table 7-8: 2412 MHz; 802.11n; 65 Mbps; Channel 1; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4824            | 1.9                                                           | 33.2                          | 35.1                             | 54.0           | -18.9       |
| 12060           | 0.3                                                           | 44.0                          | 44.3                             | 54.0           | -9.7        |
| 14472           | -9.8                                                          | 47.9                          | 38.1                             | 54.0           | -15.9       |
| 19296           | -9.4                                                          | 52.9                          | 43.5                             | 54.0           | -10.5       |

**Table 7-9: 2437 MHz; 802.11n; 65 Mbps; Channel 6; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4874            | 1.8                                                           | 33.3                          | 35.1                             | 54.0           | -18.9       |
| 7311            | -0.2                                                          | 35.7                          | 35.5                             | 54.0           | -18.5       |
| 12185           | -0.3                                                          | 44.0                          | 43.7                             | 54.0           | -10.3       |
| 19496           | -9.2                                                          | 53.0                          | 43.8                             | 54.0           | -10.2       |

**Table 7-10: 2462 MHz; 802.11n; 65 Mbps; Channel 11; Average Mode**

| Frequency (MHz) | Spectrum Analyzer Average Level (1 MHz RBW/ 10 Hz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Average Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------------------------------------------------|-------------------------------|----------------------------------|----------------|-------------|
| 4924            | 1.4                                                           | 33.4                          | 34.8                             | 54.0           | -19.2       |
| 7386            | 0.0                                                           | 35.7                          | 35.7                             | 54.0           | -18.3       |
| 12310           | -0.6                                                          | 44.0                          | 43.4                             | 54.0           | -10.6       |
| 19696           | -9.2                                                          | 53.1                          | 43.9                             | 54.0           | -10.1       |
| 22158           | -8.4                                                          | 54.2                          | 45.8                             | 54.0           | -8.2        |
| 4924            | 1.4                                                           | 33.4                          | 34.8                             | 54.0           | -19.2       |

**Table 7-11: 2412 MHz; 802.11b; 2 Mbps; Channel 1; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4824            | 21.6                                                       | 33.2                          | 54.8                          | 74.0           | -19.2       |
| 12060           | 4.4                                                        | 44.0                          | 48.4                          | 74.0           | -25.6       |
| 14472           | 4.8                                                        | 47.9                          | 52.7                          | 74.0           | -21.3       |
| 19296           | 2.4                                                        | 52.9                          | 55.3                          | 74.0           | -18.7       |

**Table 7-12: 2437 MHz; 802.11b; 2 Mbps; Channel 6; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4874            | 17.7                                                       | 33.3                          | 51.0                          | 74.0           | -23.0       |
| 7311            | 12.8                                                       | 35.7                          | 48.5                          | 74.0           | -25.5       |
| 12185           | 1.2                                                        | 44.0                          | 45.2                          | 74.0           | -28.8       |
| 19496           | 1.2                                                        | 53.0                          | 54.2                          | 74.0           | -19.8       |

**Table 7-13: 2462 MHz; 802.11b; 2 Mbps; Channel 11; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4924            | 15.1                                                       | 33.4                          | 48.5                          | 74.0           | -25.5       |
| 7386            | 13.6                                                       | 35.7                          | 49.3                          | 74.0           | -24.7       |
| 12310           | 1.3                                                        | 44.0                          | 45.3                          | 74.0           | -28.7       |
| 19696           | 0.4                                                        | 53.1                          | 53.5                          | 74.0           | -20.5       |
| 22158           | -2.0                                                       | 54.2                          | 52.2                          | 74.0           | -21.8       |

**Table 7-14: 2412 MHz; 802.11g; 11 Mbps; Channel 1; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4824            | 17.8                                                       | 33.2                          | 51.0                          | 74.0           | -23.0       |
| 12060           | 13.5                                                       | 44.0                          | 57.5                          | 74.0           | -16.5       |
| 14472           | 6.2                                                        | 47.9                          | 54.1                          | 74.0           | -19.9       |
| 19296           | 5.3                                                        | 52.9                          | 58.2                          | 74.0           | -15.8       |

**Table 7-15: 2437 MHz; 802.11g; 11 Mbps; Channel 6; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4874            | 18.0                                                       | 33.3                          | 51.3                          | 74.0           | -22.7       |
| 7311            | 13.5                                                       | 35.7                          | 49.2                          | 74.0           | -24.8       |
| 12185           | 13.3                                                       | 44.0                          | 57.3                          | 74.0           | -16.7       |
| 19496           | 4.0                                                        | 53.0                          | 57.0                          | 74.0           | -17.0       |

**Table 7-16: 2462 MHz; 802.11g; 11 Mbps; Channel 11; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4924            | 13.5                                                       | 33.4                          | 46.9                          | 74.0           | -27.1       |
| 7386            | 13.4                                                       | 35.7                          | 49.1                          | 74.0           | -24.9       |
| 12310           | 13.1                                                       | 44.0                          | 57.1                          | 74.0           | -16.9       |
| 19696           | 4.0                                                        | 53.1                          | 57.1                          | 74.0           | -16.9       |
| 22158           | 5.3                                                        | 54.2                          | 59.5                          | 74.0           | -14.5       |

**Table 7-17: 2412 MHz; 802.11n; 65 Mbps; Channel 1; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4824            | 16.5                                                       | 33.2                          | 49.7                          | 74.0           | -24.3       |
| 12060           | 13.3                                                       | 44.0                          | 57.3                          | 74.0           | -16.7       |
| 14472           | 3.3                                                        | 47.9                          | 51.2                          | 74.0           | -22.8       |
| 19296           | 3.8                                                        | 52.9                          | 56.7                          | 74.0           | -17.3       |

**Table 7-18: 2437 MHz; 802.11n; 65 Mbps; Channel 6; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4874            | 14.6                                                       | 33.3                          | 47.9                          | 74.0           | -26.1       |
| 7311            | 13.2                                                       | 35.7                          | 48.9                          | 74.0           | -25.1       |
| 12185           | 12.6                                                       | 44.0                          | 56.6                          | 74.0           | -17.4       |
| 19496           | 3.9                                                        | 53.0                          | 56.9                          | 74.0           | -17.1       |

**Table 7-19: 2462 MHz; 802.11n; 65 Mbps; Channel 11; Peak Mode**

| Frequency (MHz) | Spectrum Analyzer Peak Level (1 MHz RBW/ 3 MHz VBW) (dBuV) | Site Correction Factor (dB/m) | Corrected Peak Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|------------------------------------------------------------|-------------------------------|-------------------------------|----------------|-------------|
| 4924            | 13.1                                                       | 33.4                          | 46.5                          | 74.0           | -27.5       |
| 7386            | 13.1                                                       | 35.7                          | 48.8                          | 74.0           | -25.2       |
| 12310           | 11.8                                                       | 44.0                          | 55.8                          | 74.0           | -18.2       |
| 19696           | 4.1                                                        | 53.1                          | 57.2                          | 74.0           | -16.8       |
| 22158           | 4.9                                                        | 54.2                          | 59.1                          | 74.0           | -14.9       |

**Test Personnel:**

Daniel W. Baltzell  
EMC Test Engineer



Signature

March 29, 2015  
Date of Test

Rhein Tech Laboratories, Inc.  
360 Herndon Parkway  
Suite 1400  
Herndon, VA 20170  
<http://www.rheintech.com>

Client: Harris Corporation  
Model: XL200P (International) Multi-Band Portable Radio  
IDs: OWDTR-0145-E/3636B-0145  
Standards: FCC 15.247/IC RSS-247  
Report #: 2015216DTS

## **8 Conclusion**

The data in this measurement report shows that the Harris Corporation Model XL-200P (International) Multi-Band Portable Radio, FCC ID: OWDTR-0145-E, IC: 3636B-0145, complies with the applicable intentional radiated requirements of FCC Parts 2 and 15 and Industry Canada RSS-247 and RSS-Gen.