

FCC PART 15 SUB-PART B & C EMI TEST REPORT

on

Remote Meter Interface Transceiver [FCC ID: OWS-900]

model names

**Information Management Unit (IMU) 900 [Internal Antenna] &
Information Management Unit (IMU) 901 [External Antenna]**

provided for evaluation by

**Innovatec Communications, LLC
101 South Second Street
Milwaukee, Wisconsin 53204**

evaluated and prepared by

**International Technology Company (ITC)
9959 Calaveras Road, Box 543
Sunol, California 94586-0543
Tel: (925) 862-2944
Fax: (925) 862-9013
Email: itcemc@aol.com
Web Site: www.itcemc.com**



Deutscher
Akkreditierungs
Rat

EN45001 Accredited Compliance Laboratory (RES-GmbH)
Registration number: TTI-P-G 159/98-00 (RES-GmbH)

TEST RESULT SUMMARY

FCC PART 15 SUB-PART B & C

General Information

Product Name	Transceiver
FCC ID	OWS-900
Model / Type	IMU 900 [Internal Antenna] & IMU 901 [External Antenna]
Manufacturer's Name:	Innovatec Communications, LLC
Manufacturer's Address	101 South Second Street Milwaukee, Wisconsin 53204 USA
Contact:	Tel: (414) 272-2255 • Fax: (414) 272-5421 Mr. Kimbel A. Nap
Laboratory	International Technology Company (ITC) 9959 Calaveras Road, PO Box 543 Sunol, CA 94586-0543 Tel: (925) 862-2944 • Fax: (925) 862-9013 Email: itcemc@aol.com • Web Site: www.itcemc.com
Test Number	120000216-1
Test Report Number	0002RS116-1/F
Test Date	January 27 through February 16, 2000
Project Technician	Bruce Gordon

According to testing performed at International Technology Company (ITC); the above-mentioned unit is in compliance with the emissions requirements defined in FCC Part 15 B and C. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics. Any modifications necessary for compliance made during testing on the above mentioned date(s) must be implemented in all production units for compliance to be maintained.

International Technology Company (ITC) as an independent testing laboratory, declares that the equipment tested as specified above conforms to the emissions requirements of FCC Part 15 B & C.

AGENCY DECLARATION/DISCLAIMER

All services undertaken are subject to the following general policy: Reports are submitted for exclusive use of the client to whom they are addressed. Their significance is subject to the adequacy and representative character of the samples and to the comprehensiveness of the tests, examinations or surveys made. No quotations from reports or use of ITC name or NVLAP or VCCI logo is permitted except as expressly authorized by ITC or NVLAP or VCCI in writing. It is agreed between ITC, NVLAP, VCCI and the client that no distribution in part of any test data herein or of this reports or analysis shall be made to any third party without the prior written consent of both parties. This report is not valid unless copied in full. All parties acknowledge that this report must not be used to claim product endorsement by ITC and/or NVLAP or VCCI. Reports are maintained on file for a period of five years. Additional copies of reports are available at a nominal fee. In correspondence concerning this report please refer to the date, manufacturer's name and the report number.

EMI Test Report

Product Type	Remote Meter Interface Transceiver
Model	IMU 900 [Internal Antenna & IMU 901 [External Antenna]
Applicant / Manufacturer Address	Innovatec Communications, LLC 101 South Second Street Milwaukee, Wisconsin 53204 USA Tel: (414) 272-2255 • Fax: (414) 272-5421
Client Contact	Mr. Mr. Kimbel A. Nap
Test Results	☒ Pass ☐ Fail
Total Number of Pages including Appendices	37 Pages
Test Report File No.	0002RS116-1/F
Date of Issue:	February 24, 2000

International Technology Company is:

Accepted by the Federal Communications Commission (FCC) for FCC Methods, CISPR Methods and AUSTEL Technical Standards (Ref: NVLAP Lab Code 200172-0)

Validated by the Chinese Taipei Bureau of Standards, Metrology, and Inspection (BSMI) under APEC MRA as a Conformity Assessment Body (CAB) under Appendix B, Phase 1 Procedures. BSMI # SL2-IN-E-024R

Approved by the Industry Canada for Telecom Testing

Certified by International Technology Company (ITC) GmbH for EMC Testing according to the European EMC Directive 89/336/EEC per EN45001

Certified by Reg. TP for EMC Testing according to the European EMC Directive 89/336/EEC per EN45001 for RES GmbH (DAR-Registration number: TTI-P-G 159/98-00)

Certified by the Voluntary Control Council for Interference by Information Technology Equipment (VCCI) for EMC testing, in accordance with the Regulations for Voluntary Control Measures, Article 8, Registration Numbers- Site 1: C-714 & R-696 and Site 2: C-715 & R-697

Engineering Services Offered by ITC

1) RELIABILITY CONSULTING AND SERVICES

- Reliability Services for Systems & Components
- MTBF Calculations
- MTTF Calculations
- Temperature Cycling Testing
- Thermal Shock Testing
- Vibration Shock testing

2) ENGINEERING EVALUATION & TESTING

- OSHA Third Party Evaluations
- SEMI S2 Reviews, 1993
- USB Specification Evaluations/Testing
- SAE Specification Evaluations/Testing
- EIA/TIA Specifications i.e. 571-A and 631
- MIL-STD i.e. 461,462,1541/EMC, 883/ESD

3) COMPLIANCE DESIGN CONSULTATION AND REGULATORY TESTING SERVICES

US: EMI/Telecom (FCC)

FCC 15 /class A
FCC 15 /Class B and B DoC
FCC 15 /SubPart C
FCC 24
FCC 68 (Analog and Digital)
FCC 90
FCC 95

Product Safety (UL/NRTL)

All UL Standards, Including:
UL 1950 /ITE
UL 2601/Medical
UL 1459 /Telecom
UL 1411 /Audio, Radio, TV
UL 813 /Commercial Audio
UL 1604 /Hazard. Location
UL 508 /Energy Mgmt. Equip.

EU: EMI/EMC (EN)

EN 50081-1 /50081-2
EN 50082-1 /50082-2
EN 55103-1/ 55103-2
EN 60601-1-2
EN 55011 /55013 /55014
EN 55015 /55020 /55022
EN 60555-2 /60555-3
EN 61000-3-2 /61000-3-3
EN 61000-4-2 /61000-4-3
EN 61000-4-4 /61000-4-5
EN 61000-4-6 /61000-4-8 /61000-4-11

Canada: EMI, Safety, Telecom Asia - Australia/ International

RSS 210 & RSS 221	CISPR 11, 13, 14, 15, 16, 20, 22
Industry Canada /IC CS-03	VCCI Class 1 & 2 /Japan
All c-UL Standards for Canada	AS/NZ 3548: C-Tick Mark, EMC
All CSA Standards, including:	CNS 13438 - 1996/Taiwan
CSA No. 950/ ITE	ITU Standards
CSA No. 601-1/Medical	IEC /ETSI Standards
CSA No. 1010-1/ Lab, Measurement	BellCore Standards
CSA No. 225/ Telecom	IEEE /ANSI Standards

EU: Safety/Machinery (EN)

EN 60950 /61010-1
EN 60204 /60065
EN 60601-1-1
TÜV
*Competent Body Representation/EU

ITC – Your One-Stop-Shop

Our comprehensive capabilities, friendly environment & fast project turn-around time makes ITC the ideal **one-stop-shop** for your engineering services needs, providing manufacturers with compliance design consultation, reliability & compliance engineering. We are committed to delivering the highest-quality engineering services & expertise you can expect at reasonable, competitive rates. We look forward to working with you on your next design, reliability compliance or engineering consultation project. For more information, contact our Business Services Department.

You can call or e-mail us at:

Toll-Free: 1-888-336-7625 – **Internet:** <http://www.itcemc.com> – **E-mail:** itcemc@aol.com

Table of Contents

	<i>Pages</i>
Part 1: General	
1.1 Test Methodology	7-8
1.2 Summary	9
 Part 2: FCC Part 15 SubPart B, Powerline Conducted Emissions Information.....	
 Part 3: FCC Part 15 SubPart B, Open Field Radiated Emissions	
3.1 Configuration and Procedure.....	11
3.1.1 EUT Configuration.....	11
3.1.2 Test Procedure.....	11
3.1.3 Field Strength Calculation.....	12
3.1.4 Spectrum Analyzer Configuration.....	12
3.2 Open Field Radiated Emissions.....	13
3.2.1 Administrative Details.....	13
3.2.2 Open Field Radiated Emissions Test Results	13
 Part 4: FCC Part 15 SubPart C, Occupied Bandwidth Tests	
4.1 Configuration and Procedure.....	14
4.1.1 EUT Configuration.....	14
4.1.2 Test Procedure.....	14
4.2 6dB Bandwidth Plots	15-17
 Part 5: Fundamental Harmonic and Spurious Emissions	
5.1 Configuration and Procedure.....	18
5.1.1 EUT Configuration.....	18
5.1.2 Test Procedure.....	18
5.1.3 Spectrum Analyzer Configuration.....	18
5.2 Fundamental Harmonic and Spurious Emissions	19
5.2.1 Administrative Detail... ..	19
5.2.2 Fundamental Harmonic and Spurious Emissions Test Results.....	19-21

Table of Contents.....

	<i>Pages</i>
Part 6: FCC Part 15 SubPart C, RF Power Output	
6.1 Configuration and Procedure.....	22
6.1.1 EUT Configuration.....	22
6.1.2 Test Procedure.....	22
6.1.3 Spectrum Analyzer Configuration.....	22
6.2 Maximum Peak Output Power Plot.....	23-28

Tables

3.2.2 Open Field Radiated Emissions.....	13
5.2.2 Fundamental Harmonic and Spurious Emissions	19-21

Plots

4.2 6dB Bandwidth Plot at 1m Distance (Low, Middle and High Frequencies).....	15-17
6.2 Maximum Peak Output Power (Low, Middle and High Frequencies).....	23-28

Appendices

A: Measurement Procedures.....	29
B: Description of Open Field Test Site... ..	30
C: Test Equipment.....	31-32
D: EUT Technical Description.....	33-36
E: Modification.....	37

PART 1

GENERAL

1.1 Test Methodology

The tests described in this report were performed by an independent electromagnetic compatibility Laboratory, International Technology Company, in accordance with the FCC test procedure ANSI C63.4-1992.

1.1.1 Test Facility

The open area test site, the conducted measurement facility, and the test equipment used to collect the emissions data is located in Sunol, California, and is fully described in site attenuation report. The approved site attenuation description is on file at the Federal Communications Commission.

1.1.2 Accuracy of Test Data

The test results contained in this report accurately represent Open Field Radiated Emissions, Occupied Bandwidth, Frequency Stability, RF Power Output, Spurious and Harmonic Emissions and Modulation Characteristics tests generated by the sample equipment under test.


<i>Equipment Tested</i>	Transceiver
<i>FCC ID</i>	OWS-900
<i>Date of Test</i>	January 27 through February 16, 2000

Test Methodology.....

Tests Performed:

1. Radiated Emissions in a 3-meter open area site in accordance with the FCC test procedure 47 CFR §15.209 and §15.31(m). Part 3 of this report contains details.
2. Occupied Bandwidth Test in accordance with the FCC test procedure 47 CFR §15.247(2). Part 4 of this report contains details.
3. Harmonics and Spurious Emissions Test in accordance with the FCC test procedure 47 CFR §2.1053 and §15.249(a). Part 5 of this report contains details.
4. Maximum Peak Output Power Test Requirement in accordance with 47 CFR §15.247(b). Part 6 of this report contains details.

The results show that the sample equipment tested as described in this report is in compliance with the FCC Rules Part 15, SubPart B: Open Field Radiated Emissions. Occupied Bandwidth, Harmonics and Spurious Emissions and Maximum Peak Output Power test requirement limits of, SubPart C.



Michael Gbadebo, PE
Chief Engineer/Principal Consultant

1.2 Summary

1.2.1 Description of Equipment under Test (EUT)

See Appendix D for more information

Model Name(s): Information Management Unit
IMU 900 (Internal Antenna)
IMU 901 (External Antenna)

Applicant: Innovatec Communications, LLC
Address: 101 South Second Street
Milwaukee, Wisconsin 53204 USA
• Tel: (414) 272-2255
• Fax: (414) 272-5421

Client Contact: Mr. Mr. Kimbel A. Nap

Test Technician: Bruce Gordon

Test Number: 120000216-1
File Number: 0002RS116-1/F

EUT: IMU 900
Test data on IMU 901 (external Antenna) will be submitted shortly under the same
FCC ID No: OWS-900.

1.2.2 Support Equipment included in the Tests:

The Transceiver was tested as a stand-alone device.

PART 2

POWERLINE CONDUCTED EMISSIONS

per FCC PART 15 SUBPART B

**Powerline Conducted Emissions test was not performed on the Transceiver
because it was powered by 3.6Vdc Lithium-Ion Battery**

PART 3

OPEN FIELD RADIATED EMISSIONS

per FCC PART 15 SUBPART B

3.1 Configuration and Procedure

3.1.1 EUT Configuration

Pre-scan measurements were first performed with a spectrum analyzer set in fast sweep mode. Significant peaks are marked and then quasi-peaked. Measurement range investigated was from 30 MHz to 1 Ghz. The EUT (IMU) was set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-1992. The measurement instrumentation used was a receiver with bandwidth parameters as stipulated in ANSI C63.4-1992. The IMU Transceiver was set up on a wooden non-conductive table top, 80 cm above the ground reference plane, in an open field. The dimension of the table was 1.5m x 1.0m. Excess cord (if provided) was folded back to form a 30-cm by 40-cm bundle, which was hanging mid-way above the ground plane. Frequency measurement was taken from 30MHz up to 10th harmonic.

3.1.2 Test Procedure

The EUT was set up as described above while transmitting and receiving continuously. The EUT (IMU) was rotated 360 degrees azimuth and the search antenna height varied 1 to 4 m in order to maximize the emissions from the EUT. The highest emissions were also analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. While doing so, interconnecting cables were moved around to maximize the emissions.

Configuration and Procedure...

3.1.3 Data Table Legend and Field Strength Calculation

'Margin' indicates the degree of compliance with the applicable limit. For example, a margin of -8 dB means that the emissions are 8 dB below the limit (in compliance); +a margin of +4 dB means that the emission is 4 dB over the limit (out of compliance). The margin calculated as follows:

Margin = Corrected Amplitude - Limit, where Corrected Amplitude = Amplitude + Antenna Correction Factor + Cable Loss – amplifier gain.

3.1.4 Nominal Spectrum Analyzer Configuration (during swept frequency scans)

Start Frequency 30MHz
Stop Frequency.....1000MHz
Sweep SpeedManual

Measurements below 1GHz

RES Bandwidth..... 100 kHz
Video Bandwidth..... 100 kHz
Quasi Peak Adapter Mode..... Normal
Quasi peak Adapter Bandwidth..... 120 kHz

Measurements above 1GHz (unless stated otherwise)

Analyzer ModeVideo Filter
RES Bandwidth..... 1MHz
Video Bandwidth..... 1MHz
Freq. Span..... 3MHz
Offset..... 0dB
Quasi Peak Adapter Mode..... Disabled

3.2 Open Field Radiated Emissions per FCC Part 15 SubPart B

3.2.1 Administrative Details

Date(s) of Test: January 27 through February 16, 2000
Emission Limits: Class B
Temperature/Humidity: 19.8⁰⁰C / 64%
ATM Pressure: 1010 Mbar
Test Technician(s): Bruce Gordon
Antenna Used: Biconical Antenna, model # 3104, S/N 3459 and Log Periodic Antenna,
model # 3146, S/N 2075 (calibrated June 25, 1999, next calibration due
date is June 25, 2000)

3.2.2 Test Results

The table below shows a summary of the highest amplitudes of the radiated emissions from the equipment under test at various antenna heights, antenna polarization, and EUT orientations.

INDICATED		CORRECTION		CORR	T/TAB		ANT	FCC 15	CLASS B
FREQ	AMPL	ANT	CAB	AMPL	ANG	HT	POL	LIMIT	MARGIN
MHz	dBuV/m	dB	dB	dBuV/m	DEG	m	-	dBuV/m	dB
33.10	9.2	11.7	2.5	23.4	90	1.0	VB	40.0	-16.6
112.20	8.5	13.9	3.9	26.3	180	2.0	HB	43.5	-17.2
198.10	10.7	15.3	4.7	30.7	0	2.0	HB	43.5	-12.8
249.52	19.1	13.2	5.2	37.5	180	2.0	HL	46.0	-8.5
552.00	12.4	19.7	6.8	38.9	270	1.0	VL	46.0	-7.1
946.00	0.5	23.8	8.3	32.6	180	3.0	HL	46.0	-13.4

Table 3.2.2 Open Field Radiated Emissions for Information Management Unit (IMU)

No emissions of significant levels were observed between 30 Mhz to 1 Ghz. No significant emission levels were observed between 1 Ghz to 10th harmonics of the EUT.

Conclusion: The Information Management Unit meets the requirements of the test reference for Open Field Radiated Emissions of Section 15.109 for class B Digital Devices.

PART 4

OCCUPIED BANDWIDTH

per FCC PART 15 SECTION 47 CFR §15.247(2)

4.1 Configuration and Procedure

4.1.1 EUT Configuration

The IMU Transceiver was set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-1992. The measurement instrumentation used was an Hewlett Packard 8566B Spectrum Analyzer with detector and bandwidth parameters as stipulated in C63.4-1992. The Transceiver was powered by 3.6Vdc power supply.

4.1.2 Test Procedure

The EUT was placed on the wooden turntable and the table was rotated until the highest emissions were observed. The EUT was transmitting continuously with modulation on at low, medium, and high channel frequencies. Signal was monitored with HP 8566B Spectrum Analyzer, using the EMCO Double-Ridged Wave-guide Horn Antenna, model #3115. Unless stated otherwise. The receiving antenna was raised to maximize the signal strength (1-1.6 meter above the referenced ground plane). At each channel frequency, the EUT was monitored for spurious modulation products including harmonics (up to 10th), 6dB bandwidth, peak spectral power density, peak conductive power, and dwell time.

4.2.1 Bandwidth Test

Per FCC Part 15 Section 47 CFR §15.247(2)

6dB Bandwidth Plot Performed at 3-Meter Distance (Low Channel Frequency)