

TEST REPORT



Certification # 1367-01

Laboratory ID

PRODUCT SAFETY ENGINEERING, INC.
12955 Bellamy Brothers Boulevard
Dade City, Florida 33525 USA
PH (352) 588-2209 FX (352) 588-2544

Submitter ID

PFK Electronics
P.O. Box 3660

Durban, 4000

Report Issue Date: 25 JUL 06
Sample S/N: Sample 2
Sample Receipt Date: 13 JUN 06
Sample Test Date: see data sheets

Test Report Number: 06F242B
Model Designation: PFK 743-301
Product Description: Remote Control 433.92 MHz

Description of non-standard test method or test practice: *None*

Estimated Measurement Uncertainty: *Not Applicable*

Special limitations of use: *None*

Traceability: *reference standards of measurement have been calibrated by a competent body using standards traceable to the NIST.*

According to testing performed at Product Safety Engineering, Inc., the above-mentioned unit is in compliance with the electromagnetic compatibility requirements defined in regulations indicated on page (3) of the test report. The test results contained herein relate only to the model(s) identified above. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Project Engineer, I hereby declare that the equipment tested as specified above conforms to the requirements indicated on page (3) of the test report.

Signature David Foerstner Name David Foerstner

Title Engineering Group Leader Date 25 JUL 06

Reviewed by: John E. Hule Date 25 JUL 06
Approved Signatory

This report may only be reproduced in full with written permission from Product Safety Engineering, Inc.

Test Report Number 06F242B

Product Safety Engineering, Inc. 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

DIRECTORY - EMISSIONS

		Page(s)
A) Documentation		
Test report		1 - 10
Directory		2
Test Regulations		3
General Remarks		10
Test-setups (Photos)		11 - 12
B) Test data		
Conducted emissions	10/150 kHz - 30 MHz	5, 9
Radiated emissions	10 kHz - 30 MHz	5, 9
Radiated emissions	30 MHz - 1000 MHz	6, 9
Interference power	30 MHz - 300 MHz	6, 9
Equivalent Radiated emissions	1 GHz - 18 GHz	7, 9
Antenna Disturbance Voltage	30 MHz - 1,000 MHz	7, 9
C) Appendix A		
Test Equipment Calibration Information		A2
Test Data Sheets		A3 - A7
D) Appendix B		
System Under Test Description		B2 - B4
E) Appendix C		
Measurement Protocol		C1 - C2

Test Report Number 06F242B

EMISSIONS TEST REGULATIONS :

The emissions tests were performed according to following regulations:

- ☐ - EN 61000-6-3:2001
- ☐ - EN 61000-6-4:2001

- ☐ - EN 55011 : 1998 / A1:1999
- ☐ - Group 1
- ☐ - Group 2
- ☐ - Class A
- ☐ - Class B

- ☐ - EN 55013 : 1990 / A12:1994 / A13:1996 / A14:1999

- ☐ - EN 55014 -1: 2001
- ☐ - Household appliances and similar
- ☐ - Portable tools
- ☐ - Semiconductor devices

- ☐ - EN 55022 (1998) /A1:2001 /A2:2003
- ☐ - Class A
- ☐ - Class B

- ☐ -AS/NZS 3548:1995
- ☐ - Class A
- ☐ - Class B

- ☐ - ICES-003
- ☐ - Class A
- ☐ - Class B

- ☐ - CNS 13438
- ☐ - Class A
- ☐ - Class B

- ☐ - VCCI : 1999
- ☐ - Class A
- ☐ - Class B

- ☒ - FCC Part 15
- ☐ - Class A
- ☒ - Class B

- ☒ - Certification
- ☐ - Verification
- ☐ - Declaration of Conformity

- ☐ - FCC Part 18

Test Report Number 06F242B

Environmental conditions during testing:

	LAB	OATS
Temperature: *	_____	: _____
Relative Humidity: **	_____	: _____

* The ambient temperature during the testing was within the range of (50° - 104° F) unless indicted above.

** The humidity levels during the testing was within the range of (10% - 90%) relative humidity unless indicated above.

Power supply system : _____ 12 _____ Volts _____ DC _____ Hz _____ Battery _____

Sign Explanations:

- ☐ - not applicable
- ☒ - applicable

Test Report Number 06F242B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

Emissions Test Conditions: CONDUCTED EMISSIONS (Interference Voltage)

The *CONDUCTED EMISSIONS (INTERFERENCE VOLTAGE)* measurements were performed at the following test location:

■ - Test not applicable

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ - Darby Laboratory

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - 8028-50	Solar	50 Ω LISN	829012, 829022
☐ - 3825/2	Solar	50 Ω LISN	924840
☐ - EMC-30	Electro-Metrics	EMI Receiver	191
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - 85662A	Hewlett Packard	Analyzer Display	2403A07352
☐ - 8028-50	Solar	50 Ω LISN	903725, 903726
☐ - FCC-TLISN-T4	Fisher Custom Com.	Telecom ISN	20072

Emissions Test Conditions: RADIATED EMISSIONS (Magnetic Field)

The *RADIATED EMISSIONS (MAGNETIC FIELD)* measurements were performed at the following test location:

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ -
- ☐ -

at a test distance of :

- ☐ - 3 meters
- ☐ - 30 meters

■ - Test not applicable

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - 3148	EMCO	Log Periodic Antenna	00044783
☐ - BIA-25	Electro-Metrics	Biconical Antenna	4283
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - ALR-30M	Electro-Metrics	Loop Antenna	824
☐ - 8447D	Hewlett Packard	Preamplifier	2944A06832
☐ - EMC-30	Electro-Metrics	EMI Receiver	191
☐ - ALA-130/A	Antenna Research	Loop Antenna	106

Test Report Number 06F242B

Emissions Test Conditions: RADIATED EMISSIONS (Electric Field)

The *RADIATED EMISSIONS (ELECTRIC FIELD)* measurements, in the frequency range of 30 MHz-1000 MHz, were tested in a horizontal and vertical polarization at the following test location :

☐ - Test not applicable

- ☒ - Darby Site (Open Area Test Site)
- ☐ - Darby Lab
- ☐ -

at a test distance of :

- ☒ - 3 meters
- ☐ - 10 meters
- ☐ - 30 meters

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☒ - 3148	EMCO	Log Periodic Antenna	00044783
☒ - BIA 25	Electro-Metrics	Biconical Antenna	4283
☒ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☒ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☒ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☒ - 8447D	Hewlett-Packard	Preamplifier (26dB)	2944A06832
☐ - EMC-30	Electro-Metrics	EMI Receiver	191
☐ - 8568B	Hewlett Packard	Spectrum Analyzer	2407A03213
☐ - 85650A	Hewlett Packard	Quasi-Peak Adapter	2043A00358
☐ - 85662A	Hewlett Packard	Analyzer Display	2340A05806
☐ - LPA30	Electro-Metrics	Log Periodic	2280
☐ - BIA-30	Electro-Metrics	Biconical Antenna	3852

Emissions Test Conditions): INTERFERENCE POWER

The *INTERFERENCE POWER* measurements were performed by using the absorbing clamp on the mains and interface cables in the frequency range 30 MHz - 300 MHz at the following test location :

☒ - Test not applicable

- ☐ - Darby Lab
- ☐ -

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - MDS-21	Rhode&Schwarz	Absorbing Clamp	8608447020
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - 8447D	Hewlett-Packard	Amplifier (26 dB)	2944A06832
☐ - EMC-30	Electro-Metrics	EMI Receiver	191

Test Report Number 06F242B

The *EQUIVALENT RADIATED EMISSIONS* measurements in the frequency range 1 GHz - 4.4 GHz were performed in a horizontal and vertical polarization at the following test location :

☒ - Darby Test Site (Open Area Test Site)

☐ -

☐ -

☐ -

at a test distance of:

☐ - 1 meters

☒ - 3 meters

☐ - 10 meters

☐ - Test not applicable

Test equipment used :

	Model Number	Manufacturer	Description	Serial Number
☒ -	8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☒ -	85662A	Hewlett-Packard	Analyzer Display	2403A07352
☒ -	85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☒ -	8449B	Hewlett-Packard	Preamplifier	3008A00320
☒ -	3115	Electro-Mechanics	Double Ridge Guide Horn	3810

The *ANTENNA TERMINAL DISTURBANCE VOLTAGE* in the frequency range 30 MHz - 1,000 MHz were performed.

☐ - Darby Test Site (Open Area Test Site)

☐ - Laboratory

☐ -

☐ -

☒ - Test not applicable

	Model Number	Manufacturer	Description	Serial Number
☐ -	2F9-3C4-3C5	Wavecom	UHF PAL TV Modulator	185879
☐ -	2F1-3C4-3C5	Wavecom	VHF PAL TV Modulator	157728
☐ -	A-8000	IFR	Spectrum Analyzer	1306
☐ -	8648B	Hewlett-Packard	Signal Generator	3623A01433
☐ -	8648B	Hewlett-Packard	Signal Generator	3623A01477
☐ -	LMV-182A	Leader	RMS Milli-Voltmeter	8010091
☐ -	3202	Krhon-Hite	Active filter	5899
☐ -	FMT115	Leaming	FM Modulator	NONE
☐ -	371	UDT	Optical power meter	06657
☐ -	TSG95	Tektronix	PAL video / Audio generator	B028883
☐ -				

Test Report Number 06F242B

Equipment Under Test (EUT) Test Operation Mode - Emission tests :

The device under test was operated under the following conditions during emissions testing:

- ☐ - Standby
- ☐ - Test program (H - Pattern)
- ☐ - Test program (color bar)
- ☐ - Test program (customer specific)
- ☐ - Practice operation
- ☒ - Normal Operating Mode
- ☐ -

Configuration of the device under test:

- ☒ - See System Under Test Information in Appendix B

Rationale for EUT setup / configuration:

Test Report Number 06F242B

Emission Test Results:

Conducted emissions 150 kHz - 30 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
Remarks:

Radiated emissions (magnetic field) 10 kHz - 30 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
Remarks:

Radiated emissions (electric field) 30 MHz - 1000 MHz

The requirements are ☒ - MET ☐ - NOT MET
Minimum limit margin 2.0 dB at 868.0 MHz
Remarks:

Interference Power at the mains and interface cables 30 MHz - 300 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
Remarks:

Radiated emissions 1GHz - 4.4 GHz

The requirements are ☒ - MET ☐ - NOT MET
Minimum limit margin 4.3 dB at 1.736 GHz
Remarks:

Antenna Terminal Disturbance Voltage 30 MHz - 1,000 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
Remarks:

Test Report Number 06F242B

GENERAL REMARKS:

SUMMARY:

The requirements according to the technical regulations are

■ - met

□ - **not** met.

The device under test does

■ - fulfill the general approval requirements mentioned on page 3.

□ - **not** fulfill the general approval requirements mentioned on page 3.

Testing Start Date June 22, 2006

Testing End Date: June 22, 2006

- PRODUCT SAFETY ENGINEERING INC -

Test Report Number 06F242B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

Test-setup photo(s):

Conducted emission 150 kHz - 30 MHz

N/A

Test Report Number 06F242B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

Test-setup photo(s):
Radiated emission 30 MHz - 1000 MHz



Test Report Number 06F242B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

APPENDIX

A

Test Equipment Calibration Information & Test Data Sheets

Test Report Number 06F242B

TEST EQUIPMENT CALIBRATION INFORMATION

Manufacturer	Model	Description	Serial Number	Cal Due
Hewlett Packard	8566B	Spectrum Analyzer	2421A00526	07/18/06
Hewlett Packard	85662A	Display	2403A07352	07/18/06
Hewlett Packard	85650A	Quasi-Peak Adapter	2043A00209	07/18/06
Hewlett Packard	8447D	Preamplifier 0.1 - 1,000 MHz	2944A06832	12/08/06
Hewlett Packard	8568B	Spectrum Analyzer	2407A03213	08/03/06
Hewlett Packard	85662A	Display	2340A05806	08/03/06
Hewlett Packard	85650A	Quasi-Peak Adapter	2043A00358	08/03/06
Hewlett Packard	8447D	Preamplifier 0.1 - 1,000 MHz	2944A06901	08/03/06
Hewlett Packard	8447D	Preamplifier 0.1 - 1,000 MHz	1937A03247	08/03/06
Hewlett Packard	8449B	Preamplifier 1 - 26.5 GHz	3008A00320	12/08/06
Hewlett Packard	8648B	Signal Generator	3443U00312	05/26/06
Hewlett Packard	8672A	Signal Generator	2211A02426	12/08/06
EMCO	3148	Log Periodic Antenna	00044783	03/24/07
Electro-Metrics	LPA 30	Log Periodic Antenna	2280	12/14/06
Electro-Metrics	BIA 30	Biconical Antenna	3852	12/12/06
Electro-Metrics	BIA 25	Biconical Antenna	4283	04/10/07
Electro-Mechanics	3115	Double Ridge Guide Ant.	3810	11/28/07
Electro-Metrics	ALR30M	Magnetic Loop Antenna	824	12/12/06
Solar	8012	LISN	924840	04/06/07
Solar	8028	LISN	829012/809022	12/12/06
Solar	8028	LISN	903725/903726	11/22/06
Schwartzbeck	MDS-21	Absorbing Clamp	02581	04/27/07
Leader	LFG1310	Function Generator	8060233	05/26/06
Electro-Metrics	EMC-30	EMI Receiver	191	05/26/06
Antenna Research	ALA-130/A	Loop Antenna	106	06/02/06
Cole-Palmer	9970-00	Digital Barometer	61493735	03/13/07

Test Report Number 06F242B

Page A2 of A7

PRODUCT EMISSIONS

PRODUCT SAFETY ENGINEERING

PRODUCT SAFETY ENGINEERING

Data File: PFK 743-301 FCC-B 6-22-2006

No	EMISSION	SPEC LIMIT	MEASUREMENTS			SITE			CORR FACTOR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE	POL	HGT cm	AZM deg		
				dB					dB	
1	433.995	92.9	89.7	-3.2	PK	V	100	2	-9.2	
2	867.976	72.9	70.9	-2.0	PK	V	100	2	-1.2	

06F242B

A3

PFK 743-301

Measured @ 3 Meters

Frequency (GHz)	Spec Limit (dB μ V/M)	Measurement (dB μ V/M)	Δ Limit	Polarity	Height (cm)
1.302	72.9	68.2	-4.7	Vertical	100
1.735	72.9	69.5	-3.4	Vertical	100
2.169	72.9	66.1	-6.8	Vertical	100
2.602	72.9	45.3	-27.6	Vertical	100
3.036	72.9	50.0	-22.9	Vertical	100
3.469	72.9	55.9	-17.0	Vertical	100
3.903	72.9	64.4	-8.5	Vertical	100
4.336	72.9	61.4	-11.5	Vertical	100

Test Report Number 06F242B

Page A4 of A7

Ref 107 dBμV

Atten 10 dB

Mkr1 Δ 329.0 kHz
0.013 dB


Peak

Log

10

dB/

M1 S2
S3 FC
AA



Center 434 MHz
Res BW 120 kHz

VBW 300 kHz

Span 629.8 kHz
Sweep 5 ms (401 pts)

File

Create Dir

Format


More
2 of 2

06F242B

A5

Tek Stop: 10.0kS/s

27 Acqs



Cursor
Function

Off

H Bars

V Bars

paired

paired

Function
V Bars

Mode
Indep

Time
Units
seconds

Amplitude
Units
Base

06 F 242 B

A6

APPENDIX

B

System Under Test Description

Test Report Number 06F242B

Page B1 of B4

SYSTEM COMPONENTS

DEVICE TYPE: EUT, PFK 743-301 TRANSMITTER

Test Report Number 06F242B

Page B2 of B4

INTERFACE CABLES

DEVICE TYPE: EUT **NONE**

SHIELD:

LENGTH:

CONNECTOR TYPE:

PORT:

Test Report Number 06F242B

Page B3 of B4

AC LINE CORDS

DEVICE TYPE: EUT **NONE**

SHIELD:

LENGTH:

CONNECTOR TYPE:

Test Report Number 06F242B

Page B4 of B4

APPENDIX

C

Measurement Protocol

Test Report Number 06F242B

Page C1 of C2

The test methodology followed during the collection of the data included within this technical report was ANSI C63.4:2003.

The EUT was powered with (12) VDC during the collection of data included within.

The data is compared to the FCC Part 15 Class B limits.

The "EMI" instrumentation is capable of calculating the final emission level based on the following formula:

Level at the receiver (dB μ V) + Antenna Correction Factor (dB/M) + Cable Loss (dB) - Preamp Gain (dB) = Actual Level in dB μ V/M.

The sample calculation below is based on the actual test data collected:

Observed Level		90.8	dB μ V	
ACF	+	17.2	dB/M	
Cable Loss	+	7.7	dB	
Preamp Gain	-	26.0	dB	
Actual Level		89.7	dB μ V/M	@ 434.0 MHz

Please have a company official review this report and sign.
