



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Date: September 29, 2006

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: The Toro Company
5825 Jasmine Street
Riverside, CA 92504

Equipment: TMR-1-TX, CMR-TX
FCC ID: OXP

FCC Rules: Radiofrequency Radiation Exposure Limits
47 CFR 1.1310

MPE - Mobiles

X

Fixed Based Station

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

Hoosamuddin S. Bandukwala, Lab
Director



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Environmental Assessment

for

Mobiles / Fixed Base Station

for

FCC ID:

Model: TMR-1-TX, CMR-TX

to

Federal Communications Commission

47 CFR 1.1310 (MPE)

Radiofrequency Radiation Exposure Limits

Date Of Report: September 29, 2006

On the Behalf of the Applicant:

The Toro Company

At the Request of:

P.O.

The Toro Company
5825 Jasmine Street
Riverside, CA 92504

Attention of:

Nick Nguyen
(909)785-3629
email: Nick.Nguyen@Toro.com

Supervised By:

Hoosamuddin S. Bandukwala, Lab
Director

Table of Contents

Rule	Description	Page
	Test Report	1
	Identification of the Equipment Under Test	2
	Standard Test Conditions and Engineering Practices	5

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) **Test Report (Supplemental)**

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0690013

d) Client: The Toro Company
5825 Jasmine Street
Riverside, CA 92504

e) Identification: TMR-1-TX, CMR-TX

Description: Wireless Maintenance Remote Control

f) EUT Condition: Not required unless specified in individual tests.


g) Report Date: September 29, 2006
EUT Received:

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



Hoosamuddin S. Bandukwala, Lab
Director

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

Identification of the Equipment Under Test (EUT)

Name and Address of Applicant:

The Toro Company
5825 Jasmine Street
Riverside, CA 92504

Manufacturer:

The Toro Company

FCC ID:

OXF

Model Number:

TMR-1-TX, CMR-TX

Description:

Wireless Maintenance Remote Control

Type of Emission:

11K0F1D

Frequency Range, MHz:

154.600
151.820

Power Rating, Watts:

____ Switchable

____ Variable

0.5 to 0.5

____ x N/A

Modulation:

____ AMPS

____ TDMA

____ CDMA

X OTHER

Antenna:

____ Helical

____ Monopole

X Whip

____ Other

Note: For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.

Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-2003 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

 THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION ACCREDITED LABORATORY A2LA has accredited FLOM TEST LABS Chandler, AZ for technical competence in the field of Electrical Testing The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025-1999 "General Requirements for the Competence of Testing and Calibration Laboratories" and any additional program requirements in the identified field of testing. Presented this 14th day of June 2004. <i>Pete. R. R. R.</i> President For the Accreditation Council Certificate Number 2152-01 Valid to November 30th, 2006 Revised September 25, 2006 For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.	A2LA "A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 – 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing." Certificate Number: 2152-01
---	--



A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 - 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: **2152-01**

Name of Test: R.F. Radiation Exposure / MPE Calculation

FCC Rules: 1.1307, 1.1310, 1.1311, 2.1091


Description, EUT: See page 2 of Test Report

Limits: Controlled Exposure 47 CFR 1.1310 Table 1, (A)	0.3-3.0 MHz:	Limit [mW/cm ²] = 100
	3.0-30 MHz:	Limit [mW/cm ²] = (900/f ²)
	30-300 MHz:	Limit [mW/cm ²] = 1.0
	300-1500 MHz	Limit [mW/cm ²] = f/300
	1500-100,000 MHz:	Limit [mW/cm ²] = 5.0

Limits: Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)	0.3-1.234 MHz:	Limit [mW/cm ²] = 100
	1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
	30-300 MHz:	Limit [mW/cm ²] = 0.2
	300-1500 MHz	Limit [mW/cm ²] = f/1500
	1500-100,000 MHz:	Limit [mW/cm ²] = 1.0

Test Frequencies, MHz	154.6
Power, Conducted, W	= 0.5
Antenna Gain	= 0 dB
Antenna Model	¼ Wave Whip

Calculations	$Power_{[W\ EIRP]} = P_{[conducted]} \times G_{[antenna]}$	= 0.5
	$Limit_{[mW/cm^2]}$	= 0.2
	$Limit_{[W/m^2]} = 10 \times Limit_{[mW/cm^2]}$	= 2.0
	$R_{[m]} = [P_{[W\ EIRP]} / (4\pi \times Limit_{[W/m^2]})]^{1/2}$	= 0.141



Supervised By:

Hoosamuddin S. Bandukwala, Lab
Director

(The following will be placed in the Instruction Manual)

Mandatory Safety Instructions to Installers & Users

Use only manufacturer or dealer supplied antenna.

Antenna Minimum Safe Distance: .

Antenna Gain: zero dBd referenced to a dipole.

The Federal Communications Commission has adopted a safety standard for human exposure to RF (Radio Frequency) energy which is below the OSHA (Occupational Safety and Health Act) limits.

Antenna Mounting: The antenna supplied by the manufacturer or radio dealer must not be mounted at a location such that during radio transmission, any person or persons can come closer than the above indicated minimum safe distance to the antenna i.e. .

To comply with current FCC RF Exposure limits, the antenna must be installed at or exceeding the minimum safe distance shown above, and in accordance with the requirements of the antenna manufacturer or supplier.

Base Station Installation: The antenna should be fixed-mounted on an outdoor permanent structure. RF Exposure compliance must be addressed at the time of installation.

Antenna Substitution: Do not substitute any antenna for the one supplied or recommended by the manufacturer or radio dealer. You may be exposing person or persons to excess radio frequency radiation. You may contact your radio dealer or the manufacturer for further instructions.


Warning: Maintain a separation distance from the antenna to a person(s) of at least .

You, as the qualified end-user of this radio device must control the exposure conditions of bystanders to ensure the minimum separation distance (above) is maintained between the antenna and nearby persons for satisfying RF Exposure compliance. The operation of this transmitter must satisfy the requirements of Occupational/Controlled Exposure Environment, for work-related use. Transmit only when person(s) are at least the minimum distance from the properly installed, externally mounted antenna.

**Testimonial
and
Statement of Certification**

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.



Certifying Engineer:

Hoosamuddin S. Bandukwala, Lab
Director