

Test Report

Test report no.: 23099117-34649-1

Date of issue: 2023-11-17

Test result: The test item - **passed** - and complies with the listed standards.

Applicant

Huf Baolong Electronics Bretten GmbH

Manufacturer

Huf Baolong Electronics Bretten GmbH

Test Item

TMSS5B4

Radio Frequency Testing according to:

Title 47
FCC Regulations Subpart 15C
§15.231

Tested by
(name, function, signature)

Piotr Sardyko
Lab Manager RF



signature

Approved by
(name, function, signature)

Andreas Bender
Deputy Managing Director



signature

Applicant and Test item details

Applicant	Huf Baolong Electronics Bretten GmbH Gewerbestr. 40, 75015 Bretten Germany
Manufacturer	Huf Baolong Electronics Bretten GmbH Gewerbestr. 40, 75015 Bretten Germany
Test item description	TPMS Sensor S5.xF 433 MHz
Model/Type reference	TMSS5B4

FCC ID	OYGTMSS5B4
---------------	------------

Disclaimer and Notes

The content of this test report relates to the mentioned test sample(s) only.
Without a written permit of IBL-Lab GmbH, this test report shall not be reproduced, except in full.

Copyright ©: All rights reserved by IBL-Lab GmbH

Within this test report, a ☒ point / ☐ comma is used as a decimal separator.
If otherwise, a detailed note is added adjoined to its use.

Decision rule: Binary Statement for Simple Acceptance Rule according ILAC-G8:09/2019

1 TABLE OF CONTENTS

.....	1
1 TABLE OF CONTENTS	3
2 GENERAL INFORMATION	4
2.1 ADMINISTRATIVE DETAILS.....	4
2.2 POSSIBLE VERDICTS OF THE RESULTS	4
2.3 OBSERVATIONS	4
2.4 OPINIONS AND INTERPRETATIONS	4
2.5 REVISION HISTORY.....	5
2.6 FURTHER DOCUMENTS	5
2.7 FORMULA FOR DETERMINATION OF CORRECTION VALUES (E_c)	5
2.8 SOFTWARE/FIRMWARE USED FOR MEASUREMENTS.....	5
2.9 BLOCK DIAGRAMS.....	6
3 ENVIRONMENTAL & TEST CONDITIONS	7
3.1 ENVIRONMENTAL CONDITIONS.....	7
4 TEST STANDARDS AND REFERENCES.....	7
5 EQUIPMENT UNDER TEST (EUT)	8
5.1 PRODUCT DESCRIPTION*	8
5.2 TECHNICAL DATA OF EQUIPMENT*	8
5.3 TEST ITEM (EQUIPMENT UNDER TEST) DESCRIPTION*	8
5.4 AUXILIARY EQUIPMENT (AE) DESCRIPTION*	8
5.5 TEST ITEM OPERATING MODES DESCRIPTION*	9
5.6 TEST ITEM SET-UPS DESCRIPTION	9
5.7 TEST CONDITIONS.....	9
5.8 ADDITIONAL INFORMATION	9
6 SUMMARY OF TEST RESULTS	10
7 TEST RESULTS.....	11
7.1 FUNDAMENTAL FIELD STRENGTH.....	11
7.2 RADIATED FIELD STRENGTH MEASUREMENTS.....	12
7.3 TRANSMIT TIME	14
7.4 OCCUPIED BANDWIDTH.....	15
8 MEASUREMENT EQUIPMENT	16
9 MEASUREMENT UNCERTAINTIES	19

2 GENERAL INFORMATION

2.1 Administrative details

Testing laboratory	IBL-Lab GmbH Heinrich-Hertz-Allee 7 66386 Sankt Ingbert / Germany Fon: +49 6894 38938-0 Fax: +49 6894 38938-99 URL: www.ib-lenhardt.de E-Mail: info@ib-lenhardt.de
Accreditation	The testing laboratory is accredited by Deutsche Akkreditierungsstelle GmbH (DAkKS) in compliance with DIN EN ISO/IEC 17025:2018. Scope of testing and registration number: - Electronics, EMC, Radio D-PL-21375-01-01 - Electromagnetic Compatibility and Telecommunication (FCC requirements) D-PL-21375-01-02 Testing Laboratory Designation Number DE0024 - Telecommunication (TC) and Electromagnetic Compatibility (EMC) for Canadian Standards D-PL-21375-01-03 ISED Company Number 27156 Testing Laboratory CAB Identifier DE0020 Website DAkKS: https://www.dakks.de/ The Deutsche Akkreditierungsstelle GmbH (DAkKS) is also a signatory to the ILAC Mutual Recognition Arrangement
Date of receipt of test samples	2023-10-16
Start – End of tests	2023-10-16 – 2023-10-19

2.2 Possible verdicts of the results

Test sample meets the requirements	P (PASS) – the measured value is below the acceptance limit, AL = TL
Test sample does not meet the requirements	F (FAIL) – the measured value is above the acceptance limit, AL = TL
Test case does not apply to the test sample	N/A (Not applicable)
Test case not performed	N/P (Not performed)

2.3 Observations

No additional observations other than the reported observations within this test report have been made.

2.4 Opinions and Interpretations

No appropriate opinions or interpretations according ISO/IEC 17025:2017 clause 7.8.7 are within this test report.

2.5 Revision History

-0 Initial Version

-1:

- **Chapter 7.1.:** Fundamental field strength test was remade with samples with CW mode. Chapter 7.1. and Annexes were corrected accordingly.

This test report 23099117-34649-1 replaces the previous test report 23099117-34649-0.

2.6 Further documents

List of further applicable documents belonging to the present test report:

Measurement plots: 23099117-34649-1_Annex A

EUT photographs: 23099117-34649-1_Annex B

Test setup photographs: 23099117-34649-1_Annex C

2.7 Formula for determination of correction values (E_C)

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

E_C = Electrical field – corrected value

E_R = Receiver reading

M = Margin

L_T = Limit

AF = Antenna factor

C_L = Cable loss

D_F = Distance correction factor (if used)

G_A = Gain of pre-amplifier (if used)

All units are dB-units, positive margin means value is below limit.

2.8 Software/Firmware used for measurements

All measurements were done directly with spectrum analyzer or SW R&S EMC32.

In some measurements (please see test equipment list for each test) R&S ESW 26 was used (please see chapter 8).

(Instrument) Firmware Version: **1.70**

In some measurements (please see test equipment list for each test) R&S FSW 50 was used (please see chapter 8).


(Instrument) Firmware Version: **4.61**

In some measurements SW R&S EMC32 was used.

Version: **11.10.00**

2.9 Block diagrams

Block diagram 1:



3 ENVIRONMENTAL & TEST CONDITIONS

3.1 Environmental conditions

Temperature	20°C ± 5°C
Relative humidity	25-75 % R.H.
Barometric Pressure	860-1060 mbar
Power supply	Battery and External power supply

4 TEST STANDARDS AND REFERENCES

Test standard (accredited)

FCC CFR Title 47 Part 15 Subpart C:2016	---
ANSI C63.10: 2013	---

Test standard (not accredited)

None

Reference	Description
none	---

5 EQUIPMENT UNDER TEST (EUT)

5.1 Product Description*

TPMS Sensor for Tire Pressure Monitoring System (TPMS) of passenger cars. The Sensor will be installed inside the tire by the use of a special TPMS valve. The device measure the pressure, temperature and acceleration and transmit the data to the TPMS ECU in the car. The RF transmissison take place in the ISM band 434 MHz.

*: declared by the applicant

5.2 Technical Data of Equipment*

TX Frequency band:	[433.050 – 434.790] MHz
Number of channel:	1
Modulation type:	ASK, FSK
Channel bandwidth:	115 kHz
Channel tested:	f_{cent} : 433.92 MHz
Duty cycle (%):	< 0.1 %
Spectrum Access Mechanism:	Duty Cycle
Adaptive Frequency Agility:	No
DSSS:	No
RF mode:	TX
Antenna Type:	Internal
Antenna gain:	-18 dBi
Antenna connector:	None
Equipment type:	Production model
Temperature range:	Tmin: -40 °C, Tmax: 125 °C
Type of power source:	3 V battery
Operational voltage(minimal, nominal and maximal):	Vmin: 2.8 VDC, Vnom: 3 VDC, Vmax: 3.4 VDC

*: declared by the applicant

5.3 Test Item (Equipment Under Test) Description*

Short designation	EUT Model	EUT Description	Serial number	Hardware status	Software status
EUT A	TMSS5B4	Radiated sample with housing	N/A, please see photos in Annex A	300.334.00	61.6.4
EUT B	TMSS5B4	Radiated sample with housing	N/A, please see photos in Annex A	300.334.00	61.6.4
EUT C	TMSS5B4	Radiated sample with housing	N/A, please see photos in Annex A	300.334.00	61.6.4
EUT D	TMSS5B4	Radiated sample with housing	N/A, please see photos in Annex A	300.334.00	61.6.4

*: declared by the applicant

5.4 Auxiliary Equipment (AE) Description*

AE short designation	AE Name (if available)	AE Description	Serial number (if available)	Software (if used)
AE1	SmarTool	TPMS Trigger Tool	-	-

*: declared by the applicant

5.5 Test Item Operating Modes Description*

EUT operating mode no.	Description of operating modes	Additional information
op. 1	EMC mode	ASK+FSK
op. 2	Long Protocol	This is the mode with the highest possible duty cycle.
op. 3	CW mode Lower	CW Lower (433.89 MHz)
op. 4	CW mode Upper	CW Upper (433.95 MHz)

*: declared by the applicant

5.6 Test Item Set-ups Description

set. 1	EUT A + AE1
set. 2	EUT B
set. 3	EUT C
set. 4	EUT D

5.7 Test conditions

Temperatur, [°C]		Voltage, [V]	
Tnom	20 ± 5	Vnom	3

5.8 Additional Information

Test items differences	-
Additional application considerations to test a component or sub-assembly	Declaration of the manufacturer: The TPM electronic module and battery can be mounted in one of six plastic housings to provide the mounting option for four different types of valves. The outer housing shape has no influence on the EMC behavior. For the measurements the option S5.5 was used. Please see photos of the housings in Annex B.

6 SUMMARY OF TEST RESULTS

Test specification

FCC 15.231

Requirement / Test Case	Test Conditions	Set-up	Operating mode	Result / Remark	Verdict
Fundamental field strength	Nominal	3, 4	3, 4	None	Pass
Radiated field strength measurements	Nominal	1	1	None	Pass
Transmit time	Nominal	2	2	None	Pass
Occupied Bandwidth	Nominal	1	1	None	Pass

Notes

None

Comments and observations

None

7 TEST RESULTS

7.1 Fundamental field strength

Test equipment (Please see Chapter 8 for exact information of test equipment)

Radiated: C1, R1, A2, SW2

Description

The measurement test set-up and test procedure are in accordance with the provisions described in ANSI 63.10: 2013.

The measurement antenna was situated in 3 m distance to the EUT.

RBW for frequency range 30 MHz- 1 GHz: 120 kHz.

See photos in Annex C for test Set-up and block diagram in Chapter 2.9.

Limits

According to FCC 15.231(e) Field strength of fundamental:

Frequency [MHz]	Frequency [MHz]		Frequency [MHz]	Frequency [MHz]
	[μV/m]	[dBμV/m]		
40.66-40.70	40.66-40.70	40.66-40.70	40.66-40.70	40.66-40.70
70-130	70-130	70-130	70-130	70-130
130-174	130-174	130-174	130-174	130-174
174-260	174-260	174-260	174-260	174-260
260-470	260-470	260-470	260-470	260-470
Above 470	Above 470	Above 470	Above 470	Above 470

Measurement Level = Reading Level + Correction Factor.

Limit(μV/m@433.9MHz):

$X_{11}=260$, $Y_{11}=1500$, $X_{12}=470$, $Y_{12}=5000$

$f(x)=mx+b$, $m=(5000-1500)/(470-260)=3500/210=16.66$, $b=f(x)-mx=5000-16.66*470=-2833.33$

$\Rightarrow f(x)=16.66*x-2833.33 \Rightarrow f(433.9)=16.66*433.9-2833.33=4398.33$

Limit dBμV/m RMS/Peak:

Average/RMS Limit = $20\text{LOG}(4398.33) = 72.86$ dBμV/m. Peak Limit = RMS Limit + 20 dB=92.86 dBμV/m.

Results Peak Detector*

Set./ Op.	Peak field strength, [dBμV/m]	Limit Peak, [dBμV/m]	Margin [dB]	DC CorFac**, [dB]	AV field strength, [dBμV/m]	Limit AV, [dBμV/m]	Margin [dB]	Verdict
Set.3, Op. 3	79.91	92.86	12.95	-15.48	64.43	72.86	8.43	Pass
Set.4, Op. 4	79.59	92.86	13.27	-15.48	64.11	72.86	8.75	Pass

* Please see measurement plots in Annex A.

** Please see Plot 3.2 in Annex A: $20*\text{LOG}(\text{DC}/100)=20*\text{LOG}(0.1682)=-15.48$ dB

7.2 Radiated field strength measurements

Test equipment

Frequency range 9 kHz – 30 MHz

Measurement in a semianechoic room with the distance between the EUT and the reference point of the antenna 3 m (see photos in Annex B). The measurement was done with software R&S EMC 32 V11.00.

Radiated: A1, C1, R1, SW2

Frequency range 30 MHz – 1 GHz

Measurement in a semianechoic room with the distance between the EUT and the reference point of the antenna 3 m (see photos in Annex B). The measurement was done with software R&S EMC 32 V11.00.

Radiated: A2, C1, R1, SW2

Frequency range 1 GHz – 5 GHz

Measurement in a fully anechoic room with the distance between the EUT and the reference point of the antenna 3 m (see photos in Annex B). The measurement was done directly with spectrum analyzer.

Radiated: A3, Amp2, C1, R1, F4

Description

The measurement test set-up and test procedure are in accordance with the provisions described in ANSI 63.10: 2013.

The measurement antenna was situated in 3 m distance to the EUT.

RBW for frequency range 9 kHz- 30 MHz: 200 Hz, 9 kHz.

RBW for frequency range 30 MHz- 1 GHz: 120 kHz.

RBW for frequency range 1 GHz- 5 GHz: 1 MHz.

See photos in Annex C for test Set-up and block diagram in Chapter 2.9.

Limits

According to FCC 15.209(a):

Frequency (MHz)	Magnetic field strength (HField) ($\mu\text{A/m}$)**	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490*	6.37/F (F in kHz)	2400/F(kHz)	300
0.490-1.705*	63.7/F (F in kHz)	24000/F(kHz)	30
1.705-30.0*	0.08	30	30

* Limit line was corrected due to measurement distance of 3 m

** the measurement was done with dBuV/m units. Please see the appropriate dBuV/m limits in the same table

Limits

According to FCC 15.231(e) Field strength of spurious emission:

Frequency [MHz]	Field strength@3m		Measurement distance [meters]	Remarks
	[$\mu\text{V/m}$]	[dBuV/m]		
40.66-40.70	100	40	3	Linear interpolation
70-130	50	33.98		
130-174	50 to 150	33.98 to 43.52		
174-260	150	43.52		
260-470	150 to 500	43.52 to 53.98		
Above 470	500	53.98		

Results*

Op./ Set.	Frequency	Detector	Test distance [m]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Verdict
Op.1, Set.1	9 kHz – 30 MHz	Peak	3	11.79	29.54	17.75	Pass

Op.1, Set.1	30 MHz – 1 GHz	Quasi-Peak	3	14.27	34.00	19.73	Pass
Op.1, Set.1	960 MHz – 5 GHz	Peak	3	62.16	74	11.84	Pass
Op.1, Set.1	960 MHz – 5 GHz	RMS	3	46.67**	54	7.33	Pass

All Readings below 1 GHz are Quasi-Peak or Peak detector, above 1 GHz with Peak and RMS detector.

* Please see measurement plots in Annex A.

** the measurement was done with peak detector. The “worst case” limit for average detector in used frequency range is 54 dBuV/m. There is only one value above this limit, measured with peak detector (M1: 62.12 dBuV/m at 4.333884 GHz, see plot 2.3.2. in Annex A). It is the 10th harmonic of the main signal. Please see chapter to OBW measurements. Correction factor is used to get an average value. Correction factor = $20 \cdot \text{LOG}(DC/100) = 20 \cdot \text{LOG}(0.1682) = -15.48 \text{ dB}$ (please see Chapter to Transmit time measurements).

=> M1_average value = $62.16 \text{ dBuV/m} - 15.48 \text{ dB} = 46.67 \text{ dBuV/m}$

7.3 Transmit time

Test equipment (Please see Chapter 8 for exact information of test equipment)

Radiated: R4, A4

Description

Please see test set-up photos in Annex C.
Measurement was done radiated.

Limits

FCC 15.231(e):

Devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

FCC 15.231(a)(4):

Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Results*

Plot No	Set./ Op.	Frequency, [MHz]	Measured value, [ms]	Limit**, [sec]	Result
3.3	2, 2	433.92	500.831	1	Pass
3.1	2, 2	433.92	15000	10	Pass

* Please see measurement plots in Annex A.

** The manufacturer is responsible for not exceeding this requirement.

7.4 Occupied Bandwidth

Test equipment (Please see Chapter 8 for exact information of test equipment)

Radiated: R4, A4

Description

The measurement test set-up and test procedure are in accordance with the provisions described in ANSI 63.10: 2013.

Please see test set-up photos in Annex C and block diagram in Chapter 2.9.

Please see Plots in Annex A for spectrum analyzer settings.

Measurement was done radiated.

Limits

The bandwidth of the emission shall be not wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be not wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Results*

Set./ Op.	Frequency, [MHz]	Measured value (99% BW), [kHz]	Limit, [MHz]	Result
Set.1, Op. 1	433.92	110.414	1.0848	Pass
Set./ Op.	Frequency, [MHz]	Measured value (20dB BW), [kHz]	Limit, [MHz]	Result
Set.1, Op. 1	433.92	119.4	1.0848	Pass

* Please see measurement plots in Annex A.

8 MEASUREMENT EQUIPMENT

No	Equipment	Type	Manufacturer	Serial No.	Int. No.	Last Calibration	Next Calibration
Antennas (A):							
1.	Active Loop Antenna	HFH2-Z2E	Rohde & Schwarz	100108	LAB000108	2023-05-05	2026-05-05
2.	Ultrabroadband antenna	HL562E	Rohde & Schwarz	102005	LAB000150	2022-12-22	2025-12-22
3.	Double-Ridged Waveguide Horn Antenna	HF-907	Rohde & Schwarz	102899	LAB000151	2023-05-05	2026-05-05
4.	Rod Antenna	-	-	-	LAB000290	-	-
5.	Horn Antenna (2.6 GHz – 3.95 GHz)	PE9863/SF-10	Pasternack	-	LAB000312	2021-01-13	-
6.	Horn Antenna (3.95 GHz – 5.85 GHz)	PE9861/SF-10	Pasternack	-	LAB000264	2020-09-29	-
7.	Horn Antenna (10 GHz – 15 GHz)	PE9855 SF-20	Pasternack	-	LAB000263	2020-09-29	-
8.	Horn Antenna (12.4 GHz – 18 GHz)	62-HA20-A-SMF	TTE Europe	-	LAB000282	2020-09-29	-
9.	Horn Antenna (17.6 GHz – 26.7 GHz)	20240-20	Flann Microwave Ltd	266402	LAB000127	2020-06-29	-
10.	Horn Antenna (26.4 GHz – 40.1 GHz)	22240-20	Flann Microwave Ltd	270447	LAB000129	2020-06-29	-
11.	Horn Antenna (33 GHz – 50.1 GHz)	23240-20	Flann Microwave Ltd	273430	LAB000132	2020-07-01	-
12.	Horn Antenna (49.9 GHz – 75.8 GHz)	25240-20	Flann Microwave Ltd	272860	LAB000133	2020-07-01	-
13.	Horn Antenna (60.5 GHz – 91.5 GHz)	26240-20	Flann Microwave Ltd	273417	LAB000135	2020-07-01	-
14.	Horn Antenna (73.8 GHz – 114 GHz)	27240-20	Flann Microwave Ltd	273368	LAB000138	2020-07-01	-
15.	Horn Antenna (114 GHz – 173 GHz)	29240-20	Flann Microwave Ltd	273382	LAB000139	2020-07-01	-
16.	Horn Antenna (145 GHz – 220 GHz)	30240-20	Flann Microwave Ltd	273390	LAB000178	2020-08-01	-
17.	Horn Antenna (217 GHz – 330 GHz)	32240-20	Flann Microwave Ltd	273469	LAB000152	2020-08-01	-
18.	Horn Antenna (49.9 GHz – 75.8 GHz)	25240-20	Flann Microwave Ltd	272861	LAB000134	2020-07-01	-
19.	Horn Antenna (60.5 GHz – 91.5 GHz)	26240-20	Flann Microwave Ltd	273418	LAB000136	2020-08-01	-
Amplifiers (Amp)*:							
1.	Pre-Amplifier	BBV 9718 C	Schwarzbeck Mess-Elektronik OHG	84	LAB000169	-	-
2.	Low noise amplifier	BZ-01000900-111550-202320	B&Z Technologies	24336	LAB000296	-	-
3.	Low noise amplifier	BZ-08001800-180855-202020	B&Z Technologies	22105	LAB000297	-	-
4.	Low noise amplifier	BZ-18004000-270845-252525	B&Z Technologies	22449	LAB000298	-	-
Attenuator (Att)*:							
1.	Attenuator	25081-20 (49.9 GHz - 75.8 GHz)	Flann Microwave Ltd	234411	LAB000229	-	-

2.	Attenuator	27081-20 (73.8 GHz – 112 GHz)	Flann Microwave Ltd	270004	LAB000230	-	-
RF Cables (Cab)*:							
1.	Coaxial cable	LU7-022-1000	Rosenberger	33	LAB000153	-	-
2.	Coaxial cable	LU7-022-1000	Rosenberger	34	LAB000153	-	-
3.	Coaxial cable	SF101/1.5m	Huber & Suhner	503987/1	LAB000165	-	-
Chambers (C):							
1.	Semi/Fully Anecoic Chamber	SAC5	Albatross Projects GmbH	20168.PRB	LAB000235	2022-01-31	2025-01-31
2.	Climatic chamber	T-65/50	CTS GmbH	204002	LAB000110	2023-05-11	2024-05-11
3.	Shielding Cover	CMU-Z11	Rohde & Schwarz	100876	LAB000039	-	-
4.	Climatic chamber	T-70/350	CTS GmbH	194027	LAB000066	2023-06-30	2024-06-30
5.	Shielded room	Sputnik 1 (Schirmkabine)	Albatross Projects GmbH	-	LAB000257	-	-
Corner Reflector (CR):							
1.	Trihedral Corner Reflector	SAJ-080-S1	ERAVANT	04756-01	LAB000201	-	-
Directional coupler (DC):							
1.	Directional coupler	CPL-5230-10-SMA-79	Midwest Microwave	-	LAB000672	-	-
Distance meter (DM):							
1.	Laser distance meter	GLM 50 C	Bosch	-	-	-	-
2.	Laser distance meter	GLM 120 C	Bosch	-	-	-	-
Filter (F)*:							
1.	High-pass filter (84 GHz – 110 GHz)	10-WHPF-84.5-UG387	TTE	-	LAB000299	-	-
2.	High-pass filter (7 GHz – 23 GHz)	HPF 7-23	AtlantRF	-	LAB000444	-	-
3.	High-pass filter (3.3 GHz – 12.75 GHz)	HPF 3.3-11	AtlantRF	-	LAB000382	-	-
4.	High-pass filter (1.3 GHz – 12.75 GHz)	H1G713G1	Microwave Circuits Inc	46291	LAB000443	-	-
5.	High-pass filter (1.3 GHz – 12.75 GHz)	H1G713G1	Microwave Circuits Inc	1896-01	LAB000670	-	-
6.	Bandstop filter (30MHz – 3GHz for 900 MHz Band)	WRCG876/960- 847/989-50/8SS	Wainwright Instruments GmbH	-	LAB000671	-	-
Harmonic mixers (H):							
1.	Harmonic Mixer	FS-Z60	Rohde & Schwarz	101350	LAB000375	2023-04-13	2024-04-13
2.	Harmonic Mixer	FS-Z75	Rohde & Schwarz	102015	LAB000112	2023-05-03	2024-05-03
3.	Harmonic Mixer	FS-Z90	Rohde & Schwarz	102020	LAB000113	2023-04-06	2024-04-06
4.	Harmonic Mixer	FS-Z110	Rohde & Schwarz	102000	LAB000114	2023-05-02	2024-05-02
5.	Harmonic Mixer	FS-Z170	Rohde & Schwarz	100996	LAB000126	2023-04-26	2024-04-26
6.	Harmonic Mixer	FS-Z220	Rohde & Schwarz	101039	LAB000116	2023-04-16	2024-04-06
7.	Harmonic Mixer	FS-Z325	Rohde & Schwarz	101015	LAB000117	2023-04-11	2024-04-11
LISN (L):							
1.	Two-line V-Network	ENV216	Rohde & Schwarz	102597	LAB000220	2022-09-27	2023-09-27
2.	Two-line V-Network	ENV216	Rohde & Schwarz	102598	LAB000217	2023-06-01	2024-06-01
Multimeters (M):							
1.	Multimeter	U1242B	Keysight	MY59240021	LAB000187	2022-06-20	2024-06-20
2.	Multimeter	U1242B	Keysight	MY59160026	LAB000018	2021-08-30	2023-08-30
Multipliers (Mp):							
1.	Multiplier	SMZ75	Rohde & Schwarz	101307	-	2018-03-15	-
2.	Multiplier	SMZ110	Rohde & Schwarz	100001	-	2020-05-09	-
Power Supply (P):							
1.	Power Supply	PS 2042-10 B	Elektro-Automatic GmbH	2878350263	LAB000190	-	-

2.	Power Supply	PS 2042-10 B	Elektro-Automatic GmbH	2878350322	LAB000192	-	-
3.	Power Supply	E3640A	Agilent	MY40005693	LAB000036	-	-
Power meters (PM):							
1.	Power meter	NRP-Z81	Rohde & Schwarz	106194	LAB000120	2023-05-10	2024-05-10
2.	Power meter	NRP110T	Rohde & Schwarz	101151	LAB000119	2023-06-05	2024-06-05
Receivers and Spectrumanalyzers (R):							
1.	Test Receiver, SAC5	ESW-26	Rohde & Schwarz	101517	LAB000363	2023-01-31	2024-01-30
2.	Test Receiver	ESW-26	Rohde & Schwarz	101481	LAB000236	-	-
3.	Spectrum Analyzer 1 Hz – 50 GHz	FSW-50	Rohde & Schwarz	101450	LAB000111	2023-07-26	2024-07-26
4.	Spectrum Analyzer 2 Hz – 43 GHz	FSW-43	Rohde & Schwarz	101391	LAB000289	2023-06-02	2024-06-02
Signal Generators (SG):							
1.	Signal generator 8 kHz – 50 GHz	SMA100B	Rohde & Schwarz	103838	LAB000118	2021-06-30	2024-06-30
2.	Vector Signal Generator	SMW200A	Rohde & Schwarz	108822	LAB000288	-	-
Software (SW):							
No	Type	Name	Manufacturer	Version	Int. No.	Build	Rev
1.	Software	R&S Power Viewer	Rohde & Schwarz	11.3, 3.2.2020	-	7338	3230
2.	Software	R&S EMC32	Rohde & Schwarz	11.20	-	-	-

* The gain values of Amp and attenuation values of Cab and Att are remeasured annually internal.

9 MEASUREMENT UNCERTAINTIES

Test case	Measurement uncertainty*
Radiated field strength	$\leq \pm 6$ dB
Occupied bandwidth	± 100 kHz
Time domain measurement	± 2.32 ms
DC and low frequency voltages	± 3 %
Temperature	± 1 °C
Humidity	± 3 %

*) The indicated expanded measurement uncertainty corresponds to the standard measurement uncertainty for the measurement results multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %.

END OF THE REPORT

Annex A

Measurement plots

part of / in addition to


Test report no.: 23099117-34649-1

Table of contents:

1	Fundamental field strength.....	3
1.1	Set-up 3, Op. 3, lying	3
1.2	Set-up 3, Op. 3, staying	4
1.3	Set-up 4, Op. 4, lying	5
1.4	Set-up 4, Op. 4, staying	6
2	General Limit - Radiated field strength emissions, 9 kHz - 5 GHz.....	7
2.1	Radiated field strength measurements ($f < 30$ MHz)	7
2.1.1	Set-up 1, 9 kHz – 30 MHz, Op. 1, EUTs lying	7
2.1.2	Set-up 1, 9 kHz – 30 MHz, Op. 1, EUTs staying	8
2.2	Radiated field strength measurements ($30 \text{ MHz} < f < 1000 \text{ MHz}$)	9
2.2.1	Lying, Set-up 1, Op. 1	9
2.2.2	Staying, Set-up 1, Op. 1	10
2.3	Radiated field strength measurements ($1 \text{ GHz} < f < 5 \text{ GHz}$)	11
2.3.1	960 MHz – 1400 MHz, Set-up 1, Op. 1, lying	11
2.3.2	1400 MHz – 5000 MHz, Set-up 1, Op. 1, lying, Peak detector*	12
3	Transmit time	13
3.1	Set-up 2, Op. mode 2, Measurement time 100 s.....	13
3.2	Set-up 2, Op. mode 2, Measurement time 100 ms.....	13
3.3	Set-up 2, Op. mode 2, Measurement time 1 s.....	14
4	Occupied Bandwidth	15
4.1	20 dB bandwidth, set-up 1, op. 1	15
4.2	99 % occupied bandwidth, set-up 1, op. 1	16

1 Fundamental field strength

1.1 Set-up 3, Op. 3, lying




— Preview Result 1-PK+ * Critical_Freqs PK+ ◆ Final_Result QPK

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
433.900000	79.91	---	---	100.0	120.000	126.0	V	209.0


1.2 Set-up 3, Op. 3, staying



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
433.900000	76.21	---	---	100.0	120.000	125.0	V	161.0


1.3 Set-up 4, Op. 4, lying



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
433.950000	79.59	---	---	100.0	120.000	136.0	V	217.0

1.4 Set-up 4, Op. 4, staying




Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
433.950000	75.91	---	---	100.0	120.000	126.0	V	155.0

2 General Limit - Radiated field strength emissions, 9 kHz - 5 GHz

2.1 Radiated field strength measurements ($f < 30$ MHz)


2.1.1 Set-up 1, 9 kHz – 30 MHz, Op. 1, EUTs lying



Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)	Corr. (dB/m)
13.083000	12.67	29.54	16.87	100.0	9.000	V	60.0	-1.2
13.328250	11.79	29.54	17.75	100.0	9.000	V	300.0	-1.0
13.560000	14.03	29.54	15.51	100.0	9.000	V	345.0	-0.9

2.1.2 Set-up 1, 9 kHz – 30 MHz, Op. 1, EUTs staying




Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)	Corr. (dB/m)
13.083000	15.54	29.54	14.00	100.0	9.000	V	345.0	-1.2
13.328250	15.16	29.54	14.38	100.0	9.000	V	239.0	-1.0
13.560000	16.66	29.54	12.88	100.0	9.000	V	201.0	-0.9

2.2 Radiated field strength measurements (30 MHz < f < 1000 MHz)


2.2.1 Lying, Set-up 1, Op. 1



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
79.910000	7.09	34.00	26.91	100.0	120.000	100.0	V	246.0
84.375000	7.37	34.00	26.63	100.0	120.000	250.0	V	240.0
87.985000	12.57	34.00	21.43	100.0	120.000	103.0	V	246.0
175.365000	7.22	43.52	36.30	100.0	120.000	400.0	H	66.0
433.960000	74.26	52.20	-22.06	100.0	120.000	104.0	V	201.0
867.800000	22.29	54.00	31.71	100.0	120.000	103.0	V	-24.0

2.2.2 Staying, Set-up 1, Op. 1




Final_Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
88.005000	14.27	34.00	19.73	100.0	120.000	104.0	V	150.0
433.960000	71.40	52.20	-19.20	100.0	120.000	103.0	V	156.0
867.930000	21.95	54.00	32.05	100.0	120.000	104.0	V	-24.0

2.3 Radiated field strength measurements (1 GHz < f < 5 GHz)

2.3.1 960 MHz – 1400 MHz, Set-up 1, Op. 1, lying



2.3.2 1400 MHz – 5000 MHz, Set-up 1, Op. 1, lying, Peak detector*




05:54:15 PM 10/17/2023

* the “worst case” limit for average detector is 54 dBuV/m. There is only one value above this limit, measured with peak detector (M1: 62.12 dBuV/m at 4.333884 GHz). It is the 10th harmonic of the main signal. Please see chapter to OBW measurements. Correction factor is used to get an average value. Correction factor = $20 \cdot \log(\text{DC}/100) = 20 \cdot \log(0.1682) = -15.48 \text{ dB}$ (please see Chapter to Transmit time measurements).
 => M1_average value = 62.16 dBuV/m - 15.48 dB = 46.67 dBuV/m


Annex A of TR no.: 23099117-34649-1

3 Transmit time

3.1 Set-up 2, Op. mode 2, Measurement time 100 s




3.2 Set-up 2, Op. mode 2, Measurement time 100 ms



DC=16.682 %

Annex A of TR no.: 23099117-34649-1

3.3 Set-up 2, Op. mode 2, Measurement time 1 s




03:08:13 10/10/2023

Annex A of TR no.: 23099117-34649-1

4 Occupied Bandwidth

4.1 20 dB bandwidth, set-up 1, op. 1



03:33:52 10/18/2023

4.2 99 % occupied bandwidth, set-up 1, op. 1



03:34:52 10/18/2023