



APPENDIX J

: ANTENNA SPECIFICATION

ANTENNA SPECIFICATIONS

Product Name	BLE Antenna
Model Name	C502 Antenna

CONTENTS

1. Features3

2. Antenna Characteristics3

 2.1 Antenna Performance3

 2.2 Network analyzer data4

 2.3 Efficiency5

3. Antenna Test Condition6

1. Features

- BLE Antenna
- Frequency range : 2.4GHz ~ 2.5GHz
- PCB Pattern Antenna

2. Antenna Characteristics

2.1 Antenna Performance

Parameter	Min.	Typ	Max.	Unit
Frequency Range	2400	2450	2500	MHz
Directivity		Omni		-
Polarization		Linear		-
VSWR	3:1			Under
Impedance		50		Ohm
Peak gain	0.25		1.02	dB


2.2 Network analyzer data

ANTENNA Measurement

Gongdan 1-dong, Gumi-si, Gyeongbuk, Korea TEL : 054)468-7130 , FAX : 054)461-8368


Report No	-	Testing person	KIM KYEONG SIK
Product name	C502	PCB P/No , REV.	PMCCA1677A_REV01
Measurement date	2025-02-17	Case on/off	ON
Measurement sites	Shield Room	Connect the product	-

Used equipment - RF Network Analyzer(Agilent E5071B)



- 300KHz ~ 8.5GHz
- More than 125dB dynamic range

S-PARAMETER



ANTENNA TUNING DATA

Date	담당자	RF Matching Location No.								Return loss			Result	
		R4	R5	R6	R7	C19	C20	C21	기타	2402MHz	2440MHz	2480MHz	Limit	
2/17	배대영	NC	0R	NC	NC	0.5pF	1.8pF	0.5pF		-5.00dB	-10.00dB	-5.00dB	PASS	


A4(210x297mm)

2.3 Efficiency


	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Frequency [MHz]	2400	2405	2410	2415	2420	2425	2430	2435	2440	2445	2450	2455	2460	2465	2470	2475	2480	2485	2490	2500
Efficiency [dB]	-4.36	-4.38	-4.41	-4.43	-4.42	-4.48	-4.50	-4.46	-4.45	-4.59	-4.44	-4.62	-4.54	-4.52	-4.55	-4.68	-4.79	-4.88	-4.92	-4.93
Efficiency [%]	36.45	36.49	36.27	36.09	36.17	35.70	35.51	35.89	35.93	34.77	35.97	34.51	35.15	35.30	35.04	34.02	33.14	33.48	33.79	33.77
TRC _θ [dB]	-6.77	-6.83	-6.90	-6.83	-6.80	-6.78	-6.95	-6.94	-6.84	-7.08	-6.83	-7.09	-6.88	-6.89	-6.89	-7.22	-7.36	-7.50	-7.59	-7.66
TRC _φ [dB]	-8.12	-8.03	-8.00	-8.15	-8.16	-8.32	-8.15	-8.05	-8.17	-8.18	-8.18	-8.25	-8.34	-8.28	-8.37	-8.23	-8.30	-8.33	-8.42	-8.65
UHRG [dB]	-6.40	-6.40	-6.43	-6.45	-6.43	-6.49	-6.51	-6.48	-6.45	-6.61	-6.46	-6.65	-6.54	-6.53	-6.55	-6.71	-6.82	-6.92	-7.01	-7.15
UHRG/TRG [%]	62.80	62.75	62.71	62.78	62.89	62.91	62.91	62.70	62.97	62.76	62.84	62.69	63.14	62.98	63.17	62.65	62.76	62.51	62.66	62.61
H-Plane	-5.72	-5.78	-5.85	-5.78	-5.75	-5.74	-5.87	-5.88	-5.82	-6.02	-5.79	-6.03	-5.84	-5.87	-5.85	-6.13	-6.25	-6.37	-6.43	-6.43
E1-Plane, AVG [dB]	-5.14	-5.19	-5.23	-5.17	-5.15	-5.12	-5.32	-5.29	-5.20	-5.42	-5.19	-5.44	-5.26	-5.24	-5.27	-5.53	-5.67	-5.81	-5.90	-5.93
E2-Plane, AVG [dB]	-10.65	-10.71	-10.86	-10.75	-10.68	-10.68	-10.90	-10.85	-10.71	-11.03	-10.64	-11.05	-10.68	-10.64	-10.65	-11.13	-11.27	-11.37	-11.53	-11.62
Peak Gain [dB]	1.04	1.03	1.01	1.00	1.00	0.99	0.99	0.98	0.94	0.91	0.90	0.86	0.83	0.81	0.76	0.74	0.64	0.44	0.42	0.36
Directivity [dB]	6.41	6.40	6.40	6.42	6.40	6.45	6.47	6.42	6.37	6.49	6.33	6.47	6.36	6.32	6.30	6.41	6.43	6.32	6.39	6.37
Minimum Gain [dB]	-16.13	-15.94	-16.01	-16.01	-16.43	-16.81	-16.19	-16.18	-17.44	-16.37	-17.18	-16.40	-17.35	-17.54	-16.99	-16.33	-16.24	-15.95	-15.55	-14.84
Test Condition	FS																			
Antenna Type																				
FS=Free Space, BHR=Beside Head Right Side, BHL=Beside Head Left Side, HR=Hand Right, HL=Hand Left, BHHR=Beside Head and Hand Right Side, BHHL=Beside Head and Hand Left Side, NB=Notebook																				
Average Efficiency	-4.57 dB, 35.17 %																			

3. Antenna Test Condition

- CTIA OTA Test Chamber : 6.0 x 3.0 x 3.0 m



- Passive Test System



- Active Test System

