

FCC PART 15 Subpart C
EMI MEASUREMENT AND TEST REPORT

For

CRS Electronic Co., Ltd.

12F, No. 100 Sec. 1, Hsin Tai Wu Road,
Hsichi, Taipei Hsien, Taiwan

FCC ID: OZB-SI519

April 30, 2002

This Report Concerns: ☒ Original Report	Equipment Type: RF 2.4GHz Video Camera
Test Engineer: Wayne Chia	
Report No.: R0204034	
Test Date: April 8, 2002	
	
Reviewed By: John Y. Chan - Engineering Manager	
Prepared By: Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel (408) 732-9162 Fax (408) 732-9164	

Note: This test report is specially limited to the above client company and product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 OBJECTIVE	3
1.3 RELATED SUBMITTAL(S)/GRANT(S)	3
1.4 TEST METHODOLOGY	3
1.5 TEST FACILITY	3
1.6 TEST EQUIPMENT LIST	4
2 - SYSTEM TEST CONFIGURATION.....	5
2.1 DESCRIPTION OF TEST CONFIGURATION	5
2.2 EUT EXERCISE SOFTWARE	5
2.3 SPECIAL ACCESSORIES	5
2.4 EQUIPMENT MODIFICATIONS	5
2.5 CONFIGURATION OF TEST SYSTEM.....	6
2.6 TEST SETUP BLOCK DIAGRAM	6
3 - CONDUCTED EMISSIONS TEST DATA.....	7
3.1 MEASUREMENT UNCERTAINTY	7
3.2 EUT SETUP	7
3.3 SPECTRUM ANALYZER SETUP	7
3.4 TEST PROCEDURE	8
3.5 SUMMARY OF TEST RESULTS	8
3.6 CONDUCTED EMISSIONS TEST DATA	8
3.7 PLOT OF CONDUCTED EMISSIONS TEST DATA	8
4 - RADIATED EMISSION DATA	10
4.1 MEASUREMENT UNCERTAINTY	10
4.2 EUT SETUP	10
4.3 SPECTRUM ANALYZER SETUP	10
4.4 TEST PROCEDURE	11
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	11
4.6 SUMMARY OF TEST RESULTS	11
4.7 RADIATED EMISSIONS TEST RESULT DATA.....	12
5 - BAND EDGES TESTING	14
5.1 TEST PROCEDURE	14
5.2 TEST EQUIPMENT	14
5.3 TEST RESULTS	14

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

The *CRS Electronic Co., Ltd.*'s product, model no.: *SI519* or the "EUT" as referred to in this report is a RF 2.4GHz video camera which measures approximately 5.25" L x 5.0" W x 5.5"H.

The transmitter utilized CRS AC/DC Power adapter (9Vdc, SCP41-90500).

1.2 Objective

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4-1992.

The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the specification limits defined by FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.249.

1.3 Related Submittal(s)/Grant(s)

No Related Submittals

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 –1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, IEC/CISPR 22: 1998, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8566B	2610A02165	12/6/2002
HP	Spectrum Analyzer	8593B	2919A00242	12/20/2002
HP	Amplifier	8349B	2644A02662	12/20/2002
HP	Quasi-Peak Adapter	85650A	917059	12/6/2002
HP	Amplifier	8447E	1937A01046	12/6/2002
A.H. System	Horn Antenna	SAS0200/571	261	12/27/2002
Com-Power	Log Periodic Antenna	AL-100	16005	11/2/2002
Com-Power	Biconical Antenna	AB-100	14012	11/2/2002
Solar Electronics	LISN	8012-50-R-24-BNC	968447	12/28/2002
Com-Power	LISN	LI-200	12208	12/20/2002
Com-Power	LISN	LI-200	12005	12/20/2002
BACL	Data Entry Software	DES1	0001	12/20/2002

* Statement of Traceability: Bay Area Compliance Laboratory Corp. certifies that all calibration has been performed using suitable standards traceable to National Institute of Standard and Technology (NIST).

2 - SYSTEM TEST CONFIGURATION

2.1 Description of Test Configuration

The EUT was configured for testing in a typical fashion (as normally used by a typical user).

2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

The sequence used is as follows:

1. The video camera sends the signal.

The complete cycle takes approximately 5 - 10 seconds and the process is continuously repeated.

2.3 Special Accessories


As shown in section 2.5, interface cable used for compliance testing is shielded as normally supplied by customer and its respective support equipment manufacturers.

2.4 Equipment Modifications

No modification(s) to the EUT were made to comply with the applicable limits.

2.5 Configuration of Test System


Video Camera



Video Camera

2.6 Test Setup Block Diagram

Video Camera



3 - CONDUCTED EMISSIONS TEST DATA

3.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

3.2 EUT Setup

The measurement was performed at the **Open Area Test Site**, using the same setup per ANSI C63.4 - 1992 measurement procedure. Specification used was with the FCC Class B limits.

The video camera EUT was connected to a 110 Vac / 60 Hz power source and it was placed at the center back edge of the test table.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped over edge of the test table and bundle when necessary.

3.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configurations during the conducted emission test:

Start Frequency.....	450 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	100 kHz
Video Bandwidth.....	100 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode.....	Normal

3.4 Test Procedure

During the conducted emission test, the EUT power cord was connected to the auxiliary outlet of the first LISN with all support equipment power cords connected to the second.

The EUT was tested with the *CRS* (SCP41-90500) power adapter to represent worst-case results for the final qualification test. Therefore, these results were used for final test data recorded in the table listed under section 3.6 of this report.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination. All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB of specification limit). Quasi-peak readings are distinguished with a "Qp".

3.5 Summary of Test Results

According to the data in section 3.6, the EUT complied with the FCC Class B Conducted margin and these test results is deemed satisfactory evidence of compliance with RSS-210 of the Canadian Interference-Causing Equipment Regulations, with the *worst* margin reading of:

-19.6 dB μ V at 0.78 MHz in the **Line** mode for Video Camera with the **CRS** power adapter,

M/N: SCP41-90500, **0.45 ~ 30 MHz**


3.6 Conducted Emissions Test Data

3.6.1 Video Camera with CRS Adapter, M/N: SCP41-90500, 0.45 - 30 MHz

LINE CONDUCTED EMISSIONS				FCC 15 SUBPART B	
Frequency MHz	Amplitude dB μ V	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dB μ V	Margin dB
0.78	28.4	QP	Line	48	-19.6
0.45	23.7	QP	Neutral	48	-24.3
1.19	21.2	QP	Line	48	-26.8
1.13	20.9	QP	Neutral	48	-27.1
1.34	19.0	QP	Neutral	48	-29.0
1.37	17.0	QP	Line	48	-31.0

3.7 Plot of Conducted Emissions Test Data

Plots of Conducted Emissions test data for transmitter and receive are presented hereinafter in sequence as reference.



4 - RADIATED EMISSION DATA

4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

4.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup in accordance with the ANSI C63.4 - 1992. The specification used was the FCC 15 Subpart C limits.

The Video Camera EUT was connected to a 110 Vav / 60 Hz power source and it was placed at the center back edge of the test table.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped over edge of the test table and bundle when necessary.

4.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR 15.33 (a) (1), the system was tested to 25000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency	30 MHz
Stop Frequency	25000 MHz
Sweep Speed	Auto
IF Bandwidth	1 MHz
Video Bandwidth	1 MHz
Quasi-Peak Adapter Bandwidth.....	120 kHz
Quasi-Peak Adapter Mode	Normal
Resolution Bandwidth	1MHz

4.4 Test Procedure

For the radiated emissions test, both the EUT and all support equipment power cords were connected to the AC floor outlet since the power supply (SCP41-90500) used in the EUT did not provide an accessory power outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "Qp" in the data table.

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

4.6 Summary of Test Results

According to the data in section 4.7, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.249 after tested to 10th harmonics as required by FCC and had the worst margin of:

Video Camera:

-2.1 dB μ V at 4826.00 MHz in the Vertical polarization, Low Channel, 30MHz to 25000 MHz, 3 meters

-1.2 dB μ V at 4862.00 MHz in the Vertical polarization, Sub-Low Channel, 30MHz to 25000 MHz, 3 meters

-1.4 dB μ V at 4902.00 MHz in the Vertical polarization, Middle Channel, 30MHz to 25000 MHz, 3 meters

-1.5 dB μ V at 4836.00 MHz in the Vertical polarization, Low Channel, 30MHz to 25000 MHz, 3 meters

-11.4 dB μ V at 414.25 MHz in the Horizontal polarization, Unintentional Emission, 30 to 1000 MHz, 3 meters

4.7 Radiated Emissions Test Result Data

Video Camera, Intentional Emission, 30 MHz to 25000 MHz, 3 meters

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 Subpart C	
Frequency MHz	Ampl. dBμV/m	Angle Degree	Height Meter	Polar H/ V	Antenna dBμV/m	Cable dB	Amp. dB	Corr. Ampl. dBμV/m	Limit dBμV/m	Margin dB
Low Channel										
2413.00	91.7	150	1.2	V	28.1	3.4	30.0	93.2	94	-0.8
2413.00	91.1	30	2.0	H	28.1	3.4	30.0	92.6	94	-1.5
4826.00	44.5	270	1.0	V	32.5	4.9	30.0	51.9	54	-2.1
7239.00	40.4	0	2.0	V	35.1	5.6	30.0	51.1	54	-2.9
4826.00	43.6	330	2.2	H	32.5	4.9	30.0	51.0	54	-3.0
7239.00	39.8	60	2.0	H	35.1	5.6	30.0	50.5	54	-3.5
Sub-Low Channel										
2431.00	90.8	230	1.0	H	28.1	3.4	30.0	92.3	94	-1.8
2431.00	90.4	320	1.0	V	28.1	3.4	30.0	91.9	94	-2.2
4862.00	45.4	180	1.2	V	32.5	4.9	30.0	52.8	54	-1.2
4862.00	45.1	330	2.0	H	32.5	4.9	30.0	52.5	54	-1.5
7293.00	40.2	270	2.0	H	35.1	5.6	30.0	50.9	54	-3.1
7293.00	39.8	90	2.0	V	35.1	5.6	30.0	50.5	54	-3.5
Middle Channel										
2451.00	91.4	230	1.0	H	28.1	3.4	30.0	92.9	94	-1.2
2451.00	91.10	160	2.00	V	28.1	3.4	30.0	92.6	94	-1.5
4902.00	45.2	210	1.0	V	32.5	4.9	30.0	52.6	54	-1.4
7352.00	41.7	30	1.0	V	35.1	5.6	30.0	52.4	54	-1.6
4902.00	44.80	330	1.20	H	32.5	4.9	30.0	52.2	54	-1.8
7352.00	40.9	0	1.2	H	35.1	5.6	30.0	51.6	54	-2.4
High Channel										
2468.00	91.8	0	1.5	V	28.1	3.4	30.0	93.3	94	-0.8
2468.00	91.2	90	2.0	H	28.1	3.4	30.0	92.7	94	-1.3
4936.00	45.1	180	1.0	V	32.5	4.9	30.0	52.5	54	-1.5
4936.00	44.7	90	1.0	H	32.5	4.9	30.0	52.1	54	-1.9
7404.00	41.2	180	1.0	H	35.1	5.6	30.0	51.9	54	-2.1
7404.00	39.8	230	1.2	V	35.1	5.6	30.0	50.5	54	-3.5

Video Camera, Unintentional Emission, 30 MHz to 1000 MHz, 3 meters

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 Subpart C	
Frequency MHz	Ampl. dBμV/m	Angle Degree	Height Meter	Polar H/ V	Antenna dBμV/m	Cable dB	Amp. dB	Corr. Ampl. dBμV/m	Limit dBμV/m	Margin dB
414.25	39.6	30	1.5	H	16.8	3.2	25.0	34.6	46	-11.4
752.50	33.6	90	2.0	H	22.5	2.4	25.0	33.5	46	-12.5
490.80	37.6	330	2.0	H	18.2	2.3	25.0	33.1	46	-12.9
202.80	36.8	180	2.0	H	12.4	4.6	25.0	28.8	43.5	-14.7
414.25	35.4	45	1.2	V	16.8	3.2	25.0	30.4	46	-15.6
535.60	29.7	90	1.5	V	19.4	1.8	25.0	25.9	46	-20.1

5 - BAND EDGES TESTING

Requirements: Per FCC 15.249 (c), the emission power at the START and STOP frequencies shall be at least 50 dB below the level of the fundamental or to the general radiated emission limits in FCC 15.209, whichever is the lesser attenuation.

5.1 Test Procedure

The antenna was removed and a low loss RF cable was connected to the transmitter output. The other end of cable was connected to a spectrum analyzer with the START and STOP frequencies set to the operation band. Transmitter output was read off the spectrum analyzer in dBm. The power output at the transmitter was determined by adding the value of the attenuator to the spectrum analyzer reading.

The test was performed for handset and the base respectively.

5.2 Test Equipment

HP 8566B Spectrum Analyzer
HP 7470A Plotter

5.3 Test Results

Passed. Refer to the attached plots.

