

1

2

Rev No.

Comments

A

Initial Release

4.000

1.400

Tantalus Systems
Corporation

MODEL: TUNet 3205

REV:

MD:

TYPE 3R 600 VOLT (250 AMPS MAX) 200 AMPS CONTINUOUS

RATED 200 CONTINUOUS AMPS WHEN USED IN A METER SOCKET RATED 200 CONTINUOUS
AMPS. SHORT CIRCUIT CURRENT WITHSTAND RATING 10,000 RMS SYMMETRICAL AMP, 600 V
MAX. WATTHOUR METER NOT INCLUDED IN SHORT CIRCUIT WITHSTAND RATING.


This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device
may not cause harmful interference, and (2) this device must accept any interference received, including interference that
may cause undesired operation.

FCC ID: OZFR22002

NID:

Material: Brady Corporation B-486 (Ultra Aggressive Matte Metalized Polyester) Thermal Transfer Label

NOTE: ALL DIMENSIONS IN INCHES.



Tantalus

Tantalus Systems Corp.

4224 Manor Street
Burnaby
British Columbia
Canada, V5G 1B2

tel: (604) 299-0458

fax: (604) 451-4111

www.tantalus-systems.com

Title:

TUNet 3205 FRONT LABEL

Filename: 280-0004-FAB-A

Doc No.: 280-0004-FAB

Rev:

A

Sheet

1

of

1

Copyright 1989-2002 (c) Tantalus Systems Corporation. All rights reserved. No part of this publication, or any software included with it may be reproduced, stored in a retrieval system, or transmitted in any form or by any means including photocopying, electronic, mechanical, recording or otherwise without the prior written permission of the copyright holder. This document contains proprietary information of Tantalus Systems Corporation. The contents are confidential and any disclosure to persons other than the officers, employees, agents or subcontractors of the owner or licensee of this document, without the prior written consent of Tantalus Systems Corp. is strictly prohibited.

1

2