FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Mad Catz, Inc.

Mad Catz F.R.E.Q.9 Wireless Headset

Model Number: 43401R

FCC ID: P25D2434011101AR

Prepared for : Mad Catz, Inc.
7480 Mission Valley Road, Suite 101, San Diego,
California, 92108, USA

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F14168
Date of Test : Feb.18~Mar.19, 2014
Date of Report : Sep.24, 2014

TABLE OF CONTENTS

Description Page

1. SUMMARY OF STANDARDS AND RESULTS 1-1
1.1. Description of Standards and Results 1-1
2. GENERAL INFORMATION 2-1
2.1. Description of Device (EUT) 2-1
2.2. Tested Supporting System Details 2-2
2.3. Block Diagram of Test Setup 2-2
2.4. Test information 2-2
2.5. Test Facility 2-3
2.6. Measurement Uncertainty (95% confidence levels, k=2) 2-3
3. POWER LINE CONDUCTED EMISSION MEASUREMENT 3-1
3.1. Test Equipment 3-1
3.2. Block Diagram of Test Setup 3-1
3.3. Power Line Conducted Emission Test Limits 3-1
3.4. Configuration of EUT on Test 3-1
3.5. Operating Condition of EUT 3-2
3.6. Test Procedure 3-2
3.7. Conducted Emission at Mains Terminals Test Results 3-2
4. RADIATED EMISSION MEASUREMENT 4-1
4.1. Test Equipment 4-1
4.2. Block Diagram of Test Setup 4-2
4.3. Radiated Emission Limit Standard: FCC 15.247 4-3
4.4. EUT Configuration on Test 4-3
4.5. Operating Condition of EUT 4-3
4.6. Test Procedure 4-3
4.7. Radiated Emission Test Results 4-4
5. CONDUCTED SPURIOUS EMISSIONS 5-1
5.1. Test Equipment 5-1
5.2. Limit 5-1
5.3. Test Procedure 5-1
5.4. Test result 5-1
6. CARRIER FREQUENCY SEPARATION TEST 6-1
6.1. Test Equipment 6-1
6.2. Limit 6-1
6.3. Test Results. 6-1
7. 20 DB BANDWIDTH TEST 7-1
7.1. Test Equipment 7-1
7.2. Limit 7-1
7.3. Test Results 7-1
8. NUMBER OF HOPPING FREQUENCY TEST 8-1
8.1. Test Equipment 8-1
8.2. Limit 8-1
8.3. Test Results 8-1
9. DWELL TIME 9-1
9.1. Test Equipment 9-1

9.2. Limit 9-1
9.3. Test Results 9-1
10. MAXIMUM PEAK OUTPUT POWER TEST 10-1
10.1. Test Equipment 10-1
10.2. Limit 10-1
10.3. Test Procedure 10-1
10.4. Test Results 10-2
11. BAND EDGE COMPLIANCE TEST 11-1
11.1. Test Equipment 11-1
11.2. Limit 11-1
11.3. Test Produce 11-1
11.4. Test Results 11-1
12. DEVIATION TO TEST SPECIFICATIONS 12-1
13. PHOTOGRAPH OF TEST 13-1
13.1. Photos of Power Line Conducted Emission Test 13-1
13.2. Photos of Radiated Emission Test 13-2
14. PHOTOS OF THE EUT 14-1

TEST REPORT CERTIFICATION

Applicant : Mad Catz, Inc.

Manufacturer : Mad Catz, Inc.

EUT Description : Mad Catz F.R.E.Q.9 Wireless Headset

FCC ID : P25D2434011101AR

(A) MODEL NO. : 43401R
(B) SERIAL NO. : N/A
(C)TEST VOLTAGE : DC 5V From PC Input AC 120V/60Hz

Tested for comply with:
FCC Rules and Regulations Part 15 Subpart C: 2013
Test procedure used:
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Feb.18~Mar.19, 2014 Report of date: Sep.24, 2014

Prepared by : Lisa Liang
Lisa Liang / Assistant

Reviewed by :
Sunny Lu / Assistant Manager

AUDIX® 信華科技（深圳）有限公司
Audix Technology (Shenzhen) Co., Ltd.
EMC 部門報告專用章
Stamp only for EMC Dept. Report
Signature: David Jin 9.24

Approved & Authorized Signer :
David Jin / Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1.Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	**Standard**	**Results**
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 :2009 ANSI C63.4 :2003	PASS
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2009 ANSI C63.4 :2003	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 :2009	PASS
Number Of Hopping Frequency Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1)\ ANSI C63.10 :2009	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION

2.1.Description of Device (EUT)

Product Name	: Mad Catz F.R.E.Q.9 Wireless Headset
Model Number	: 43401R
FCC ID	: P25D2434011101AR
Radio	: Buletooth3.0+EDR
Operation frequency	: 2402MHz-2480MHz
Antenna	: Integrated PCB Antenna, 0.251711dBi PK gain
Modulation	: GFSK, π/4 DQPSK, 8-DPSK
Applicant	: Mad Catz, Inc. 7480 Mission Valley Road, Suite 101, San Diego, California, 92108, USA
Manufacturer	: Mad Catz, Inc. 7480 Mission Valley Road, Suite 101, San Diego, California, 92108, USA
USB Cable	: Unshielded, Detachable, 1.0m
Optical Cable	: Unshielded, Detachable, 1.0m
Audio Cable	: Unshielded, Detachable, 1.0m
Xbox 360 Digital Optical Adapter Cable	: Unshielded, Detachable, 23cm
3.5mm to Dual Phone Lead Cable	: Unshielded, Detachable, 1.0m
Micro USB Charge Cable	: Unshielded, Detachable, 1.0m
Xbox 360 3.5mm to 2.5mm Chat Lead	Unshielded, Detachable, 1.0m
Date of Test	: Feb.18~Mar.19, 2014
Date of Receipt	: Feb.17, 2014
Sample Type	: Prototype production

2.2.Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1.	Notebook	N/A	DELL	PP09S	N/A	☑FCC DoC ☑BSMI ID: R41108
		Power Cord: Unshielded, Detachabled, 1.8m Power Adapter: Manufacturer: DELL, M/N: LA65NS1-00 Cable: Unshielded, Detachabled, 4.0m(Bond one ferrite core)				
2.	DVD Player	ACS-EMC-DVD01	DENON	DVD-3910	4098400342E	☐FCC ID ☐BSMI ID
		Data Cable: Shielded, Detachabled, 1.8m Power Cord: Unshielded, Detachabled , 1.8m				

2.3.Block Diagram of Test Setup



(EUT: Mad Catz F.R.E.Q.9 Wireless Headset)

2.4.Test information

The test software "bluesuite.exe" was used to control EUT work in Continuous TX mode, and select test channel.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	Low :CH 0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
Tx Mode 8-DPSK modulation	3	Low :CH 0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480
Note: π/4DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.			

2.5.Test Facility

Site Description

Name of Firm	:	Audix Technology (Shenzhen) Co., Ltd. No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park,Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 90454 Valid Date: Feb.22, 2015
3m & 10m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 794232 Valid Date: Oct.31, 2015
EMC Lab.	:	Certificated by Industry Canada Registration Number: IC 5183A-1 Valid Date: May.14, 2017 Certificated by DAkkS, Germany Registration No: D-PL-12151-01-00 Valid Date: Dec.15, 2016 Accredited by NVLAP, USA NVLAP Code: 200372-0 Valid Date: Mar.31, 2015

2.6.Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.10 dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.22 dB(30~200MHz, Polarize: H)
	3.23 dB(30~200MHz, Polarize: V)
	3.49 dB(200M~1GHz, Polarize: H)
	3.39 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	4.97dB (1~6GHz, Distance: 3m)
	4.99dB (6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6℃
	3%

3. POWER LINE CONDUCTED EMISSION MEASUREMENT

3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.18,13	1 Year
2.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 13	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	100429	Jan.22, 14	1 Year
4.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 13	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 13	1 Year
6.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 13	1 Year
7.	RF Cable	Hubersuhner	RG58	0100.6954.20#	Jan.22, 14	1 Year
8.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 13	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101838	Jan.22, 14	1 Year
10.	Oscilloscope	Tektronix	TDS3052B	B026036	May.16, 13	1 Year

3.2. Block Diagram of Test Setup



:50Ω Terminator

3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Mad Catz F.R.E.Q.9 Wireless Headset (EUT)

Model Number : 43401R
Serial Number : N/A

3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turn on the power of all equipment.

3.5.3. Let the EUT work in test mode (TX Mode) and measure it.

3.6. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

3.7. Conducted Emission at Mains Terminals Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)



Site no :1#conduction Data No :4
Dis./Ant. :** 2013 ESH2-Z5 LINE
Limit :FCC PART 15 C
Env./Ins. :25.5*C/53% Engineer :Eric
EUT :Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating :DC 5V From PC
Test Mode :Tx Mode
M/N:43401R

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.28630	0.15	0.01	40.18	40.34	60.63	20.29	QP
2	0.49673	0.16	0.02	35.17	35.35	56.05	20.70	QP
3	0.89441	0.18	0.03	32.33	32.54	56.00	23.46	QP
4	2.794	0.25	0.05	31.12	31.42	56.00	24.58	QP
5	4.622	0.31	0.07	32.10	32.48	56.00	23.52	QP
6	5.805	0.36	0.07	35.01	35.44	60.00	24.56	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.
2.If the average limit is met when useing a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Site no :1#conduction Data No :3
Dis./Ant. :** 2013 ESH2-Z5 NEUTRAL
Limit :FCC PART 15 C
Env./Ins. :25.5*C/53% Engineer :Eric
EUT :Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating :DC 5V From PC
Test Mode :Tx Mode
M/N:43401R

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.29554	0.20	0.01	38.81	39.02	60.37	21.35	QP
2	0.49150	0.23	0.02	32.15	32.40	56.14	23.74	QP
3	0.91357	0.26	0.03	32.47	32.76	56.00	23.24	QP
4	1.487	0.26	0.03	30.68	30.97	56.00	25.03	QP
5	2.839	0.28	0.05	32.50	32.83	56.00	23.17	QP
6	3.964	0.31	0.06	35.03	35.40	56.00	20.60	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.
2.If the average limit is met when useing a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION MEASUREMENT

4.1.Test Equipment

Frequency rang: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 13	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 13	1 Year
5	Bilog Antenna	TESEQ	CBL6112D	35375	May.30, 13	1 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 13	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 13	1 Year

Frequency rang: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 13	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 13	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 13	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 13	1 Year
6	Horn Antenna	EMCO	3116	00060089	Aug.28, 13	1 Year

4.2.Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.3. Radiated Emission Limit Standard: FCC 15.247

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark： (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

(4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Mad Catz F.R.E.Q.9 Wireless Headset (EUT)

Model Number : 43401R
Serial Number : N/A

4.5. Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 4.2.
4.5.2. Turned on the power of all equipment.
4.5.3. Let EUT work in Tx mode.

4.6. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.7. Radiated Emission Test Results

PASS.

All the emissions from 30MHz to 25GHz were comply with the 15.247 Limit.
Note: The duty cycle factor for calculate average level is 9.11dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.

Duty cycle: 0.4383ms /1.247ms *100% =35%
Duty cycle factor = 20log（1/duty cycle）= 9.11







Note：The Dwell time less than 100ms.

Frequency: 30MHz~1GHz



Site no. : 3m Chamber Data no. : 3
Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 C (3M)
Env. / Ins. : 24*C/34% Engineer : Donjon
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power rating : DC 5V From PC
Test Mode : Tx Mode
M/N:43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.10	0.83	3.68	24.61	40.00	15.39	QP
2	172.590	10.07	1.69	15.26	27.02	43.50	16.48	QP
3	184.230	9.60	1.73	15.72	27.05	43.50	16.45	QP
4	382.110	15.94	2.41	6.49	24.84	46.00	21.16	QP
5	776.900	20.60	3.54	2.48	26.62	46.00	19.38	QP
6	897.180	21.54	3.92	5.79	31.25	46.00	14.75	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 4
Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL
Limit : FCC PART 15 C (3M)
Env. / Ins. : 24*C/34% Engineer : Donjon
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power rating : DC 5V From PC
Test Mode : Tx Mode
M/N:43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	34.850	17.09	0.92	8.84	26.85	40.00	13.15	QP
2	57.160	7.07	1.22	17.12	25.41	40.00	14.59	QP
3	144.460	11.65	1.58	14.26	27.49	43.50	16.01	QP
4	626.550	19.53	3.11	2.83	25.47	46.00	20.53	QP
5	776.900	20.60	3.54	4.52	28.66	46.00	17.34	QP
6	935.980	21.82	4.04	2.97	28.83	46.00	17.17	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz




```
Site no.      : 3m Chamber                        Data no.   : 1
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : GFSK 2402MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 2
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	93.57	91.85	74.00	-17.85	Peak
2	4804.000	32.85	8.56	35.70	46.18	51.89	74.00	22.11	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 3
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : GFSK 2402MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 4
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	90.66	88.94	74.00	-14.94	Peak
2	4804.000	32.85	8.56	35.70	45.33	51.04	74.00	22.96	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.  : 7
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : GFSK 2441MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 8
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2441MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	92.65	91.08	74.00	-17.08	Peak
2	4882.000	32.99	8.64	35.70	45.70	51.63	74.00	22.37	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 9
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : GFSK 2441MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 10
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2441MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	92.65	91.08	74.00	-17.08	Peak
2	4882.000	32.99	8.64	35.70	44.10	50.03	74.00	23.97	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.  : 11
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : GFSK 2480MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 12
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	84.63	83.20	74.00	-9.20	Peak
2	4960.000	33.13	8.72	35.70	43.85	50.00	74.00	24.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 13
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : GFSK 2480MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 14
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	88.93	87.50	74.00	-13.50	Peak
2	4960.000	33.13	8.72	35.70	46.63	52.78	74.00	21.22	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 17
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2402MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 18
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	85.63	83.91	74.00	-9.91	Peak
2	4804.000	32.85	8.56	35.70	44.64	50.35	74.00	23.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 19
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2402MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 20
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	92.54	90.82	74.00	-16.82	Peak
2	4804.000	32.85	8.56	35.70	47.86	53.57	74.00	20.43	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 23
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2441MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 24
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2441MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	86.52	84.95	74.00	-10.95	Peak
2	4882.000	32.99	8.64	35.70	45.17	51.10	74.00	22.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 25
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2441MHz  Tx
M/N           : 43401R
```




```
Site no.      : 3m Chamber                        Data no.  : 26
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2441MHz  Tx
M/N           : 43401R
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	91.86	90.29	74.00	-16.29	Peak
2	4882.000	32.99	8.64	35.70	48.45	54.38	74.00	19.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4882	54.38	9.11	45.27	54	Pass




```
Site no.      : 3m Chamber                        Data no.   : 27
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2480MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 28
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	84.96	83.53	74.00	-9.53	Peak
2	4960.000	33.13	8.72	35.70	46.81	52.96	74.00	21.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 29
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Leo-Li
EUT           : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating  : DC 5V From PC
Test Mode     : 8-DPSK 2480MHz  Tx
M/N           : 43401R
```



Site no. : 3m Chamber Data no. : 30
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	82.36	80.93	74.00	-6.93	Peak
2	4960.000	33.13	8.72	35.70	44.20	50.35	74.00	23.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

5. CONDUCTED SPURIOUS EMISSIONS

5.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.31, 13	1Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,13	1 Year

5.2.Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3.Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

5.4.Test result

PASS (The testing data was attached in the next pages.)

GFSK

2402MHz






Agilent Spectrum Analyzer - Swept SA
Marker 1 24.025000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 36/100
06:22:36 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 24.025 GHz
-57.655 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 48.80 ms (1001 pts)
1 N 1 f 24.025 GHz -57.655 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
Start Freq 2.310000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:23:03 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.401 960 GHz
-1.671 dBm
Start 2.31000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.40500 GHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.401 960 GHz -1.671 dBm
2 N 1 f 2.390 000 GHz -70.179 dBm
3 N 1 f 2.400 000 GHz -59.955 dBm
Frequency
Auto Tune
Center Freq
2.357500000 GHz
Start Freq
2.310000000 GHz
Stop Freq
2.405000000 GHz
CF Step
9.500000 MHz
Auto
Man
Freq Offset
0 Hz

2441MHz


Agilent Spectrum Analyzer - Swept SA
Start Freq 1.000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 99/100
06:23:44 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.440 GHz
-2.528 dBm
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 10.000 GHz
Sweep 29.27 ms (1001 pts)
1 N 1 f 2.440 GHz -2.528 dBm
Frequency
Auto Tune
Center Freq
5.500000000 GHz
Start Freq
1.000000000 GHz
Stop Freq
10.000000000 GHz
CF Step
900.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Marker 1 813.760000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:23:56 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 813.76 MHz
-66.949 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 3.200 ms (1001 pts)
1 N 1 f 813.76 MHz -66.949 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
Marker 1 24.025000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 19/100
06:24:03 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 24.025 GHz
-57.692 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 48.80 ms (1001 pts)
1 N 1 f 24.025 GHz -57.692 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

2480MHz


Agilent Spectrum Analyzer - Swept SA
Start Freq 1.000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:24:36 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 2.476 GHz
-1.023 dBm
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 10.000 GHz
Sweep 29.27 ms (1001 pts)
1 N 1 f 2.476 GHz -1.023 dBm
2 N 1 f 3.304 GHz -55.396 dBm
Frequency
Auto Tune
Center Freq
5.500000000 GHz
Start Freq
1.000000000 GHz
Stop Freq
10.000000000 GHz
CF Step
900.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Marker 1 827.340000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:24:49 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 827.34 MHz
-66.308 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 3.200 ms (1001 pts)
1 N 1 f 827.34 MHz -66.308 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
Marker 1 24.670000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 12/100
06:24:54 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 24.670 GHz
-57.504 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 48.80 ms (1001 pts)
1 N 1 f 24.670 GHz -57.504 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2



8-DPSK

2402MHz




Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:31:17 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 909.79 MHz
-50.825 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 3.200 ms (1001 pts)
1 N 1 f 909.79 MHz -50.825 dBm
Frequency
Auto Tune
Center Freq
515.000000 MHz
Start Freq
30.000000 MHz
Stop Freq
1.000000000 GHz
CF Step
97.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Marker 1 24.535000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 17/100
06:31:28 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 24.535 GHz
-57.762 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 48.80 ms (1001 pts)
1 N 1 f 24.535 GHz -57.762 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
Start Freq 2.310000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:32:03 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.402 150 GHz
-4.198 dBm
Start 2.31000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.40500 GHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.402 150 GHz -4.198 dBm
2 N 1 f 2.390 000 GHz -71.180 dBm
3 N 1 f 2.400 000 GHz -62.895 dBm
Frequency
Auto Tune
Center Freq
2.357500000 GHz
Start Freq
2.310000000 GHz
Stop Freq
2.405000000 GHz
CF Step
9.500000 MHz
Auto
Man
Freq Offset
0 Hz

2441MHz


Agilent Spectrum Analyzer - Swept SA
Start Freq 1.000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:30:02 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.440 GHz
-5.259 dBm
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 10.000 GHz
Sweep 29.27 ms (1001 pts)
1 N 1 f 2.440 GHz -5.259 dBm
2 N 1 f 3.259 GHz -53.658 dBm
Frequency
Auto Tune
Center Freq
5.500000000 GHz
Start Freq
1.000000000 GHz
Stop Freq
10.000000000 GHz
CF Step
900.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Marker 1 813.760000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:30:12 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 813.76 MHz
-67.424 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 3.200 ms (1001 pts)
1 N 1 f 813.76 MHz -67.424 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
Marker 1 24.025000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 23/100
06:30:19 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 24.025 GHz
-57.063 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 48.80 ms (1001 pts)
1 N 1 f 24.025 GHz -57.063 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

2480MHz


Agilent Spectrum Analyzer - Swept SA
Start Freq 2.477000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:27:29 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.480 036 GHz
-3.824 dBm
Start 2.47700 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.51000 GHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.480 036 GHz -3.824 dBm
2 N 1 f 2.483 500 GHz -54.825 dBm
3 N 1 f 2.500 000 GHz -63.908 dBm
4 N 1 f 2.499 011 GHz -46.026 dBm
5 N 1 f 2.501 057 GHz -47.943 dBm
Frequency
Auto Tune
Center Freq
2.493500000 GHz
Start Freq
2.477000000 GHz
Stop Freq
2.510000000 GHz
CF Step
3.300000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Start Freq 1.000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:28:30 PM Sep 16, 2014
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.476 GHz
-3.803 dBm
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 10.000 GHz
Sweep 29.27 ms (1001 pts)
1 N 1 f 2.476 GHz -3.803 dBm
2 N 1 f 3.304 GHz -55.689 dBm
Frequency
Auto Tune
Center Freq
5.500000000 GHz
Start Freq
1.000000000 GHz
Stop Freq
10.000000000 GHz
CF Step
900.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
06:28:45 PM Sep 16, 2014
Marker 1 939.860000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 939.86 MHz
-67.490 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 3.200 ms (1001 pts)
1 N 1 f 939.86 MHz -67.490 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
06:28:59 PM Sep 16, 2014
Marker 1 23.920000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 14/100
Ref Offset 1.5 dB
10 dB/div
Ref 11.00 dBm
Mkr1 23.920 GHz
-57.150 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 48.80 ms (1001 pts)
1 N 1 f 23.920 GHz -67.150 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

6. CARRIER FREQUENCY SEPARATION TEST

6.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum	Agilent	N9030A	MY51380221	Oct.31, 13	1Year

6.2.Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.3.Test Results.

EUT: Mad Catz F.R.E.9 Wireless Headset		
M/N: 43401R		
Test date: 2014-03-19	Pressure: 101.2±1.0 kpa	Humidity: 53.8±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature：24 .4±0.6℃

Test Mode	Channel separation	Conclusion
8-DPSK	1.0MHz	PASS
GFSK	1.0MHz	PASS

Agilent Spectrum Analyzer - Swept SA
Marker 3 2.441145000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr3 2.441 145 GHz
1.175 dBm
Center 2.441000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 5.000 MHz
Sweep 2.53 ms (1001 pts)
1 Δ2 1 f (Δ) -1.000 MHz (Δ) -0.014 dB
2 F 1 f 2.443 145 GHz 1.206 dBm
3 N 1 f 2.441 145 GHz 1.175 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

7. 20 DB BANDWIDTH TEST

7.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Attenuator(20dB)	Agilent	8491B	MY39262165	May.08, 13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	May.08, 13	1 Year

7.2.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.3.Test Results

EUT: Mad Catz F.R.E.9 Wireless Headset		
M/N: 43401R		
Test date: 2014-03-19	Pressure: 101.2±1.0 kpa	Humidity: 53.8±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature：24 .4±0.6℃

Cable loss: 1.0 dB		Attenuator loss: 20 dB	
Test Mode	CH （MHz）	20dB bandwidth （KHz）	Limit (KHz)
GFSK	2402	827.643	N/A
	2441	830.176	N/A
	2480	834.335	N/A
8-DPSK	2402	1204	N/A
	2441	1205	N/A
	2480	1208	N/A
Conclusion：PASS			

GFSK

Test Frequency: 2402MHz



Test Frequency: 2441MHz



Test Frequency: 2480MHz



8-DPSK

Test Frequency: 2402MHz



Test Frequency: 2441MHz



Test Frequency: 2480MHz



8. NUMBER OF HOPPING FREQUENCY TEST

8.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum	Agilent	N9030A	MY51380221	Oct.31, 13	1Year

8.2.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

8.3.Test Results

EUT: Mad Catz F.R.E.9 Wireless Headset		
M/N: 43401R		
Test date: 2014-03-19	Pressure: 101.2±1.0 kpa	Humidity: 53.8±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature：24 .4±0.6℃

Test Mode	Number of channel	Limit	Conclusion
8-DPSK	79	>=15	PASS
GFSK	79	>=15	PASS


Agilent Spectrum Analyzer - Swept SA
Marker 2 2.402000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr2 2.402 000 GHz
-0.075 dBm
Start 2.39000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.44100 GHz
Sweep 4.93 ms (1001 pts)
1 N 1 f 2.441 000 GHz 0.786 dBm
2 N 1 f 2.402 000 GHz -0.075 dBm
Marker
Select Marker 2
Normal
Delta
Fixed
Off
Properties
More 1 of 2


Agilent Spectrum Analyzer - Swept SA
Marker 2 2.441000000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr2 2.441 000 0 GHz
-4.490 dBm
Start 2.44100 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.48350 GHz
Sweep 4.07 ms (1001 pts)
1 N 1 f 2.480 085 0 GHz 0.998 dBm
2 N 1 f 2.441 000 0 GHz -4.490 dBm
Marker
Select Marker 2
Normal
Delta
Fixed
Off
Properties
More 1 of 2

9. DWELL TIME

9.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08, 13	1 Year

9.2.Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.3.Test Results

EUT: Mad Catz F.R.E.9 Wireless Headset		
M/N: 43401R		
Test date: 2014-03-19	Pressure: 101.2±1.0 kpa	Humidity: 53.8±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature：24 .4±0.6℃

Mode		dwell time	Limit	Conclusion
GFSK	DH1	51hops/5s*0.4*79chanels*0.4417ms =142.36ms	<400ms	PASS
	DH3	25hops/5s*0.4*79chanels*1.7ms =268.6ms	<400ms	PASS
	DH5	17hops/5s*0.4*79chanels*3.025ms=325.006ms	<400ms	PASS
8-DPSK	DH1	50hops/5s*0.4*79chanels*0.455ms=143.78ms	<400ms	PASS
	DH3	26hops/5s*0.4*79chanels*1.735ms =285.09ms	<400ms	PASS
	DH5	17hops/5s*0.4*79chanels*3.033ms =325.86ms	<400ms	PASS

Note: All the lower levels were signal from receiver's, and should not considered in here.

Test Mode: GFSK
DH1





DH3


Agilent
R T
Trace
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Trace
1 2 3
Clear Write
Max Hold
Min Hold
View
Blank
More
1 of 2
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 5 s (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
R T
Marker
Mkr1 1.7 ms
-0.72 dB
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref
Span Pair
Span Center
Off
More
1 of 2
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 3 ms (601 pts)
Copyright 2000-2005 Agilent Technologies

DH5


Agilent
R T
Marker
Mkr1 3.025 ms
1.82 dB
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 5 ms (601 pts)
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref
Span Pair
Span Center
Off
More
1 of 2
Copyright 2000-2005 Agilent Technologies


Agilent
R T
Freq/Channel
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 5 s (601 pts)
Center Freq
2.44100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.44100000 GHz
CF Step
100.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies

Test Mode: 8DPSK
DH1





DH3


Agilent
R T
Marker
Mkr1 1.735 ms
Ref 11 dBm
#Atten 20 dB
-0.77 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref
Span Pair
Span Center
Off
More
1 of 2
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 3 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
R T
Freq/Channel
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Center Freq
2.44100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.44100000 GHz
CF Step
100.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 5 s (601 pts)
Copyright 2000-2005 Agilent Technologies

DH5


Agilent
R T
Freq/Channel
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Center Freq
2.44100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.44100000 GHz
CF Step
100.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 5 s (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
R T
Freq/Channel
Mkr1 3.033 ms
1.07 dB
Ref 11 dBm
#Atten 20 dB
#Peak
Log
10
dB/
Offst
1
dB
LgAv
W1 S2
S3 LS
£(f):
f>50k
Center Freq
2.44100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.44100000 GHz
CF Step
100.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 2.441 000 GHz
Span 0 Hz
Res BW 100 kHz
#VBW 100 kHz
Sweep 5 ms (601 pts)
Copyright 2000-2005 Agilent Technologies

10. MAXIMUM PEAK OUTPUT POWER TEST

10.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
3.	Power meter	Anritsu	ML2487A	6K00002472	May.08, 13	1Year
4.	Power sensor	Anritsu	MA2491A	0033005	May.08, 13	1Year
5.	Attenuator(20dB)	Agilent	8491B	MY39262165	May.08, 13	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	May.08, 13	1 Year

10.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.3. Test Procedure

1. Connected the EUT's antenna port to power meter Via suitable attenuator.
2. Read the peak output power from power meter directly

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

10.4.Test Results

EUT: Mad Catz F.R.E.Q.9 Wireless Headset		
M/N: 43401R		
Test date: 2014-03-19	Pressure: 101.2±1.0 kpa	Humidity: 54.3±3.0%
Tested by: Eric	Test site: RF site	Temperature:25.1±0.6 ℃

Cable loss: 1.0 dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	Peak output Power （dBm）	Limit (dBm)
GFSK	2402	5.15	30
	2441	5.01	30
	2480	5.35	30
8-DPSK	2402	4.42	30
	2441	4.68	30
	2480	4.17	30
Conclusion: PASS			

11. BAND EDGE COMPLIANCE TEST

11.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Amp	HP	8449B	3008A02495	May.08, 13	1 Year
3.	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	274094/4	May.08, 13	1 Year
5	RF Cable	Hubersuhner	Sucoflex102	28618/2	May.08,13	1 Year

11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

11.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz）from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205

For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
   (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
   (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

11.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Site no. : 3m Chamber Data no. : 5
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2367.285	28.11	5.75	35.70	49.64	47.80	74.00	26.20	Peak
2	2390.000	28.16	5.78	35.70	47.70	45.94	74.00	28.06	Peak
3	2400.000	28.18	5.80	35.70	56.00	54.28	74.00	19.72	Peak
4	2402.150	28.18	5.80	35.70	90.19	88.47	74.00	-14.47	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 6
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2314.275	27.99	5.67	35.70	50.53	48.49	74.00	25.51	Peak
2	2390.000	28.16	5.78	35.70	47.76	46.00	74.00	28.00	Peak
3	2400.000	28.18	5.80	35.70	60.55	58.83	74.00	15.17	Peak
4	2402.150	28.18	5.80	35.70	93.98	92.26	74.00	-18.26	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.970	28.36	5.91	35.70	88.43	87.00	74.00	-13.00	Peak
2	2483.500	28.36	5.92	35.70	47.71	46.29	74.00	27.71	Peak
3	2495.414	28.39	5.94	35.70	50.21	48.84	74.00	25.16	Peak
4	2500.000	28.40	5.94	35.70	47.81	46.45	74.00	27.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : GFSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.36	5.91	35.70	83.42	81.99	74.00	-7.99	Peak
2	2483.500	28.36	5.92	35.70	47.52	46.10	74.00	27.90	Peak
3	2489.606	28.38	5.93	35.70	49.53	48.14	74.00	25.86	Peak
4	2500.000	28.40	5.94	35.70	49.01	47.65	74.00	26.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 21
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2338.500	28.04	5.71	35.70	49.80	47.85	74.00	26.15	Peak
2	2390.000	28.16	5.78	35.70	48.25	46.49	74.00	27.51	Peak
3	2400.000	28.18	5.80	35.70	59.43	57.71	74.00	16.29	Peak
4	2401.960	28.18	5.80	35.70	92.07	90.35	74.00	-16.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 22
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2402MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2346.765	28.06	5.72	35.70	49.74	47.82	74.00	26.18	Peak
2	2390.000	28.16	5.78	35.70	48.49	46.73	74.00	27.27	Peak
3	2400.000	28.18	5.80	35.70	51.33	49.61	74.00	24.39	Peak
4	2402.150	28.18	5.80	35.70	85.01	83.29	74.00	-9.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 31
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.904	28.36	5.91	35.70	82.15	80.72	74.00	-6.72	Peak
2	2483.500	28.36	5.92	35.70	48.53	47.11	74.00	26.89	Peak
3	2487.989	28.37	5.93	35.70	49.41	48.01	74.00	25.99	Peak
4	2500.000	28.40	5.94	35.70	48.15	46.79	74.00	27.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24°C/56% Engineer : Leo-Li
EUT : Mad Catz F.R.E.Q.9 Wireless Headset
Power Rating : DC 5V From PC
Test Mode : 8-DPSK 2480MHz Tx
M/N : 43401R

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.135	28.36	5.91	35.70	84.49	83.06	74.00	-9.06	Peak
2	2483.500	28.36	5.92	35.70	47.25	45.83	74.00	28.17	Peak
3	2491.256	28.38	5.93	35.70	50.13	48.74	74.00	25.26	Peak
4	2500.000	28.40	5.94	35.70	47.26	45.90	74.00	28.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

12. DEVIATION TO TEST SPECIFICATIONS

[NONE]