

FCC ID: P27MDC450
Report No.: T190626D05-RP2

Page 1 / 55
Rev. 02

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

Test Standard	FCC Part 15.247
Product name	Full HD PoE Mini-Dome Camera
Brand Name	Rhombus Systems Inc.; Sercomm
Model	MDC450
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.


The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:

Tested by:



Kevin Tsai
Deputy Manager



Dally Hong
Engineer

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T190626D05-RP2

Page 2 / 55

Rev. 02

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 30, 2019	Initial Issue	ALL	Allison Chen
01	September 11, 2019	See the following note Rev.(01)	P.6, P.28, P.34-35, P.37	Allison Chen
02	September 12, 2019	See the following note Rev.(02)	P.37	Allison Chen

Rev.(01)

1. Modify antenna type in section 1.4.
2. Modify description of remark in section 5.5.4.
3. Modify frequency in section 5.7.4.
4. Modify duty cycle value in section 5.8.2.

Rev.(02)

1. Modify duty cycle value in section 5.8.2.



Table of contents

1. GENERAL INFORMATION	4
1.1 EUT INFORMATION	4
1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS.....	5
1.3 EUT CHANNEL INFORMATION	6
1.4 ANTENNA INFORMATION	6
1.5 MEASUREMENT UNCERTAINTY	7
1.6 FACILITIES AND TEST LOCATION	7
1.7 INSTRUMENT CALIBRATION.....	8
1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT.....	9
1.9 TEST METHODOLOGY AND APPLIED STANDARDS	9
2. TEST SUMMERY	10
3. DESCRIPTION OF TEST MODES	11
3.1 THE WORST MODE OF OPERATING CONDITION.....	11
3.2 THE WORST MODE OF MEASUREMENT	12
4. EUT DUTY CYCLE	13
5. TEST RESULT	14
5.1 AC POWER LINE CONDUCTED EMISSION	14
5.2 20dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)	17
5.3 OUTPUT POWER MEASUREMENT.....	22
5.4 FREQUENCY SEPARATION.....	24
5.5 NUMBER OF HOPPING	27
5.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION	29
5.7 TIME OF OCCUPANCY (DWELL TIME).....	34
5.8 RADIATION BANDEDGE AND SPURIOUS EMISSION	36
APPENDIX-A TEST PHOTO	A-1



Report No.: T190626D05-RP2

Page 4 / 55

Rev. 02

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Sercomm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan
Manufacturer	Sercomm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan
Equipment	Full HD PoE Mini-Dome Camera
Model No.	MDC450
Model Discrepancy	N/A
Trade Name	Rhombus Systems Inc.; Sercomm
Received Date	June 26, 2019
Date of Test	August 5 ~ 15, 2019
Output Power (W)	GFSK : 0.0067 8DPSK : 0.0037
Power Supply	Power from Adapter.

1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS

1.2.1 Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

1.2.2 Equal Hopping Frequency Use

The channels of this system will be used equally over the long-term distribution of the hopsets.

1.2.3 Example of a 79 hopping sequence in data mode:

02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 16, 68, 74, 59, 63, 55

1.2.4 System Receiver Input Bandwidth

Each channel bandwidth is 1MHz.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

1.2.5 Equipment Description

15.247(a)(1) that the Rx input bandwidths shift frequencies in synchronization with the transmitted signals.

15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

1.3 EUT CHANNEL INFORMATION

Frequency Range	2402MHz-2480MHz
Modulation Type	1. GFSK for BDR-1Mbps 2. $\pi/4$ -DQPSK for EDR-2Mbps 3. 8DPSK for EDR-3Mbps
Number of channel	79 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.4 ANTENNA INFORMATION

Antenna Type	☐ PIFA ☐ PCB ☐ Dipole ☐ Coils ☒ Embedded Antenna
Antenna Gain	Gain: 1.4dBi
Antenna Connector	I-Pex

1.5 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.6 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Dally Hong	-
Radiation	Jerry Lu	-
RF Conducted	Dally Hong	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.7 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	07/31/2019	07/30/2020
Power Meter	Anritsu	ML2495A	1149001	02/12/2019	02/11/2020
Power Seneor	Anritsu	MA2491A	030982	02/12/2019	02/11/2020
Software	N/A				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/26/2019	02/25/2020
Bilog Antenna	Sunol Sciences	JB3	A030105	07/26/2019	07/25/2020
Cable	HUBER SUHNER	SUCOFLEX 104PEA	25157	02/26/2019	02/25/2020
Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/26/2019	02/25/2020
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/30/2019	01/29/2020
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	08/20/2018	08/19/2019
Loop Ant	COM-POWER	AL-130	121051	03/22/2019	03/21/2020
Pre-Amplifier	EMEC	EM330	060609	02/26/2019	02/25/2020
Pre-Amplifier	HP	8449B	3008A00965	02/26/2019	02/25/2020
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	05/29/2019	05/28/2020
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

AC Conducted Emissions Test Site					
Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/27/2019	06/26/2020
EMI Test Receiver	R&S	ESCI	100064	07/26/2019	07/25/2020
LISN	SCHWARZBECK	NSLK 8127	8127-541	01/31/2019	01/30/2020
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2019	02/12/2020
Software	EZ-EMC(CCS-3A1-CE-wugu)				

Note:

- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- N.C.R. = No Calibration Required.



Report No.: T190626D05-RP2

Page 9 / 55

Rev. 02

1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

1.9 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247.



Report No.: T190626D05-RP2

Page 10 / 55

Rev. 02

2. TEST SUMMERY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	5.1	AC Conducted Emission	Pass
15.247(a)(1)	5.2	20 dB Bandwidth	-
-	5.2	Occupied Bandwidth (99%)	-
15.247(b)(1)	5.3	Output Power Measurement	Pass
15.247(a)(1)	5.4	Frequency Separation	Pass
15.247(a)(1)(iii)	5.5	Number of Hopping	Pass
15.247(d)	5.6	Conducted Band Edge	Pass
15.247(d)	5.6	Conducted Spurious Emission	Pass
15.247(a)(1)(iii)	5.7	Time of Occupancy	Pass
15.247(d)	5.8	Radiation Band Edge	Pass
15.247(d)	5.8	Radiation Spurious Emission	Pass



Report No.: T190626D05-RP2

Page 11 / 55
Rev. 02

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	GFSK for BDR-1Mbps (DH5) 8DPSK for EDR-3Mbps (3DH5)
Test Channel Frequencies	GFSK for BDR-1Mbps: 1.Lowest Channel: 2402MHz 2.Middle Channel: 2441MHz 3.Highest Channel: 2480MHz 8DPSK for EDR-3Mbps: 1.Lowest Channel: 2402MHz 2.Middle Channel: 2441MHz 3.Highest Channel: 2480MHz

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)


Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y and Z for radiated measurement. The worst case(X-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

4. EUT DUTY CYCLE

Duty Cycle			
Configuration	TX ON (ms)	TX ALL (ms)	Duty Cycle (%)
BR-1Mbps	0.4493	3.7391	12.02%
EDR-3Mbps	0.3043	3.7536	8.11%



5. TEST RESULT

5.1 AC POWER LINE CONDUCTED EMISSION

5.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

5.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

5.1.3 Test Setup




5.1.4 Test Result

PASS

Test Data

Test Mode	Mode 1	Temp/Hum	24(°C)/ 50%RH
Phase	Line	Test Date	August 15, 2019
		Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1620	27.37	17.28	10.14	37.51	27.42	65.36	55.36	-27.85	-27.94	Pass
0.2100	24.18	18.91	10.13	34.31	29.04	63.21	53.21	-28.90	-24.17	Pass
0.3220	23.49	16.04	10.14	33.63	26.18	59.66	49.66	-26.03	-23.48	Pass
0.4500	31.20	24.51	10.14	41.34	34.65	56.88	46.88	-15.54	-12.23	Pass
0.6420	20.59	14.68	10.15	30.74	24.83	56.00	46.00	-25.26	-21.17	Pass
0.9740	25.46	19.84	10.17	35.63	30.01	56.00	46.00	-20.37	-15.99	Pass

Test Mode	Mode 1	Temp/Hum	24(°C)/ 50%RH
Phase	Neutral	Test Date	August 15, 2019
		Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1620	30.64	17.71	10.02	40.66	27.73	65.36	55.36	-24.70	-27.63	Pass
0.2100	24.40	18.03	10.02	34.42	28.05	63.21	53.21	-28.79	-25.16	Pass
0.3180	20.05	13.42	10.03	30.08	23.45	59.76	49.76	-29.68	-26.31	Pass
0.4420	30.65	23.49	10.03	40.68	33.52	57.02	47.02	-16.34	-13.50	Pass
0.6700	15.46	8.09	10.03	25.49	18.12	56.00	46.00	-30.51	-27.88	Pass
1.2380	15.28	8.33	10.04	25.32	18.37	56.00	46.00	-30.68	-27.63	Pass

5.2 20dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

5.2.1 Test Limit

According to §15.247(a) (1),

20 dB Bandwidth : For reporting purposes only.


Occupied Bandwidth(99%) : For reporting purposes only.

5.2.2 Test Procedure

Test method Refer as Section 8.1 and ANSI C63.10: 2013 clause 7.8.7,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW =30kHz, VBW = 100kHz and Detector = Peak, to measurement 20dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth.
5. Measure and record the result of 20 dB Bandwidth and 99% Bandwidth. in the test report.

5.2.3 Test Setup



5.2.4 Test Result

Test mode: GFSK_BDR-1Mbps mode / 2402-2480 MHz			
Channel	Frequency (MHz)	OBW(99%) (MHz)	20dB BW (MHz)
Low	2402	0.8335	0.8956
Mid	2441	0.8335	0.8826
High	2480	0.8379	0.9043


Test mode: 8DPSK_EDR-3Mbps mode / 2402-2480 MHz			
Channel	Frequency (MHz)	OBW(99%) (MHz)	20dB BW (MHz)
Low	2402	1.1548	1.2173
Mid	2441	1.1461	1.2130
High	2480	1.1418	1.2130



Report No.: T190626D05-RP2


Test Data

20 dB Bandwidth




8DPSK_EDR-3Mbps mode


Low CH




Mid CH




High CH



99% Bandwidth





5.3 OUTPUT POWER MEASUREMENT

5.3.1 Test Limit

According to §15.247(b)(1).

Peak output power :

FCC

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Limit	☒ Antenna not exceed 6 dBi : 21dBm ☐ Antenna with DG greater than 6 dBi : 21dBm [Limit = 30 – (DG – 6)]
-------	---

Average output power : For reporting purposes only.

5.3.2 Test Procedure

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

5.3.3 Test Setup



5.3.4 Test Result

Peak output power :

BT						
Config.	CH	Freq. (MHz)	Power Setting	PK Power (dBm)	PK Power (W)	Limit (dBm)
GFSK BR-1Mbps (DH5)	0	2402	15	8.25	0.0067	21
	39	2441	15	8.22	0.0066	
	78	2480	15	8.16	0.0065	
8DPSK EDR-3Mbps (3DH5)	0	2402	14	5.63	0.0037	
	39	2441	14	5.15	0.0033	
	78	2480	14	5.23	0.0033	

Average output power :

BT				
Config.	CH	Freq. (MHz)	Power Setting	AV Power (dBm)
GFSK BR-1Mbps (DH5)	0	2402	15	7.59
	39	2441	15	7.84
	78	2480	15	7.33
8DPSK EDR-3Mbps (3DH5)	0	2402	14	4.32
	39	2441	14	4.45
	78	2480	14	4.59

5.4 FREQUENCY SEPARATION

5.4.1 Test Limit

According to §15.247(a)(1),


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Limit	> two-thirds of the 20 dB bandwidth
-------	-------------------------------------

5.4.2 Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = 300kHz, Sweep = auto.
Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency

5.4.3 Test Setup



5.4.4 Test Result


Test mode: GFSK_BDR-1Mbps mode / 2402-2480 MHz				
Channel	Frequency (MHz)	Channel Separation (MHz)	Channel Separation Limits (MHz)	Result
Low	2402	1.0029	0.597	PASS
Mid	2441	1.0029	0.588	PASS
High	2480	1.0029	0.603	PASS

Test mode: 8DPSK_EDR-3Mbps mode / 2402-2480 MHz				
Channel	Frequency (MHz)	Channel Separation (MHz)	Channel Separation Limits (MHz)	Result
Low	2402	1.0029	0.812	PASS
Mid	2441	1.0029	0.809	PASS
High	2480	1.0029	0.809	PASS

Report No.: T190626D05-RP2


Test Data

GFSK_BDR-1Mbps mode



Note: We selected worst case to performed test in middle channel, The results can be meet other channel.

8DPSK_EDR-3Mbps mode



Note: We selected worst case to performed test in middle channel, The results can be meet other channel.

5.5 NUMBER OF HOPPING

5.5.1 Test Limit

According to §15.247(a)(1)(iii)


Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

5.5.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 7.8.3

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set spectrum analyzer Start Freq. = 2400 MHz, Stop Freq. = 2483.5 MHz, RBW = 100KHz, VBW = 300KHz.
4. Max hold, view and count how many channel in the band.

5.5.3 Test Setup




5.5.4 Test Result

Number of Hopping				
Mode	Frequency (MHz)	Hopping Channel Number	Hopping Channel Number Limits	Result
BDR-1Mbps	2402-2480	79	15	Pass
EDR-3Mbps	2402-2480	79	15	

REMARK:

In the AFH mode, this device operation was using 20 channels, so the requirement for minimum number of hopping channels is satisfied

Test Data



5.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

5.6.1 Test Limit


According to §15.247(d),

Limit	-20 dBc
-------	---------

5.6.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. The Band Edge at 2.4GHz and 2.4835GHz are investigated with both hopping“ON” and “OFF” modes “


5.6.3 Test Setup





Report No.: T190626D05-RP2


5.6.4 Test Result

Test Data









5.7 TIME OF OCCUPANCY (DWELL TIME)

5.7.1 Test Limit


According to §15.247(a)(1)(iii),

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.7.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=1MHz, Sweep = 1 ms

5.7.3 Test Setup




5.7.4 Test Result

Time of Occupancy (Dwell Time)							
Mode	Frequency (MHz)	Pulse Time Per Hopping (ms)	Minimum Number of Hopping Freq.	Number of pulse in	Dwell Time IN	Dwell Time Limits (s)	Result
				(0.4 * N sec)	(0.4 * N sec)		
DH5	2402	0.4493	79	106.67	0.0479	0.4	Pass
3DH5	2402	0.3043	79	106.67	0.0325	0.4	

Non-AFH: DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $3.37 * 0.4 * 79 = 106.6$

Test Data



Note: We selected worst case to performed test in low channel. The results can be meet other channel.

5.8 RADIATION BANDEDGE AND SPURIOUS EMISSION

5.8.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

5.8.2 Test Procedure


1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.
3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.
4. For harmonic, the worst case of output power was BDR-1Mbps. Therefore only BDR-1Mbps record in the report.
5. The SA setting following :
 - (1) Below 1G : RBW = 100kHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.
 - (2) Above 1G :
 - (2.1) For Peak measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.
 - (2.2) For Average measurement : RBW = 1MHz, VBW
If Duty Cycle $\geq$ 98%, VBW=10Hz.
If Duty Cycle < 98%, VBW $\geq$ 1/T.

Configuration	Duty Cycle (%)	T(ms)	1/T (kHz)	VBW setting
GFSK_BDR-1Mbps	12.02%	0.4493	2.226	2.4kHz
8DPSK_EDR-3Mbps	8.11%	0.3043	3.289	3.3kHz


Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

5.8.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



5.8.4 Test Result


Band Edge Test Data

Test Mode:	GFSK_BR-1Mbps Low CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2371.50	Average	42.05	-3.35	38.70	54.00	-15.30
2371.50	Peak	59.07	-3.35	55.72	74.00	-18.28
2376.80	Average	40.79	-3.36	37.43	54.00	-16.57
2376.80	Peak	58.24	-3.36	54.88	74.00	-19.12
2390.00	Average	40.02	-3.38	36.64	54.00	-17.36
2390.00	Peak	52.56	-3.38	49.18	74.00	-24.82

Test Mode:	GFSK_BR-1Mbps Low CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2377.00	Average	40.52	-3.36	37.16	54.00	-16.84
2377.00	Peak	59.06	-3.36	55.70	74.00	-18.30
2389.30	Average	42.16	-3.39	38.77	54.00	-15.23
2389.30	Peak	59.15	-3.39	55.76	74.00	-18.24
2390.00	Average	42.01	-3.38	38.63	54.00	-15.37
2390.00	Peak	56.69	-3.38	53.31	74.00	-20.69

Test Mode:	GFSK_BR-1Mbps High CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2483.50	Average	41.11	-2.83	38.28	54.00	-15.72
2483.50	Peak	56.92	-2.83	54.09	74.00	-19.91

Test Mode:	GFSK_BR-1Mbps High CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2483.50	Average	41.17	-2.83	38.34	54.00	-15.66
2483.50	Peak	53.66	-2.83	50.83	74.00	-23.17

Test Mode:	8DPSK_EDR-3Mbps Low CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2377.00	Average	42.60	-3.36	39.24	54.00	-14.76
2377.00	Peak	55.51	-3.36	52.15	74.00	-21.85
2388.20	Average	43.67	-3.39	40.28	54.00	-13.72
2388.20	Peak	59.13	-3.39	55.74	74.00	-18.26
2390.00	Average	41.14	-3.38	37.76	54.00	-16.24
2390.00	Peak	52.57	-3.38	49.19	74.00	-24.81

Test Mode:	8DPSK_EDR-3Mbps Low CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2377.30	Average	40.85	-3.36	37.49	54.00	-16.51
2377.30	Peak	55.36	-3.36	52.00	74.00	-22.00
2389.50	Average	43.66	-3.39	40.27	54.00	-13.73
2389.50	Peak	58.60	-3.39	55.21	74.00	-18.79
2390.00	Average	43.48	-3.38	40.10	54.00	-13.90
2390.00	Peak	55.88	-3.38	52.50	74.00	-21.50

Test Mode:	8DPSK_EDR-3Mbps High CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2483.50	Average	45.39	-2.83	42.56	54.00	-11.44
2483.50	Peak	57.71	-2.83	54.88	74.00	-19.12


Test Mode:	8DPSK_EDR-3Mbps High CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Band Edge	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2483.50	Average	46.05	-2.83	43.22	54.00	-10.78
2483.50	Peak	57.69	-2.83	54.86	74.00	-19.14

Below 1G Test Data


Test Mode:	BT Mode	Temp/Hum	28.6(°C)/ 44%RH
Test Item	30MHz-1GHz	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
34.85	Peak	39.30	-5.51	33.79	40.00	-6.21
102.75	Peak	48.10	-11.87	36.23	43.50	-7.27
350.10	Peak	45.64	-7.03	38.61	46.00	-7.39
839.95	Peak	33.68	3.58	37.26	46.00	-8.74
849.65	Peak	34.91	3.01	37.92	46.00	-8.08
900.09	Peak	33.45	4.19	37.64	46.00	-8.36

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Test Mode:	BT Mode	Temp/Hum	28.6(°C)/ 44%RH
Test Item	30MHz-1GHz	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
100.81	Peak	49.55	-12.44	37.11	43.50	-6.39
172.59	Peak	45.94	-10.87	35.07	43.50	-8.43
183.26	Peak	46.30	-11.23	35.07	43.50	-8.43
350.10	Peak	45.99	-7.03	38.96	46.00	-7.04
839.95	Peak	34.28	3.58	37.86	46.00	-8.14
900.09	Peak	30.61	4.19	34.80	46.00	-11.20

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Above 1G Test Data

Test Mode:	GFSK_BR-1Mbps Low CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Harmonic	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4804.00	Average	42.83	3.05	45.88	54.00	-8.12
4804.00	Peak	46.55	3.05	49.60	74.00	-24.40
7206.00	Average	38.53	10.64	49.17	54.00	-4.83
7206.00	Peak	44.51	10.64	55.15	74.00	-18.85

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	GFSK_BR-1Mbps Low CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Harmonic	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4804.00	Average	39.15	3.05	42.20	54.00	-11.80
4804.00	Peak	44.56	3.05	47.61	74.00	-26.39
7206.00	Average	34.71	10.64	45.35	54.00	-8.65
7206.00	Peak	41.90	10.64	52.54	74.00	-21.46

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	GFSK_BR-1Mbps Mid CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Harmonic	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4882.00	Average	41.59	3.38	44.97	54.00	-9.03
4882.00	Peak	45.62	3.38	49.00	74.00	-25.00
7323.00	Average	37.28	11.06	48.34	54.00	-5.66
7323.00	Peak	43.25	11.06	54.31	74.00	-19.69

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	GFSK_BR-1Mbps Mid CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Harmonic	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4882.00	Average	38.28	3.38	41.66	54.00	-12.34
4882.00	Peak	43.27	3.38	46.65	74.00	-27.35
7323.00	Average	33.54	11.06	44.60	54.00	-9.40
7323.00	Peak	40.57	11.06	51.63	74.00	-22.37

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	GFSK_BR-1Mbps High CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Harmonic	Test Date	August 7, 2019
Polarize	Vertical	Test Engineer	Jerry Lu
Detector	Peak and Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4960.00	Average	40.92	4.06	44.98	54.00	-9.02
4960.00	Peak	44.71	4.06	48.77	74.00	-25.23
7440.00	Average	36.76	10.67	47.43	54.00	-6.57
7440.00	Peak	42.28	10.67	52.95	74.00	-21.05

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	GFSK_BR-1Mbps High CH	Temp/Hum	28.6(°C)/ 44%RH
Test Item	Harmonic	Test Date	August 7, 2019
Polarize	Horizontal	Test Engineer	Jerry Lu
Detector	Peak and Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4960.00	Average	37.28	4.06	41.34	54.00	-12.66
4960.00	Peak	42.67	4.06	46.73	74.00	-27.27
7440.00	Average	32.85	10.67	43.52	54.00	-10.48
7440.00	Peak	40.03	10.67	50.70	74.00	-23.30

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

--End of Test Report--