



FCC PART 15 SUBPART C
EMI MEASUREMENT AND TEST REPORT
For
FU KUANG HUI ELECTRONICS CO., LTD.(SHEN ZHEN)

The second Industrial Park of Xia Village, Gongming Baoan District,
Shenzhen City, Guongdong Province, China

FCC ID: P2DBTU97

2003-09-25

This Report Concerns: ☒ Original Report	Equipment Type: UFD+Bluetooth
Test Engineer: Jerry Wang / Ming Jing  	
Report No.: R0308085	
Test Date: 2003-08-22 / 2003-09-24	
Reviewed By: Ling Zhang / 	
Prepared By: Bay Area Compliance Laboratory Corporation (BACL) 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is specially limited to the above client company and product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 OBJECTIVE	4
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	4
1.4 TEST METHODOLOGY	4
1.5 TEST FACILITY	5
1.6 TEST EQUIPMENT LIST	5
1.7 LOCAL SUPPORT EQUIPMENT LIST AND DETAILS.....	6
1.8 EXTERNAL I/O CABLING.....	6
2 - SYSTEM TEST CONFIGURATION.....	7
2.1 JUSTIFICATION	7
2.2 EUT EXERCISE SOFTWARE	7
2.3 SPECIAL ACCESSORIES.....	7
2.4 SCHEMATICS / BLOCK DIAGRAM	7
2.5 EQUIPMENT MODIFICATIONS	7
2.6 CONFIGURATION OF TEST SYSTEM.....	8
2.7 TEST SETUP BLOCK DIAGRAM	8
3 - SUMMARY OF TEST RESULTS.....	9
4 - MAXIMUM PEAK OUTPUT POWER.....	10
4.1 STANDARD APPLICABLE	10
4.2 MEASUREMENT PROCEDURE.....	10
4.3 TEST EQUIPMENT	10
4.4 MEASUREMENT RESULT	10
4.5 PLOTS OF MAXIMUM PEAK OUTPUT POWER	10
5 - CHANNEL BANDWIDTH	13
5.1 STANDARD APPLICABLE	13
5.2 MEASUREMENT PROCEDURE.....	13
5.3 TEST EQUIPMENT	13
5.4 MEASUREMENT RESULT	13
5.5 PLOT OF CHANNEL BANDWIDTH	13
6 - NUMBER OF HOPPING FREQUENCY USED	16
6.1 STANDARD APPLICABLE	16
6.2 MEASUREMENT PROCEDURE.....	16
6.3 TEST EQUIPMENT	16
6.4 MEASUREMENT PROCEDURE.....	16
6.5 PLOTS OF NUMBER OF HOPPING FREQUENCY	16
7 - HOPPING CHANNEL SEPARATION	19
7.1 STANDARD APPLICABLE	19
7.2 MEASUREMENT PROCEDURE.....	19
7.3 TEST EQUIPMENT	19
7.4 MEASUREMENT RESULTS.....	19
7.5 PLOTS OF HOPPING CHANNEL SEPARATION	19
8 - 100 KHZ BANDWIDTH OF BAND EDGES	22
8.1 STANDARD APPLICABLE	22
8.2 MEASUREMENT PROCEDURE.....	22
8.3 TEST EQUIPMENT	22
8.4 PLOTS OF 100kHz BANDWIDTH OF BAND EDGE	22
9 - DWELL TIME	25
9.1 STANDARD APPLICABLE	25
9.2 MEASUREMENT PROCEDURE.....	25
9.3 TEST EQUIPMENT	25
9.4 MEASUREMENT RESULTS.....	25

9.5 PLOTS OF DWELL TIME	25
10 - SPURIOUS EMISSION AT ANTENNA PORT.....	29
10.1 STANDARD APPLICABLE	29
10.2 MEASUREMENT PROCEDURE.....	29
10.3 TEST EQUIPMENT	29
10.4 MEASUREMENT RESULTS.....	29
11 - RADIATED EMISSION.....	33
11.1 MEASUREMENT UNCERTAINTY	33
11.2 TEST SETUP.....	33
11.3 SPECTRUM ANALYZER SETUP	33
11.4 TEST PROCEDURE	34
11.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	34
11.6 SUMMARY OF TEST RESULTS	34
11.7 RADIATED EMISSION TEST DATA.....	35
12 - CONDUCTED EMISSION	37
12.1 MEASUREMENT UNCERTAINTY	37
12.2 TEST SETUP.....	37
12.3 SPECTRUM ANALYZER SETUP	37
12.4 TEST PROCEDURE	37
12.5 SUMMARY OF TEST RESULTS	38
12.6 CONDUCTED EMISSIONS TEST DATA	38
12.7 PLOT OF CONDUCTED EMISSIONS TEST DATA.....	38
13 - ANTENNA REQUIREMENT.....	41
14 - RF EXPOSURE.....	42

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

The *Fu Kuang Hui Electronics Co., Ltd. (Shen Zhen)* 's product, model no.: *BTU97* or the "EUT" as referred to this report is a UFD+Bluetooth which is measured approximately 4.1"L x 1.2"W x 0.6" H. The EUT is a portable USB hard drive used store and transport data safely and easily between computers through USB interface.

** The test data gathered are from typical production samples provided by the manufacturer.*

1.2 Objective

This type approval report is prepared on behalf of *Fu Kuang Hui Electronics Co., Ltd. (Shen Zhen)* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communication Commissions rules.

The objective of the manufacturer is to demonstrate compliance with FCC 15.247 rules for the bluetooth transmitter:

- Maximum Peak Output Power
- Hopping Channel Separation
- Number of Hopping Frequency Used
- 20 dB Bandwidth
- Dwell Time on Each Channel
- 100 kHz Bandwidth of Band Edge
- Conducted Emission
- Spurious Emission
- Radiated Emission
- Antenna Requirement
- RF Exposure Limit

1.3 Related Submittal(s)/Grant(s)

No Related Submittals.

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2001, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at BACL. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.5 Test Facility

The Open Area Test site used by BACL to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2001.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, CISPR 22: 1997: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods.

1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2517A01610	2003-10-30
HP	Amplifier	8447E	2944A07030	2004-06-28
HP	Quasi-Peak Adapter	85650A	2521A00718	2004-03-08
ETS	Biconical Antenna	8100B	9603-2315	2004-09-05
ETS	Log Periodic Antenna	3148	0004-1155	2004-08-23
Agilent	Spectrum Analyzer (9KHz – 40GHz)	8564E	3943A01781	2004-08-01
Agilent	Spectrum Analyzer (9KHz – 50GHz)	8565EC	3946A00131	2004-05-03
HP	Amplifier (1-26.5GHz)	8449B	3147A00400	2004-03-14
A.H.System	Horn Antenna (700MHz-18GHz)	SAS-200/571	261	2004-05-31
Rohde & Schwarz	Artificial LISN	ESH2-Z5	871884/039	2004-03-28
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2003-12-03

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. certifies that all calibration has been performed using suitable standards traceable to the NIST.

1.7 Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
Dell	Laptop	PP02X	00045-423-864-633	DOC
HP	ThinkJet	2225C+	2821S14783	DS16XU2225

1.8 External I/O Cabling

Cable Description	Length (M)	From/Port	To
Shielded USB	1.5	USB Port/Host	EUT USB Port
Shielded Printer Cable	2.0	Parallel/EUT	HP Printer

2 - SYSTEM TEST CONFIGURATION

2.1 Justification

The host system was configured for testing in a typical fashion (as a normally used by a typical user).

The EUT was tested in the normal (native) operating mode to represent *worst-case* results during the final qualification test.

2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The test software, bluetest, provided by the customer, is started the Windows 98 terminal program under the Windows 98 operating system. Once started, select USB from “choose a protocol”, select TXDATA1 from “bluetest” then click execute. The process is continuous throughout all tests.

2.3 Special Accessories

As shown in section 2.7, all interface cables used for compliance testing are shielded as normally supplied by their respective support equipment manufacturers.


2.4 Schematics / Block Diagram

Please refer to Exhibit D.


2.5 Equipment Modifications

No modifications were made by BACL Corporation to ensure the EUT to comply with the applicable limits and requirements.

2.6 Configuration of Test System



2.7 Test Setup Block Diagram



3 - SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT	REFERENCE
§ 2.1093	RF Safety Requirements	Compliant	Section 14
§15.203	Antenna Requirement	Compliant	Section 13
§15.207 (a)	Conducted Emission	Compliant	Section 12
§ 15.205	Restricted Bands	Compliant	Section 11
§15.247 (a) (1) (iii)	Number of Hopping Frequencies Used	Compliant	Section 6
§15.209	Radiated Emission	Compliant	Section 11
§15.247 (a) (1)	Hopping Channel Separation	Compliant	Section 7
§15.247 (a) (1) (iii)	Dwell Time of Each Frequency within a 10 Second Period of time (0.4 x Number of Channel)	Compliant	Section 9
§15.247 (a) (1) (iii)	Channel Bandwidth	Compliant	Section 5
§15.247 (b) (1)	Maximum Peak Output Power	Compliant	Section 4
§ 15.247 (c)	100 kHz Bandwidth of Frequency Band Edge	Compliant	Section 8
§ 15.247 (g)	Full and complete compliance with applicable requirements for FHSS. Compliance with the definition of frequency hopping system, distribute transmission over minimum number of hopping channel	Compliant	Technical Manual
§ 15.247 (h)	Limitation on avoidance on hopping on occupied channel	Compliant	Technical Manual

4 - MAXIMUM PEAK OUTPUT POWER

4.1 Standard Applicable

According to §15.247(b) (1), for frequency hopping systems in the 2400-2483.5MHz band employing at least 75 hopping channels, and all direct sequence systems, the maximum peak output power of the transmitter shall not exceed 1 Watt.

4.2 Measurement Procedure

1. Place the EUT on the turntable and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

4.3 Test Equipment



Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01


4.4 Measurement Result

Channel	Frequency	Output Power in dBm	Output Power in W	Standard	Result
Low	2402	3.00	0.0020	$\leq 1\text{W}$	Compliant
Middle	2442	3.33	0.0022	$\leq 1\text{W}$	Compliant
High	2480	2.67	0.0018	$\leq 1\text{W}$	Compliant

4.5 Plots of Maximum Peak Output Power

Please refer to following plots.





5 - CHANNEL BANDWIDTH

5.1 Standard Applicable

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

5.3 Test Equipment



Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01


5.4 Measurement Result

Frequency	Measurement (kHz)	Standard	Result
Low	780	$\leq 1\text{MHz}$	Compliant
Middle	984	$\leq 1\text{MHz}$	Compliant
High	723	$\leq 1\text{MHz}$	Compliant

5.5 Plot of Channel Bandwidth

Please refer to following plots.





6 - NUMBER OF HOPPING FREQUENCY USED

6.1 Standard Applicable

According to §15.247(a)(1)(iii), frequency hopping systems operating in the 2400-2483.5Mhz band shall use at least 75 hopping frequencies.

6.2 Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the bench without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

6.3 Test Equipment



Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01


6.4 Measurement Procedure

Measurement	Standard	Result
79	75	Compliant

6.5 Plots of Number of Hopping Frequency

Please refer to the attached plots.





7 - HOPPING CHANNEL SEPARATION

7.1 Standard Applicable

According to §15.247(a)(1), frequency hopping system shall have, hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on a bench without connection to measurement instrument Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the Max-Hold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function, and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

7.3 Test Equipment



Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01


7.4 Measurement Results

Channel	Measurement (kHz)	Result
Low	996	Compliant
Middle	999	Compliant
High	984	Compliant

7.5 Plots of Hopping Channel Separation

Please refer to the following plots.





8 - 100 KHZ BANDWIDTH OF BAND EDGES

8.1 Standard Applicable

According to §15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required.

8.2 Measurement Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



8.3 Test Equipment

Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01

8.4 Plots of 100kHz Bandwidth of Band Edge

Please refer the following plots.





9 - DWELL TIME

9.1 Standard Applicable

According to §15.247 (a)(1)(iii), the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

9.3 Test Equipment

Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01

9.4 Measurement Results



Low Channel: $5 \times 2.917(\text{ms}) \times [(79 \times 0.4) / 2 (\text{s})] = 0.230 < 0.4 \text{ s}$



Middle Channel: $5 \times 2.917(\text{ms}) \times [(79 \times 0.4) / 2 (\text{s})] = 0.230 < 0.4 \text{ s}$



High Channel: $5 \times 2.900(\text{ms}) \times [(79 \times 0.4) / 2 (\text{s})] = 0.229 < 0.4 \text{ s}$

9.5 Plots of Dwell Time

Please refer the following plots.







10 - SPURIOUS EMISSION AT ANTENNA PORT

10.1 Standard Applicable

According to §15.209 (f) and §15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in §15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in §15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit.

10.2 Measurement Procedure



1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on a bench without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in transmitting mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.



10.3 Test Equipment



Manufacturer	Model No.	Description	Calibration Due Date
Agilent	8564E	Spectrum Analyzer	2004-08-01

10.4 Measurement Results

Please refer to the following plots.







11 - RADIATED EMISSION

11.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

11.2 Test Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup in accordance with the ANSI C63.4-2001. The specification used was the FCC 15 Subpart C limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The notebook was connected with 120Vac/60Hz power source.

11.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR §15.33 (a) (1), the system was tested to 25000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency	30 MHz
Stop Frequency	25000 MHz
Sweep Speed	Auto
IF Bandwidth	1 MHz
Video Bandwidth	1 MHz
Quasi-Peak Adapter Bandwidth.....	120 kHz
Quasi-Peak Adapter Mode.....	Normal
Resolution Bandwidth.....	1MHz

11.4 Test Procedure

For the radiated emissions test, both the laptop and all peripheral power cords were connected to the AC floor outlet since the power supply used in the laptop did not provide an accessory power outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB μ V of specification limits), and are distinguished with a "Qp" in the data table.

11.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

11.6 Summary of Test Results

According to the data in section 11.7, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.207, and 15.247, and had the worst margin of:

- 7.0 dB at 7206.90 MHz in the **Horizontal** polarization, Low Channel.
- 12.6 dB at 7326.00 MHz in the **Vertical** polarization, Middle Channel.
- 16.6 dB at 7440.00 MHz in the **Vertical** polarization, High Channel.
- 12.9 dB at 480.00 MHz in the **Horizontal** polarization, Unintentional Emission.

11.7 Radiated Emission Test Data

Indicated		Direction	Antenna Height	Antenna		Correction Factor			FCC 15 Subpart C		
Frequency	Ampl.			Polar	Antenna	Cable Loss	Amp.	Corr. Ampl.	Limit	Margin	Mode
MHz	dBμV/m	Degree	Meter	H/V	dBμV/m	dBμV/m	dB	dBμV/m	dBμV/m	dB	
Low Channel											
2402.30	59.8	90	1.2	V	28.1	3.4	35.2	56.1			FUND / AVE.
2402.30	61.2	200	1.8	H	28.1	3.4	35.2	57.5			FUND / AVE.
2402.30	96.7	0	1.2	V	28.1	3.4	35.2	93.0			FUND / PEAK.
2402.30	95.3	270	1.8	H	28.1	3.4	35.2	91.6			FUND / PEAK.
7206.90	39.8	30	1.5	H	35.1	5.6	33.5	47.0	54	-7.0	AVG
7206.90	37.8	90	1.2	V	35.1	5.6	33.5	45.0	54	-9.0	AVG
4804.60	39.6	45	1.2	V	32.5	4.9	33.0	44.0	54	-10.0	AVG
4804.60	38.4	90	1.2	H	32.5	4.9	33.0	42.8	54	-11.2	AVG
7206.90	48.7	30	1.2	V	35.1	5.6	33.5	55.9	74	-18.1	PEAK
4804.60	50.1	120	1.2	V	32.5	4.9	33.0	54.5	74	-19.5	PEAK
4804.60	49.8	90	1.2	H	32.5	4.9	33.0	54.2	74	-19.8	PEAK
7206.90	46.3	30	1.5	H	35.1	5.6	33.5	53.5	74	-20.5	PEAK
Middle Channel											
2441.90	60.8	30	1.8	H	28.1	3.4	35.2	57.1			FUND / AVE.
2442.00	61.2	200	1.2	V	28.1	3.4	35.2	57.5			FUND / AVE.
2441.90	96.2	30	1.8	H	28.1	3.4	35.2	92.4			FUND / PEAK.
2441.22	97.1	200	1.2	V	28.1	3.4	35.2	93.4			FUND / PEAK.
7326.00	34.2	180	1.2	V	35.1	5.6	33.5	41.4	54	-12.6	AVG
4884.00	32.3	200	1.2	V	32.5	4.9	33.0	36.7	54	-17.3	AVG
7326.00	48.6	90	1.5	H	35.1	5.6	33.5	55.8	74	-18.2	PEAK
7326.00	28.3	90	1.2	H	35.1	5.6	33.5	35.5	54	-18.5	AVG
7326.00	48.2	180	1.2	V	35.1	5.6	33.5	55.4	74	-18.6	PEAK
4883.90	29.4	120	1.2	H	32.5	4.9	33.0	33.8	54	-20.2	AVG
4884.00	49.4	200	1.2	V	32.5	4.9	33.0	53.8	74	-20.2	PEAK
4883.90	49.3	120	1.2	H	32.5	4.9	33.0	53.7	74	-20.3	PEAK

Indicated			Antenna	Antenna		Correction Factor			FCC 15 Subpart C		
Frequency	Ampl.	Direction	Height	Polar	Antenna	Cable Loss	Amp.	Corr. Ampl.	Limit	Margin	Mode
MHz	dB μ V/m	Degree	Meter	H/V	dB μ V/m	dB μ V/m	dB	dB μ V/m	dB μ V/m	dB	
High Channel											
2479.90	57.9	90	1.2	V	28.1	3.4	35.2	54.2			FUND / AVE.
2480.13	58.6	120	1.2	H	28.1	3.4	35.2	54.9			FUND / AVE.
2479.90	94.3	90	1.2	V	28.1	3.4	35.2	90.6			FUND / PEAK.
2480.13	93.8	120	1.2	H	28.1	3.4	35.2	90.1			FUND / PEAK.
7440.00	30.2	180	1.2	V	35.1	5.6	33.5	37.4	54	-16.6	AVG
7440.00	28.7	180	1.5	H	35.1	5.6	33.5	35.9	54	-18.1	AVG
7440.39	47.6	180	1.2	V	35.1	5.6	33.5	54.8	74	-19.2	PEAK
4960.60	30.1	180	1.5	H	32.5	4.9	33.0	34.5	54	-19.5	AVG
4960.00	29.8	180	1.2	V	32.5	4.9	33.0	34.2	54	-19.8	AVG
7440.39	45.9	200	1.5	H	35.1	5.6	33.5	53.1	74	-20.9	PEAK
4960.60	47.2	180	1.5	H	32.5	4.9	33.0	51.6	74	-22.4	PEAK
4960.00	46.5	200	1.2	V	32.5	4.9	33.0	50.9	74	-23.1	PEAK

Note:

FUND: Fundamental

AVG: Average

Unintentional Emission

Indicated			Antenna	Antenna		Correction Factor			FCC 15 Subpart C	
Frequency	Ampl.	Direction	Height	Polar	Antenna	Cable Loss	Amp.	Corr. Ampl.	Limit	Margin
MHz	dB μ V/m	Degree	Meter	H/V	dB μ V/m	dB μ V/m	dB	dB μ V/m	dB μ V/m	dB
480.00	36.7	300	3.0	H	18.3	3.1	25.0	33.1	46	-12.9
72.00	40.6	0	1.2	V	9.2	1.2	25.0	26.0	40	-14.0
240.00	40.9	300	3.0	H	13.8	2.2	25.0	31.9	46	-14.1
268.00	40.8	180	1.2	V	13.4	2.2	25.0	31.4	46	-14.6
144.00	39.5	270	2.5	H	12.4	1.6	25.0	28.5	43.5	-15.0
72.00	39.6	300	1.8	H	9.2	1.2	25.0	25.0	40	-15.0
480.00	34.2	180	1.2	V	18.3	3.1	25.0	30.6	46	-15.4
144.00	37.5	200	1.2	V	12.4	1.6	25.0	26.5	43.5	-17.0
60.00	36.5	200	1.2	V	9.4	1.3	25.0	22.2	40	-17.8
48.00	34.9	30	1.2	V	11.1	1.1	25.0	22.1	40	-18.0
48.00	33.7	180	2.0	H	11.1	1.1	25.0	20.9	40	-19.2

12 - CONDUCTED EMISSION

12.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

12.2 Test Setup

The measurement was performed at shield room, using the same setup per ANSI C63.4 – 2001 measurement procedure. The specification used was FCC Class B limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The notebook was connected with 120Vac/60Hz power source.

12.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configurations during the conduction test:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Video Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode.....	Normal

12.4 Test Procedure

During the conducted emission test, the power cord of the host system was connected to the auxiliary outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of each modes tested to ensure EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB μ V of specification limits). Quasi-peak readings are distinguished with a "Qp".

12.5 Summary of Test Results

According to the data in section 12.6, the EUT complied with the FCC Conducted margin for a Class B device, with the *worst* margin reading of:

-13.2 dB μ V at 0.15 MHz in the Line mode

12.6 Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				FCC CLASS B	
Frequency MHz	Amplitude dB μ V	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dB μ V	Margin dB
0.15	52.8	QP	Line	66	-13.2
0.43	44.1	QP	Line	57	-13.2
0.53	42.7	QP	Line	56	-13.3
0.63	40.1	QP	Neutral	56	-15.9
0.53	29.1	Ave	Line	46	-16.9
0.35	40.7	QP	Neutral	59	-18.3
0.15	47.3	QP	Neutral	66	-18.7
0.63	27.2	Ave	Neutral	46	-18.8
0.35	29.3	Ave	Neutral	49	-19.7
0.15	35.1	Ave	Line	56	-20.9
0.43	24.8	Ave	Line	47	-22.5
0.15	33.1	Ave	Neutral	56	-22.9

12.7 Plot of Conducted Emissions Test Data

Plot(s) of Conducted Emissions Test Data is presented in the following page as reference.

Bay Area Compliance Laboratory Corp
Class B


20. Aug 03 17:48

EUT: BTU97
Manuf: Fu Kuang Hui
Op Cond: Normal
Operator: Jerry
Comment: N

Scan Settings (3 Ranges)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp
150k	1M	10k	9k	QP+AV	20ms	10dB LN	OFF
1M	3M	10k	9k	QP+AV	20ms	10dB LN	OFF
3M	30M	100k	9k	QP+AV	1ms	10dB LN	OFF

Final Measurement: x QP / + AV
Measure Time: 1 s
Subranges: 25
Acc Margin: 6dB



Bay Area Compliance Laboratory Corp
Class B


20. Aug 03 17:33

EUT: BTU97
Manuf: Fu Kuang Hui
Op Cond: Normal
Operator: Jerry
Comment: L

Scan Settings (3 Ranges)

Frequencies			Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten Preamp
150k	1M	10k	9k	QP+AV	20ms	10dB LN OFF
1M	3M	10k	9k	QP+AV	20ms	10dB LN OFF
3M	30M	100k	9k	QP+AV	1ms	10dB LN OFF

Final Measurement: x QP / + AV
Meas Time: 1 s
Subranges: 25
Acc Margin: 6dB



13 - ANTENNA REQUIREMENT

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to § 15.247 (1), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The gain of antenna used for transmitting is 1 dBi by default, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

14 - RF EXPOSURE

According to §15.247(b)(4) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-15000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 3.33 (dBm)

Maximum peak output power at antenna input terminal: 2.15 (mW)

Prediction distance: 3 (cm)

Predication frequency: 2400 (MHz)

Antenna Gain (typical): 1 (dBi)

Maximum antenna gain: 1.26(numeric)

Power density at predication frequency at 3 cm: 0.024(mW/cm²)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm²)

Test Result

The predicted power density level at 3 cm is 0.024 mW/cm². This is below the uncontrolled exposure limit of 1mW/cm² at 2400 MHz. The EUT is used at least 3cm away from user's body, so it is determined as portable equipment.