

Straubing, 10 February 2004

TEST - REPORT

No. 55106-30770

for

E51 (S4517B)

Remote Control Transmitter

Applicant: META System S. p. A.

Test Specification: FCC Code of Federal Regulations,
Part 15 Subpart C, Section 15.231

Note:

The test data of this report relate only to the individual item which has been tested.
This report shall not be reproduced except in full extent without the written approval of
the testing laboratory.

Table of Contents

1.	Administrative Data.....	3
2.	Identification of Test Laboratory.....	4
3.	Operation Mode of EUT	5
4.	Configuration.....	6
5.	Measuring Methods	7
5.1.	Field Strength of Emissions, Prescans in a fully-anechoic room (30 MHz – 1 GHz).....	8
5.2.	Fieldstrength of Emissions, Measurement at Open Area Test Site (30 MHz – 1 GHz).....	9
5.3.	Fieldstrength of Emissions above 1 GHz.....	10
6.	Photographs Taken During Testing	11
7.	List of Measurements.....	16
8.	Referenced Regulations	21
	Charts taken during testing.....	22

1. Administrative Data

Test item (EUT)	
Type designation	E51 (S4517B)
Serial number(s):	001
Type of equipment:	Remote Control Transmitter
Parts/accessories:	
FCC-ID:	P3OS4517
Technical data	
Frequency range	433.05 – 434.79MHz
Operational frequency	433.92 MHz
Type of modulation	10K0A1D
Pulse frequency	N/A
Pulse width	N/A
Antenna	Integrated
Power supply	
Applicant: (full address)	META System S. p. A. Via Majakovskij, 10/b/c/d/e I-42100 Reggio Emilia Italy
Contract identification:	---
Contact person:	Mr. Giorgio Maldini
Manufacturer:	META System S. p. A.
Application details	
Receipt of EUT:	19. November 2003
Date of test:	November – December 2003
Note:	
Responsible for testing:	M. Steindl
Responsible for test report:	M. Steindl

2. Identification of Test Laboratory

DETAILS OF THE TEST LABORATORY

COMPANY NAME:	Senton GmbH EMI/EMC Test Center
ADDRESS:	Aeussere Fruehlingsstrasse 45 D-94315 Straubing Germany
LABORATORY ACCREDITATION:	DAR-Registration No. TTI-P-G 062/94-01
FCC TEST SITE LISTING	90926
INDUSTRY CANADA TEST SITE REGISTRATION	IC 3050
NAME FOR CONTACT PURPOSES:	Mr. Johann Roidt
TELEPHONE: (+49) (0)9421 5522-0	FAX: (+49) (0)9421 5522-99

PERSONNEL INVOLVED IN THIS TEST REPORT

LABORATORY MANAGER:	 Mr. Johann Roidt
RESPONSIBLE FOR TESTING:	Mr. Martin Steindl
RESPONSIBLE FOR TEST REPORT:	Mr. Martin Steindl

SUMMARY OF TEST RESULTS

The tested sample complies with the requirements set forth in the
FCC Code of Federal Regulations
Part 15, Subpart C, Section 15.231

3. Operation Mode of EUT

While one button is pressed, the transmitter continuously sends the corresponding datagram. When the button is released, the transmitter stops working instantly.

4. Configuration

Configuration of the EUT
The EUT was fixted in a pneumatic system, which triggered the EUT continiously.

Cables connected to the EUT
Not applicable

Peripheral devices connected to the EUT
Not applicable

5. Measuring Methods


5.1. Field Strength of Emissions, Prescans in a fully-anechoic room (30 MHz – 1 GHz)

Rules and Specifications:	Sections 15.109 & 15.231
Guide:	ANSI C63.4 1997

Measurement Procedure:

Radiated emissions are measured over the frequency range from 30 MHz to 1 GHz.

Measurements were made in both the horizontal and vertical planes of polarization in a fully anechoic room using a spectrum analyzer with the detector function set to peak and resolution bandwidth set to 100 kHz. All tests were performed at a test-distance of 3 meters. Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.



Fully anechoic chamber

Test instruments used:

No.	Type	Model	Serial Number	Manufacturer
01	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
113	Preamplifier	CPA9231A	3393	Schaffner
141	Biconical antenna	HK 116	829708/006	Rohde & Schwarz
143	Log. periodic antenna	3147	9112-1054	EMCO
003	Fully anechoic room	No. 2	1452	Albatross Projects

5.2. Fieldstrength of Emissions, Measurement at Open Area Test Site (30 MHz – 1 GHz)


Rules and Specifications:	Sections 15.109 & 15.231
Guide:	ANSI C63.4 1997

Measurement Procedure:

Measurement Procedure:

For final testing an open-area test-site was used. Radiated emissions are measured over the frequency range from 30 MHz to 1 GHz.

Measurements were made in both the horizontal and vertical planes of polarisation at a open area test site using a spectrum analyser with the detector function set to CISPR. All test were performed at a test distance of 3 meters. During the tests the EUT is rotated all around, and the receiving-antenna is rased and lowered from 1m to 4m to find the maximum levels of emissions. The cables and equipment were placed and moved within the range of position likely to find their maximum emissions.



Test instruments used:

No.	Type	Model	Serial Number	Manufacturer
01	EMI Receiver	ESVP	881414/009	Rohde & Schwarz
141	Biconical antenna	HK 116	829708/006	Rohde & Schwarz
143	Log. periodic antenna	3147	9112-1054	EMCO
003	Open Field Test Site	No. 1	N/A	Senton

5.3. Fieldstrength of Emissions above 1 GHz

Rules and Specifications:	Sections 15.109 & 15.209
Guide:	ANSI C63.4 1997

Measurement Procedure:


Radiated emissions are measured in the frequency range 1 GHz to the 10th harmonic of the maximum frequency of the EUT.

Resolution and video bandwidth of the spectrum analyzer are set to 1 MHz. Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing. Additional measurements are performed at critical frequencies with reduced span.

EUT is rotated all around and receiving antenna is raised and lowered to find the maximum levels of emission. The cables and equipment are placed and moved within the range of position likely to find their maximum emissions.

All tests are performed in a fully-anechoic chamber with a test-distance of 3 meters.

If required preamplifiers are used for the whole frequency range. Special care is taken to avoid overload in transmit mode (using appropriate attenuators and filters if necessary).



Fully anechoic



Test instruments used:

No.	Type	Model	Serial Number	Manufacturer
01	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
143	Log. periodic antenna	3147	9112-1054	EMCO
145	Horn antenna	3115	9508-4553	EMCO
146	Horn antenna set	3160-03/-09	9112-1003	EMCO
114	Preamplifier 1-8 GHz	AFS3-00100800-32-LN	847743	Miteq
115	Preamplifier 8-18 GHz	ACO/180-3530	32641	CTT
003	Fully anechoic room	No. 2	1452	Albatross Projects

6. Photographs Taken During Testing

Test setup for radiated emission measurement (fully anechoic room)







Test setup for radiated emission measurement (open-area test-side)



7. List of Measurements

FCC Part 15			
Section(s):	Test	Page(s)	Result
15.205			
15.207	Restricted Bands		Pass
15.231 (a) (1)	AC powerline emissions		Not Applicable
15.231 (b)	Periodic operation		Pass
15.231 (b)	Duty Cycle Correction		
15.231 (b)	Field strength of emissions		Pass
15.231 (c)	Bandwidth of emissions		Pass

Field strength of emissions

Rules and Specifications:	15.231 (b) Radiated Emission Limits		
Guide:	ANSI C63.4		
Limit:	In addition to the provisions of Section 15.205, the field strength of emissions from intentional radiators operated under Section 15.231 shall not exceed the following:		
	Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
	40.66 – 40.70	2.250	225
	70 – 130	1.250	125
	130 - 174	1.250 to 3.750**	125 to 375 **
	174 - 260	3.750	375
	260 – 470	3750 to 12.500**	375 to 1250 **
	above 470	12.500	1250

** linear interpolations

Test Site:	Open Area Test Site (< 1 GHz), Fully anechoic chamber (> 1 GHz)
Distance:	3 Meter

Frequency (MHz)	Detector	Antenna Polarization	Analyzer Reading (dBμV)	Antenna Correction (dB)	Duty Cycle Correction (dB)	Field Strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
433.92	QP	HOR	58.6	19.50	-5.97	72.13	80.83	-8.7
867.90	QP	HOR	28.40	27.20	-5.97	49.63	61.93	-12.3
1300.00	Peak	HOR	18.49	27.22	-5.97	39.74	61.93	-22.2
2170.00	Peak	HOR	26.67	32.42	-5.97	53.12	61.93	-8.8
2602.00	Peak	HOR	30.94	35.4	-5.97	60.37	61.93	-1.6
3037.44	Peak	VER	22.40	36.64	-5.97	53.07	61.94	-8.9

*** = All emissions showed more than 20 dB margin to the limit

A negative value for Margin indicates, that the limit is kept.

Sample calculation of erp values:


$$\text{Field Strength (dB}\mu\text{V/m)} = \text{Analyzer Reading (dB}\mu\text{V)} + \text{Antenna Correction (dB/m)} + \text{Duty Cycle Correction (dB)}$$

Test Results:	Pass
---------------	------

Duty Cycle Correction

Rules and Specifications:	15.231 (b) (2) Limits on the Field Strength of Emissions
Guide:	ANSI C63.4
ANSI C63.4	When average detector function limits are specified for a pulse modulated transmitter, the average level of emissions may be found by measuring the peak levels of the emissions and correcting them with the duty cycle according to ANSI C64.4, section I4 (10)

$$\text{Duty Cycle Correction [dB]} = 20 \cdot \log \left(\frac{\text{Sum of the Pulse Widths}}{100 \text{ ms}} \right) = - \text{dB}$$



Comment A: META 30770: Duty Cycle Correction
Date: 5.DEC.2003 14:09:28




RBW 100 kHz Delta 1 [T1]
 * VBW 300 kHz 2.29 dB
 SWT 5 ms 860.000000 µs

Ref 87 dBµV

Att 10 dB

1 AP
CLRWR



A
SGL
TRG
PRN


Center 433.92 MHz

500 µs/

Comment A: META 30770: Duty Cycle Correction
 Date: 5.DEC.2003 14:11:28

Bandwidth of Emission

Rules and Specifications:	15.231 c
Guide:	ANSI C63.4
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB from the modulated carrier



Comment A: Meta 30770: Bandwidth of Emission
Date: 24.NOV.2003 16:47:46

Test Results:	Pass	Bandwidth of Emission = 8.4 kHz = 0.0019 %
---------------	------	---

8. Referenced Regulations

All tests were performed with reference to the following regulations and standards:

☒	FCC Part 2	Code of Federal Regulations Part 2 Frequency allocation and radio treaty matters; General rules and regulations	October 01, 1999
☐	FCC Part 15 Subpart A	Code of Regulations Part 15 (Radio Frequency Devices), Subpart A (General) of the Federal Communication Commission (FCC)	May 30, 2002
☐	FCC Part 15 Subpart B	Code of Regulations Part 15 (Radio Frequency Devices), Subpart B (Unintentional Radiators) of the Federal Communication Commission (FCC)	May 30, 2002
☒	FCC Part 15 Subpart C	Code of Regulations Part 15 (Radio Frequency Devices), Subpart C (Intentional Radiators) of the Federal Communication Commission (FCC)	May 30, 2002
☐	FCC Part 74 Subpart H	Code of Regulations Part 15 (Radio Frequency Devices), Subpart H (Low Power Auxiliary Stations) of the Federal Communication Commission (FCC)	October 20, 1997
☒	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz - 40 GHz	October, 1992
☐	RSS-210	Radio Standards Specification RSS-210 Issue 5 for Low Power Licence-Exempt Radiocommunication Devices of Industry Canada	November, 2001

Charts taken during testing

Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT flat on table

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

dB μ V/m

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT flat on table

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

dB μ V/m

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT on long side

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

dB μ V/m

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT on long side

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

dB μ V/m

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT in upright position

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

dB μ V/m

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT in upright position

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT flat on table
- with WHKS500-10SS high pass filter

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization


Date of test: 11/24/2003 Operator: M. Steindl

Test performed: automatically File name: default.emi

Comment:
- 3 V lithium battery supply
- switching on continuously
- EUT flat on table
- with WHKS500-10SS high pass filter

Detector:
Peak

List of values:
10 dB Margin 50 Subranges



Result:
Prescan

Project file:
55106-30770 Page of Pages

Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT on long side
- with WHKS500-10SS high pass filter

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT on long side
- with WHKS500-10SS high pass filter

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT in upright position
- with WHKS500-10SS high pass filter

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT in upright position
- with WHKS500-10SS high pass filter

Detector:
Peak


List of values:

10 dB Margin

50 Subranges

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:


- 3 V lithium battery supply
- switching on continuously
- EUT flat on table
- with WHKS1000-10SS high pass filter

Detector:
Peak

List of values:
Selected by hand

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:


- 3 V lithium battery supply
- switching on continuously
- EUT flat on table
- with WHKS1000-10SS high pass filter

Detector:
Peak

List of values:
Selected by hand

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically


File name:
default.emi

Comment:

- 3 V lithium battery supply
- switching on continuously
- EUT on long side
- with WHKS1000-10SS high pass filter

Detector:
Peak

List of values:
Selected by hand



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:


- 3 V lithium battery supply
- switching on continuously
- EUT on long side
- with WHKS1000-10SS high pass filter

Detector:
Peak

List of values:
Selected by hand

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Horizontal Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:


- 3 V lithium battery supply
- switching on continuously
- EUT in upright position
- with WHKS1000-10SS high pass filter

Detector:
Peak

List of values:
Selected by hand

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan

Project file:
55106-30770

Page of Pages

Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model:
E51 (S4517B)

Serial no.:
0001

Applicant:
Meta System S. p. A.

Test site:
Fully anechoic room, cabin no. 2

Tested on:
Test distance 3 metres
Vertical Polarization

Date of test:
11/24/2003

Operator:
M. Steindl

Test performed:
automatically

File name:
default.emi

Comment:


- 3 V lithium battery supply
- switching on continuously
- EUT in upright position
- with WHKS1000-10SS high pass filter

Detector:
Peak

List of values:
Selected by hand

$\text{dB}\mu\text{V/m}$

Limit1: FCC Part 15 Transducer: VULB 9163



Result:
Prescan


Project file:
55106-30770

Page of Pages

Radiated Emission Test 3.95 GHz - 4.5 GHz acc. to FCC Part 15 (EMCO 3160)

Model: E51 (S4517B)	Comment: - 3 V lithium battery supply - switching on continuously - EUT flat on table - with WHK3M/13G-10SS high-pass-filter
Serial no.: 0001	
Applicant: Meta System S. p. A.	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 11/24/2003	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: 10 dB Margin 50 Subranges
--------------------------	--




Result: Prescan	Project file: 55106-30770
	Page of Pages

Radiated Emission Test 3.95 GHz - 4.5 GHz acc. to FCC Part 15 (EMCO 3160)

Model: E51 (S4517B)	Comment: - 3 V lithium battery supply - switching on continuously - EUT flat on table - with WHK3M/13G-10SS high-pass-filter
Serial no.: 0001	
Applicant: Meta System S. p. A.	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 11/24/2003	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: 10 dB Margin 50 Subranges
--------------------------	--




Result: Prescan	Project file: 55106-30770
	Page of Pages

Radiated Emission Test 3.95 GHz - 4.5 GHz acc. to FCC Part 15 (EMCO 3160)

Model: E51 (S4517B)	Comment: - 3 V lithium battery supply - switching on continuously - EUT on long side - with WHK3M/13G-10SS high-pass-filter
Serial no.: 0001	
Applicant: Meta System S. p. A.	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 11/24/2003	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: 10 dB Margin 50 Subranges
--------------------------	--




Result: Prescan	Project file: 55106-30770 Page of Pages
---------------------------	---

Radiated Emission Test 3.95 GHz - 4.5 GHz acc. to FCC Part 15 (EMCO 3160)

Model: E51 (S4517B)	Comment: - 3 V lithium battery supply - switching on continuously - EUT on long side - with WHK3M/13G-10SS high-pass-filter
Serial no.: 0001	
Applicant: Meta System S. p. A.	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 11/24/2003	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: Selected by hand
--------------------------	--




Result: Prescan	Project file: 55106-30770
	Page of Pages

Radiated Emission Test 3.95 GHz - 4.5 GHz acc. to FCC Part 15 (EMCO 3160)

Model: E51 (S4517B)	Comment: - 3 V lithium battery supply - switching on continuously - EUT in upright position - with WHK3M/13G-10SS high-pass-filter
Serial no.: 0001	
Applicant: Meta System S. p. A.	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 11/24/2003	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: 10 dB Margin 50 Subranges
--------------------------	--




Result: Prescan	Project file: 55106-30770 Page of Pages
---------------------------	---

Radiated Emission Test 3.95 GHz - 4.5 GHz acc. to FCC Part 15 (EMCO 3160)

Model: E51 (S4517B)	Comment: - 3 V lithium battery supply - switching on continuously - EUT in upright position - with WHK3M/13G-10SS high-pass-filter
Serial no.: 0001	
Applicant: Meta System S. p. A.	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 11/24/2003	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: Selected by hand
--------------------------	--



Result: Prescan	Project file: 55106-30770
	Page of Pages