FCC TEST REPORT (BLUETOOTH)

REPORT NO.: RF140312C10-3

MODEL NO.: N435

FCC ID: P4Q-N435WIFI

RECEIVED: Mar. 12, 2014

TESTED: Jul. 04, 2014 ~ Jul. 21, 2014

ISSUED: Jul. 25, 2014

APPLICANT: MiTAC International Corp.

ADDRESS: Building B, No. 209, Sec. 1, Nan Gang Rd., Nan Gang Dist., Taipei 11568, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 5
1. CERTIFICATION 6
2. SUMMARY OF TEST RESULTS 7
2.1 MEASUREMENT UNCERTAINTY 8
3. GENERAL INFORMATION 9
3.1 GENERAL DESCRIPTION OF EUT 9
3.2 DESCRIPTION OF TEST MODES 11
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 12
3.3 DESCRIPTION OF SUPPORT UNITS 16
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST 16
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 17
4. TEST TYPES AND RESULTS (FOR BLUETOOTH EDR) 18
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
4.1.2 TEST INSTRUMENTS 19
4.1.3 TEST PROCEDURES 20
4.1.4 DEVIATION FROM TEST STANDARD 20
4.1.5 TEST SETUP 21
4.1.6 EUT OPERATING CONDITIONS 22
4.1.7 TEST RESULTS 23
4.2 CONDUCTED EMISSION MEASUREMENT 28
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 28
4.2.2 TEST INSTRUMENTS 28
4.2.3 TEST PROCEDURES 29
4.2.4 DEVIATION FROM TEST STANDARD 29
4.2.5 TEST SETUP 30
4.2.6 EUT OPERATING CONDITIONS 30
4.2.7 TEST RESULTS 31
4.3 NUMBER OF HOPPING FREQUENCY USED 33
4.3.1 LIMIT OF HOPPING FREQUENCY USED 33
4.3.2 TEST SETUP 33
4.3.3 TEST INSTRUMENTS 33
4.3.4 TEST PROCEDURE 33
4.3.5 DEVIATION FROM TEST STANDARD 33
4.3.6 TEST RESULTS 33
4.4 DWELL TIME ON EACH CHANNEL 35
4.4.1 LIMITS OF DWELL TIME USED 35
4.4.2 TEST SETUP 35
4.4.3 TEST INSTRUMENTS 35
4.4.4 TEST PROCEDURES 35
4.4.5 DEVIATION FROM TEST STANDARD 35
4.4.6 TEST RESULTS 36
4.5 CHANNEL BANDWIDTH 39
4.5.1 LIMITS OF CHANNEL BANDWIDTH 39
4.5.2 TEST SETUP 39
4.5.3 TEST INSTRUMENTS 39
4.5.4 TEST PROCEDURE 39
4.5.5 DEVIATION FROM TEST STANDARD 39
4.5.6 EUT OPERATING CONDITION 39
4.5.7 TEST RESULTS 40
4.6 HOPPING CHANNEL SEPARATION 41
4.6.1 LIMITS OF HOPPING CHANNEL SEPARATION 41

4.6.2 TEST SETUP 41
4.6.3 TEST INSTRUMENTS 41
4.6.4 TEST PROCEDURE 41
4.6.5 DEVIATION FROM TEST STANDARD 41
4.6.6 TEST RESULTS 42
4.7 MAXIMUM OUTPUT POWER 43
4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT 43
4.7.2 TEST SETUP 43
4.7.3 TEST INSTRUMENTS 43
4.7.4 TEST PROCEDURE 43
4.7.5 DEVIATION FROM TEST STANDARD 43
4.7.6 EUT OPERATING CONDITION 43
4.7.7 TEST RESULTS 44
4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT 45
4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT 45
4.8.2 TEST INSTRUMENTS 45
4.8.3 TEST PROCEDURE 45
4.8.4 DEVIATION FROM TEST STANDARD 45
4.8.5 EUT OPERATING CONDITION 45
4.8.6 TEST RESULTS 45
5. TEST TYPES AND RESULTS (FOR BLUETOOTH LE 4.0) 49
5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 49
5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 49
5.1.2 TEST INSTRUMENTS 49
5.1.3 TEST PROCEDURES 50
5.1.4 DEVIATION FROM TEST STANDARD 50
5.1.5 TEST SETUP 51
5.1.6 EUT OPERATING CONDITIONS 51
5.1.7 TEST RESULTS 52
5.2 CONDUCTED EMISSION MEASUREMENT 57
5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 57
5.2.2 T EST INSTRUMENTS 57
5.2.3 TEST PROCEDURES 57
5.2.4 DEVIATION FROM TEST STANDARD 57
5.2.5 TEST SETUP 57
5.2.6 EUT OPERATING CONDITIONS 57
5.2.7 TEST RESULTS 58
5.3 6dB BANDWIDTH MEASUREMENT 60
5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 60
5.3.2 TEST SETUP 60
5.3.3 TEST INSTRUMENTS 60
5.3.4 TEST PROCEDURE 60
5.3.5 DEVIATION FROM TEST STANDARD 60
5.3.6 EUT OPERATING CONDITIONS 60
5.3.7 TEST RESULTS 61
5.4 CONDUCTED OUTPUT POWER 62
5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT 62
5.4.2 TEST SETUP 62
5.4.3 INSTRUMENTS 62
5.4.4 TEST PROCEDURES 62
5.4.5 DEVIATION FROM TEST STANDARD 62
5.4.6 EUT OPERATING CONDITIONS 62
5.4.7 TEST RESULTS 62
5.5 POWER SPECTRAL DENSITY MEASUREMENT 63
5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 63

5.5.2 TEST SETUP 63
5.5.3 TEST INSTRUMENTS 63
5.5.4 TEST PROCEDURE. 63
5.5.5 DEVIATION FROM TEST STANDARD 63
5.5.6 EUT OPERATING CONDITION 63
5.5.7 TEST RESULTS 64
5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT 65
5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 65
5.6.2 TEST SETUP 65
5.6.3 TEST INSTRUMENTS 65
5.6.4 TEST PROCEDURE 65
5.6.5 DEVIATION FROM TEST STANDARD 65
5.6.6 EUT OPERATING CONDITION 65
5.6.7 TEST RESULTS 66
6. PHOTOGRAPHS OF THE TEST CONFIGURATION 67
7. INFORMATION ON THE TESTING LABORATORIES 68
8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 69

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140312C10-3	Original release	Jul. 25, 2014

1. CERTIFICATION

PRODUCT:	Tablet PC
MODEL NO.:	N435
BRAND:	Mio ; Mitac ; Code ; Janam ; Stryker
APPLICANT:	MiTAC International Corp.
TESTED:	Jul. 04, 2014 ~ Jul. 21, 2014
TEST SAMPLE:	Production Unit
STANDARDS:	**FCC Part 15, Subpart C (Section 15.247)**
	ANSI C63.10-2009

The above equipment (model: N435) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ **, DATE :** Jul. 25, 2014

Ivonne Wu / Supervisor

APPROVED BY : _____ **, DATE :** Jul. 25, 2014

Sam Chen / Senior Project Engineer

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Bluetooth EDR)			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.91dB at 0.20078MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -12.52dB at 2498.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) (Bluetooth LE 4.0)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.06dB at 0.51328MHz.
15.205 & 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -7.36dB at 138.81MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Tablet PC	
MODEL NO.	N435	
POWER SUPPLY	5Vdc (adapter) 3.7Vdc (Li-ion battery)	
MODULATION TYPE	**Bluetooth EDR**	GFSK, π/4-DQPSK, 8DPSK
	Bluetooth LE 4.0	GFSK
TRANSFER RATE	**Bluetooth EDR**	1/2/3Mbps
	Bluetooth LE 4.0	1Mbps
OPERATING FREQUENCY	2402 ~ 2480MHz	
NUMBER OF CHANNEL	**Bluetooth EDR**	79
	Bluetooth LE 4.0	40
CHANNEL SPACING	**Bluetooth EDR**	1MHz
	Bluetooth LE 4.0	2MHz
OUTPUT POWER	**Bluetooth EDR**	1.648mW
	Bluetooth LE 4.0	1.690mW
ANTENNA TYPE	PCB antenna with 3.3dBi gain	
ANTENNA CONNECTOR	NA	
DATA CABLE	Refer to Note as below	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Refer to Note as below	

NOTE:

1. The EUT contains following accessory devices.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter 1	TPT	MII050200	I/P: 100-240Vac, 50-60Hz, 0.3A O/P: 5Vdc, 2A
Adapter 2	SINPRO	MPU16A-102	I/P: 100-240Vac, 47-63Hz, 0.33-0.18A O/P: 5Vdc, 2.6A
Battery	Tian Yu	SJS3060	3.7Vdc, 3060mAh
BCR Scanner 1 (2D LED)	Honeywell	N5600, N56X3, N56X0, N5603	--
BCR Scanner 2 (2D)	Code	CR8012	--
BCR Scanner 3 (1D)	Opticon	MDL-2XXX : MSL-2XXX	--
BCR Scanner 4 (2D Laser)	Honeywell	N5603, N56X3	--
LCD Panel	TIANME	TM059YDH01	5.88 inch
Front Camera	LITE-ON	10P2SA511	--
Rear Camera	LITE-ON	10P2SF130	--
WLAN, BT Module	Jorjin	WG7833-B0 & WX7833-B0	--

2. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Bluetooth EDR:

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Bluetooth LE 4.0:

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

BLUETOOTH EDR

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Tablet w/ 2D Laser Honeywell Scanner + Adapter 1
B	-	√	-	-	Tablet w/ 2D Laser Honeywell Scanner + Adapter 2

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: 1. For Radiated emission test, pre-tested GFSK, π/4-DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.

2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane.**

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A, B	0 to 78	78	GFSK	DH5

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	78	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	GFSK	DH5
A	0 to 78	0, 39, 78	π/4-DQPSK	DH5
A	0 to 78	0, 39, 78	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Will Chen
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Will Chen
PLC	25deg. C, 65%RH	120Vac, 60Hz	Gavin Wu
APCM	25deg. C, 65%RH	120Vac, 60Hz	David Huang

BLUETOOTH LE 4.0:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Tablet w/ 2D Laser Honeywell Scanner + Adapter 1
B	-	√	-	-	Tablet w/ 2D Laser Honeywell Scanner + Adapter 2

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane.**

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A	0 to 39	0, 19, 39	GFSK	1.0

RADIATED EMISSION TEST (BELOW 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A, B	0 to 39	39	GFSK	1.0

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A	0 to 39	39	GFSK	1.0

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A	0 to 39	0, 19, 39	GFSK	1.0

Test CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Will Chen
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Will Chen
PLC	25deg. C, 65%RH	120Vac, 60Hz	Gavin Wu
APCM	25deg. C, 65%RH	120Vac, 60Hz	David Huang

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Earphone	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

NOTE: 1. All power cords of the above support units are non shielded (1.8m).

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2009
558074 D01 DTS Meas Guidance v03r01
FCC Public Notice DA 00-705

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS (FOR BLUETOOTH EDR)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 15, 2014	Apr. 14, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2013	Dec. 20, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 27. 2014	Feb. 26, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 19, 2014	Feb. 18, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 18, 2013	Dec. 17, 2014
Loop Antenna	HFH2-Z2	100070	Mar. 06, 2014	Mar. 05, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Bluetooth Tester	CBT	100980	Apr. 18, 2013	Apr. 17, 2015
Power Meter	ML2495A	1232002	Aug. 23, 2013	Aug. 22, 2014
Power Sensor	MA2411B	1207325	Aug. 23, 2013	Aug. 22, 2014

NOTE:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 10.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 690701.
6. The IC Site Registration No. is IC 7450F-10.

4.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Frequency Range 30MHz ~ 1GHz



Frequency Range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Placed the EUT on a testing table.

b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

GFSK

MODE A

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2378	39.59	37.93	54	-14.41	31.78	5.37	35.49	134	54	Average
2378	53.16	51.5	74	-20.84	31.78	5.37	35.49	134	54	Peak
2402	98.38	96.65			31.8	5.4	35.47	134	54	Average
2402	101.02	99.29			31.8	5.4	35.47	134	54	Peak
2494	39.95	37.93	54	-14.05	31.9	5.53	35.41	134	54	Average
2494	52.25	50.23	74	-21.75	31.9	5.53	35.41	134	54	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2322	39.31	37.8	54	-14.69	31.73	5.3	35.52	137	213	Average
2322	52.1	50.59	74	-21.9	31.73	5.3	35.52	137	213	Peak
2402	94.85	93.12			31.8	5.4	35.47	137	213	Average
2402	97.47	95.74			31.8	5.4	35.47	137	213	Peak
2492	39.99	37.97	54	-14.01	31.9	5.53	35.41	137	213	Average
2492	52.24	50.22	74	-21.76	31.9	5.53	35.41	137	213	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2402MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2340	39.35	37.78	54	-14.65	31.74	5.33	35.5	132	51	Average
2340	51.45	49.88	74	-22.55	31.74	5.33	35.5	132	51	Peak
2441	98.84	96.97			31.85	5.46	35.44	132	51	Average
2441	101.48	99.61			31.85	5.46	35.44	132	51	Peak
2484	39.95	37.99	54	-14.05	31.88	5.5	35.42	132	51	Average
2484	52.76	50.8	74	-21.24	31.88	5.5	35.42	132	51	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2326	39.31	37.8	54	-14.69	31.73	5.3	35.52	105	247	Average
2326	52.05	50.54	74	-21.95	31.73	5.3	35.52	105	247	Peak
2441	95.59	93.72			31.85	5.46	35.44	105	247	Average
2441	98.24	96.37			31.85	5.46	35.44	105	247	Peak
2498	39.98	37.96	54	-14.02	31.9	5.53	35.41	105	247	Average
2498	52.27	50.25	74	-21.73	31.9	5.53	35.41	105	247	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2441MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2352	39.35	37.76	54	-14.65	31.76	5.33	35.5	148	170	Average
2352	51.53	49.94	74	-22.47	31.76	5.33	35.5	148	170	Peak
2480	99.12	97.16			31.88	5.5	35.42	148	170	Average
2480	101.8	99.84			31.88	5.5	35.42	148	170	Peak
2498	41.48	39.46	54	-12.52	31.9	5.53	35.41	148	170	Average
2498	52.72	50.7	74	-21.28	31.9	5.53	35.41	148	170	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2342	39.33	37.76	54	-14.67	31.74	5.33	35.5	103	273	Average
2342	51.31	49.74	74	-22.69	31.74	5.33	35.5	103	273	Peak
2480	96.22	94.26			31.88	5.5	35.42	103	273	Average
2480	98.88	96.92			31.88	5.5	35.42	103	273	Peak
2484	40.51	38.55	54	-13.49	31.88	5.5	35.42	103	273	Average
2484	53.72	51.76	74	-20.28	31.88	5.5	35.42	103	273	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2480MHz: Fundamental frequency.

BELOW 1GHz WORST-CASE DATA:

MODE A

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
130.44	9.65	31.3	43.5	-33.85	9.2	1.38	32.23	163	227	Peak
197.67	25.66	45.55	43.5	-17.84	10.79	1.61	32.29	169	216	Peak
268.14	20.2	36.83	46	-25.8	13.54	1.94	32.11	174	214	Peak
470.1	19.68	30.53	46	-26.32	18.72	2.56	32.13	141	217	Peak
603.8	22.38	30.46	46	-23.62	21.24	2.87	32.19	162	236	Peak
800.5	25.76	29.9	46	-20.24	24.6	3.32	32.06	165	275	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
130.17	15.45	37.1	43.5	-28.05	9.2	1.38	32.23	114	215	Peak
235.2	21.01	38.95	46	-24.99	12.36	1.85	32.15	169	236	Peak
282.99	23.46	39.78	46	-22.54	13.77	2.03	32.12	174	212	Peak
513.5	20.87	30.35	46	-25.13	19.94	2.7	32.12	162	341	Peak
635.3	23.74	30.87	46	-22.26	22.1	2.93	32.16	175	113	Peak
937.7	29.12	30.5	46	-16.88	26.2	3.62	31.2	142	221	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

MODE B

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	**FREQUENCY RANGE**	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	**DETECTOR FUNCTION**	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	**TESTED BY**	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
138.54	24.06	45.67	43.5	-19.44	9.28	1.38	32.27	136	215	Peak
220.35	27.72	46.57	46	-18.28	11.72	1.65	32.22	174	258	Peak
252.75	27.16	44.24	46	-18.84	13.08	1.94	32.1	147	248	Peak
482.7	19.39	30.01	46	-26.61	18.93	2.56	32.11	168	247	Peak
671.7	25.27	30.94	46	-20.73	23.4	3.05	32.12	149	263	Peak
803.3	26.54	30.66	46	-19.46	24.6	3.32	32.04	134	217	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
96.96	22.51	43.87	43.5	-20.99	9.46	1.28	32.1	185	241	Peak
130.44	18.08	39.73	43.5	-25.42	9.2	1.38	32.23	167	234	Peak
219.81	22.48	41.38	46	-23.52	11.67	1.65	32.22	134	116	Peak
534.5	21.09	30.04	46	-24.91	20.52	2.7	32.17	162	317	Peak
707.4	26.23	32.03	46	-19.77	23.19	3.11	32.1	174	275	Peak
896.4	27.74	30.76	46	-18.26	25	3.49	31.51	134	294	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

Tested Date: Jul. 17, 2014

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Apr. 24, 2014	Apr. 23, 2015
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 23, 2013	Dec. 22, 2014
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 10, 2014	Jul. 09, 2015
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA：

PHASE	Line 1	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18906	0.28	50.23	32.08	50.51	32.36	64.08	54.08	-13.57	-21.72
2	0.20078	0.28	50.39	36.49	50.67	36.77	63.58	53.58	-12.91	-16.81
3	0.25156	0.29	41.35	20.26	41.64	20.55	61.71	51.71	-20.07	-31.16
4	0.31797	0.29	38.29	20.27	38.58	20.56	59.76	49.76	-21.18	-29.20
5	0.44297	0.30	36.59	17.23	36.89	17.53	57.01	47.01	-20.11	-29.47
6	0.60313	0.31	35.90	20.58	36.21	20.89	56.00	46.00	-19.79	-25.11

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Line 2	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18906	0.28	46.93	29.57	47.21	29.85	64.08	54.08	-16.87	-24.23
2	0.25938	0.29	40.26	26.27	40.55	26.56	61.45	51.45	-20.91	-24.90
3	0.39609	0.30	39.27	27.69	39.57	27.99	57.93	47.93	-18.37	-19.95
4	0.49766	0.31	38.69	23.48	39.00	23.79	56.04	46.04	-17.04	-22.25
5	0.63438	0.32	38.80	27.24	39.12	27.56	56.00	46.00	-16.88	-18.44
6	0.94688	0.34	37.31	22.89	37.65	23.23	56.00	46.00	-18.35	-22.77

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
d. Set the SA on View mode and then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plot, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 1 MHz
VBW 1 MHz
SWT 500 ms
[T1] MP MAXH
[T2] MP VIEW
Ref 25 dBm
Att 20 dB
Offset 15 dB
25
20
10
0
-10
-20
-30
-40
-50
-60
-70
-75
Start 2.4 GHz
4.1 MHz/
Stop 2.441 GHz


RBW 1 MHz
VBW 1 MHz
SWT 500 ms
[T1] MP MAXH
[T2] MP VIEW
Ref 25 dBm
Att 20 dB
Offset 15 dB
25
20
10
0
-10
-20
-30
-40
-50
-60
-70
-75
Start 2.441 GHz
4.25 MHz/
Stop 2.4835 GHz

4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMITS OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 TEST RESULTS

GFSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.20	456.73	0.15	0.4
DH3	5.00	1698.72	0.27	0.4
DH5	3.40	2956.73	0.32	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.

DH1





DH3





DH5





π/4-DQPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.00	437.50	0.14	0.4
DH3	5.40	1690.71	0.29	0.4
DH5	3.20	2988.78	0.30	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.

DH1





DH3





DH5





8DPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.20	519.23	0.17	0.4
DH3	5.40	1714.74	0.29	0.4
DH5	3.20	2972.76	0.30	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.

DH1





DH3





DH5





4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)		
		GFSK	π/4-DQPSK	8DPSK
0	2402	0.888	1.29	1.29
39	2441	0.893	1.29	1.29
78	2480	0.895	1.29	1.29

SPECTRUM PLOT OF WORST VALUE

GFSK



π/4-DQPSK



8DPSK



4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMITS OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 TEST RESULTS

CHAN.	FREQ. (MHz)	ADJACENT CHANNEL SEPARATION (MHz)			20dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)			PASS / FAIL
		GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK	
0	2402	1.01	1.01	1.00	0.888	1.29	1.29	0.592	0.860	0.860	PASS
39	2441	1.01	1.00	1.00	0.893	1.29	1.29	0.595	0.860	0.860	PASS
78	2480	1.00	1.00	1.00	0.895	1.29	1.29	0.597	0.860	0.860	PASS

NOTE:

1. The minimum limit is two-third 20dB bandwidth.

SPECTRUM PLOT OF WORST VALUE

GFSK



π/4-DQPSK



8DPSK



4.7 MAXIMUM OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.7.2 TEST SETUP



4.7.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.7.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
d. Measure the captured power within the band and recording the plot.
e. Repeat above procedures until all frequencies required were complete.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)			OUTPUT POWER (dBm)			POWER LIMIT (mW)	PASS / FAIL
		GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK		
0	2402	1.648	0.356	0.416	2.17	-4.49	-3.81	125	PASS
39	2441	1.455	0.324	0.374	1.63	-4.90	-4.27	125	PASS
78	2480	1.371	0.353	0.351	1.37	-4.52	-4.55	125	PASS

SPECTRUM PLOT OF WORST VALUE

GFSK



π/4-DQPSK



8DPSK



4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.8.3 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set VBW =300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit continuously.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel



Hopping enabled_ High Channel



π/4-DQPSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel



Hopping enabled_ High Channel



8DPSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel



Hopping enabled_ High Channel



5. TEST TYPES AND RESULTS (FOR BLUETOOTH LE 4.0)

5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

5.1.2 TEST INSTRUMENTS

Same as section 4.1.2.

5.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

5.1.6 EUT OPERATING CONDITIONS

a. Placed the EUT on a testing table.

b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.

5.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

MODE A

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2366	41.59	39.95	54	-12.41	31.76	5.37	35.49	162	256	Average
2366	56.26	54.62	74	-17.74	31.76	5.37	35.49	162	256	Peak
2402	105.38	103.65			31.8	5.4	35.47	162	256	Average
2402	106.25	104.52			31.8	5.4	35.47	162	256	Peak
2492	41.55	39.53	54	-12.45	31.9	5.53	35.41	162	256	Average
2492	55.7	53.68	74	-18.3	31.9	5.53	35.41	162	256	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2332	43.22	41.68	54	-10.78	31.73	5.33	35.52	140	258	Average
2332	55.98	54.44	74	-18.02	31.73	5.33	35.52	140	258	Peak
2402	96.84	95.11			31.8	5.4	35.47	140	258	Average
2402	97.72	95.99			31.8	5.4	35.47	140	258	Peak
2494	41.65	39.63	54	-12.35	31.9	5.53	35.41	140	258	Average
2494	55.68	53.66	74	-18.32	31.9	5.53	35.41	140	258	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2402MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 19	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2338	41.24	39.69	54	-12.76	31.74	5.33	35.52	161	258	Average
2338	57.1	55.55	74	-16.9	31.74	5.33	35.52	161	258	Peak
2440	105.13	103.28			31.85	5.46	35.46	161	258	Average
2440	105.93	104.08			31.85	5.46	35.46	161	258	Peak
2484	41.79	39.83	54	-12.21	31.88	5.5	35.42	161	258	Average
2484	56.24	54.28	74	-17.76	31.88	5.5	35.42	161	258	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2330	40.96	39.42	54	-13.04	31.73	5.33	35.52	141	271	Average
2330	55.9	54.36	74	-18.1	31.73	5.33	35.52	141	271	Peak
2440	97.07	95.22			31.85	5.46	35.46	141	271	Average
2440	97.87	96.02			31.85	5.46	35.46	141	271	Peak
2486	41.64	39.65	54	-12.36	31.88	5.53	35.42	141	271	Average
2486	55.89	53.9	74	-18.11	31.88	5.53	35.42	141	271	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2440MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2388	41.37	39.66	54	-12.63	31.8	5.4	35.49	154	258	Average
2388	55.7	53.99	74	-18.3	31.8	5.4	35.49	154	258	Peak
2480	104.21	102.25			31.88	5.5	35.42	154	258	Average
2480	105.11	103.15			31.88	5.5	35.42	154	258	Peak
2484	43.88	41.92	54	-10.12	31.88	5.5	35.42	154	258	Average
2484	56.85	54.89	74	-17.15	31.88	5.5	35.42	154	258	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2378	40.93	39.27	54	-13.07	31.78	5.37	35.49	141	256	Average
2378	56.45	54.79	74	-17.55	31.78	5.37	35.49	141	256	Peak
2480	96.57	94.61			31.88	5.5	35.42	141	256	Average
2480	97.49	95.53			31.88	5.5	35.42	141	256	Peak
2490	42.35	40.34	54	-11.65	31.9	5.53	35.42	141	256	Average
2490	56.46	54.45	74	-17.54	31.9	5.53	35.42	141	256	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2480MHz: Fundamental frequency.

BELOW 1GHz WORST-CASE DATA：

MODE A

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	**FREQUENCY RANGE**	30MHz ~ 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION**	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	**TESTED BY**	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
89.94	14.48	36.18	43.5	-29.02	8.9	1.11	31.71	116	167	Peak
138.81	36.14	57.74	43.5	-7.36	9.29	1.38	32.27	146	275	Peak
250.32	27.25	44.5	46	-18.75	13	1.85	32.1	162	223	Peak
318.2	18.53	33.68	46	-27.47	14.85	2.11	32.11	145	211	Peak
608.7	22.51	30.44	46	-23.49	21.39	2.87	32.19	167	197	Peak
715.8	25.37	31.1	46	-20.63	23.27	3.11	32.11	184	231	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
76.71	13.47	36.28	40	-26.53	8.3	1.11	32.22	132	249	Peak
137.19	25.45	47.05	43.5	-18.05	9.28	1.38	32.26	181	112	Peak
264.36	21.84	38.6	46	-24.16	13.41	1.94	32.11	163	277	Peak
478.5	19.7	30.35	46	-26.3	18.91	2.56	32.12	169	279	Peak
622	22.99	30.27	46	-23.01	21.96	2.93	32.17	132	222	Peak
831.3	25.8	30.71	46	-20.2	23.6	3.38	31.89	111	49	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

MODE B

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Will Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
89.4	17	38.77	43.5	-26.5	8.88	1.11	31.76	174	249	Peak
218.73	27.97	46.91	46	-18.03	11.63	1.65	32.22	114	132	Peak
280.56	22.7	39.04	46	-23.3	13.75	2.03	32.12	164	216	Peak
463.8	18.98	30.01	46	-27.02	18.54	2.56	32.13	134	276	Peak
629	22.57	29.71	46	-23.43	22.1	2.93	32.17	139	218	Peak
928.6	28.6	30.05	46	-17.4	26.2	3.62	31.27	175	123	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
66.99	18.58	42.17	40	-21.42	7.73	0.9	32.22	136	217	Peak
138.54	29.31	50.92	43.5	-14.19	9.28	1.38	32.27	157	249	Peak
273.27	23.96	40.47	46	-22.04	13.66	1.94	32.11	167	214	Peak
412.7	17.53	29.44	46	-28.47	17.88	2.41	32.2	134	275	Peak
600.3	21.92	30.14	46	-24.08	21.1	2.87	32.19	169	246	Peak
874	27.05	30.46	46	-18.95	24.8	3.44	31.65	152	178	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

5.2 CONDUCTED EMISSION MEASUREMENT

5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

Same as section 4.2.1.

5.2.2 T EST INSTRUMENTS

Same as section 4.2.2.

5.2.3 TEST PROCEDURES

Same as section 4.2.3.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

5.2.5 TEST SETUP

Same as section 4.2.5.

5.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

5.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA：

PHASE	Line 1	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19687	0.28	46.16	33.01	46.44	33.29	63.74	53.74	-17.30	-20.45
2	0.25938	0.29	39.19	24.78	39.48	25.07	61.45	51.45	-21.98	-26.39
3	0.43125	0.30	33.89	14.95	34.19	15.25	57.23	47.23	-23.04	-31.98
4	0.50938	0.31	36.96	22.98	37.27	23.29	56.00	46.00	-18.73	-22.71
5	0.72031	0.32	33.66	18.62	33.98	18.94	56.00	46.00	-22.02	-27.06
6	0.98203	0.34	30.62	15.15	30.96	15.49	56.00	46.00	-25.04	-30.51

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Line 2	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19297	0.28	47.18	33.09	47.46	33.37	63.91	53.91	-16.45	-20.54
2	0.25938	0.29	39.17	26.20	39.46	26.49	61.45	51.45	-22.00	-24.97
3	0.41953	0.30	40.30	26.92	40.60	27.22	57.46	47.46	-16.86	-20.24
4	0.51328	0.31	41.63	28.10	41.94	28.41	56.00	46.00	-14.06	-17.59
5	0.64609	0.32	38.12	24.55	38.44	24.87	56.00	46.00	-17.56	-21.13
6	0.96250	0.34	35.81	23.16	36.15	23.50	56.00	46.00	-19.85	-22.50

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

5.3.2 TEST SETUP



5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.3.4 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

5.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (KHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	715.37	0.5	PASS
19	2440	718.79	0.5	PASS
39	2480	711.95	0.5	PASS

SPECTRUM PLOT OF WORST VALUE



5.4 CONDUCTED OUTPUT POWER

5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt (30dBm).

5.4.2 TEST SETUP



5.4.3 INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

5.4.6 EUT OPERATING CONDITIONS

Same as section 4.3.6.

5.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	1.690	2.28	30	PASS
19	2440	1.626	2.11	30	PASS
39	2480	1.652	2.18	30	PASS

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST SETUP



5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.5.4 TEST PROCEDURE.

a. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

5.5.6 EUT OPERATING CONDITION

Same as section 4.3.6.

5.5.7 TEST RESULTS

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS / FAIL
0	2402	-15.53	8	PASS
19	2440	-15.60	8	PASS
39	2480	-15.25	8	PASS

SPECTRUM PLOT OF WORST VALUE



5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST SETUP

5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Ensure that the number of measurement points ≥ span/RBW
4. According to measurement points to set differ measurement span.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.

5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

5.6.6 EUT OPERATING CONDITION

Same as section 4.3.6.

5.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

CH 0





CH 19





CH 39





6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---