

RF EXPOSURE EVALUATION

EUT Specification

EUT	The Tablet
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☐ Others(Bluetooth: 2.402GHz ~ 2.480GHz
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others ____
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	7.39dBm (5.48mW, Max. AVG output power)
Antenna gain	1.5 dBi
Evaluation applied	☐ MPE Evaluation ☒ SAR Evaluation

Standard Requirement

Portable Device

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output AVG power (dBm)	Max Output AVG power (mW)	Calculation Value ^(Note 1)	Threshold Value
WIFI (802.11b)					
Low	2412	6.23	4.20	1.305	3.0
Middle	2437	7.39	5.48	1.711	3.0
High	2462	6.76	4.76	1.494	3.0
WIFI (802.11g)					
Low	2412	2.38	1.73	0.537	3.0
Middle	2437	2.01	1.59	0.496	3.0
High	2462	1.65	1.46	0.458	3.0
WIFI [802.11n(HT20)]					
Low	2412	1.95	1.57	0.488	3.0
Middle	2437	1.84	1.53	0.478	3.0
High	2462	1.54	1.43	0.449	3.0

Note 1: Calculation Value = [(max. power of channel, mW)/(min. test separation distance, mm)] • [√ f(GHz)].
 Fox example: $4.20/5 \cdot \sqrt{2.412} = 1.305 \leq 3.0$

According to KDB447498 D01 v05, threshold at which no SAR required is ≤ 3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.