

8

7

6

5

4

3

2

1

PROPRIETARY NOTICE
THIS DOCUMENT AND THE INFORMATION DISCLOSED HEREIN ARE PROPRIETARY DATA OF HONEYWELL INC. NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED HEREIN SHALL BE REPRODUCED, USED, OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF HONEYWELL INC.

NOTICE
FREEDOM OF INFORMATION ACT (5 USC 552) AND DISCLOSURE OF CONFIDENTIAL INFORMATION GENERALLY (18 USC 1905)
THIS DOCUMENT IS BEING FURNISHED IN CONFIDENCE BY HONEYWELL INC. THE INFORMATION DISCLOSED HEREIN FALLS WITHIN EXEMPTION (b) (4) OF 5 USC 552 AND THE PROHIBITIONS OF 18 USC 1905.

REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED
	—	INITIAL RELEASE	27 JUN00	R.BACULA
	A	SH IDX REV. PL AFFECTED. 26232 (NA)	03 OCT 00	L. KEEFER R. RICHARDS
	B	TABLES: TABLE II: COND NO. 607 TO CIRCUIT POINT WAS U86-2. SH IDX REV. PL NOT AFFECTED. 26223 (NA)	13 NOV 00	J. OLSON

TABLE I
CUT RUN DATA

CUT NO.	PWB SIDE	FROM CIRCUIT POINT	TO CIRCUIT POINT
1	B	U57-28 LAND	U57-28 PROBE PAD
2	B	U57-33 LAND	U57-33 PROBE PAD
3	B	U85-19 LAND	U85-19 PROBE PAD
4	B	U86-1 LAND	U86-1 PROBE PAD
5	B	U86-2 LAND	U86-2 PROBE PAD
6	B	U86-3 LAND	U86-3 PROBE PAD
7	B	U86-6 LAND	U86-6 PROBE PAD
8	B	U24-9 LAND	U24-9 PROBE PAD
9	B	U24-12 LAND	U24-12 PROBE PAD
10	B	U24-14 LAND	U24-14 PROBE PAD
11	B	U24-16 LAND	U24-16 PROBE PAD

TABLE II
BUSWIRE DATA

CONDUCTOR		PWB SIDE	FROM CIRCUIT POINT	TO CIRCUIT POINT
COND. NO.	ITEM NO.			
601	702	B	U57-33	U57-34
602	702	B	U75-1	U78-20
603	702	B	U12-25	J1-60
604	702	B	U11-31	J1-58
605	702	B	U45-24	J1-62
606	702	B	U55-49	J1-44
607	702	B	U86-6	U85-2
608	702	B TO A	U86-1	J1-39
609	702	B TO A	U86-2	J1-49
610	702	B TO A	U86-3	J1-54
611	702	B TO A	R19 RT PROBE PAD	J1-65

NOTES:

1. ASSEMBLE PER ITEM 701.

2.

CAUTION
ELECTROSTATIC SENSITIVE EQUIPMENT
SPECIAL HANDLING REQUIRED

THIS ASSEMBLY INCLUDES COMPONENTS WHICH ARE SUBJECT TO DAMAGE BY ELECTROSTATIC CHARGES; THEREFORE, ALL COMPONENTS SHALL BE HANDLED IN ACCORDANCE WITH GUIDELINES FOR ELECTROSTATIC DISCHARGE CONTROL.

3. REWORK CCA (ITEM 1) PER TABLE I AND II.

4. MAKE CUTS PER TABLE I, LEFT OR RIGHT, TOP OR BOTTOM AS VIEWED FROM INDICATED SIDE.

5. INSTALL BUS WIRES PER TABLE II, LEFT OR RIGHT, TOP OR BOTTOM AS VIEWED FROM INDICATED SIDE.

6. REMOVE C63, R20 AND R24.

7. REPLACE R27 WITH ITEM 51.

8. CUT PIN 42 OF U57.

REV STATUS OF PARTS LIST SHALL BE SAME AS BASIC DRAWING NUMBER SEE SEPARATE PARTS LIST

CONTRACT		SHEET INDEX		OPERATIONAL NOTE	
TCAS II				SIMILAR ASSEMBLY	
DRAWN BY	DATE	DRAWN BY	DATE		
J. OLSON	15 JUN00	J. OLSON	15 JUN00		
DESIGNED BY	DATE	CHECKED BY	DATE	TITLE	
		E. THIESSEN	15 JUN00	ALTERED CARD ASSEMBLY-PROCESSOR	
APVD FOR MFG	DATE	APVD FOR ENGRG	DATE	SIZE	CAGE CODE
J. DEBERNARDIS	15 JUN00	L. KEEFER	15 JUN00	E	55939
APVD FOR GE	DATE	APVD FOR ENGRG	DATE	DRAWING NO.	REV
				4066019-913	B
APVD FOR	DATE	APVD FOR	DATE	SCALE	UNIT
				NONE	WT

4066019-913

1

5231-040 (ANSI Y14.1-1980) HONEYWELL INC. (REV 3-87)

7

6

5

4

3

2

1

COMPUTER GENERATED

NOV 08 2000 jolson 10:26:10