



SAR EVALUATION REPORT

Report No. : 25DE0080-HO-3A

Applicant : KODAK DIGITAL PRODUCT CENTER, JAPAN LTD
Type of Equipment : Kodak Wi-Fi card
Model No. : 3F8508
FCC ID : PA4050449
Test standard : FCC47CFR 2.1093
FCC OET Bulletin 65, Supplement C
Test Result : Complied
Max SAR Measured : 0.616W/kg (Body, 2412MHz)

1. This test report shall not be reproduced except full or partial, without the written approval of UL Apex Co., Ltd.
2. The results in this report apply only to the sample tested.
3. This equipment is in compliance with above regulation. We hereby certify that the data contain a true representation of the SAR profile.
4. The test results in this test report are traceable to the national or international standards.

Date of test : February 02 and 08, 2005

Tested by : 
Miyo Ikuta
EMC Lab.Head Office

Approved by : 
Tetsuo Maeno
Site Manager of Head Office EMC Lab.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

<u>CONTENTS</u>	PAGE
SECTION 1 : Client information.....	3
SECTION 2 : Equipment under test	4
SECTION 3 : Requirements for compliance testing defined by the FCC	6
SECTION 4 : Dosimetry assessment setup	6
SECTION 5 : Test system specifications.....	10
SECTION 6 : Measurement outline	11
SECTION 7 : Test setup of EUT	12
SECTION 8 : Measurement uncertainty	16
SECTION 9 : Simulated tissue liquid parameter.....	17
SECTION 10 : System validation data.....	18
SECTION 11 : Evaluation procedure	19
SECTION 12 : Exposure limit	20
SECTION 13 : SAR Measurement results.....	21
SECTION 14 : Equipment & calibration information	23
SECTION 15 : References.....	24
APPENDIX 1 : Photographs of test setup	25
APPENDIX 2 : SAR Measurement Reference data (Head).....	35
APPENDIX 3 : SAR Measurement data (Body)	44
APPENDIX 4 : Validation Measurement data.....	57
APPENDIX 5 : System Validation Dipole (D2450V2,S/N: 713).....	60
APPENDIX 6 : Dosimetric E-Field Probe Calibration (ET3DV6,S/N: 1684).....	72

SECTION 1 : Client information

Company Name : KODAK DIGITAL PRODUCT CENTER, JAPAN LTD
Brand Name : KODAK
Address : Yokohama Dia Building Kohhokukan, 1-1, Sakuranamiki, Tsuzuki-ku,
Yokohama-shi, Kanagawa 221-0046 Japan
Telephone Number : 81-45-943-7560
Facsimile Number : 81-45-943-7604
Contact Person : Koji Matsumoto

SECTION 2 : Equipment under test

2.1 Identification of Wi-Fi card

This EUT has IEEE 802.11b wireless LAN function with SD card interface.

Applicant : KODAK DIGITAL PRODUCT CENTER, JAPAN LTD

Type of Equipment : Kodak Wi-Fi card

Model No. : 3F8508

Serial No. : NO.1C

Country of Manufacture : Japan

Receipt Date of Sample : January 29, 2005

Condition of EUT : Production prototype
(Not for sale: This sample is equivalent to mass-produced items.)

Size : 24 * 40 * 2.1 mm (W*L*H)

Category Identified : Portable device

2.2 Product description of Wi-Fi card

Tx Frequency : 2412MHz~2462MHz
Modulation : DSSS: Direct sequence spread spectrum (IEEE802.11b)
Rating : DC 3.3V / 0.39A
Max.Output Power Tested : 18.76 dBm Peak Conducted
Antenna Type : Inverted F type
Antenna Gain : Max 2.1dBi

Wi-Fi card



SECTION 3 : Requirements for compliance testing defined by the FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

1 Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).

2 IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

SECTION 4 : Dosimetry assessment setup

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than +/- 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetry probe ET3DV6, SN: 1684 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [2] with accuracy of better than +/-10%. The spherical isotropy was evaluated with the procedure described in [3] and found to be better than +/-0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE P1528 and CENELEC EN50361.

UL Apex Co., Ltd.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

4.1 Configuration and peripherals



The DASY4 system for performing compliance tests consist of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software.
An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE), which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection.
The EOC is connected to the measurement server.
5. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
6. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
7. A computer operating Windows 2000.
8. DASY4 software.
9. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
10. The SAM twin phantom enabling testing left-hand and right-hand usage.
11. The device holder for handheld mobile phones.
12. Tissue simulating liquid mixed according to the given recipes.
13. Validation dipole kits allowing to validate the proper functioning of the system.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

4.2 System components

4.2.1 ET3DV6 Probe Specification

Construction:

Symmetrical design with triangular core
Built-in optical fiber for surface detection System
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g., glycol ether)

Calibration:

Basic Broad Band calibration in air from 10 MHz to 2.5 GHz
In brain and muscle simulating tissue at
Frequencies of 450 MHz, 900 MHz, 1.8 GHz and 2.45GHz (accuracy +/-8%)

Frequency:

10 MHz to 3GHz; Linearity: +/-0.2 dB
(30 MHz to 3 GHz)

Directivity:

+/-0.2 dB in brain tissue (rotation around probe axis)
+/-0.4 dB in brain tissue (rotation normal probe axis)

Dynamic Range:

5 mW/g to > 100 mW/g; Linearity: +/-0.2 dB

Optical Surface Detection:

+/-0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces.

Dimensions:



Overall length: 330 mm (Tip: 16 mm)
Tip length: 16 mm
Body diameter: 12 mm (Body: 12 mm)

Tip diameter: 6.8 mm

Distance from probe tip to dipole centers: 2.7 mm

Application:

General dosimetric up to 3 GHz
Compliance tests of mobile phones
Fast automatic scanning in arbitrary phantoms



ET3DV6 E-field Probe

4.2.2 SAM Phantom

Construction:

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC EN 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness:


2 +/-0.2 mm

Filling Volume:

Approx. 25 liters

Dimensions:

(H x L x W): 810 x 1000 x 500 mm



SAM Phantom

4.2.3 Device Holder for Transmitters

In combination with the SAM Twin Phantom V4.0, the Mounting Device enables the rotation of the mounted transmitter

in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations.

To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



Device Holder

Device holder couldn't be used at this SAR measurement.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 5 : Test system specifications

Robot RX60L

Number of Axes	:	6
Payload	:	1.6 kg
Reach	:	800mm
Repeatability	:	+/-0.025mm
Control Unit	:	CS7M
Programming Language	:	V+
Manuafacture	:	Stäubli Unimation Corp. Robot Model: RX60

DASY4 Measurement server

Features	:	166MHz low power Pentium MMX 32MB chipdisk and 64MB RAM Serial link to DAE (with watchdog supervision) 16 Bit A/D converter for surface detection system Two serial links to robot (one for real-time communication which is supervised by watchdog) Ethernet link to PC (with watchdog supervision) Emergency stop relay for robot safety chainTwo expansion slots for future applications
Manufacture	:	Schimid & Partner Engineering AG

Data Acquisition Electronic (DAE)

Features	:	Signal amplifier, multiplexer, A/D converter and control logic Serial optical link for communication with DASY4 embedded system (fully remote controlled) 2 step probe touch detector for mechanical surface detection and emergency robot stop (not in -R version)
Measurement Range	:	1 μ V to > 200 mV (16 bit resolution and two range settings: 4mV, 400mV)
Input Offset voltage	:	< 1 μ V (with auto zero)
Input Resistance	:	200 M Ω
Battery Power	:	> 10 h of operation (with two 9 V battery)
Dimension	:	60 x 60 x 68 mm
Manufacture	:	Schimid & Partner Engineering AG

Software

Item	:	Dosimetric Assesment System DASY4
Type No.	:	SD 000 401A, SD 000 402A
Software version No.	:	4.1
Manufacture / Origin	:	Schimid & Partner Engineering AG

E-Field Probe

Model	:	ET3DV6
Serial No.	:	1684
Construction	:	Triangular core fiber optic detection system
Frequency	:	10 MHz to 6 GHz
Linearity	:	+/-0.2 dB (30 MHz to 3 GHz)
Manufacture	:	Schimid & Partner Engineering AG

Phantom

Type	:	SAM Twin Phantom V4.0
Shell Material	:	Fiberglass
Thickness	:	2.0 +/-0.2 mm
Volume	:	Approx. 25 liters
Manufacture	:	Schimid & Partner Engineering AG

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 6 : Measurement outline

We tested the Camera with which this EUT was inserted.

The detail of the Camera that we used for SAR testing is showing in the following.

The shortest distance between the surface of this camera and antenna is 1mm.

6.1 The informations of Camera

Manufacture	: Kodak
Model No.	: EASYSHARE-ONE
Serial No.	: TP138
Resolution	: 4.0 MEGA PIXELS
Display	: 3 inch LCD
Card slot	: 1 slot for Wi-Fi card, 1 slot for Memory card
Size	: 102 x 60 x 25 (W x L x H)
Battery option	: Only one model with EUT Type : Li-ion Battery Model name : KLIC-5000 V/mAh : 3.7V / 1050mAh



*The outside cable from camera is to rewrite firmware for test mode, which is not affected the test result.



UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 7 : Test setup of EUT

7.1 Photographs of test setup

When users operate camera with this EUT (Wi-Fi card) inserted in, it could be considered to touch or get close to their bodies. In order to assume this situation, we performed the test at the following positions. Please refer to "APPENDIX 1" for more details.

- 1.Front : The test was performed in touch with front surface of Camera to the flat section of SAM pantom .
Wi-Fi card was distanced 13mm from the flat section.
- 2.Closed Back : The test was performed in touch with closed back surface of Camera to the flat section of SAM pantom .Wi-Fi card was distanced 9mm from the flat section.
- 3.Opened Back : The test was performed in touch with opened back surface of Camera Terminal to the flat section of SAM pantom .Wi-Fi card was distanced 1mm from the flat section.
- 4.Left Side : The test was performed in touch with left side of Camera to the flat section of SAM pantom .
Wi-Fi card was distanced 25mm from the flat section.
- 5.Right Side : The test was performed in touch with right side of Camera to the flat section of SAM pantom .
Wi-Fi card was distanced 55mm from the flat section.
- 6.Top : The test was performed in touch with top of Wi-Fi card to the flat section of SAM pantom.

1. Front



UL Apex Co., Ltd.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124


2. Closed Back




3. Opened Back



4. Left Side



5. Right Side



6. Top



7.2 EUT Tune-up procedure

This EUT has IEEE.802.11b.

The frequency range and the modulation were used in the testing of each mode are shown as the following.

1. IEEE802.11b

Tx Frequency : 2412-2462MHz
Channel : 1ch(2412MHz), 6ch(2437MHz), 11ch(2462MHz)
Modulation : DSSS(CCK)
Crest factor : 1

7.3 Distance between Camera and Phantom

The measurement was performed with the distance, 5mm, 10mm and 15mm to check if the shortest distance (1mm) may not have the worst value at the conditions of the highest SAR value of this Camera with the EUT.

As a result, the shortest distance (1mm) had the worst value.

7.4 About Head SAR measurement

Head SAR measurement is only for reference.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 8 : Measurement uncertainty

8.1 Uncertainty of 802.11b testing

The uncertainty budget has been determined for the DASY4 measurement system according to the NIS81 [13] and the NIST1297 [6] documents and is given in the following Table.

Error Description	Uncertainty value $\pm$ %	Probability distribution	divisor	(ci)1 lg	Standard Uncertainty (1g)	vi or v _{eff}
Measurement System						
Probe calibration	± 4.8	Normal	1	1	± 4.8	∞
Axial isotropy of the probe	± 4.7	Rectangular	$\sqrt{3}$	$(1-c_p)^{1/2}$	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	$\sqrt{3}$	$(c_p)^{1/2}$	± 3.9	∞
Boundary effects	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Probe linearity	± 4.7	Rectangular	$\sqrt{3}$	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Readout electronics	± 1.0	Normal	1	1	± 1.0	∞
Response time	± 0.8	Rectangular	$\sqrt{3}$	1	± 0.5	∞
Integration time	± 2.6	Rectangular	$\sqrt{3}$	1	± 1.5	∞
RF ambient conditions	± 3.0	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Mech. constraints of robot	± 0.4	Rectangular	$\sqrt{3}$	1	± 0.2	∞
Probe positioning	± 2.9	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Extrap. and integration	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Test Sample Related						
Device positioning	± 2.9	Rectangular	$\sqrt{3}$	1	± 2.9	18
Device holder uncertainty	± 3.6	Rectangular	$\sqrt{3}$	1	± 3.6	8
Power drift	± 10.0	Rectangular	$\sqrt{3}$	1	± 5.8	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.64	± 1.8	∞
Liquid conductivity (meas.)	± 5.0	Rectangular	$\sqrt{3}$	0.64	± 1.8	∞
Liquid permittivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (meas.)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Combined Standard Uncertainty					± 11.51	
Expanded Uncertainty (k=2)					± 23.0	

The result of some test showed that the power drift has exceeded 5%. Therefore, the uncertainty of power drift expanded to 10%. However, the extended uncertainty (k= 2) of a test is less than 30%.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 9 : Simulated tissue liquid parameter

9.1 Simulated Tissue Liquid Parameter confirmation

The dielectric parameters were checked prior to assessment using the HP85070D dielectric probe kit.
The dielectric parameters measurement are reported in each correspondent section.

9.2 Head 2450 MHz

Type of liquid : Head 2450 MHz
Ambient temperature (deg.c.) : 25.0(February 2 and 8)
Relative Humidity (%) : 31(February 2), 34(February 8)
Liquid depth (cm) : 15.0

DIELECTRIC PARAMETERS MEASUREMENT RESULTS								
Date	Frequency	Liquid Temp [deg.c]		Parameters	Target Value	Measured	Deviation [%]	Limit [%]
		Before	After					
2-Feb	2450	23.3	23.3	Relative Permittivity ϵ_r	39.2	39.4	0.5	+/-5
				Coductivity σ [mho/m]	1.80	1.89	5.0	+/-5
8-Feb	2450	23.3	23.3	Relative Permittivity ϵ_r	39.2	37.7	-3.8	+/-5
				Coductivity σ [mho/m]	1.80	1.86	3.3	+/-5

9.3 Muscle 2450 MHz

Type of liquid : Muscle 2450 MHz
Ambient temperature (deg.c.) : 25.0(February 8)
Relative Humidity (%) : 34(February 8)
Liquid depth (cm) : 15.2

DIELECTRIC PARAMETERS MEASUREMENT RESULTS								
Date	Frequency	Liquid Temp [deg.c]		Parameters	Target Value	Measured	Deviation [%]	Limit [%]
		Before	After					
8-Feb	2450	24.3	24.3	Relative Permittivity ϵ_r	52.7	50.1	-4.9	+/-5
				Coductivity σ [mho/m]	1.95	1.97	1.0	+/-5

9.4 Simulated Tissues Composition of 2450MHz

Ingredient	MiXTURE(%)	
	Head 2450MHz	Muscle 2450MHz
Water	45.0	69.83
DGMBE	55.0	30.2

Note:DGMBE(Diethylenglycol-monobuthyl ether)

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 10 : System validation data


Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of +/-10%.

10.1 System validation of 2450MHz

Type of liquid : HEAD 2450MHz
Frequency : 2450MHz
Ambient temperature (deg.c.) : 25.0(February 2 & 8)
Relative Humidity (%) : 31(February 2), 34(February 8)
Dipole : D2450V2 SN:713
Power : 250mW

SYSTEM PERFORMANCE CHECK										
Date	Liquid (HEAD 2450MHz)						System dipole validation target & measured			
	Liquid Temp [deg.c.]		Relative Permittivity		Conductivity		SAR 1g [W/kg]		Deviation [%]	Limit [%]
	Before	After	Target	Measured	Target	Measured	Target	Measured		
2-Feb	23.3	23.3	39.2	39.4	1.80	1.89	13.1	14.0	6.9	+/-10
8-Feb	23.3	23.3	39.2	37.7	1.80	1.86	13.1	14.0	6.9	+/-10

Note: Please refer to Attachment for the result representation in plot format



2450MHz System
performance check
setup

Test system for the system performance check setup diagram

SECTION 11 : Evaluation procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the E-field at a fixed location above the ear point or central position of flat phantom was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of head or body position was measured at a distance of each device from the inner surface of the shell. The area covered the entire dimension of the antenna of EUT and the horizontal grid spacing was 20 mm x 20 mm . Based on these data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Around this point found in the Step 2 (area scan) , a volume of 32 mm x 32 mm x 30 mm was assessed by measuring 5 x 5 x 7 points. And for any secondary peaks found in the Step2 which are within 2dB of maximum peak and not with this Step3 (Zoom scan) is repeated. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm [4]. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
2. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x, y and z-directions) [4], [5]. The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
3. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the E-field at the same location as in Step 1.

SECTION 12 : Exposure limit

(A) Limits for Occupational/Controlled Exposure (W/kg)

Spatial Average (averaged over the whole body)	Spatial Peak (averaged over any 1g of tissue)	Spatial Peak (hands/wrists/feet/ankles averaged over 10g)
0.4	8.0	20.0

(B) Limits for General population/Uncontrolled Exposure (W/kg)

Spatial Average (averaged over the whole body)	Spatial Peak (averaged over any 1g of tissue)	Spatial Peak (hands/wrists/feet/ankles averaged over 10g)
0.08	1.6	4.0

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE:GENERAL POPULATION/UNCONTROLLED EXPOSURE SPATIAL PEAK(averaged over any 1g of tissue) LIMIT 1.6 W/kg

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 13 : SAR Measurement results

13.1 Conducted peak power measurement result

[IEEE802.11b : 11Mbps]						
Ch	Freq. [MHz]	S/A Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result [dBm]	Converted [mW]
Low	2412.0	7.86	0.85	10.00	18.71	74.30
Mid	2437.0	7.91	0.85	10.00	18.76	75.16
High	2462.0	7.17	0.85	10.00	18.02	63.39

13.2 Head 2450MHz SAR (Only for refernce data)

Liquid Depth (cm) : 15.0 Model : 3F8508
Parameters : $\epsilon_r = 39.4$, $\sigma = 1.89$ Serial No. : No.1C
Ambient temperature (deg.c.) : 25.0 Modulation : DSSS
Relative Humidity (%) : 31 Crest factor : 1

Date : February 02, 2005
Measured By : Miyo Ikuta

HEAD SAR MEASUREMENT RESULTS										
Frequency		Modulation	Phantom Section	EUT Set-up Conditions				Liquid Temp.[deg.c]		SAR(1g) [W/kg]
Channel	[MHz]			Antenna	Position	Separation [mm]		Before	After	Maximum value of multi-peak
						Camera	Wi-Fi Card			
Position search										
Mid	2437	DSSS(CCK)	Flat	Fixed	Front	0	13	23.2	23.2	0.0576
Mid	2437	DSSS(CCK)	Flat	Fixed	Closed Back	0	9	23.2	23.2	0.0684
Mid	2437	DSSS(CCK)	Flat	Fixed	Opened Back	0	1	23.2	23.2	0.435
Mid	2437	DSSS(CCK)	Flat	Fixed	Left side	0	25	23.3	23.3	0.0220
Mid	2437	DSSS(CCK)	Flat	Fixed	Right side	0	55	23.2	23.2	0.0258
Mid	2437	DSSS(CCK)	Flat	Fixed	Top	0	0	23.2	23.2	0.379
Frequency Change										
Low	2412	DSSS(CCK)	Flat	Fixed	Opened Back	0	1	23.3	23.3	0.186
High	2462	DSSS(CCK)	Flat	Fixed	Opened Back	0	1	23.3	23.3	0.412
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population								Body SAR: 1.6 W/kg (averaged over 1 gram)		

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

13.3 Body 2450MHz SAR

Liquid Depth (cm) : **15.2** Model : **3F8508**
Parameters : $\epsilon_r = 50.1$ $\sigma = 1.97$ Serial No. : **No.1C**
Ambient temperature (deg.c.) : **25.0** Modulation : **DSSS**
Relative Humidity (%) : **34** Crest factor : **1**

Date : February 08, 2005

Measured By : Miyo Ikuta

BODY SAR MEASUREMENT RESULTS										
Frequency		Modulation	Phantom Section	EUT Set-up Conditions				Liquid Temp.[deg.c]		SAR(1g) [W/kg]
Channel	[MHz]			Antenna	Position	Separation [mm]		Before	After	Maximum value of multi-peak
						Camera	Wi-Fi Card			
Position search										
Mid	2437	DSSS(CCK)	Flat	Fixed	Front	0	13	24.0	24.0	0.160
Mid	2437	DSSS(CCK)	Flat	Fixed	Closed Back	0	9	24.0	24.0	0.105
Mid	2437	DSSS(CCK)	Flat	Fixed	Opened Back	0	1	24.0	24.0	0.560
Mid	2437	DSSS(CCK)	Flat	Fixed	Left side	0	25	24.0	24.0	0.0161
Mid	2437	DSSS(CCK)	Flat	Fixed	Right side	0	55	24.0	24.0	0.0218
Mid	2437	DSSS(CCK)	Flat	Fixed	Top	0	0	24.0	24.0	0.378
Frequency Change										
Low	2412	DSSS(CCK)	Flat	Fixed	Opened Back	0	1	24.1	24.2	0.616
High	2462	DSSS(CCK)	Flat	Fixed	Opened Back	0	1	24.2	24.2	0.504
Separation change										
High	2462	DSSS(CCK)	Flat	Fixed	Opened Back	0	5	24.2	24.2	0.396
High	2462	DSSS(CCK)	Flat	Fixed	Opened Back	0	10	24.2	24.2	0.129
High	2462	DSSS(CCK)	Flat	Fixed	Opened Back	0	15	24.2	24.2	0.0314
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population								Body SAR: 1.6 W/kg (averaged over 1 gram)		

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 14 : Equipment & calibration information

Name of Equipment	Manufacture	Model number	Serial number	Calibration	
				Last Cal	due date
Power Meter	Agilent	E4417A	GB41290639	2004/11/09	2005/11/08
Power Sensor	Agilent	E9300B	US40010300	2004/11/15	2005/11/14
Power Sensor	Agilent	E9327A	US40440545	2004/03/11	2005/03/10
Spectrum Analyzer	Agilent	E4448A	MY44020357	2004/06/12	2005/06/11
S-Parameter Network Analyzer	Agilent	8753ES	US39174808	2003/10/23	2006/10/22
Signal Generator	Rohde&Schwarz	SML40	100023	2005/01/05	2006/01/04
RF Amplifier	TSJ	CBP02063033	-	2004/02/24	2005/02/23
Dosimetric E-Field Probe	Schmid&Partner Engineering AG	ET3DV6	1684	2004/09/02	2005/09/01
Data Acquisition Electronics	Schmid&Partner Engineering AG	DAE3 V1	509	2004/04/22	2005/04/21
Robot,SAM Phantom	Schmid&Partner Engineering AG	DASY4	I021834	N/A	N/A
Attenuator	Agilent	US40010300	08498-60012	2004/12/16	2005/12/15
Attenuator	HIROSE ELECTRIC CO.,LTD.	AT-110	-	2005/01/11	2006/01/10
2450MHz System Validation Dipole	Schmid&Partner Engineering AG	D2450V2	713	2004/12/13	2006/12/12
Dual Directional Coupler	N/A	Narda	03702	N/A	N/A
Head 2450MHz	N/A	N/A	N/A	N/A	N/A
Body 2450MHz	N/A	N/A	N/A	N/A	N/A

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124

SECTION 15 : References

- [1] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [2] Katja Pokovic, Thomas Schmid, and Niels Kuster, "Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15-17, 1997, pp. 120-124.
- [3] Katja Pokovic, Thomas Schmid, and Niels Kuster, "E- field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23-25 June, 1996, pp.172-175.
- [4] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [5] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992.
- [6] Barry N. Taylor and Christ E. Kuyatt, "Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8116

Facsimile: +81 596 24 8124