

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. Result

Worse case is as below:

Mode	Frequency (MHz)	Prediction distance (cm)	Peak RF power output		MPE (mW/cm ²)	Limit (mW/cm ²)	SAR Test Exclusion
			dBm	mW			
BLE	2402-2480	20	6.669	4.6441	0.00300	1	Yes
2.4GWIFI	2402-2480	20	15.005	31.6592	0.02048	1	Yes

Maximum Simultaneous transmission MPE Ratios for BLE+2.4GWIFI:

Max MPE ratio BLE/Limit	Max MPE ratio WIFI/Limit	ΣMPE ratios	Limit	Result
0.00300	0.02048	0.02348	1	PASS

BLE Antenna Gain:

Internal antenna, max gain 5.12dBi, 3.25(numeric)

2.4GWIFI Antenna Gain:

Internal antenna, max gain 5.12dBi, 3.25(numeric)

Meet MPE requirements, then SAR evaluation is not required.