Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

Test Report

Report No.:	CQASZ20240801620E
Applicant:	Kan Tsang New Technology Development Limited.
Address of Applicant:	Unit 1,11/F., Nan Fung Commercial Centre, No. 19 Lam Lok Street, Kowloon Bay, Hong Kong
Equipment Under Test (EUT):	
Product:	Baby Monitor
Model No.:	KT-901, KT-902, KT-903, KT-903B, KT-903C, CP010, CP030, KT-905, DC-BBM002, DC-BBM002, DC-BBM003, DC-BBM004, DC-BBM005, DC-BBM006, DC-BBM007, DC-BBM008, DC-BBM009, DC-BBM010
Test Model No.:	KT-902
Brand Name:	N/A
FCC ID:	PAZ-KT-902PU
Standards:	47 CFR Part 15, Subpart C
	KDB558074 D01 15.247 Meas Guidance v05r02
	ANSI C63.10:2013
Date of Receipt:	2024-08-06
Date of Test:	2024-08-06 to 2024-11-07
Date of Issue:	2024-11-07
Test Result:	**PASS***

***In the configuration tested, the EUT complied with the standards specified above.**

Tested By: lewis zhou

(Lewis Zhou)

Reviewed By: Timo Lei

(Timo Lei)

Approved By: Alex

(Alex Wang)

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240801620E	Rev.01	Initial report	2024-11-07

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

3 Contents

Page

1 VERSION **2**

2 TEST SUMMARY **3**

3 CONTENTS **4**

4 GENERAL INFORMATION **5**

4.1 CLIENT INFORMATION 5
4.2 GENERAL DESCRIPTION OF EUT 5
4.3 ADDITIONAL INSTRUCTIONS 7
4.4 TEST ENVIRONMENT 8
4.5 DESCRIPTION OF SUPPORT UNITS 8
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY 9
4.7 TEST LOCATION 10
4.8 TEST FACILITY 10
4.9 DEVIATION FROM STANDARDS 10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 10
4.11 EQUIPMENT LIST 11

5 TEST RESULTS AND MEASUREMENT DATA **12**

5.1 ANTENNA REQUIREMENT 12
5.2 CONDUCTED EMISSIONS 13
5.3 CONDUCTED PEAK OUTPUT POWER 17
5.4 6DB OCCUPY BANDWIDTH 20
5.5 POWER SPECTRAL DENSITY 23
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS 26
5.7 SPURIOUS RF CONDUCTED EMISSIONS 28
5.8 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS 33
5.8.1 Spurious Emissions *33*

6 PHOTOGRAPHS - EUT TEST SETUP **39**

6.1 RADIATED SPURIOUS EMISSION 39
6.2 CONDUCTED EMISSIONS TEST SETUP 40

7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS **41**

4 General Information

4.1 Client Information

Applicant:	Kan Tsang New Technology Development Limited.
Address of Applicant:	Unit 1,11/F., Nan Fung Commercial Centre, No. 19 Lam Lok Street, Kowloon Bay, Hong Kong
Manufacturer1:	Dong Guan Kan Tsang Electroacoustic Technology Co.,Ltd.
Address of Manufacturer1:	Room 402 First Building, No.8, LuYi First Road,TangXia Town, Dong Guan City, China.
Factory1:	Dong Guan Kan Tsang Electroacoustic Technology Co.,Ltd.
Address of Factory1:	Room 402 First Building, No.8, LuYi First Road,TangXia Town, Dong Guan City, China.
Manufacturer2:	Dongguan Qinyuan Gaotu Electronic Technology Co., Ltd
Address of Manufacturer2:	Room 401, Building 2, No. 6 Luyi 1st Road, Tangxia Town, Dongguan City, GuangDong
Factory2:	Dongguan Qinyuan Gaotu Electronic Technology Co., Ltd
Address of Factory2:	Room 401, Building 2, No. 6 Luyi 1st Road, Tangxia Town, Dongguan City, GuangDong

4.2 General Description of EUT

Product Name:	Baby Monitor
Model No.:	KT-901, KT-902, KT-903, KT-903B, KT-903C, CP010, CP030, KT-905, DC-BBM002, DC-BBM002, DC-BBM003, DC-BBM004, DC-BBM005, DC-BBM006, DC-BBM007, DC-BBM008, DC-BBM009, DC-BBM010
Test Model No.:	KT-902
Trade Mark:	N/A
Software Version:	RX828-1
Hardware Version:	V05
Operation Frequency:	2410MHz~2477MHz
Modulation Type:	GFSK
Number of Channel:	20
Product Type:	☐ Mobile ☒ Portable
Test Software of EUT:	EUT key
Antenna Type:	FPC antenna
Antenna Gain:	3.12dBi
EUT Power Supply:	Li-ion battery: DC 3.7V 1500mAh, Charge by DC 5V for adapter
	Model:YC-R02051000UU Input:100-240V~50/60Hz 0.2A Output:5V 1A 5W
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency	Channel	Frequency
1	2410	11	2445	/	/	/	/
2	2413.5	12	2448.5	/	/	/	/
3	2417	13	2452	/	/	/	/
4	2420.5	14	2455.5	/	/	/	/
5	2424	15	2459	/	/	/	/
6	2427.5	16	2462.5	/	/	/	/
7	2431	17	2466	/	/	/	/
8	2434.5	18	2469.5	/	/	/	/
9	2438	19	2473	/	/	/	/
10	2441.5	20	2477	/	/	/	/

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH1)	2410MHz
The middle channel (CH10)	2441.5MHz
The highest channel (CH20)	2477MHz

4.3 Additional Instructions

EUT Test Software Settings:		
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *#*#3646633#*#*	
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
GFSK	CH1	2410
	CH20	2441.5
	CH40	2477

Run Software:

4.4 Test Environment

Operating Environment:	
Temperature:	24.5°C
Humidity:	59% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1）Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	3×10^{-8}
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8℃
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Deviation from Standards

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Spectrum analyzer	R&S	FSU26	CQA-038	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Spectrum analyzer	R&S	FSU40	CQA-075	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Preamplifier	EMCI	EMC184055SE	CQA-089	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2023/09/08 2024/09/02	2024/09/07 2025/09/01
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Antenna Connector	CQA	RFC-01	CQA-080	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2023/09/08 2024/09/02	2024/09/07 2025/09/01
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Power meter	R&S	NRVD	CQA-029	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2023/09/08 2024/09/02	2024/09/07 2025/09/01
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08 2024/09/02	2024/09/07 2025/09/01
LISN	R&S	ENV216	CQA-003	2023/09/08 2024/09/02	2024/09/07 2025/09/01
Coaxial cable	CQA	N/A	CQA-C009	2023/09/08 2024/09/02	2024/09/07 2025/09/01
DC power	KEYSIGHT	E3631A	CQA-028	2023/09/08 2024/09/02	2024/09/07 2025/09/01

Note:

The temporary antenna connector is soldered on the pcb board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is Copper tube antenna. The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment This is either permanently attachment or a unique coupling that satisfies the requirement.	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	150kHz to 30MHz
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Procedure:

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.

Test Setup:	
Test Mode:	Through Pre-scan, find the transmitting mode at the lowest channel is the worst case.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

Live line:



		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.165	28.09	9.67	37.76	55.21	-17.45	Average	Line
2	PP	0.165	41.00	9.67	50.67	65.21	-14.54	QP	Line
3		0.180	25.00	9.64	34.64	54.49	-19.85	Average	Line
4		0.180	36.62	9.64	46.26	64.49	-18.23	QP	Line
5		0.220	24.62	9.58	34.20	52.82	-18.62	Average	Line
6		0.220	36.90	9.58	46.48	62.82	-16.34	QP	Line
7		0.240	23.38	9.56	32.94	52.10	-19.16	Average	Line
8		0.240	34.08	9.56	43.64	62.10	-18.46	QP	Line
9		0.295	22.56	9.50	32.06	50.38	-18.32	Average	Line
10		0.295	31.99	9.50	41.49	60.38	-18.89	QP	Line
11	AV	0.370	23.32	9.58	32.90	48.50	-15.60	Average	Line
12		0.370	32.81	9.58	42.39	58.50	-16.11	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:

2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	27.90	9.70	37.60	56.00	-18.40	Average	Neutral
2	0.150	38.92	9.70	48.62	66.00	-17.38	QP	Neutral
3	0.185	26.10	9.63	35.73	54.26	-18.53	Average	Neutral
4	0.185	37.61	9.63	47.24	64.26	-17.02	QP	Neutral
5	0.225	24.12	9.57	33.69	52.63	-18.94	Average	Neutral
6	0.225	35.77	9.57	45.34	62.63	-17.29	QP	Neutral
7	0.240	23.26	9.55	32.81	52.10	-19.29	Average	Neutral
8	0.240	34.90	9.55	44.45	62.10	-17.65	QP	Neutral
9	0.300	22.26	9.48	31.74	50.24	-18.50	Average	Neutral
10	0.300	31.78	9.48	41.26	60.24	-18.98	QP	Neutral
11 PP	0.545	23.47	9.75	33.22	46.00	-12.78	Average	Neutral
12 QP	0.545	33.23	9.75	42.98	56.00	-13.02	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	30dBm
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

Measurement Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	5.83	30.00	Pass
Middle	5.07	30.00	Pass
Highest	5.78	30.00	Pass

GFSK_Ant1_2410

GFSK_Ant1_2441.5

GFSK_Ant1_2477


Spectrum
Ref Level 30.00 dBm Offset 11.79 dB RBW 2 MHz
Att 40 dB SWT 936 ns VBW 5 MHz Mode Auto FFT
Count 100/100
1Pk View
M1[1] 5.78 dBm
2.475979380 GHz
M1
20 dBm
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
CF 2.477 GHz
8001 pts
Span 6.0 MHz
Date: 14.AUG.2024 16:23:37

5.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	≥ 500 kHz
Instruments Used:	Refer to section 4.11 for details.
Test Results:	Pass

Measurement Data

GFSK mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	1.23	≥500	Pass
Middle	1.27	≥500	Pass
Highest	1.28	≥500	Pass

GFSK_Ant1_2410



GFSK_Ant1_2441.5



GFSK_Ant1_2477


Spectrum
Ref Level 30.00 dBm Offset 11.79 dB RBW 100 kHz
Att 40 dB SWT 18.9 µs VBW 300 kHz Mode Auto FFT
Count 100/100
1Pk View
M1[1] -0.21 dBm 2.47588800 GHz
M2[1] 5.65 dBm 2.47597600 GHz
20 dBm
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
D1 -0.350 dBm
M2
M1
D3
CF 2.477 GHz
1001 pts
Span 8.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.475888 GHz -0.21 dBm
M2 1 2.475976 GHz 5.65 dBm
D3 M1 1 1.28 MHz -0.08 dB
Date: 14.AUG.2024 16:23:23

5.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	≤8.00dBm/3kHz
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

Measurement Data

GFSK mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	4.63	≤8.00	Pass
Middle	3.88	≤8.00	Pass
Highest	4.32	≤8.00	Pass

Test plot as follows:

GFSK_Ant1_2410



GFSK_Ant1_2441.5



GFSK_Ant1_2477


Spectrum
Ref Level 20.00 dBm Offset 11.79 dB RBW 3 kHz
Att 30 dB SWT 632.1 µs VBW 10 kHz Mode Auto FFT
Count 100/100
1Pk View
M1[1] 4.32 dBm
2.4759774930 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.477 GHz
30000 pts
Span 2.56 MHz
Date: 14.AUG.2024 16:23:44

5.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

TestMode	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
GFSK	High	2477	5.75	-39.99	≤-14.25	PASS
	Low	2410	5.94	-28.36	≤-14.06	PASS

Test plot as follows:

GFSK_Ant1_High_2477

GFSK_Ant1_Low_2410



5.7 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

Test plot as follows:

BLE_1M_Ant1_2410_0~Reference

BLE_1M_Ant1_2410_30~1000



BLE_1M_Ant1_2410_1000~26500



Date: 6.NOV.2024 14:32:02

BLE_1M_Ant1_2441.5_0~Reference



Date: 14.AUG.2024 16:33:20

BLE_1M_Ant1_2441.5_30~1000



Date: 14.AUG.2024 16:33:26

BLE_1M_Ant1_2441.5_1000~26500



BLE_1M_Ant1_2477_0~Reference



BLE_1M_Ant1_2477_30~1000



BLE_1M_Ant1_2477_1000~26500



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.8 Radiated Spurious Emission & Restricted bands

5.8.1 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10 2013
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Receiver Setup:	

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

	horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation. Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of data type and GFSK modulation is the worst case. For below 1GHz part, through pre-scan, the worst case is the highest channel. Only the worst case is recorded in the report.
Test Results:	Pass

Radiated Emission below 1GHz

30MHz~1GHz, the worst case		
Test mode:	Transmitting mode	Horizontal



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	216.02	21.57	10.52	32.09	46.00	-13.91	Peak	HORIZONTAL
2	241.68	19.41	13.22	32.63	46.00	-13.37	Peak	HORIZONTAL
3	306.75	20.94	15.50	36.44	46.00	-9.56	Peak	HORIZONTAL
4	768.75	13.57	24.40	37.97	46.00	-8.03	Peak	HORIZONTAL
5 pp	869.13	11.25	26.78	38.03	46.00	-7.97	Peak	HORIZONTAL

30MHz~1GHz, the worst case		
Test mode:	Transmitting mode	Vertical



		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		260.14	16.32	13.96	30.28	46.00	-15.72	Peak	VERTICAL
2		400.43	16.25	16.88	33.13	46.00	-12.87	Peak	VERTICAL
3		504.71	14.12	20.36	34.48	46.00	-11.52	Peak	VERTICAL
4		574.63	17.51	21.24	38.75	46.00	-7.25	Peak	VERTICAL
5	pp	801.79	13.80	25.14	38.94	46.00	-7.06	Peak	VERTICAL
6		1000.00	13.61	27.71	41.32	54.00	-12.68	Peak	VERTICAL

Transmitter Emission above 1GHz

Worse case mode:		GFSK		Test channel:		Lowest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2390	54.69	-9.2	45.49	74	-28.51	**Peak**	**H**
2400	54.50	-9.39	45.11	74	-28.89	Peak	H
4820	52.62	-4.33	48.29	74	-25.71	Peak	H
7230	51.17	1.01	52.18	74	-21.82	Peak	H
2390	53.41	-9.2	44.21	74	-29.79	**Peak**	**V**
2400	53.11	-9.39	43.72	74	-30.28	Peak	V
4820	53.13	-4.33	48.80	74	-25.20	Peak	V
7230	50.09	1.01	51.10	74	-22.90	Peak	V

Worse case mode:		GFSK		Test channel:		Middle	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4883	50.72	-4.11	46.61	74	-27.39	peak	H
7324.5	50.26	1.51	51.77	74	-22.23	peak	H
4883	52.69	-4.11	48.58	74	-25.42	peak	V
7324.5	48.98	1.51	50.49	74	-23.51	peak	V

Worse case mode:		GFSK		Test channel:		Highest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2483.5	56.11	-9.29	46.82	74	-27.18	**Peak**	**H**
4954	52.60	-4.04	48.56	74	-25.44	Peak	H
7431	50.87	1.57	52.44	74	-21.56	Peak	H
2483.5	56.20	-9.29	46.91	74	-27.09	**Peak**	**V**
4954	51.72	-4.04	47.68	74	-26.32	Peak	V
7431	50.14	1.57	51.71	74	-22.29	Peak	V

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emissions Test Setup

7 Photographs - EUT Constructional Details



M
OK
CM
Made in China
撸尺

CM
Made in China
撸尺