

## EMC TEST REPORT For FCC



Test Report No. : CTK03-F064

Date of Issue : June 9, 2003

Model/Type No: : DAH-1100 [FCC ID : PCMDAH1100]

Kind of Product : MP3 PLAYER

Applicant : HYUN WON INC.

Applicant Address : 333-1 Shindea-Ri, Kumho-Eup, Young cheon-City Kyung Buk, Korea

Manufacturer : HYUN WON INC.

Manufacturer Address : 333-1 Shindea-Ri, Kumho-Eup, Young cheon-City Kyung Buk, Korea

Contact Person : Mr. Chang-Bae Lee (Assistant Manager)

Telephone : +82-54-337-9977

Received Date : May 28, 2003


Test period : Start: May 28, 2003 End: June 7, 2003

Test Results : ☒ **In Compliance** ☐ **Not in Compliance**

The test results presented in this report relate only to the object tested.


CERTiTEK Standards Laboratory Co., Ltd. is accredited by Korea Laboratory Accreditation Scheme (KOLAS) which signed the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA) for the above test item(s) and test method(s).

Tested by



Joon Pak  
EMC Test Engineer  
Date: June 9, 2003

Reviewed by



James Hong  
EMC Technical Manager  
Date: June 9, 2003

## REPORT REVISION HISTORY

| Date         | Revision            | Page No |
|--------------|---------------------|---------|
| June 9, 2003 | Issued (CTK03-F064) | All     |
|              |                     |         |
|              |                     |         |
|              |                     |         |
|              |                     |         |
|              |                     |         |
|              |                     |         |
|              |                     |         |
|              |                     |         |
|              |                     |         |

*This report shall not be reproduced except in full, without the written approval of CERTiTEK Standards Laboratory Co., Ltd. This document may be altered or revised by CERTiTEK Standards Laboratory Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CERTiTEK Standards Laboratory Co., Ltd. will constitute fraud and shall nullify the document.*

## TABLE OF CONTENTS

|                                                                 |    |
|-----------------------------------------------------------------|----|
| 1.0 General Product Description .....                           | 4  |
| 1.1 Model Differences.....                                      | 4  |
| 1.2 Device Modifications .....                                  | 4  |
| 1.3 EUT Configuration(s) .....                                  | 5  |
| 1.4 Test Software .....                                         | 5  |
| 1.5 EUT Operating Mode(s) .....                                 | 5  |
| 1.6 Calibration Details of Equipment Used for Measurement ..... | 6  |
| 1.7 Test Facility .....                                         | 6  |
| 1.8 Measurement Procedure .....                                 | 6  |
| 1.9 Laboratory Accreditations and Listings .....                | 7  |
| 2.0 Emissions Test Regulations.....                             | 8  |
| 2.1 Conducted Voltage Emissions .....                           | 9  |
| 2.2 Radiated Electric Field Emissions .....                     | 10 |
| Configurations.....                                             | 11 |
| APPENDIX A - TEST DATA.....                                     | 12 |
| Conducted Voltage Emissions (Quasi-Peak reading) .....          | 12 |
| Radiated Electric Field Emissions (Quasi-Peak reading) .....    | 14 |

## 1.0 General Product Description

### 1.0.1 Tested Equipment

- ☒ Unless otherwise indicated, all tests were conducted on Model DAH-1100.
- ☐ Tests performed on Model \_\_\_\_\_ were considered to be representative of Model(s) \_\_\_\_\_.

### 1.0.2 Equipment Size, Mobility and Identification

Dimensions: 84 by 14 by 46 ☒ mm ☐ in  
Mobility: ☒ Hand-Held ☐ Table-top ☐ Floor-standing  
☐ -  
Serial No.: Not applicable

### 1.0.3 Electrical Ratings

Input: When MP3 playing – DC 1.5V (Dry Cell Battery 1EA×AAA size)  
When USB downloading – Supplied by PC's USB port power  
Output: Not applicable

### 1.0.4 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage: DC 1.5V or PC's USB port power  
Frequency: Not applicable

### 1.0.5 Clock & Other Frequencies Utilized

32.768kHz, 24.576MHz

## 1.1 Model Differences

Not applicable

## 1.2 Device Modifications

The following modifications were necessary for compliance:

Not applicable

### 1.3 EUT Configuration(s)

See Appendix A for individual test set-up configuration(s). The following peripheral devices and/or interface cables were connected during the measurement:

☒ Peripheral Devices

| Device           | Manufacturer        | Model No.    | Serial No.             | FCC ID or DoC |
|------------------|---------------------|--------------|------------------------|---------------|
| Adaptor          | LITE-ON ELECTRONICS | PA-1500-02   | 3100036102             | -             |
| Notebook PC      | ACER                | MS2133       | LXT270E01831800421M000 | DoC           |
| Adaptor          | KANGWON             | SMPS-1205200 | -                      | -             |
| ODD              | AOpen               | ESV-189i     | 915MD37A01311004BEM000 | DoC           |
| Mouse (USB type) | SAMSUNG             | OMS3CB       | 0303009875             | DoC           |

☒ Cable Description

| # | Description                    | Ferrited | Length (m) | Other Details                   |
|---|--------------------------------|----------|------------|---------------------------------|
| 1 | AC power cable, Unshielded     | No       | 1.8        | Connect to AC power             |
| 2 | DC output cable, Unshielded    | Yes      | 1.8        | -                               |
| 3 | AC power cable, Unshielded     | No       | 1.8        | Connect to AC power             |
| 4 | DC output cable, Unshielded    | No       | 1.2        | -                               |
| 5 | USB cable, Shielded            | No       | 1.2        | Between the EUT and notebook PC |
| 6 | Earphone cable, Unshielded     | No       | 2.1        | -                               |
| 7 | IEEE 1394 port cable, Shielded | No       | 0.2        | Between the notebook PC and ODD |
| 8 | Mouse cable, Shielded          | No       | 1.8        | -                               |

n/a = not available

### 1.4 Test Software

☐ Pinging

☒ Not applicable

### 1.5 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:

☐ Test program (H-Pattern)

☐ Test program (color bar)

☐ Standby

☐ Test program (customer specific)

☒ Practice operation – MP3 playing and USB downloading mode

## **1.6 Calibration Details of Equipment Used for Measurement**

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

## **1.7 Test Facility**

The measurement facility is located at 386-1, Ho-Dong, Yongin-City, Kyungki-Do, Korea 449-100. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

## **1.8 Measurement Procedure**

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested. Final AC power line conducted emissions test was performed shielded room. (location is same as Preliminary test)

Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed anechoic chamber (Distance of antenna and EUT was 3 m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Open Area Test Site. Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

\* Measurement procedures was In accordance with ANSI C63.4-1992 7.2.3, 7.2.4, 8.3.1.1, 8.3.1.2

## 1.9 Laboratory Accreditations and Listings

| Country       | Agency       | Scope of Accreditation                                                                                                                                                                                                                                                      | Logo                                                                                                    |
|---------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| USA           | <b>FCC</b>   | 3 and 10 meter Open Area Test Sites to perform FCC Part 15/18 measurements.                                                                                                                                                                                                 | <br>93250            |
| JAPAN         | <b>VCCI</b>  | 10 meter Open Area Test Site and one conducted site.                                                                                                                                                                                                                        | <br>R-948, C-986     |
| KOREA         | <b>MIC</b>   | EMI (CE, RE)<br>EMS (ESD, Burst, RS, Surge, CS,<br>Power-Frequency Susceptibility,<br>Voltage Dips and Short Interruptions)                                                                                                                                                 | <br>No. 51, KR0025   |
| International | <b>KOLAS</b> | EMC                                                                                                                                                                                                                                                                         | <br>NO.119          |
| Europe        | <b>GLAS</b>  | EMC<br>EN 55011, EN 55022, EN 55024, EN 61326,<br>EN 50130-4, EN 50081-1, EN 50081-2,<br>EN 50082-1, EN 50082-2, EN 61000-6-2,<br>EN 61000-4-2, EN 61000-4-3,<br>EN 61000-4-4, EN 61000-4-5,<br>EN 61000-4-6, EN 61000-4-8,<br>EN 61000-4-11, EN 61000-3-2,<br>EN 61000-3-3 | <br>No.13000796-02 |

## 2.0 Emissions Test Regulations

The emissions tests were performed according to following regulations:

- |                                                                                |                                                           |                                             |
|--------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------|
| <input type="checkbox"/> EN 50081-1:1992                                       |                                                           |                                             |
| <input type="checkbox"/> EN 55011:1998 +A1:1999                                | <input type="checkbox"/> Group 1                          | <input type="checkbox"/> Group 2            |
|                                                                                | <input type="checkbox"/> Class A                          | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55013:1990 +A12:1994 +A13:1996 +A14:1999           |                                                           |                                             |
| <input type="checkbox"/> EN 55013:2001                                         |                                                           |                                             |
| <input type="checkbox"/> EN 55014-1:1993 +A1:1997 +A2:1999                     | <input type="checkbox"/> Household appliances and similar |                                             |
|                                                                                | <input type="checkbox"/> Portable tools                   |                                             |
|                                                                                | <input type="checkbox"/> Semiconductor devices            |                                             |
| <input type="checkbox"/> EN 55014-1:2000                                       |                                                           |                                             |
| <input type="checkbox"/> EN 55014-2:1997                                       |                                                           |                                             |
| <input type="checkbox"/> EN 55015:1996 +A1:1997 +A2:1999                       |                                                           |                                             |
| <input type="checkbox"/> EN 55015:2000                                         |                                                           |                                             |
| <input type="checkbox"/> EN 55020:1994 +A11:1996 +A13:1999 +A14:1999           |                                                           |                                             |
| <input type="checkbox"/> EN 55020:1994 +A11:1996 +A12:1999 +A13:1999 +A14:1999 |                                                           |                                             |
| <input type="checkbox"/> EN 55022:1994 +A1:1995 +A2:1997                       | <input type="checkbox"/> Class A                          | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55022:1998 +A1:2000                                | <input type="checkbox"/> Class A                          | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 61000-3-2:1995 +A1:1998 +A2:1998                   |                                                           |                                             |
| <input type="checkbox"/> EN 61000-3-2:1995 +A1:1998 +A2:1998 +A14:2000         |                                                           |                                             |
| <input type="checkbox"/> EN 61000-3-2:2000                                     |                                                           |                                             |
| <input type="checkbox"/> EN 61000-3-3:1995                                     |                                                           |                                             |
| <input type="checkbox"/> VCCI V-3/99.05 : 1999                                 | <input type="checkbox"/> Class A                          | <input type="checkbox"/> Class B            |
| <input checked="" type="checkbox"/> FCC Part 15 SUBPART B                      | <input type="checkbox"/> Class A                          | <input checked="" type="checkbox"/> Class B |
| <input type="checkbox"/> AS 3548 (1992)                                        | <input type="checkbox"/> Class A                          | <input type="checkbox"/> Class B            |
| <input checked="" type="checkbox"/> CISPR 22 (1997)                            | <input type="checkbox"/> Class A                          | <input checked="" type="checkbox"/> Class B |

## 2.1 Conducted Voltage Emissions

### Test Date

June 2, 2003

### Test Location

EMI-CE: Shielded Room

### Test Instruments

|                                                          |                 |        |            |
|----------------------------------------------------------|-----------------|--------|------------|
| <input checked="" type="checkbox"/> Field Strength Meter | Rohde & Schwarz | ESHS30 | 828144/002 |
|----------------------------------------------------------|-----------------|--------|------------|

### Test Accessories

|                                                |      |            |            |
|------------------------------------------------|------|------------|------------|
| <input type="checkbox"/> LISN                  | EMCO | 3825/2     | 9206-1971  |
| <input checked="" type="checkbox"/> LISN       | EMCO | 3825/2     | 9409-2246  |
| <input checked="" type="checkbox"/> LISN       | EMCO | 3825/2     | 9607-2574  |
| <input checked="" type="checkbox"/> Control PC | HP   | Vectra 500 | SG72000192 |

### Frequency Range of Measurement

☒ 150 kHz to 30 MHz  
☐ 450 kHz to 30 MHz  
☐ \_\_\_\_\_

### Instrument Settings

IF Band Width: 9 kHz

### Test Results

The requirements are:

|                                         |                                                    |
|-----------------------------------------|----------------------------------------------------|
| <input checked="" type="checkbox"/> MET | minimum margin is 5.3 dBuV at 0.16 MHz             |
| <input type="checkbox"/> NOT MET        | limit exceeded by maximum of ____ dBuV at ____ MHz |
| <input type="checkbox"/> NOT APPLICABLE |                                                    |

### Remarks

See Appendix A for test data.

## 2.2 Radiated Electric Field Emissions

### Test Date

June 3, 2003

### Test Location

- ☒ EMI-OATS: Testing was performed at a test distance of 10 m  
☐ EMI-OATS: Testing was performed at a test distance of 3 m

### Test Instruments

- |                                                          |                 |        |            |
|----------------------------------------------------------|-----------------|--------|------------|
| <input checked="" type="checkbox"/> Field Strength Meter | Rohde & Schwarz | ESVS30 | 826638/008 |
|----------------------------------------------------------|-----------------|--------|------------|

### Test Accessories

- |                                                             |                 |         |            |
|-------------------------------------------------------------|-----------------|---------|------------|
| <input checked="" type="checkbox"/> ULTRA Broadband Antenna | Rohde & Schwarz | HL562   | 361324/014 |
| <input type="checkbox"/> Biconical Antenna                  | Schwarzbeck     | BBA9106 | 41-00201   |
| <input type="checkbox"/> Biconical Antenna                  | EMCO            | 3110B   | 9607-2564  |
| <input type="checkbox"/> Log-periodic Antenna               | EMCO            | 3146    | 9607-4567  |

### Frequency Range of Measurement

30 MHz to 1 GHz

### Instrument Settings

IF Band Width: 120 kHz

### Test Results


The requirements are:

- |                                         |                                                        |
|-----------------------------------------|--------------------------------------------------------|
| <input checked="" type="checkbox"/> MET | minimum margin is 3.72 dB (uV/m) at 260.90 MHz         |
| <input type="checkbox"/> NOT MET        | limit exceeded by maximum of ____ dB(uV/m) at ____ MHz |
| <input type="checkbox"/> NOT APPLICABLE |                                                        |

### Remarks

See Appendix A for test data



## Configuration



## APPENDIX A – TEST DATA

### Conducted Voltage Emissions (Quasi-Peak reading)

| Frequency<br>[MHz] | Correction<br>Factor |       | Line | Quasi-peak      |                   |                  |                | Average         |                   |                  |                |
|--------------------|----------------------|-------|------|-----------------|-------------------|------------------|----------------|-----------------|-------------------|------------------|----------------|
|                    | LISN                 | Cable |      | Limit<br>[dBuV] | Reading<br>[dBuV] | Result<br>[dBuV] | Margin<br>[dB] | Limit<br>[dBuV] | Reading<br>[dBuV] | Result<br>[dBuV] | Margin<br>[dB] |
| 0.16               | 2.2                  | 0.1   | L    | 65.5            | 57.9              | 60.2             | 5.3            | 55.5            | 13.6              | 15.9             | 39.6           |
| 0.18               | 1.7                  | 0.1   | L    | 64.5            | 56.8              | 58.6             | 5.9            | 54.5            | 21.9              | 23.7             | 30.8           |
| 0.20               | 1.7                  | 0.1   | L    | 63.6            | 55.8              | 57.6             | 6.0            | 53.6            | 30.9              | 32.7             | 20.9           |
| 0.22               | 1.7                  | 0.1   | L    | 63.0            | 55.4              | 57.2             | 5.8            | 53.0            | 31.8              | 33.6             | 19.4           |
| 0.29               | 0.8                  | 0.1   | L    | 60.5            | 47.5              | 48.4             | 12.1           | 50.5            | 28.6              | 29.5             | 21.0           |
| 0.32               | 0.8                  | 0.1   | L    | 59.7            | 47.2              | 48.1             | 11.6           | 49.7            | 28.4              | 29.3             | 20.4           |
| 0.44               | 0.5                  | 0.1   | L    | 57.2            | 44.5              | 45.1             | 12.1           | 47.2            | 30.1              | 30.7             | 16.4           |



## Radiated Electric Field Emissions (Quasi-Peak reading)

| Frequency<br>[MHz] | Reading<br>[dBuV / m] | Pol. | Height<br>[m] | Correction<br>Factor |       | Limits<br>[dBuV / m] | Result<br>[dBuV / m] | Margin<br>[dB] |
|--------------------|-----------------------|------|---------------|----------------------|-------|----------------------|----------------------|----------------|
|                    |                       |      |               | Antenna              | Cable |                      |                      |                |
| 119.80             | 13.3                  | V    | 1.0           | 9.70                 | 2.00  | 30.0                 | 25.01                | 4.99           |
| 195.40             | 14.7                  | V    | 1.1           | 7.00                 | 2.70  | 30.0                 | 24.40                | 5.60           |
| 260.90             | 20.3                  | H    | 4.0           | 9.80                 | 3.20  | 37.0                 | 33.28                | 3.72           |
| 265.60             | 13.5                  | H    | 4.0           | 9.90                 | 3.30  | 37.0                 | 26.71                | 10.29          |
| 298.70             | 13.7                  | H    | 4.0           | 10.90                | 3.60  | 37.0                 | 28.21                | 8.79           |
| 699.00             | 9.0                   | H    | 2.5           | 18.40                | 5.70  | 37.0                 | 33.10                | 3.90           |
| 725.00             | 1.1                   | H    | 2.5           | 18.90                | 6.00  | 37.0                 | 26.02                | 10.98          |
| 730.50             | 4.3                   | V    | 2.0           | 18.90                | 6.00  | 37.0                 | 29.21                | 7.79           |